

# Building a Student Intervention System: An Udacity Nanodegree ML Project

Omoju Miller

May 12, 2016

## Introduction

Your goal is to identify students who might need early intervention - which type of supervised machine learning problem is this, classification or regression? Why?

- This task sounds like a problem that would be best suited for a classification algorithm. The inherent task is to develop learners that can "predicting a category." If we look at the problem from another perspective, we can consider the student data available as a "labeled" dataset. We have features that we can use to determine who has succeeded in the class versus who has not. For that insight, we could use 'passed' column as our class label. Therefore, this is a binary classification problem for predicting discrete labels that a student might belong to.

## Models

For the student intervention challenge, three supervised learning algorithms have been selected as appropriate learners for the task. The algorithms are as follows:

1. Decision Tree Classifier
2. Random Forest Classifier
3. Support Vector Machines

## Decision Tree Classifier

- What is the theoretical  $O(n)$  time & space complexity in terms of input size?  
The theoretical time & space complexity of decision trees classifiers as implemented in sci-kit learn package is:

- Best Case:  $\Theta(pN \log^2 N)$
- Worst Case:  $O(pN^2 \log N)$

- Average Case:  $\Theta(pN \log^2 N)$

Where  $N$  denotes the number of samples, and  $p$  the number of input variables.<sup>1</sup>

- What are the general applications of this model?

The decision tree algorithm is usually applied to classification and regression problems.

What are its strengths and weaknesses?

- Strengths of decision trees:

- \* Very intuitive. You can look at the results and understand it.
- \* Requires little data preparation.
- \* The cost of using the tree (i.e., predicting data) is logarithmic in the number of data points used to train the tree. In average case the cost of training  $O(pN \log^2 N)$
- \* Able to handle both numerical and categorical data.
- \* Very robust. Performs well even if its assumptions are somewhat violated by the true model from which the data were generated.

- Weaknesses of decision trees:

- \* Decision-tree learners can create over-complex trees that do not generalize the data well. They are prone to over-fitting especially in the case of data with lots of features.
- \* Decision trees can be unstable because small variations in the data might result in a completely different tree being generated.
- \* The problem of learning an optimal decision tree is known to be NP-complete under several aspects of optimality and even for simple concepts.
- \* There are concepts that are hard to learn because decision trees do not express them easily, such as XOR, parity or multiplexer problems.
- \* Decision tree learners create biased trees if some classes dominate.

- Given what you know about the data so far, why did you choose this model to apply?

The decision tree classifier was chosen because of its ease of use and its relatively cheap time complexity.

Another *major* reason why the decision tree classifier was selected was its interpretability. For this problem domain, it isn't just satisfactory to identify students that need intervention, what learning researchers ultimately want is to gain *insights* into the nature of learning, and the social factors that lead to certain outcomes for at-risk students. A decision tree learner, with its ability to graphically plot out the tree becomes a research tool in the hands of learning scientist. Consequently, this can help the school board of supervisors build better solutions for those students which well executed could potentially reduce the costs associated with remediating failed students.

---

<sup>1</sup>Complexity analysis gotten from Louppe, Gilles PhD dissertation *Understanding Random Forests: From Theory to Practice*, 2014.

## Random Forest Classifier

- What is the theoretical  $O(n)$  time & space complexity in terms of input size?  
The theoretical time & space complexity for building a complete unpruned decision tree is:
    - Best Case:  $\Theta(MK\tilde{N}\log^2\tilde{N})$
    - Worst Case:  $O(MK\tilde{N}^2\log\tilde{N})$
    - Average Case:  $\Theta(MK\tilde{N}\log^2\tilde{N})$
- Where  $M$  denotes number of randomized trees,  $N$  the number of samples, and  $K$  the number of variables randomly drawn at each node.  $\tilde{N} = 0.632N$ , due to the fact that bootstrap samples draw, on average, 63.2% of unique samples. <sup>2</sup>
- What are the general applications of this model?  
Ensemble learners are used in supervised learning. The goal of the random forest classifier is to combine the results of multiple classifiers, yielding an ensemble of decision trees. The prediction of the classifier is the averaged prediction of the individual classifiers.
  - What are its strengths and weaknesses?
    - Strengths of SVMs:
      - \* Considered one of the best off-the-shelf learning algorithm, requires almost no tuning.
      - \* Fast to train because algorithm lends itself well to parallelization
      - \* Flexible, can be used with large number of attributes, small or large datasets
      - \* Good control of bias and variance because of the averaging and randomization which leads to better performance.
    - Weaknesses of decision trees:
      - \* Loss of interpretability as compared to decision trees give.
  - Given what you know about the data so far, why did you choose this model to apply?  
This learners was chosen as a means of reducing the effects of overfitting of decision trees.

## Support Vector Machine (SVMs)

- What is the theoretical  $O(n)$  time & space complexity in terms of input size?  
The theoretical time & space complexity of SVMs is:
  - Best Case:  $\Theta(pN^2)$
  - Worst Case:  $O(pN^3)$
  - Average Case:  $\Theta(pN^2)$

Where  $N$  denotes the number of samples, and  $p$  the number of input variables. It can be a costly algorithm since the compute and storage requirements increase rapidly with the

---

<sup>2</sup>Complexity analysis gotten from Louppe, Gilles PhD dissertation *Understanding Random Forests: From Theory to Practice*, 2014.

number of training vectors. Even though the algorithm spends more time in the training, however, it achieves better  $F_1$  score for prediction – thus it is more accurate.

- What are the general applications of this model?

SVMs are an algorithm used for classification, regression and outlier detection.

What are its strengths and weaknesses?

– Strengths of SVMs:

- \* Effective in high dimensional spaces.
- \* Still effective in cases where number of dimensions is greater than the number of samples.
- \* Uses a subset of training points in the decision function (called support vectors), so it is also memory efficient.
- \* Versatile: utilizes kernel transformation and several functional forms so can be applied to nonlinear data.

– Weaknesses of decision trees:

- \* If the number of features is much greater than the number of samples, the method is likely to give poor performances.
- \* SVMs do not directly provide probability estimates, these are calculated using an expensive five-fold cross-validation.
- \* SVM is a binary classifier. To do a multi-class classification, only pair-wise classifications can be used (one class against all others, for all classes).

- Given what you know about the data so far, why did you choose this model to apply?

The general approach is to try a few different algorithms for each problem. Sci-kit learn provides a guide to choosing estimators. Based on the guide, and our task satisfying the following criteria:  $100K > \text{samples} > 50$ , goal of predicting a category & availability of labeled data, a linear SVC was selected.

## Best Model

**Question** Based on the experiments you performed earlier, in 1-2 paragraphs explain to the board of supervisors what single model you chose as the best model. Which model is generally the most appropriate based on the available data, limited resources, cost, and performance?

**Answer** For the problem of identifying students that need intervention, I would advise the board of supervisors to go with a **Support Vector Machine**. First, it is a relatively fast algorithm to train and predict. Second, as we can see from figure 1, the dataset is quite unbalanced (number of passed students  $\gg$  number of failed students) a relatively small. The SVM algorithm is able to handle this better than the other two models.

While its marginally slower in prediction than Random Forest classifier with a prediction time of 0.001 versus 0.006 as can be seen from tables 3 and 4. The difference of negligible and SVM




Figure 1: **Values of ‘passed’ column** The histograms shows an unbalanced target dataset with approximately 125 values of (0) and over 250 values of (1).

makes up for what it loses in speed with improvement in accuracy.

**Question** In 1-2 paragraphs explain to the board of supervisors in layman’s terms how the final model chosen is supposed to work (for example if you chose a Decision Tree or Support Vector Machine, how does it make a prediction).

**Answer**

**Question** Fine-tune the model. What is the model’s final F1 score?

Table 1: Result of tuning with **GridSearchCV**

	GridSearchCV
F1 score for training set	1.000
F1 score for test set	0.803

## Tables

Table 2: Result of training with a **DecisionTreeClassifier**

	Training set size		
	100	200	300
Training time (secs)	0.001	0.001	0.002
Prediction time (secs)	0.000	0.000	0.000
F1 score for training set	1.000	1.000	1.000
F1 score for test set	0.746	0.649	0.720

Table 3: Result of training with a **Random Forest Classifier**

	Training set size		
	100	200	300
Training time (secs)	0.031	0.030	0.026
Prediction time (secs)	0.001	0.001	0.001
F1 score for training set	0.994	1.000	0.988
F1 score for test set	0.701	0.744	0.713

Table 4: Result of training with a **SVMs**

	Training set size		
	100	200	300
Training time (secs)	0.001	0.003	0.006
Prediction time (secs)	0.001	0.001	0.002
F1 score for training set	0.886	0.879	0.877
F1 score for test set	0.782	0.754	0.752