

Package ‘catSurv’

March 14, 2017

Title What the Package Does (one line, title case)

Version 0.0.0.9000

Description What the package does (one paragraph).

Depends R(>= 3.3.2)

License What license is it under?

Imports ltm(>= 1.0.0),
methods(>= 3.3.2),
stats(>= 3.3.2),
Rcpp(>= 0.12.9),

LinkingTo BH(>= 1.60.0.2),
Rcpp(>= 0.12.9),
RcppArmadillo,
RcppGSL(>= 0.3.1)

LazyData true

RoxygenNote 5.0.1

SystemRequirements C++11

Suggests catIrt(>= 0.5.0),
catR(>= 3.10),
testthat(>= 1.0.2)

R topics documented:

Cat-class	2
checkStopRules	3
d2LL	5
dLL	6
estimateSE	7
estimateTheta	8
expectedKL	9
expectedObsInf	10
expectedPV	11
fisherInf	12
fisherTestInfo	13
getModel	14
gpcm-class	14
grm-class	15

likelihood	16
likelihoodKL	17
lookAhead	18
ltm-class	19
makeTree	20
nfc	20
npi	21
obsInf	23
polknow	24
posteriorKL	29
prior	30
probability	31
selectItem	33
setGuessing<-	36
storeAnswer	36
tpm-class	37
Index	39

Cat-class

A Computerized Adaptive Testing Survey (catSurv) Object

Description

Objects of class Cat are used in administering Computerized Adaptive Testing (CAT) Surveys. These objects contain several pieces of information relevant for CAT surveys, and are used as input in the main functions of the catSurv package. They are created using the initialize function.

Details

Assume we have a survey battery with I questions. An object of the class Cat has the following slots:

- guessing A named vector of length I of guessing parameters. Note: guessing parameters are only applicable for binary Cat objects.
- discrimination A named vector of length I of discrimination parameters.
- difficulty A named vector or list of length I of difficulty parameters. For binary Cat objects, the vector will contain difficulty parameters for each item. For categorical Cat objects, a list will contain a vector for each item, and each vector will contain a difficulty parameter for each response option.
- answers A named vector of length I of answers to questions as given by the survey respondent. Unanswered questions have the value NA.
- priorName A character vector of length one giving the prior distribution to use for the latent trait estimates. The options are NORMAL for the normal distribution, STUDENT_T for the student's t distribution, and UNIFORM for the uniform distribution.
- priorParams A numeric vector of length two of parameters for the distribution specified in the priorName slot. See 'details' for more information.
- lowerBound A numeric indicating the lower bound of the interval of the latent scale used in estimation. The default value is -6 .

- **upperBound** A numeric indicating the upper bound of the interval of the latent scale used in estimation. The default value is 6.
- **poly** A logical containing the type of answers. TRUE indicates categorical response options, FALSE indicates binary response options. Default is TRUE.
- **estimation** A character vector of length one indicating the choice of approach to estimate ability parameters. The options are EAP, MAP, MLE, and WLE.
- **estimationDefault** A character vector of length one indicating the choice of approach to estimate ability parameters when the primary estimation choice indicating in the estimation slot fails to converge. The options are EAP and MAP.
- **selection** A character vector of length one indicating the choice of approach select the next item. The options are EPV, MEI, MFI, MPWI, MLWI, KL, LKL, PKL, MFII, and RANDOM.
- **z** A numeric. Used in calculating delta, which is used in calculating the bounds of integration for some selectItem methods. See 'details' for more information.
- **lengthThreshold** A numeric. The number of questions answered must be greater than or equal to this threshold.
- **seThreshold** A numeric. The standard error estimate of the latent trait must be less than this threshold.
- **infoThreshold** A numeric. The Fisher's information for all remaining items must be less than this threshold.
- **gainThreshold** A numeric. The absolute value of the difference between the standard error of the latent trait estimate and the square root of the expected posterior variance for each item must be less than this threshold.
- **lengthOverride** A numeric. The number of questions answered must be less than this override.
- **gainOverride** A numeric. The absolute value of the difference between the standard error of the latent trait estimate and the square root of the expected posterior variance for each item must be less than this override.

When **priorName** is set to "NORMAL", the first element of **priorParams** is the mean, the second element is the standard deviation. When **priorName** is set to "STUDENT_T", the first element of **priorParam** is mu, a location parameter, the second is degrees of freedom. When **priorName** is set to "UNIFORM", the elements of **priorParams** are lower and upper, respectively. Note that the uniform distribution is only applicable for the "EAP" estimation method.

Talk about 'z' and how it's used to calculate delta.

Author(s)

AA

checkStopRules

Check if Stop and/or Override Rules are Met

Description

Evaluates the specified stopping and/or override rules to check if respondent should be asked further questions

Usage

```
checkStopRules(catObj)
```

Arguments

catObj An object of class Cat

Details

The stopping rule thresholds are stored in the following Cat object slots: lengthThreshold, seThreshold, infoThreshold, and gainThreshold. The override thresholds are stored in the following Cat object slots: lengthOverride, gainOverride. A value of NA indicates the rule should not be used.

A return value of TRUE indicates that additional questions should be asked; FALSE indicates no additional questions should be asked.

A user can specify any combination of stopping rules and/or overrides. The function returns TRUE if all specified stopping rules are met and no specified overrides are met. The function returns FALSE if at least one specified stopping rule is not met, or if any specified override threshold is met.

Stopping Rules:

lengthThreshold: Number of question's answered $\geq a$

seThreshold: $SE(\hat{\theta}) < a$

infoThreshold:

$$FI < a \forall$$

remaining items

gainThreshold:

$$|SE(\hat{\theta}) - \sqrt{EPV}| < a \forall$$

remaining items

Overrides:

lengthOverride: Number of question's answered $< a$

gainOverride:

$$|SE(\hat{\theta}) - \sqrt{EPV}| \geq a \forall$$

remaining items

Value

This function returns a boolean, where TRUE indicates the the stopping rules are met (no further questions should be asked) and FALSE indicates the stoppings rules are not met (additional questions are needed)

d2LL

*The second derivative of the log likelihood***Description**

When `usePrior = FALSE`, this function evaluates the second derivative of the log-likelihood evaluated at point θ . When `usePrior = TRUE`, this function evaluates the second derivative of the log-posterior evaluated at point θ .

Usage

```
d2LL(catObj, theta, use_prior)
```

Arguments

<code>catObj</code>	An object of class <code>Cat</code>
<code>theta</code>	A numeric or an integer indicating the value for θ_j
<code>use_prior</code>	A logical indicating whether to use the prior parameters in estimation

Details

This method is only be available using the normal prior distribution

Value

The function returns a numeric of the second derivative of the log-likelihood (or log-posterior) for a respondent's answer profile.

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[Cat](#) and [prior](#) for information on available priors and prior specifications

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

dLL

*The first derivative of the log-likelihood***Description**

When `usePrior = FALSE`, this function evaluates the first derivative of the log-likelihood evaluated at point θ . When `usePrior = TRUE`, this function evaluates the first derivative of the log-posterior evaluated at point θ .

Usage

```
dLL(catObj, theta, use_prior)
```

Arguments

<code>catObj</code>	An object of class <code>Cat</code>
<code>theta</code>	A numeric or an integer indicating the value for θ_j
<code>use_prior</code>	A logical indicating whether to use the prior parameters in estimation

Details

This method is only be available using the normal prior distribution

Value

The function returns a numeric of the derivative of the log-likelihood (or log-posterior) for a respondent's answer profile.

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[Cat](#) and [prior](#) for information on available priors and prior specifications

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

estimateSE	<i>Standard error of the respondent's ability parameter estimate</i>
------------	--

Description

Estimates the standard error for the ability parameter estimate

Usage

```
estimateSE(catObj)
```

Arguments

catObj	An object of class Cat
--------	------------------------

Details

The EAP estimator: The MAP estimator (This is implemented only for the normal prior.) The MLE estimator (When MLE can't be calculated... estimationDefault) The WLE estimator (Brent method)

Value

The function returns a numeric for the standard error for θ_j

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[estimateTheta](#) for estimation of θ

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

estimateTheta	<i>Estimate of the respondent's ability parameter</i>
---------------	---

Description

Calculates the expected value of the ability parameter θ , conditioned on the observed answers and the item calibrations

Usage

```
estimateTheta(catObj)
```

Arguments

catObj An object of class Cat

Details

EAP MAP (This method is only available using the normal prior distribution.) The maximum likelihood (MLE) approach: (Note: When MLE will not work, estimateTheta is calculated according to the estimationDefault slot in Cat object.) The weighted maximum likelihood approach (WLE) approach: Estimating θ_j requires finding the root of the following function using the “Brent” method in the gsl library.

Value

A numeric consisting of the expected value of the ability parameter

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[probability](#) and [likelihood](#)

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

expectedKL	<i>Expected Kullback-Leibler information</i>
------------	--

Description

Calculates the expected Kullback-Leibler information for an individual question item

Usage

```
expectedKL(catObj, item)
```

Arguments

catObj	An object of class Cat
item	An integer indicating the index of the question item

Details

Binary details (Due to the conditional independence assumption, we only need to calculate the expected value for potential new items.)

Value

The function returns a numeric indicating the KL information for the desired item, given the current answer profile and ability parameter estimate

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[likelihoodKL](#) and/or [posteriorKL](#) for alternative KL methods

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

expectedObsInf	<i>Expected Observed Information</i>
----------------	--------------------------------------

Description

Calculates the expected information, which is the observed information attained from a specific response set times the probability of that profile occurring

Usage

```
expectedObsInf(catObj, item)
```

Arguments

catObj	An object of class Cat
item	An integer indicating the index of the question item

Value

The function returns a numeric value of the expected information

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[estimateTheta](#) for calculation of θ and [obsInf](#) for observed information calculation

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

expectedPV

Expected Posterior Variance

Description

Estimates the expected posterior variance for a respondent's estimated ability parameter for an item yet to be answered based on a respondent's ability parameter estimate from the already-answered items

Usage

```
expectedPV(catObj, item)
```

Arguments

catObj	An object of class Cat
item	An integer indicating the index of the question item

Value

A numeric value indicating a respondent's expected posterior variance for a yet to be asked question item

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[probability](#) for probability of responses to individual question item [estimateTheta](#) for estimation of θ

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

fisherInf

*Fisher's Information***Description**

Calculates the expected value of the observed information of the likelihood evaluated at the input value θ

Usage

```
fisherInf(catObj, theta, item)
```

Arguments

catObj	An object of class Cat
theta	A numeric or an integer indicating the potential value for θ_j
item	An integer indicating the index of the question item

Details

For the dichotomous case, this is equivalent to the observed information.

Value

The function returns a numeric of the expected value of the observed information

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[obsInf](#) for observed information calculation and [fisherTestInfo](#) for further application of Fisher's information

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

fisherTestInfo	<i>Fisher's Test Information</i>
----------------	----------------------------------

Description

Calculates the total information gained for a respondent j for all answered items, conditioned on θ .

Usage

```
fisherTestInfo(catObj)
```

Arguments

catObj An object of class Cat

Value

The total information gained for a respondent, given a specific answer set and a value of θ .

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[fisherInf](#) for calculation of Fisher's information for an individual question item

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

getModel	<i>Get methods for slots within Cat class objects</i>
----------	---

Description

These functions access and return the values currently stored in a specified slot of an object of class Cat.

Usage

```
getModel(object)
```

Arguments

object	An object of class Cat to be modified
--------	---------------------------------------

Value

The value stored in the specified slot of the Cat object.

Note

There are getters for every slot in Cat objects, all following the format getSlot: eg. getDiscrimination, getEstimationDefault, getSeThreshold, etc.

Author(s)

AA

See Also

[Cat setters](#)

gpcm-class	<i>Computerized Adaptive Testing Generalize Partial Credit Model</i>
------------	--

Description

This function fits the Generalize Partial Credit Model for ordinal polytomous data and populates the fitted values for discrimination and difficulty parameters to an object of class Cat.

Arguments

data	a data.frame or a numeric matrix of manifest variables.
quadraturePoints	a single numeric value to be passed into the grm function
...	arguments to be passed to methods. For more details about the arguments, see grm .
@return	An object of class Cat with components,

- **difficulty** a named list of difficulty parameters for use with polytomous questions/items. Each element's name tells the question/item to which it applies.
- **guessing** a vector of guessing parameter for each question/item.
- **discrimination** a vector of discrimination parameter for each question/item.
- **answers** a vector of answers to questions as given by the survey respondent.
- **priorName** a character vector of length one giving the prior distribution to use for the latent trait estimates. The options are normal for the normal distribution, cauchy for the Cauchy distribution, are t for the t-distribution. Defaults to normal.
- **priorParams** a numeric vector of parameters for the distribution specified in the priorName slot. See the details section for more information. Defaults to `c(0, 1)`.

Note

In case the Hessian matrix at convergence is not positive definite try to use `start.val="random"`.

Author(s)

AA

See Also

[ltmCat](#), [nextItem](#), [question.path](#)

grm-class	<i>Computerized Adaptive Testing Graded Response Model</i>
-----------	--

Description

This function fits the Graded Response model for ordinal polytomous data and populates the fitted values for discrimination and difficulty parameters to an object of class `Cat`.

Arguments

data a `data.frame` or a numeric matrix of manifest variables.

quadraturePoints a single numeric value to be passed into the `grm` function

... arguments to be passed to methods. For more details about the arguments, see [grm](#).

@return An object of class `Cat` with components,

- **difficulty** a named list of difficulty parameters for use with polytomous questions/items. Each element's name tells the question/item to which it applies.
- **guessing** a vector of guessing parameter for each question/item.
- **discrimination** a vector of discrimination parameter for each question/item.
- **answers** a vector of answers to questions as given by the survey respondent.

- `priorName` a character vector of length one giving the prior distribution to use for the latent trait estimates. The options are `normal` for the normal distribution, `cauchy` for the Cauchy distribution, are `t` for the t-distribution. Defaults to `normal`.
- `priorParams` a numeric vector of parameters for the distribution specified in the `priorName` slot. See the details section for more information. Defaults to `c(0, 1)`.

Note

In case the Hessian matrix at convergence is not positive definite try to use `start.val="random"`.

Author(s)

AA

See Also

[ltmCat](#)

likelihood	<i>Likelihood of the Specified Response Set</i>
------------	---

Description

Calculates the likelihood of a respondent, with ability parameter θ , having offered the specific set of responses stored in the `Cat` objects `answers` slot, conditional on the item-level parameters.

Usage

```
likelihood(catObj, theta)
```

Arguments

<code>catObj</code>	An object of class <code>Cat</code>
<code>theta</code>	A numeric or an integer indicating the value for θ_j

Value

The function returns a numeric value of the likelihood of the respondent having offered the provided response profile.

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[probability](#) for probability of responses to individual question item

Examples

```
## Not run:
## Likelihood for Cat object of the ltm model
data(npi)
cat <- ltmCat(npi)
setAnswers(cat) <- c(1,0,1,0, rep(NA, 35))
likelihood(cat, theta = 1)

## End(Not run)
```

likelihoodKL

*Expected Kullback-Leibler information, weighted by the likelihood***Description**

Calculate the expected Kullback-Leibler information, weighted by the likelihood

Usage

```
likelihoodKL(catObj, item)
```

Arguments

catObj	An object of class Cat
item	An integer indicating the index of the question item

Details

The LKL calculation follows the same procedure as expectedKL, except it requires weighting the different potential values of θ_0 by the likelihood. Thus, the equation is

Binary details:

Due to the conditional independence assumption, we only need to calculate the expected value for potential new items.

Value

A value indicating the LKL information for the desired item, given the current answer profile and ability estimate.

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[expectedKL](#) and/or [posteriorKL](#) for alternative KL methods

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

lookAhead

Look Ahead to Select Next Item

Description

Selects the next item that would be asked for all possible response options to the question the respondent is currently answering

Usage

```
lookAhead(catObj, item)
```

Arguments

catObj	An object of class Cat
item	A numeric indicating the question item the respondent is currently answering.

Value

A vector of values indicating the possible subsequent questions

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[selectItem](#) for selection method information

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

ltm-class

*Computerized Adaptive Testing Latent Trait Model with Binary Data***Description**

This function fits the latent trait model for binary data and populates the fitted values for discrimination, difficulty, and guessing parameters to an object of class Cat.

Arguments

data	a data.frame or a numeric matrix of manifest variables.
object	an object of class Cat to be populated. If omitted, a new object of class Cat is created.
...	arguments to be passed to methods. For more details about the arguments, see tpm .

@return An object of class Cat with components,

- difficulty a named vector of difficulty parameters for use with dichotomous questions/items. Each element's name tells the question/item to which it applies.
- guessing a vector of guessing parameter for each item.
- discrimination a vector of discrimination parameter for each item.
- answers a vector of answers to questions as given by the survey respondent.
- priorName a character vector of length one giving the prior distribution to use for the latent trait estimates. The options are normal for the normal distribution, cauchy for the Cauchy distribution, are t for the t-distribution. Defaults to normal.
- priorParams a numeric vector of parameters for the distribution specified in the priorName slot. See the details section for more information. Defaults to `c(0, 1)`.

Note

In case the Hessian matrix at convergence is not positive definite try to use `start.val="random"`.

Author(s)

AA

See Also[grmCat](#)

makeTree	<i>Make tree of possible question combinations</i>
----------	--

Description

Creates a tree of possible questions asked and stores it as a list of lists (flat = FALSE) or a table of values (flat = TRUE).

Usage

```
makeTree(cat, flat = FALSE)
```

Arguments

cat	an object of class Cat
flat	a logical; TRUE returns tree as a table; FALSE returns tree as a list

Details

Function takes a Cat object and generate a tree of all possible question combinations, conditional on previous answers and current θ estimates. The tree is stored as a list of lists, iteratively generated by filling in a possible answer, calculating the next question via selectItem, filling in a possible answer for that question, and so forth. The length of the tree is dictated by the lengthThreshold slot within the Cat object.

Value

An object of class list

Author(s)

AA

See Also

[selectItem](#) for specific item selection and selection methods

nfc	<i>Need For Cognition dataset from TAPS and AMT</i>
-----	---

Description

Data of survey respondents' respond to 18 NFC questions, which is a reduced version of NFC. For each question, respondents could choose one of five response options: Agree strongly, agree somewhat, neither agree nor disagree, disagree somewhat, disagree strongly. In addition, missingness is optional. Sample variable indicates where the dataset come from: 1 = The American Panel Survey, 2 = Amazon's Mechanical Turk (fall 2014), 3 = Amazon's Mechanical Turk (spring 2015)

Usage

```
data("nfc")
```

Format

A data frame with 4043 observations on the following 20 variables.

NFC1 I really enjoy a task that involves coming up with new solutions to problems
 NFC4 I would prefer a task that is intellectual, difficult, and important to one that is somewhat important but does not require much thought
 NFC10 Learning new ways to think doesnt excite me very much
 NFC12 I usually end up deliberating about issues even when they do not affect me personally
 NFC15 The idea of relying on thought to make my way to the top appeals to me
 NFC16 The notion of thinking abstractly is appealing to me
 NFC19 I only think as hard as I have to
 NFC21 I think tasks that require little thought once I've learned them
 NFC22 I prefer to think about small, daily projects to long-term ones
 NFC23 I would rather do something that requires little thought than something that is sure to challenge my thinking abilities
 NFC24 I find satisfaction in deliberating hard and for long hours
 NFC29 I like to have the responsibility of handing a situation that requires a lot of thinkings
 NFC31 I feel relief rather than satisfaction after completing a task that required a lot of mental effort
 NFC32 Thinking is not my idea of fun
 NFC33 I try to anticipate and avoid situations where there is likely a chance I will have to think in depth about something
 NFC39 I prefer my life to be filled with puzzles that I must solve
 NFC40 I would prefer complex to simple problems
 NFC43 Its enough for me that something gets the job done; I dont care how or why it works
 sample a numeric vector (1=TAPS, 2=AMT(2014), 3=AMT(2015))

Examples

```
data(nfc)
## maybe str(nfc) ; plot(nfc) ...
```

npi

Narcissistic Personality Inventory data

Description

Data from the test with the 40 paired items on one page. Respondents had to choose the one that fit them the best. Missingness is optional. Respondents' demographics were entered on the next page. In addition, they were also asked to affirm that their answers were accurate and suitable for research, those that did not (9%) are not included in this dataset.

Usage

```
data("npi")
```

Format

A data frame with 11243 observations on the following 44 variables.

score a numeric vector indicates the score for each question; see details

Q1 1=I have a natural talent for influencing people. 2=I am not good at influencing people

Q2 1=Modesty doesnt become me. 2=I am essentially a modest person

Q3 1=I would do almost anything on a dare. 2=I tend to be a fairly cautious person

Q4 1=When people compliment me I sometimes get embarrassed. 2=I know that I am good because everybody keeps telling me so.

Q5 1=The thought of ruling the world frightens the hell out of me. 2=If I ruled the world it would be a better place

Q6 1=I can usually talk my way out of anything. 2=I try to accept the consequences of my behavior

Q7 1=I prefer to blend in with the crowd. 2=I like to be the center of attention

Q8 1=I will be a success. 2=I am not too concerned about success

Q9 1=I am no better or worse than most people. 2=I think I am a special person

Q10 1=I am not sure if I would make a good leader. 2=I see myself as a good leader

Q11 1=I am assertive. 2=I wish I were more assertive

Q12 1=I like to have authority over other people. 2=I don't mind following orders

Q13 1=I find it easy to manipulate people. 2=I don't like it when I find myself manipulating people

Q14 1=I insist upon getting the respect that is due me. 2=I usually get the respect that I deserve

Q15 1=I don't particularly like to show off my body. 2=I like to show off my body

Q16 1=I can read people like a book. 2=People are sometimes hard to understand

Q17 1=If I feel competent I am willing to take responsibility for making decisions. 2=I like to take responsibility for making decisions

Q18 1=I just want to be reasonably happy. 2=I want to amount to something in the eyes of the world

Q19 1=My body is nothing special. 2=I like to look at my body

Q20 1=I try not to be a show off. 2=I will usually show off if I get the chance

Q21 1=I always know what I am doing. 2=Sometimes I am not sure of what I am doing

Q22 1=I sometimes depend on people to get things done. 2=I rarely depend on anyone else to get things done

Q23 1=Sometimes I tell good stories. 2=Everybody likes to hear my stories

Q24 1=I expect a great deal from other people. 2=I like to do things for other people

Q25 1=I will never be satisfied until I get all that I deserve. 2=I take my satisfactions as they come

Q26 1=Compliments embarrass me. 2=I like to be complimented

Q27 1=I have a strong will to power. 2=Power for its own sake doesn't interest me

Q28 1=I don't care about new fads and fashions. 2=I like to start new fads and fashions

Q29 1=I like to look at myself in the mirror. 2=I am not particularly interested in looking at myself in the mirror

Q30 1=I really like to be the center of attention. 2=It makes me uncomfortable to be the center of attention

Q31 1=I can live my life in any way I want to. 2=People can't always live their lives in terms of what they want

Q32 1=Being an authority doesn't mean that much to me. 2=People always seem to recognize my authority

Q33 1=I would prefer to be a leader. 2=It makes little difference to me whether I am a leader or not.

Q34 1=I am going to be a great person. 2=I hope I am going to be successful

Q35 1=People sometimes believe what I tell them. 2=I can make anybody believe anything I want them to

Q36 1=I am a born leader. 2=Leadership is a quality that takes a long time to develop

Q37 1=I wish somebody would someday write my biography. 2=I don't like people to pry into my life for any reason

Q38 1=I get upset when people don't notice how I look when I go out in public. 2=I don't mind blending into the crowd when I go out in public

Q39 1=I am more capable than other people. 2=There is a lot that I can learn from other people

Q40 1=I am much like everybody else. 2=I am an extraordinary person

elapse a numeric vector indicates between time submitted and time loaded of the questions; see details

gender a numeric vector indicates the gender of the respondents; see details

age a numeric vector indicates the age of the respondents; see details

Examples

```
data(npi)
## maybe str(npi) ; plot(npi) ...
```

obsInf	<i>Observed Information</i>
--------	-----------------------------

Description

Calculates the observed information of the likelihood evaluated at the input value θ for a specific item

Usage

```
obsInf(catObj, theta, item)
```

Arguments

catObj	An object of class Cat
theta	A numeric or an integer indicating the value for θ_j
item	An integer indicating the index of the question item

Details

The observed information is equivalent to the negative second derivative of the log-likelihood. Note: This function should never be called when the respondent has answered no questions.

Value

The function returns a numeric value of the observed information of the likelihood, given θ , for a specific question item

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[estimateTheta](#) for calculation of θ and [expectedObsInf](#) for further application of observed information

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

polknow

Political Knowledge (circa 2012) of Mechanical Turk Respondents

Description

Data from Amazon Mechanical Turkers responding to 64 political knowledge questions.

Usage

```
data(polknow)
```

Format

A data frame with 810 observations on the following 64 questions.

Q1 How long is one term for the President of the United States?

Eight years; Six years; Four years; Two years

Q2 The FDA is part of the national government primarily responsible for regulating

Food quality; The national parks; Electricity production and energy; Pollution and the environment

Q3 Who is the Vice President of the United States?

Leon Panetta; William Daley; Hillary Clinton; Joe Biden

- Q4 The federal debt is
Much smaller than it was 20 years ago; The difference between imports and exports with foreign countries; The annual difference between spending and tax revenues; The accumulated borrowing of the federal government that has not been repaid
- Q5 How many times can an individual be elected President of the United States under current laws?
Any number of terms; Three times; Twice; Once
- Q6 What do we call the first ten amendments to the Constitution?
The Articles of Confederation; The inalienable right; The Bill of Rights; The Declaration of Independence
- Q7 Is the U.S. federal budget deficit, the amount by which the governments spending exceeds the amount of money it collects, now bigger, about the same, or smaller than it was during most of the 1990s?
Smaller; About the same; Bigger
- Q8 Who signs bills to become laws?
The President; The Vice President; The Chief Justice of the Supreme Court; The Secretary of State
- Q9 Which party is generally more supportive of creating a way for immigrants who are in the U.S. illegally to eventually become citizens?
The Republican Party; The Democratic Party
- Q10 In what month do we vote for the President?
November; October; February; January
- Q11 What are the two parts of the U.S. Congress?
The Senate and the Supreme Court; The House of Lords and the House of Commons; The House of Representative and the Supreme Court; The Senate and House of Representatives
- Q12 Which party is generally more supportive of restricting access to abortion?
The Republican Party; The Democratic Party
- Q13 Which of these political parties is considered most conservative?
Green Party; Republican Party; Democratic Party
- Q14 The NRA is an organization that advocates for
Clean elections; A cleaner environment; The rights of gun owners; Women's rights
- Q15 Compared to 30 years ago, is the difference in incomes between the top 20% of households and the bottom 20% of households now bigger, smaller, or the same?
The difference is now the same as 30 years ago; The difference is now smaller than 30 years ago; The difference is now bigger than 30 years ago
- Q16 The EPA is part of the national government primarily responsible for regulating
Food quality; The national parks; Electricity production and energy; Pollution and the environment
- Q17 Which party is generally more supportive of reducing the size of the defense budget?
The Republican Party; The Democratic Party
- Q18 Which party is generally more supportive of increasing taxes on higher income people to reduce the federal budget deficit?
The Republican Party; The Democratic Party
- Q19 Which party is generally more supportive of allowing drilling for oil in the Arctic National Wildlife Refuge?
The Republican Party; The Democratic Party

- Q20 Who is the Commander in Chief of the military?
The Attorney General; The President; The Secretary of Defense; The Vice President
- Q21 The First Amendment to the United States Constitution guarantees all of these rights EXCEPT
Right to remain silent; Right to the free exercise of religion; Right to free speech; Right to peaceably assemble
- Q22 Roe v Wade is a case decided by the Supreme Court that relates to
Executive power; Campaign finance; Birth control; Abortion
- Q23 Social Security is
Funded by the personal income tax; Operated by state government; The responsibility of the Department of Defense; The benefit program for senior citizens
- Q24 What is Medicare?
A private, non-profit organization that runs free health clinic; A private health insurance plan sold to individuals in all 50 states; A program run by state governments to provide health care to poor people; A program run by the U.S. federal government to pay for old people's health care
- Q25 How many senators are elected from each state?
It depends on the population of the state; Four; Two; One
- Q26 How many votes are required in Congress to override a presidential veto
A simple majority of both houses of Congress; A simple majority of one house of Congress; A two-thirds majority of both houses of Congress; A two-thirds majority of one house of Congress
- Q27 The Secretary of State
Serves a two-year term; Serves the state governments; Is nominated by the president; Heads the armed services
- Q28 Near the end of an election campaign, a polls shows that an issue that no candidate has mentioned is of great concern to voters. What is most likely to happen?
Some candidates will drop out of the race; Candidates will start talking about the issue; Newspapers will not report the results of the poll; The election will be postponed
- Q29 Liberals are generally said to
Support pro-life policies; Oppose all tax increases; Support military spending; Support government programs to give government assistance the needy
- Q30 Which party is generally more supportive of reducing the size and scope of the federal government?
The Republican Party; The Democratic Party
- Q31 The ability of a minority of senators to prevent a vote on a bill is known as
Suspension of the rules; Enrollment; A veto; A filibuster
- Q32 conservatives are generally said to
Support pro-choice policies; Support tax cuts; Oppose military spending; Support government programs to give government assistance to the needy
- Q33 Which of these regions of the country is generally considered to be most supportive of Republican candidates
Midwest; South; West Coast; New England
- Q34 The presiding officer in the House of Representatives is
The Majority Leader; The Sergeant at Arms; The Vice President of the United States; The Speaker

- Q35 Which of these countries is NOT a permanent member of the U.N. Security Council
United Kingdom; France; India; China
- Q36 Which part has a majority of seats in the U.S. House of Representatives?
Neither; Democrats; Republicans
- Q37 What state holds the first primary election in Presidential primaries?
Florida; Nevada; South Carolina; New Hampshire
- Q38 Who is the Speaker of the House of Representatives?
Mitt Romney; Eric Holder; Harry Reid; John Boehner
- Q39 Most cases are considered by the Supreme Court
In even-numbered years; At the request of the Congress; Upon order of the president; With the approval of at least four justices
- Q40 How many Justices typically serve on the U.S. Supreme Court
Eleven; Nine; Eight; Seven
- Q41 What job or political office is no held by Ben Bernanke?
None of these; Minority Whip of the U.S. House; Chief Justice of the United States Supreme Court; Majority leader of the U.S. Senate, Chairman of the Federal Reserve
- Q42 Whose responsibility is it to nominate judges to the Federal Courts
The state governors; The Supreme Court; Congress; President
- Q43 Who is the Chief Justice of the U.S. Supreme Court?
Larry Thompson; Anthony Kennedy; David Cole; John Roberts
- Q44 The U.S. Senate
Votes to confirm nominees to the U.S. Supreme court chosen by the House of Representatives; Plays no role in choosing the members of the U.S. Supreme Court; Chooses members of the U.S. Supreme Court; Votes to confirm nominees to the U.S. Supreme Court chosen by the President
- Q45 Which party has a majority of seats in the U.S. Senate
Neither; Democrats; Republicans
- Q46 Which of the states listed below has the greatest number of electoral college votes in the U.S. Presidential Elections?
Puerto Rico; Nevada; North Dakota; Washington, D.C.
- Q47 Citizens United v the FEC is a case decided by the Supreme Court that relates to
Executive power; Campaign finance; Birth control; Abortion
- Q48 For how many years is a United States Senator elected that is, how many years are there in one full term of office for a U.S. Senator?
None of these; Eight years; Six years; Four years; Two years
- Q49 Who is the Prime Minister of the United Kingdom?
Richard Branson; Tony Hayward; Nick Clegg; David Cameron
- Q50 The president of Afghanistan is named
Bashar al-Assad; Hosni Mubarak; Hamid Karzai; Nouri al-Maliki
- Q51 The House of Representatives has how many voting members?
Four hundred and forty-one; Four hundred and thirty-five; Two hundred; One hundred
- Q52 The President of the Senate is
The Majority Leader; The Sergeant at Arms; The Vice President of the United States; The senior senator of the majority party

- Q53 On which of the following federal programs is the most money spent each year?
Medicare; Education; Subsidies to farmers; Aid to foreign countries
- Q54 What do all constitutional governments have?
Separation of church and state; A bill of rights; A President as the head of government; Limits on political power
- Q55 One which of the following does the U.S. federal government spend the least money?
Social Security; National defense; Medicare; Foreign aid
- Q56 The head of the Department of Justice is
Kathleen Sebelius; Eric Holder; Timothy Geithner; Hillary Clinton
- Q57 The president may NOT
Declare war; Pardon criminals without justification; Appoint federal officials when Congress is in recess; Refuse to sign legislation passed by Congress
- Q58 Which of these is NOT primarily the responsibility of the Federal government in Washington?
Interstate commerce; Negotiating treaties with foreign countries; Education; National defense
- Q59 Who is the current president of Mexico?
Vincente Fox; Hugo Chavez; Dilma Rousseff; Felipe Calderon
- Q60 Which of the following actions does the United States federal government commonly take to finance a budget deficit?
Expanding public-works projects; Borrowing from the public; Imposing import quotas; Printing more money
- Q61 Common Cause is an organization that advocates for
Women's rights; Clean elections; A cleaner environment; The right of gun owners
- Q62 The Byrd Rule is relevant
During the confirmation of cabinet members; For national party conventions; During Congressional debates over non-budgetary policies; For the Reconciliation process
- Q63 The Majority Leader of the House of Representative is
Nancy Pelosi; Kevin McCarthy; Eric Cantor; John Boehner
- Q64 On which of the following does the U.S. federal government spend the most money each year?
Education; Medicare; Interest on the national debt; National defense

Source

<https://dataverse.harvard.edu/dataset.xhtml?persistentId=hdl:1902.1/19381>

References

Jacob M. Montgomery and Joshua Cutler. 2013. "Computerized Adaptive Testing for Public Opinion Surveys." *Political Analysis* (Spring 2013) 21 (2): 172-192.

posteriorKL	<i>Expected Kullback-Leibler information, weighted by the posterior</i>
-------------	---

Description

Calculate the expected Kullback-Leibler information, weighted by the posterior

Usage

```
posteriorKL(catObj, item)
```

Arguments

catObj	An object of class Cat
item	An integer indicating the index of the question item

Details

We will follow the same procedure as `expectedKL`, except we will weight the different potential values of θ_0 by the posterior.

Due to the conditional independence assumption, we only need to calculate the expected value for potential new items.

Value

A value indicating the posterior KL information for the desired item, given the current answer profile and ability estimate.

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[likelihoodKL](#) and/or [expectedKL](#) for alternative KL methods

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

prior	<i>Prior Value</i>
-------	--------------------

Description

Calculates the density at x of either the normal, student's t , or uniform distribution

Usage

```
prior(x, dist, params)
```

Arguments

<code>x</code>	A numeric value at which to evaluate the prior
<code>dist</code>	A string indicating the distribution (slot <code>priorName</code> of <code>Cat</code> object)
<code>params</code>	A length two numeric vector indicating the parameters of the distribution (slot <code>priorParams</code> of <code>Cat</code> object)

Details

The *dist* argument needs to be either "UNIFORM", "NORMAL", or "STUDENT_T".

When *dist* is "NORMAL", the first element of *params* is the mean, the second element is the standard deviation. When *dist* is "STUDENT_T", the first element of *params* is the non-centrality parameters and the second is degrees of freedom. When *dist* is "UNIFORM", the elements of *params* are the lower and upper bounds, of the interval, respectively. Note that the "UNIFORM" is only applicable for the "EAP" estimation method.

Value

A scalar consisting of prior value, $\pi(x)$, given the value x

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

This function uses Boost C++ source libraries for the uniform and Student's t distributions and calls `dnorm4` written in C which is identical to that of `dnorm` in R.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[Cat](#) for information on `priorName` and `priorParams` slots

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

cat@priorName <- "NORMAL"
cat@priorParams <- c(0, 1) ## Parameters are mean and standard deviation
prior(x = 1, cat@priorName, cat@priorParams)

cat@priorName <- "STUDENT_T"
cat@priorParams <- c(1, 3) ## Parameters are non-centrality param and degrees of freedom
prior(x = 1, cat@priorName, cat@priorParams)

cat@priorName <- "UNIFORM"
cat@priorParams <- c(-1, 1) ## Parameters are lower bound and upper bound of interval
prior(x = 1, cat@priorName, cat@priorParams)

## End(Not run)
```

probability	<i>Probability of Responses to a Question Item or the Left-Cumulative Probability of Responses</i>
-------------	--

Description

Calculates the probability of specific responses or the left-cumulative probability of responses to item conditioned on a subject's ability (θ)

Usage

```
probability(catObj, theta, item)
```

Arguments

catObj	An object of class Cat
theta	A numeric or an integer indicating the value for θ_j
item	An integer indicating the index of the question item

Details

For the ltm model, the probability of non-zero response for respondent j on item i is

$$Pr(y_{ij} = 1|\theta_j) = \frac{\exp(a_i + b_i\theta_j)}{1 + \exp(a_i + b_i\theta_j)}$$

where θ_j is respondent j 's position on the latent scale of interest, a_i is item i 's discrimination parameter, b_i is item i 's difficulty parameter, and c_i is item i 's guessing parameter.

For the tpm model, the probability of non-zero response for respondent j on item i is

$$Pr(y_{ij} = 1|\theta_j) = c_i + (1 - c_i) \frac{\exp(a_i + b_i\theta_j)}{1 + \exp(a_i + b_i\theta_j)}$$

where θ_j is respondent j 's position on the latent scale of interest, a_i is item i 's discrimination parameter, b_i is item i 's difficulty parameter, and c_i is item i 's guessing parameter.

For the grm model, the probability of a response in category k **or lower** for respondent j on item i is

$$Pr(y_{ij} < k|\theta_j) = \frac{\exp(\alpha_{ik} - \beta_i\theta_{ij})}{1 + \exp(\alpha_{ik} - \beta_i\theta_{ij})}$$

where θ_j is respondent j 's position on the latent scale of interest, α_{ik} the k -th element of item i 's difficulty parameter, β_i is discrimination parameter vector for item i . Notice the inequality on the left side and the absence of guessing parameters.

For the gpcm model, the probability of a response in category k for respondent j on item i is

$$Pr(y_{ij} = k|\theta_j) = \frac{\exp(\sum_{t=1}^k \alpha_i[\theta_j - (\beta_i - \tau_{it})])}{\sum_{r=1}^{K_i} \exp(\sum_{t=1}^r \alpha_i[\theta_j - (\beta_i - \tau_{it})])}$$

where θ_j is respondent j 's position on the latent scale of interest, α_i is the discrimination parameter for item i , β_i is the difficulty parameter for item i , and τ_{it} is the category t threshold parameter for item i , with $k = 1, \dots, K_i$ response options for item i . For identification purposes $\tau_{i0} = 0$ and $\sum_{t=1}^1 \alpha_i[\theta_j - (\beta_i - \tau_{it})] = 0$.

Value

When the argument `catObj` is an `ltm` model, the function `probability` returns a numeric vector of length one representing the probability of observing a non-zero response.

When the argument `catObj` is an `tpm` model, the function `probability` returns a numeric vector of length one representing the probability of observing a non-zero response.

When the argument `catObj` is a `grm` model, the function `probability` returns a numeric vector of length $k+1$, where k is the number of possible responses. The first element will always be zero and the k th element will always be one. The middle elements are the cumulative probability of observing response k or lower.

When the argument `catObj` is a `gpcm` model, the function `probability` returns a numeric vector of length k , where k is the number of possible responses. Each number represents the probability of observing response k .

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

References

- Baker, Frank B. and Seock-Ho Kim. 2004. Item Response Theory: Parameter Estimation Techniques. New York: Marcel Dekker.
- Choi, Seung W. and Richard J. Swartz. 2009. <e2><80><9c>Comparison of CAT Item Selection Criteria for Polytomous Items.<e2><80><9d> Applied Psychological Measurement 33(6):419<e2><80><93>440.
- Muraki, Eiji. 1992. "A generalized partial credit model: Application of an EM algorithm." ETS Research Report Series 1992(1): 1-30.
- van der Linden, Wim J. 1998. <e2><80><9c>Bayesian Item Selection Criteria for Adaptive Testing.<e2><80><9d> Psychometrika 63(2):201<e2><80><93>216.

See Also

[Cat](#) for information on the item parameters: discrimination, difficulty, and guessing.

Examples

```
## Not run:
## Probability for Cat object of the ltm model
data(npi)
cat <- ltmCat(npi)
probability(cat, theta = 1, item = 1)

## Probability for Cat object of the tpm model
data(polknow)
cat <- tpmCat(polknow)
probability(cat, theta = 1, item = 1)

## Probability for Cat object of the grm model
data(nfc)
cat <- grmCat(nfc)
probability(cat, theta = 1, item = 1)

## End(Not run)
```

selectItem

Select the next item in the question set

Description

Selects the next item in the question set based on the specified method

Usage

```
selectItem(catObj)
```

Arguments

catObj An object of class Cat

Details

The EPV method:

This function takes in a Cat object from R and constructs the C++ representation. It then calculates the expected posterior variance for each unanswered item.

The function returns a list with the following two elements: `all.estimates`: A data frame with two columns. The first column ("questions") should be the index of the question items and the second column ("EPV") of the expected posterior variance for that corresponding item. There are as many rows in this data frame as there are unanswered questions in the battery. `next.item`: A numeric vector with the index of the item with the lowest EPV value.

See `expectedPV` for mathematical details.

The MFI method:

This function takes a Cat object and calculates Fisher's information for each unanswered item. It then finds the one item that maximizes Fisher's information, based on the respondent's position on the latent trait from the answered items.

The function returns a list with the following two elements: `all.estimates`: A data frame with two columns. The first column ("questions") should be the index of the question items and the second column of the expected posterior variance for that corresponding item. There are as many rows in this data frame as there are unanswered questions in the battery. `next.item`: A numeric vector with the index of the item with the highest Fisher's information value.

See `fisherInf` for mathematical details.

The MLWI method:

This function calculates the likelihood for each value of X at the input value of θ . Evaluates the integral over a measure of the plausibility of possible values of θ by weighting Fisher's information with the likelihood function and selecting the next question according to:

The MPWI method:

This function calculates the likelihood for each value of X at the input value of θ . Evaluates the integral over a measure of the plausibility of possible values of θ by weighting Fisher's information with the likelihood function and selecting the next question according to:

The MEI method:

This function estimates the expected observed information for a respondent's estimated position on the latent trait on an unanswered item based on the respondent's position on the latent trait calculated from answered items.

The output should be a single numeric value.

Binary details:

Categorical details:

The KL method:

This procedure chooses the next item with the largest KL value.

See `expectedKL`, `likelihoodKL`, and/or `posteriorKL` for mathematical details.

The MFII method:

This approach chooses items based on the Fisher's information in an interval near the current estimate $\hat{\theta}$.

$$FII_i = \int_{\hat{\theta}-\delta}^{\hat{\theta}+\delta} I_i(\theta_0) d\theta_0$$

where

$$\delta = z(I(\hat{\theta}))^{-1/2}$$

, $I(\hat{\theta})$ is the test information for respondent j evaluated at $\hat{\theta}$,

$$I_i(\cdot)$$

is the Fisher's information for item i , and z is a user specified z-value.

The random method:

This routine serves as a baseline for comparison. The routine simply selects an unanswered question at random.

Value

It returns a list with two elements: (1) A dataframe containing a column with the indexes of unasked questions and a column with the values (calculated by the specified selection method) for those items, and (2) a numeric containing the index of the question that should be asked next.

Note

This function is to allow users to access the internal functions of the package. During item selection, all calculations are done in compiled C++ code.

Author(s)

Haley Acevedo, Ryden Butler, Josh W. Cutler, Matt Malis, Jacob M. Montgomery, Tom Wilkinson, Erin Rossiter, Min Hee Seo, Alex Weil

See Also

[estimateTheta](#) for calculation of θ ; [obsInf](#) for observed information calculation; [fisherTestInfo](#) for Fisher's information calculation; [expctedKL](#) for expected Kullback-Leibler calculation; [likelihoodKL](#) for likelihood Kullback-Leibler calculation; [posteriorKL](#) for posterior Kullback-Leibler calculation;

Examples

```
## Not run:
## Prior calculation using Cat object of the ltm model
## specifying different distributions
data(npi)
cat <- ltmCat(npi)

## End(Not run)
```

setGuessing<-	<i>Set methods for slots within Cat class objects</i>
---------------	---

Description

This functions replaces the values currently stored in a specified slot of an object of class Cat with the user-provided values.

Usage

```
setGuessing(object) <- value
```

Arguments

object	An object of class Cat to be modified
value	The value to replace the current value stored in the specified slot of the Cat
valid	Boolean for whether to check validity of object before allowing setter method to execute, default to TRUE

Value

Modifies the Cat object that was provided by the user, and returns the modified object

Note

There are setters for every slot in Cat objects, all following the format setSlot: eg. setDiscrimination, setEstimationDefault, setSeThreshold, etc.

Author(s)

AA

See Also

[Cat](#)

storeAnswer	<i>Computerized Adaptive Testing Survey Store Answer Function</i>
-------------	---

Description

This function updates the object of class Cat by storing the answer to item k into questions data frame.

Usage

```
storeAnswer(cat, item, answer)
```

Arguments

cat	An object of class Cat
item	The question for which to estimate the expected posterior variance for a respondent with a latent trait estimate of $\theta_{i,h}$. This should be the name of a row in the "questions" data-frame in the "questions" slot of a Cat object.
answer	The answer to the item k to be stored

Value

An updated object of class Cat containing the answers to k items

Author(s)

AA

See Also

[three.pl](#), [likelihood](#), [prior.value](#), [estimateTheta](#), [estimateSE](#), [expectedPV](#), [nextItem](#), [debugNextItem](#)

tpm-class

Computerized Adaptive Testing Latent Trait Model with Binary Data

Description

This function fits the latent trait model for binary data and populates the fitted values for discrimination, difficulty, and guessing parameters to an object of class Cat.

Arguments

data	a <code>data.frame</code> or a numeric matrix of manifest variables.
object	an object of class Cat to be populated. If omitted, a new object of class Cat is created.
...	arguments to be passed to methods. For more details about the arguments, see tpm .
@return	An object of class Cat with components, <ul style="list-style-type: none"> • <code>difficulty</code> a named vector of difficulty parameters for use with dichotomous questions/items. Each element's name tells the question/item to which it applies. • <code>guessing</code> a vector of guessing parameter for each item. • <code>discrimination</code> a vector of discrimination parameter for each item. • <code>answers</code> a vector of answers to questions as given by the survey respondent. • <code>priorName</code> a character vector of length one giving the prior distribution to use for the latent trait estimates. The options are <code>normal</code> for the normal distribution, <code>cauchy</code> for the Cauchy distribution, are <code>t</code> for the t-distribution. Defaults to <code>normal</code>. • <code>priorParams</code> a numeric vector of parameters for the distribution specified in the <code>priorName</code> slot. See the details section for more information. Defaults to <code>c(0, 1)</code>.

Note

In case the Hessian matrix at convergence is not positive definite try to use `start.val="random"`.

Author(s)

AA

See Also

[grmCat](#)

Index

*Topic **datasets**

nfc, [20](#)

npi, [21](#)

polknow, [24](#)

Cat, [5](#), [6](#), [14](#), [30](#), [33](#), [36](#)

Cat-class, [2](#)

checkStopRules, [3](#)

d2LL, [5](#)

debugNextItem, [37](#)

dLL, [6](#)

estimateSE, [7](#), [37](#)

estimateTheta, [7](#), [8](#), [10](#), [11](#), [24](#), [35](#), [37](#)

expctedKL, [35](#)

expectedKL, [9](#), [18](#), [29](#)

expectedObsInf, [10](#), [24](#)

expectedPV, [11](#), [37](#)

fisherInf, [12](#), [13](#)

fisherTestInfo, [12](#), [13](#), [35](#)

getAnswers (getModel), [14](#)

getDifficulty (getModel), [14](#)

getDiscrimination (getModel), [14](#)

getEstimation (getModel), [14](#)

getEstimationDefault (getModel), [14](#)

getGainOverride (getModel), [14](#)

getGainThreshold (getModel), [14](#)

getGuessing (getModel), [14](#)

getInfoThreshold (getModel), [14](#)

getLengthOverride (getModel), [14](#)

getLengthThreshold (getModel), [14](#)

getLowerBound (getModel), [14](#)

getModel, [14](#)

getPriorName (getModel), [14](#)

getPriorParams (getModel), [14](#)

getSelection (getModel), [14](#)

getSeThreshold (getModel), [14](#)

getUpperBound (getModel), [14](#)

getZ (getModel), [14](#)

gpcm-class, [14](#)

grm, [14](#), [15](#)

grm-class, [15](#)

grmCat, [19](#), [38](#)

initialize, Cat-method (Cat-class), [2](#)

likelihood, [8](#), [16](#), [37](#)

likelihoodKL, [9](#), [17](#), [29](#), [35](#)

lookAhead, [18](#)

ltm-class, [19](#)

ltmCat, [15](#), [16](#)

makeTree, [20](#)

nextItem, [15](#), [37](#)

nfc, [20](#)

npi, [21](#)

obsInf, [10](#), [12](#), [23](#), [35](#)

polknow, [24](#)

posteriorKL, [9](#), [18](#), [29](#), [35](#)

prior, [5](#), [6](#), [30](#)

prior.value, [37](#)

probability, [8](#), [11](#), [17](#), [31](#)

question.path, [15](#)

selectItem, [18](#), [20](#), [33](#)

setAnswers (setGuessing<-), [36](#)

setDifficulty (setGuessing<-), [36](#)

setDiscrimination (setGuessing<-), [36](#)

setEstimation (setGuessing<-), [36](#)

setEstimationDefault (setGuessing<-), [36](#)

setGainOverride (setGuessing<-), [36](#)

setGainThreshold (setGuessing<-), [36](#)

setGuessing (setGuessing<-), [36](#)

setGuessing<-, [36](#)

setInfoThreshold (setGuessing<-), [36](#)

setLengthOverride (setGuessing<-), [36](#)

setLengthThreshold (setGuessing<-), [36](#)

setLowerBound (setGuessing<-), [36](#)

setPoly (getModel), [14](#)

setPoly (setGuessing<-), [36](#)

setPriorName (setGuessing<-), [36](#)

setPriorParams (setGuessing<-), [36](#)

setSelection (setGuessing<-), [36](#)

setSeThreshold (setGuessing<-), [36](#)
setters, [14](#)
setUpperBound (setGuessing<-), [36](#)
setZ (setGuessing<-), [36](#)
storeAnswer, [36](#)

three.pl, [37](#)
tpm, [19](#), [37](#)
tpm-class, [37](#)