

# Lab 1

Carmen Canedo

May 23, 2020

## About

For this lab, I used the GPS tracking app on my iPhone, myTracker, to trace myself walking a straight path outside of my house in Nashville, TN. I tried to maintain a steady pace as I walked up and down the street.

Below you will find an analysis of my path that was created using R statistical software. My code is available below, but my step by step process can be found on my GitHub page.

## Necessary Packages

```
library(mdsr)
library(XML)
library(OpenStreetMap)
library(lubridate)
library(ggmap)
library(raster)
library(sp)
```

## Getting the data ready

### Loading in data

```
walking <- read.csv("lab-1.csv", header = TRUE)
```

### Cleaning data

```
###Getting rid of unnecessary columns
```

```
walking <- walking %>%
  dplyr::select(-type, -desc, -name)
```

### Making column names simpler

```
walking <- walking %>%
  rename(altitude = altitude..ft.) %>%
  rename(speed = speed..mph.) %>%
  rename(distance_mi = distance..mi.) %>%
  rename(distance_int_ft = distance_interval..ft.)
```

## Summary stats calculations

```
sum_latitude <- favstats( ~ latitude, data = walking)

sum_longitude <- favstats( ~ longitude, data = walking)

sum_altitude <- favstats( ~ altitude, data = walking)

sum_speed <- favstats( ~ speed, data = walking)

sum_distance_mi <- favstats( ~ distance_mi, data = walking)

sum_dist_int_ft <- favstats( ~ distance_int_ft, data = walking)
```

## Results

*# Results*

sum\_latitude

```
##      min      Q1 median      Q3      max      mean      sd  n missing
## 36.18001 36.18029 36.1806 36.18091 36.18117 36.1806 0.0003514294 221      0
```

sum\_longitude

```
##      min      Q1 median      Q3      max      mean      sd  n
## -86.74297 -86.74294 -86.7429 -86.74286 -86.74278 -86.7429 4.645446e-05 221
## missing
##      0
```

sum\_altitude

```
##      min      Q1 median      Q3      max      mean      sd  n missing
## 500.8 505.8 511.2 512.4 516.1 509.3181 4.041696 221      0
```

sum\_speed

```
##      min      Q1 median      Q3      max      mean      sd  n missing
##      0 2.275      2.7 3.325 10 2.839545 1.226507 220      1
```

```
sum_distance_mi
```

```
##   min    Q1 median    Q3   max      mean      sd    n missing
##     0 0.047   0.09 0.137 0.181 0.09093213 0.05260591 221      0
```

```
sum_dist_int_ft
```

```
##   min    Q1 median    Q3   max      mean      sd    n missing
##     0 3.14   4.01 5.29 14.58 4.32362 1.937173 221      0
```


## Analysis

- Question 1:
  - The standard deviation is larger for latitude.
- Question 2:
  - This tells us that the latitude moves farther from the mean latitude.

## Creating Latitude v. Longitude Scatter Plot

```
lat_v_long <- walking %>%
  ggplot(aes(x = longitude, y = latitude)) +
  geom_point(alpha = 0.8, aes(color = speed), size = 3) +
  scale_color_gradient(low = "blue", high = "red") +
  theme_minimal() +
  labs(title = "Longitude versus Latitude",
       subtitle = "Carmen Canedo",
       caption = "STAT 202, Summer 2020",
       x = "Longitude",
       y = "Latitude",
       color = "Speed (mph)")

lat_v_long
```




STAT 202, Summer 2020

### Adding Line of Best Fit

```
lat_v_long <- lat_v_long +  
  geom_smooth(method = "lm")
```

```
lat_v_long
```

```
## 'geom_smooth()' using formula 'y ~ x'
```



## Simple Linear Regression Results

```
# Calculating model
model <- lm(latitude ~ longitude, data = walking)

# Finding correlation coefficient
coef(model)
```

```
## (Intercept)  longitude
## 651.652871    7.095362
```

Formula for line of best fit:  $latitude = 651.653 + 7.0954(longitude)$

## Analysis

- Is the line of best fit a good tool to estimate the path traveled? Why or why not?
- How does the correlation help you answer part b?

## Mapping the route

I referenced exercises from [here](#)

## Getting the data

In order to ensure that all the values work when mapped, this equation places the vectors correctly.

```
# Function to shift vectors
shift_vec <- function(vector, shift) {
  if (length(vec) <= abs(shift)) {
    rep(NA, length(vec))
  } else {
    if (shift >= 0) {
      c(rep(NA, shift), vec[1:(length(vec) - shift)])
    } else {
      c(vec[(abs(shift) + 1):length(vec)])
    }
  }
}
```

## Reading in GPX file

```
# Limits to 10 digits
options(digits = 10)

# Parsing the GPX file
parsed_file <- htmlTreeParse(file = "lab-1-raw-data.gpx",
                             error = function(...) {},
                             useInternalNodes = TRUE)

# Get all times and coordinates via the respective xpath
times <- xpathSApply(parsed_file, path = "//trkpt/time", xmlValue)
coords <- xpathSApply(parsed_file, path = "//trkpt", xmlAttrs)

# Extract latitude and longitude from the coordinates
lats <- as.numeric(coords["lat",])
lons <- as.numeric(coords["lon",])
```

## Putting values into dataframe

This allows us to have all of the GPX file in one place, ready to be placed onto a map.

```
geodf <- data.frame(lat = lats, lon = lons, time = times)
```

## Querying map background

I used my Google API to access the static map used below.


```
street <- get_map(location = "409 N 15th St., Lockeland Springs, Nashville, Tennessee",
                  zoom = 19,
                  maptype = "roadmap")
```

## Finished product

```
# Plotting points
path <- ggmap(street) +
  geom_point(data = geodf,
             aes(x = lon, y = lat),
             size = 1,
             alpha = 0.7,
             color = "red")

# Adding details
path <- path +
  labs(x = "Longitude",
       y = "Latitude",
       title = "Walking Path Plotted using myTracks",
       subtitle = "Carmen Canedo",
       caption = "STAT 202, Summer 2020")

path
```



## Conclusion

- What was learned

- Et cetera