Carmen Morales Bonet	DWEC
INSTALACIÓN DE LAMP SERVER	

## Creación del host virtual carmen.dwes.

Fichero /etc/apache2/sites-enables/dwes.conf

```
# The ServerName directive sets the request scheme, hostname and port that
# the server uses to identify itself. This is used when creating
# redirection URLs. In the context of virtual hosts, the ServerName
# specifies what hostname must appear in the request's Host: header to
# match this virtual host. For the default virtual host (this file) this
# value is not decisive as it is used as a last resort host regardless.
# However, you must set it for any further virtual host explicitly.

ServerName carmen.dwes

ServerAdmin carmenmb@admin
DocumentRoot /var/www/web
DirectoryIndex /html/index.html /html/registro.html

# Available loglevels: trace8, ..., trace1, debug, info, notice, warn,
# error, crit, alert, emerg.
# It is also possible to configure the loglevel for particular
# modules, e.g.
#LogLevel info ssl:warn

ErrorLog ${APACHE_LOG_DIR}/error.log
CustomLog ${APACHE_LOG_DIR}/access.log combined

# For most configuration files from conf-available/, which are
# enabled or disabled at a global level, it is possible to
# include a line for only one particular virtual host. For example the
# following line enables the CGI configuration for this host only
# after it has been globally disabled with "a2disconf".
#Include conf-available/serve-cgi-bin.conf

C/VirtualHost>
```

- El nombre de dominio del host virtual de la página web de prueba será carmen.dwes.
- El DocumentRoot es el directorio /var/www/web.
- El DirectoryIndex es /html/index.html ya que es donde está la página de inicio.



Si accedemos en Windows desde el navegador, podemos acceder a la página principal del proyecto.

Carmen Morales Bonet	DWEC
INSTALACIÓN DE LAMP SERVER	

## Creación del host virtual www.carmen.alberti.com

Fichero /etc/apache2/sites-enabled/carmen.alberti.conf

```
<VirtualHost *:80>
          # The ServerName directive sets the request scheme, hostname and port that
          # the server uses to identify itself. This is used when creating # redirection URLs. In the context of virtual hosts, the ServerName
          # specifies what hostname must appear in the request's Host: header to
          # match this virtual host. For the default virtual host (this file) this
# value is not decisive as it is used as a last resort host regardless.
          # However, you must set it for any further virtual host explicitly.
          ServerName www.carmen.alberti.com
          ServerAdmin webmaster@localhost
          DocumentRoot /var/www/prueba
          DirectoryIndex index.html index.php
          # Available loglevels: trace8, ..., trace1, debug, info, notice, warn,
          # error, crit, alert, emerg.
          # It is also possible to configure the loglevel for particular
          # modules, e.g.
#LogLevel info ssl:warn
          ErrorLog ${APACHE_LOG_DIR}/error.log
CustomLog ${APACHE_LOG_DIR}/access.log combined
          # For most configuration files from conf-available/, which are # enabled or disabled at a global level, it is possible to
          # include a line for only one particular virtual host. For example the
          # following line enables the CGI configuration for this host only
# after it has been globally disabled with "a2disconf".
#Include conf-available/serve-cgi-bin.conf
 VirtualHost>
```

- El nombre de dominio del host virtual de la página web de prueba será carmen.dwes.
- El DocumentRoot es el directorio /var/www/prueba.
- El DirectoryIndex es index.html y, en su defecto si no se encuentra, index.php.



Vemos la salida de la funcion phpinfo() del fichero index.php si accedemos desde el navegador instalado en la máquina física.