



# Java Programming with JDBC

1. JDBC 개요
2. JDBC Coding 절차
3. SELECT / UPDATE
4. Statement/ PreparedStatement

# JDBC ( Java Database Connectivity )

□ 자바 언어에서 Database에 접근할 수 있게 해주는 Programming API





# JDBC Driver Download – Oracle ( www.oracle.com )

Oracle JDBC drivers v9.2.0.1 – Microsoft Internet Explorer

주소(D) http://www.oracle.com/technology/software/tech/java/sqlj\_jdbc/htdocs/jdbc9201.html

ORACLE.COM TECHNOLOGY NETWORK PARTNERS STORE SUPPORT (Sign In / Register for a free)

SELECT COUNTRY

Downloads Documentation Discussion Forums Articles Sample Code Training RSS XML Resources For

search site

**PRODUCT CENTERS**  
Database  
Middleware  
Enterprise Management  
Applications Technology  
More...

**TECHNOLOGY CENTERS**  
BI & Data Warehousing  
Grid  
Java Developer  
Linux  
.NET Developer  
PHP Developer  
Security  
Service-Oriented Architecture  
Windows  
XML  
More...

**COMMUNITY**

## Oracle9i 9.2.0.5 JDBC Drivers

- [JavaDoc](#) (3,619,840 bytes)
- [Release 9.2.0.5 README](#)

The following files are all 100% pure Java and are used with both the Thin and OCI drivers. To use the OCI driver you must also download the appropriate shared library or DLL files.

**For use with JDK 1.4**

- [ojdbc14.jar](#) - JDBC classes (1,200,046 bytes)
- [ojdbc14\\_g.jar](#) - JDBC classes with debug and trace (1,412,487 bytes)
- [ocrs12.zip](#) - Additional RowSet support (37,194 bytes)

**For use with JDK 1.2 and JDK 1.3**

- [classes12.zip](#) - JDBC classes (1,232,604 bytes)
- [classes12\\_g.zip](#) - JDBC classes with debug and trace (1,472,511 bytes)
- [classes12dms.jar](#) - JDBC classes for use with Enterprise Manager (1,227,695 bytes)
- [classes12dms\\_g.jar](#) - JDBC classes for use with EM and with debug and trace (1,467,919 bytes)
- [ocrs12.zip](#) - Additional RowSet support (37,194 bytes)
- [nls\\_charset12.zip](#) - Additional National Language character set support (1,876,916 bytes)

**For use with JDK 1.1**

- [classes111.zip](#) - JDBC classes (1,063,479 bytes)
- [classes111\\_g.zip](#) - JDBC classes with debug and trace (1,409,434 bytes)
- [nls\\_charset11.zip](#) - Additional National Language character set support (1,875,945 bytes)

# JDBC Driver Download – MySql ( www.mysql.org )

The screenshot shows the MySQL website's Developer Zone. The 'Downloads' link in the navigation menu is highlighted with a red box. Below it, the 'Download Connector/J 5.0' link is also highlighted with a red box. The page content includes a note about the GPL license, a list of related pages, and download links for Source and Binaries (tar.gz and zip) for version 5.0.0-beta. The status bar at the bottom indicates the browser is Microsoft Internet Explorer.

http://www.mysql.org/ – Microsoft Internet Explorer

파일(F) 편집(E) 보기(V) 즐겨찾기(A) 도구(T) 도움말(H)

주소(D) http://www.mysql.org/ 이동

MySQL.com MySQL Network Developer Zone Partners Online Shop

Downloads Documentation Forums Lists Bugs Events User Groups Guilds Blogs Support Resources Books

FAQ

Download Connector/J 5.0

Overview Database Server Cluster MaxDB Migration Toolkit Administrator Query Browser Co

Mirror Sites

**NOTE:** By downloading the software from this page, you acknowledge that the software available from here is licensed under the GPL. We advise that you review the [GPL](#) before downloading.

If you need commercial, non-GPL, licenses, you can order them [online](#).

[MySQL Connector/J](#) is the official JDBC driver for MySQL. On this page are downloads of the current development release, and [the latest production version](#) is available on another page. A [list of changes](#) is available in the documentation.

We suggest that you [use the MD5 checksums and GnuPG signatures to verify the integrity of the packages you download](#).

Source and Binaries (tar.gz) 5.0.0-beta 8.0M [Pick a mirror](#)  
MD5: 8b673dde79ba5539f49183d2a410b1fb | [Signature](#)

Source and Binaries (zip) 5.0.0-beta 8.1M [Pick a mirror](#)  
MD5: 3b673dde79ba5539f49183d2a410b1fb | [Signature](#)

**Related pages:**

- [Product Information](#)
- [Documentation](#)
- [Connector/J 3.1 Downloads](#)
- [Connector/J 3.0 Downloads](#)


[Check out the Pogo Linux DataWare 2600:](#) a premium out-of-the-box database solution with superior performance at a low price-point.

Learn about new MySQL releases, technical articles, events and more.


Subscribe to the monthly MySQL Newsletter

알 수 없는 영역 (혼합)

□ `JAVA_HOME \jre\lib\ext` 에 driver를 추가해야 함 : `ojdbc14.jar`




# JDBC – JDBC Coding 절차





# JDBC – JDBC Coding 절차

## 1. DriverManager에 해당 DBMS Driver 등록




```
Class.forName( "oracle.jdbc.driver.OracleDriver" );
```

```
cf)  
Class.forName( "com.microsoft.jdbc.sqlserver.SQLServerDriver" );  
  
Class.forName( "org.gjt.mm.mysql.Driver" );
```

# JDBC – JDBC Coding 절차

## 2. 해당 Driver로부터 Connection instance를 획득




```
public static Connection getConnection( String url,  
                                       String user,  
                                       String password )  
  
throws SQLException
```

```
Connection conn =  
    DriverManager.getConnection(  
        "jdbc:oracle:thin:@192.168.0.200:1521:VCC",  
        "SEXXXXX",  
        "SEXXXXX" );
```

# JDBC – JDBC Coding 절차

## 3. Connection instance로부터 Statement instance 획득




```
Statement stmt = conn.createStatement();
```

# JDBC – JDBC Coding 절차

4. Statement method를 이용하여 SQL 실행

5. 실행후 결과를 ResultSet(SELECT) 혹은 int형 변수(DML)로 받아 처리



## Select


```
String query = "SELECT ID, LAST_NAME FROM EMP";  
ResultSet rset = stmt.executeQuery( query );  
  
while ( rset.next() ) {  
    System.out.println( rset.getString( "ID" ) + "\t" +  
                        rset.getString( 2 ) );  
}
```

## DML

```
String query = "UPDATE EMP " +  
               " SET LAST_NAME = 'KIM' " +  
               " WHERE ID = '100000' ";  
  
int result = stmt.executeUpdate( query );
```

# JDBC – JDBC Coding 절차

## 6. 사용한 자원 반납



### Select

```
rset.close();  
stmt.close();  
conn.close();
```

### DML

```
stmt.close();  
conn.close();
```

# JDBC – SELECT

```
package jdbc;

import java.sql.*;

public class EmpList {

    public static void main( String[] args )
        throws SQLException, ClassNotFoundException {
        Connection conn = null;
        Statement stmt = null;
        ResultSet rset = null;
        String url = "jdbc:oracle:thin:@192.168.0.200:1521:VCC";
        String query = null;

        // 1. DBMS Driver 로딩
        Class.forName( "oracle.jdbc.driver.OracleDriver" );

        // 2. Connection 객체 획득
        conn = DriverManager.getConnection( url , "SEXXXXX" , "SEXXXXX" );

        // 3. Statement 객체 생성
        stmt = conn.createStatement();

        // 4. SQL 실행
        query = "SELECT ID " +
            "          ,LAST_NAME " +
            " FROM EMP " ;
```

# JDBC – SELECT

```
rset = stmt.executeQuery( query.toString() );
```

```
System.out.println( "ID\t\t\tLAST_NAME\n" );
```

```
System.out.println( "===== \n" );
```

```
// 5. ResultSet을 이용한 결과 처리
```

```
while( rset.next() ){
```

```
    System.out.println( rset.getString( "ID" ) + "\t\t\t" +  
        rset.getString( 2 ) );
```

```
}
```

```
// 6. 사용할 Resource 반납
```

```
rset.close();
```

```
stmt.close();
```

```
conn.close();
```

```
}
```

```
}
```

# JDBC – SELECT



BOF	ID	LAST_NAME
ROW 1	10001	BOSS
ROW 2	10002	JACKSON
ROW 3	10003	HITE
...	...	...
EOF		



# JDBC – SELECT

rs.next() // true 리턴

String id = rset.getString( "ID" );  
String lastName = rset.getString( 2 );

	1	2
BOF	ID	LAST_NAME
ROW 1	10001	BOSS
ROW 2	10002	JACKSON
ROW 3	10003	HITE
...	...	...
EOF		

ID = 10001

LAST\_NAME = BOSS

	1	2
BOF	ID	LAST_NAME
ROW 1	10001	BOSS
ROW 2	10002	JACKSON
ROW 3	10003	HITE
...	...	...
EOF		

# JDBC – SELECT

rs.next() // true 리턴

String id = rset.getString( "ID" );  
String lastName = rset.getString( 2 );

ID = 10002

LAST\_NAME = JACKSON

	1	2
BOF	ID	LAST_NAME
ROW 1	10001	BOSS
ROW 2	10002	JACKSON
ROW 3	10003	HITE
...	...	...
EOF		

# JDBC – SELECT

rs.next() // false 리턴



BOF	ID	LAST_NAME
ROW 1	10001	BOSS
ROW 2	10002	JACKSON
ROW 3	10003	HITE
...	...	...
EOF		

# JDBC – SELECT

## ❑ StringBuffer Class 사용

```
StringBuffer query = new StringBuffer();
try{
    // 1. DBMS Driver 로딩
    Class.forName( "oracle.jdbc.driver.OracleDriver" );

    ....
    // 4. SQL 실행
    query.append( "SELECT ID           " )
           .append( "           , LAST_NAME " )
           .append( "FROM EMP           " );
    rs = stmt.executeQuery( query.toString() );
    ....
} catch( ClassNotFoundException ce){
    ce.printStackTrace();
} catch( SQLException se){
    se.printStackTrace();
} finally {
    // 6. 사용할 Resource 반납
    try {
        rs.close();
        stmt.close();
        conn.close();
    } catch ( SQLException e ) {
        e.printStackTrace();
    }
}
```

# JDBC – SELECT

## ❑ Exception Handling 로직 추가

```
StringBuffer query = new StringBuffer();
try{
    // 1. DBMS Driver 로딩
    Class.forName( "oracle.jdbc.driver.OracleDriver" );

    ....
    // 4. SQL 실행
    query.append( "SELECT ID          " )
           .append( "          , LAST_NAME " )
           .append( "FROM EMP          " );
    rs = stmt.executeQuery( query.toString() );
    ....
} catch( ClassNotFoundException ce){
    ce.printStackTrace();
} catch( SQLException se){
    se.printStackTrace();
} finally {
    // 6. 사용할 Resource 반납
    try {
        rs.close();
        stmt.close();
        conn.close();
    } catch ( SQLException e ) {
        e.printStackTrace();
    }
}
```

# JDBC – UPDATE Example

```
public class UpdateTest {  
  
    public static void main( String[] args ) throws SQLException, ClassNotFoundException {  
        Connection conn = null;  
        Statement stmt = null;  
        String url = "jdbc:oracle:thin:@192.168.0.200:1521:VCC";  
        StringBuffer query = new StringBuffer();  
        int updateCount = 0;  
  
        Class.forName( "oracle.jdbc.driver.OracleDriver" );  
        conn = DriverManager.getConnection( url , "SEXXXXX" , "SEXXXXX" );  
        conn.setAutoCommit( false );  
  
        query.append( "UPDATE EMP                " )  
            .append( "SET LAST_NAME = 'HITE'    " )  
            .append( "WHERE ID = '10004'        " );  
        stmt = conn.createStatement();  
  
        updateCount = stmt.executeUpdate( query.toString() );  
        System.out.println( "업데이트된 행의 갯수 : " + updateCount );  
  
        if( updateCount == 1 ){  
            conn.commit();  
        }else{  
            conn.rollback();  
        }  
  
        stmt.close();  
        conn.close();  
    }  
}
```

# JDBC – PreparedStatement

```
public class PreparedUpdateTest {

    public static void main( String[] args ) throws SQLException, ClassNotFoundException {
        Connection conn = null;
        PreparedStatement pstmt = null;
        String url = "jdbc:oracle:thin:@192.168.0.200:1521:VCC";
        StringBuffer query = new StringBuffer();
        int updateCount = 0;

        Class.forName( "oracle.jdbc.driver.OracleDriver" );
        conn = DriverManager.getConnection( url , "SEXXXXX" , "SEXXXXX" );
        conn.setAutoCommit( false );
        query.append( "UPDATE EMP          " )
              .append( "SET LAST_NAME = ?  " )
              .append( "WHERE ID = ?      " );

        pstmt = conn.prepareStatement( query.toString() );
        pstmt.setString( 1, "HTE2" );
        pstmt.setString( 2, "10005" );

        updateCount = pstmt.executeUpdate();
        if( updateCount == 1 ){
            conn.commit();
        }else{
            conn.rollback();
        }

        pstmt.close();
        conn.close();
    }
}
```

# JDBC – Statement vs PreparedStatement

	Statement	PreparedStatement
장점	원하는 Query를 직접 넣어주기 때문에 직관적이고 사용하기 쉽다.	같은 Query를 반복 수행해야 하는 경우 성능이 좋다. (loop 이용이 용이)
단점	실행시마다 SQL문을 해석해서 오버헤드가 크다.	코드가 길어질 수 있다.
Sample	<pre>Statement stmt = conn.createStatement();  stmt.executeUpdate( "Insert into emp values ( '21421', 'Kim' )" ); stmt.executeUpdate( "Insert into emp values ( '32211', Hong )" );  ...</pre>	<pre>PreparedStatement pstmt = conn.prepareStatement( " Insert into emp values ( ?, ? ) " );  pstmt.setString( 1, "21421" ); pstmt.setInt( 2, "Kim" ); pstmt.executeUpdate();  pstmt.setString( 1, "32211" ); pstmt.setInt( 2, "Hong" ); pstmt.executeUpdate();  ...</pre>