Algorithmic Approaches for Biological Data, Lecture #8

Katherine St. John

City University of New York American Museum of Natural History

17 February 2016

Outline



• More on Pattern Finding: Regular Expressions

Outline



- More on Pattern Finding: Regular Expressions
- Processing CSV files

Regular Expression	Description of Matching Strings
[ACGT]*	A DNA sequence— any string consisting only of
[ACG1]	A, C, G, and T

Regular Expression	Description of Matching Strings
[ACGT]*	A DNA sequence— any string consisting only of
	A, C, G, and T
[ACGU]*	A RNA sequence— any string consisting only of
	A.C. G. and U.

Description of Matching Strings
A DNA sequence— any string consisting only of
A, C, G, and T
A RNA sequence— any string consisting only of
A, C, G, and U 1 or more repeats of AT: AT, ATAT, ATATAT,
1 of more repeats of AT. AT, ATAT, ATATAT,

Description of Matching Strings
A DNA sequence— any string consisting only of
A, C, G, and T A RNA sequence— any string consisting only of
A. C. G. and U
1 or more repeats of AT: AT, ATAT, ATATAT,
A sequence beginning with ATG and ending
with 5 to 10 A's. Overall length is 38 to 1013
bp.

Regular Expression	Description of Matching Strings
[ACGT]*	A DNA sequence— any string consisting only of
	A, C, G, and T
[ACGU]*	A RNA sequence— any string consisting only of
	A, C, G, and U
[AT]+	1 or more repeats of AT: AT, ATAT, ATATAT,
	A sequence beginning with ATG and ending
ATG[ATGC]{30,1000}A{5,10}	with 5 to 10 A's. Overall length is 38 to 1013
	bp.
	,
([ACGT]{3})*	A DNA sequence that exactly breaks into
	codons (3-letter sequences).

Regular Expression	Description of Matching Strings
[ACGT]*	A DNA sequence— any string consisting only of A, C, G, and T
[ACGU]*	A RNA sequence— any string consisting only of A, C, G, and U
[AT]+	1 or more repeats of AT: AT, ATAT, ATATAT,
ATG[ATGC]{30,1000}A{5,10}	A sequence beginning with ATG and ending with 5 to 10 A's. Overall length is 38 to 1013 bp.
([ACGT]{3})*	A DNA sequence that exactly breaks into codons (3-letter sequences).
ATG([ATGC]{3}){30,1000}A{5,10}	An open reading frame (ORF): a sequence that starts with the start codon ATG, followed by any number of codons, and ending with a stop codon (TAA, TAG, or TGA).

• Can be used as a conditional test:





• Can be used as a conditional test:

```
if re.search(r"GC[ATGC]GC", dna):
    print "Pattern found!"
```



• Can be used as a conditional test:

```
if re.search(r"GC[ATGC]GC", dna):
    print "Pattern found!"
```

• Search returns a match object:



• Can be used as a conditional test:

```
if re.search(r"GC[ATGC]GC", dna):
    print "Pattern found!"
```

Search returns a match object:

```
dna = "ACTCGTACGAAAGCTGCTTATACGCGCGG"
m = re.search(r"GC[ATGC]GC, dna)
print "The matching string is",
m.group()
print "Match starts at", m.start()
print "Match ends at", m.end()
```



• Can be used as a conditional test:

```
if re.search(r"GC[ATGC]GC", dna):
    print "Pattern found!"
```

Search returns a match object:

```
dna = "ACTCGTACGAAAGCTGCTTATACGCGCGG"
m = re.search(r"GC[ATGC]GC, dna)
print "The matching string is",
m.group()
print "Match starts at", m.start()
print "Match ends at", m.end()
```

RE findall()



• findall() returns a list of strings: import re
dna = "ACTGCATTATATCGTACGAAATTATACGCGCG"
runs = re.findall("[AT]4,100", dna)
print runs

RE findall()



• findall() returns a list of strings: import re

```
dna = "ACTGCATTATATCGTACGAAATTATACGCGCG"
runs = re.findall("[AT]4,100", dna)
print runs
```

output:

['ATTATAT', 'AAATTATA']

Regular Expressions Overview

Python 2.7 Regular Expressions

Non-special chars match themselves. Exceptions are special characters:

Excape special char or start a sequence.

- Macch say char except newline, see re.DDTALL
- March start of the string, see re.MENTLINE

| March end of the string, see re.MENTLINE
| March end of the string, see re.MENTLINE
| March either regex & or regex S.
| Create capture group, indicate precedence

After '[', enclose a set, the only special chars are

] End the set, if not the lst char - A range, eg. a-c matches a, b or c ^ Negate the set only if it is the lst char

Quantifiers (append '?' for non-greedy):

Special sequences:

A Start of atring

1 Match septy atring at word (\w+) boundary

18 Match septy atring not at word boundary

10 Match septy atring not at word boundary

10 Bion-digit

10 Bion-digit

10 Mintepaper

11 Mintepaper

12 Mintepaper

12 Mintepaper

12 Mintepaper

13 Mintepaper

12 Mintepaper

12 Mintepaper

12 Mintepaper

12 Mintepaper

13 Mintepaper

14 Mintepaper

15 Mintepaper

16 Mintepaper

16 Mintepaper

17 Mintepaper

18 M

or \gcname> (not \g0 or \grame) Special character escapes are much like those already escaped in Python string literals. Hence regex \n' is same as regex \n'.'

```
same as regact \u00e4us

ADDIT ball (BEL)

ADDIT ball (BEL)

ADDIT barraded

Va ADDIT worth barrade

Va ADDIT worth barrade

ADDIT barraded barrade

DOD Three delight contain character goad here

addition barraded barrade

DOD Three delight contain character goad here

DOD Three delight contain character
```

Extensions. Do not cause grouping, except 'P<name>':

[Tilmenn] Match empty string, sets ws. IImpa
[Trimens...] Create a hand emptying group
[Trimens...]

Flags for re.compile(), etc. Combine with ' $|\cdot|$

Module level functions:

omplicipations[| Hopp|) ~ Repuminos main(hysitems, string), [Hopp] > Reducibjest samenhysitems, string[| Hopp] > Reducibjest samenhysitems, string[| Hopp] > Reducibjest input | Hoppinos | Ho

RegexObjects (returned from compile()):

amendacting[, pos., endpos]) ~ NationSystem assuming training for the amendacting [, pos., endpos]) ~ NationSystem assuming training for the amendacting finalize (erring), pos., endpos]) ~ itse of nationSystem application[, pos., endpos]) ~ itse of nationSystem assuming for the article and applications [, pos., endpos[, attion], pos., pos.,

MatchObjects (returned from match() and search()):

expenditure(int) is desired, Rebelland & prior apparatus equival(prior) [1] is existed an intelligible of statistics; I per our account for the control of t

Gleaned from the python 2.7 're' docs. http://docs.python.org/library/re.html https://github.com/lartley/ovthon-recex-cheatsheet

Version: v0.3.3

Regular Expressions: Matches

Non-special chars match themselves. Exceptions are special characters:

```
Lescape special char or start a sequence.

Match any char except newline, see re.DOTALL

Match start of the string, see re.MULTILINE

Match end of the string, see re.MULTILINE

Enclose a set of matchable chars

R|S Match either regex R or regex S.

Create capture group, & indicate precedence
```

After '[', enclose a set, the only special chars are:

```
] End the set, if not the 1st charA range, eg. a-c matches a, b or c^ Negate the set only if it is the 1st char
```

Quantifiers (append '?' for non-greedy):

```
{m} Exactly m repetitions
{m,n} From m (default 0) to n (default infinity)
* 0 or more. Same as {,}
+ 1 or more. Same as {1,}
? 0 or 1. Same as {,1}
```

Regular Expressions: Special Characters

Special character escapes are much like those already escaped in Python string literals. Hence regex ' \n' ' is same as regex ' \n' ':

```
\a ASCII Bell (BEL)
\f ASCII Formfeed
\n ASCII Linefeed
\r ASCII Carriage return
\t ASCII Tab
\v ASCII Vertical tab
\\ A single backslash
\xHH Two digit hexadecimal character goes here
\text{\text{000}} Three digit octal char (or just use an initial zero, e.g. \text{\text{0}}, \text{\text{\text{09}}}
\text{\text{DD}}
\text{\text{DD}} Decimal number 1 to 99, match previous numbered group
```

Regular Expressions: Special Sequences

Special sequences:

```
\A Start of string
\b Match empty string at word (\w+) boundary
\B Match empty string not at word boundary
\d Digit
\D Non-digit
\s Whitespace [ \t\n\r\f\v], see LOCALE,UNICODE
\S Non-whitespace
\w Alphanumeric: [0-9a-zA-Z_], see LOCALE
\W Non-alphanumeric
\Z End of string
\g<id>Match prev named or numbered group,
\'<' & '>' are literal, e.g. \g<0>
or \g<name> (not \g0 or \gname)
```



email.txt

In pairs:

 Design a program that will extract all the email addresses from a file.

```
Contact Us
General Information
Info-rggs@amnh.org
Admissions
Admissions-rggs@amnh.org
Fellowship Opportunities
Fellowships-rggs@amnh.org
Webmaster
Webmaster-rggs@amnh.org
Telephone - Main Office
212-769-5055
Office Hours
Monday to Friday
9am to 5pm and by appointment
Staff
Dr. John Flynn
212-769-5055
                        Beth G. Kneller
Director of Administration
212-769-5143
Maria Rios
Assistant Director for Student Affairs and Fell
212-769-5017
                        Anna Manuel
Departmental Administrator
212-769-5055
```

email.txt

In pairs:

- Design a program that will extract all the email addresses from a file.
- First, figure out a good regular expression to match email formats.

```
Contact Us
General Information
Info-rggs@amnh.org
Admissions
Admissions-rggs@amnh.org
Fellowship Opportunities
Fellowships-rggs@amnh.org
Webmaster
Webmaster-rggs@amnh.org
Telephone - Main Office
212-769-5055
Office Hours
Monday to Friday
9am to 5pm and by appointment
Staff
Dr. John Flynn
212-769-5055
                        Beth G. Kneller
Director of Administration
212-769-5143
Maria Rios
Assistant Director for Student Affairs and Fell
212-769-5017
                        Anna Manuel
Departmental Administrator
212-769-5055
```

email.txt

In pairs:


- Design a program that will extract all the email addresses from a file.
- First, figure out a good regular expression to match email formats.
- Next, use it to find the first match.

```
Contact Us
General Information
Info-rggs@amnh.org
Admissions
Admissions-rggs@amnh.org
Fellowship Opportunities
Fellowships-rggs@amnh.org
Webmaster
Webmaster-rggs@amnh.org
Telephone - Main Office
212-769-5055
Office Hours
Monday to Friday
9am to 5pm and by appointment
Staff
Dr. John Flynn
Dean
212-769-5055
                        Beth G. Kneller
Director of Administration
212-769-5143
Maria Rios
Assistant Director for Student Affairs and Fell
212-769-5017
                        Anna Manuel
Departmental Administrator
212-769-5055
```


email.txt

In pairs:


- Design a program that will extract all the email addresses from a file.
- First, figure out a good regular expression to match email formats.
- Next, use it to find the first match.
- Last, add a loop to find all.




Very structured
 – the columns and rows matter.




- Very structured
 – the columns and rows matter.
- To keep that format as a text file:



- Very structured
 – the columns and rows matter.
- To keep that format as a text file:
 - columns separated by commas (',') and



- Very structured
 – the columns and rows matter.
- To keep that format as a text file:
 - columns separated by commas (',') and
 - rows separated by new lines ('\n')




- Very structured
 – the columns and rows matter.
- To keep that format as a text file:
 - columns separated by commas (',') and
 - rows separated by new lines ('\n')
- Rows look like:
 "DOT 84 FLUID 11383", Ceyx lepidus collectoris, Solomon Islands, New Georgia Group, Vella Lavella


Island, Oula River camp,,,,07 47 30 S,156 37 30 E, Paul R. Sweet, 7-May-04, PRS-2672,,, "Tissue Fluid"




Built-in package for reading CSV files. To use it:




- Built-in package for reading CSV files. To use it:
 - At top of file, include: import csv




- Built-in package for reading CSV files. To use it:
 - At top of file, include: import csv
 - ▶ Open the file normally: f = open("in.csv", "rU")




- Built-in package for reading CSV files. To use it:
 - ► At top of file, include: import csv
 - Open the file normally: f = open("in.csv", "rU") "rU" avoids errors with different newlines, and accepts all variants.




- Built-in package for reading CSV files. To use it:
 - At top of file, include: import csv
 - Dopen the file normally: f = open("in.csv", "rU")
 "rU" avoids errors with different newlines, and accepts all variants.
 - Create a reader: reader = csv.DictReader(f)




- Built-in package for reading CSV files. To use it:
 - ► At top of file, include: import csv
 - Proper the file normally: f = open("in.csv", "rU")
 "rU" avoids errors with different newlines, and accepts all variants.
 - Create a reader: reader = csv.DictReader(f)
 Uses column names in first line of csv file to access row data.




- Built-in package for reading CSV files. To use it:
 - ► At top of file, include: import csv
 - Proper the file normally: f = open("in.csv", "rU")
 "rU" avoids errors with different newlines, and accepts all variants.
 - Create a reader: reader = csv.DictReader(f)
 Uses column names in first line of csv file to access row data.
 - Read in lines from reader:




- Built-in package for reading CSV files. To use it:
 - ► At top of file, include: import csv
 - Proper the file normally: f = open("in.csv", "rU")
 "rU" avoids errors with different newlines, and accepts all variants.
 - Create a reader: reader = csv.DictReader(f)
 Uses column names in first line of csv file to access row data.
 - ▶ Read in lines from reader: for row in reader:



- Built-in package for reading CSV files. To use it:
 - ► At top of file, include: import csv
 - Proper the file normally: f = open("in.csv", "rU")
 "rU" avoids errors with different newlines, and accepts all variants.
 - Create a reader: reader = csv.DictReader(f)
 Uses column names in first line of csv file to access row data.
 - ▶ Read in lines from reader: for row in reader:
 - ► To access individual entries in a row:




- Built-in package for reading CSV files. To use it:
 - At top of file, include: import csv
 - Proper the file normally: f = open("in.csv", "rU")
 "rU" avoids errors with different newlines, and accepts all variants.
 - Create a reader: reader = csv.DictReader(f)
 Uses column names in first line of csv file to access row data.
 - Read in lines from reader: for row in reader:
 - ➤ To access individual entries in a row: if "Malaysia" in row['COUNTRY']: ...




In pairs,

Write a program that will count female specimens in the CSV file.



In pairs,


- Write a program that will count female specimens in the CSV file.
- Write a program that returns the fraction missing a collection date.



In pairs,

- Write a program that will count female specimens in the CSV file.
- Write a program that returns the fraction missing a collection date.
- Return a list of the species ("IDENTIFICATION" row) in this file.


Recap



Anderson et al. 2014

Install anaconda for lab today.


Recap



Anderson et al. 2014

- Install anaconda for lab today.
- Email lab reports to kstjohn@amnh.org

Recap



Anderson et al. 2014

- Install anaconda for lab today.
- Email lab reports to kstjohn@amnh.org
- Challenges available at rosalind.info