

1. MAVEN LIFECYCLE

Maven follows a well-defined build lifecycle, which consists of several phases that help in compiling, testing, packaging, and deploying Java-based projects. The primary build lifecycles in Maven are:

a. Default Lifecycle (Build Process)

- validate – Validates project and necessary information.
- compile – Compiles the source code of the project.
- test – Runs unit tests.
- package – Packages the compiled code into a distributable format (JAR/WAR).
- verify – Verifies the integration tests.
- install – Installs the package into the local repository.
- deploy – Deploys the package to a remote repository.

b. Clean Lifecycle

- pre-clean – Performs pre-cleaning actions.
- clean – Deletes the target directory.
- post-clean – Executes any necessary cleanup tasks.

c. Site Lifecycle

- site – Generates project documentation.
- site-deploy – Deploys the generated documentation.

2. What is pom.xml File and Why We Use It?

a. Definition

The `pom.xml` (Project Object Model) file is the core configuration file of a Maven project. It contains information about the project, dependencies, plugins, and build configurations.

b. Why We Use It?

- Defines dependencies for automatic downloading.
- Configures plugins and build execution.
- Specifies project structure and properties.
- Manages different environments using profiles.

```

<project xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>

  <groupId>com.example</groupId>
  <artifactId>my-project</artifactId>
  <version>1.0.0</version>
  <packaging>jar</packaging>

  <dependencies>
    <dependency>
      <groupId>org.apache.commons</groupId>
      <artifactId>commons-lang3</artifactId>
      <version>3.12.0</version>
    </dependency>
  </dependencies>
</project>

```

3. How Dependencies Work?

- Dependencies in Maven are external libraries required by the project.
- Declaring dependencies in `pom.xml` allows Maven to fetch them automatically from repositories.
- Maven follows a dependency resolution mechanism where it checks for dependencies in:
 1. Local Repository (`.m2/repository` folder)
 2. Central Repository (<https://repo.maven.apache.org/maven2>)
 3. Remote Repositories (custom repositories defined in `pom.xml`)

4. Checking the Maven Repository

The **Maven Central Repository** can be accessed at: <https://mvnrepository.com/>

To check dependencies:

```
mvn dependency:tree
```

Maven follows a **multi-module build** approach, where multiple modules (sub-projects) are managed within a single parent project.

- A **parent project** contains multiple **child modules**.
- The `pom.xml` in the parent directory defines configurations for all modules.
- Each module has its own `pom.xml` with specific configurations.
- To build all modules:
 - `mvn clean install`

6. Can We Build a Specific Module?

Yes, a specific module can be built using:

```
mvn clean install -pl module-name -am
```

Where:

- `-pl module-name`: Specifies the module to build.
- `-am`: Builds required dependencies for the module.

7. Role of ui.apps, ui.content, and ui.frontend Folder in AEM

- **ui.apps**: Contains code related to AEM components, templates, and client libraries.
- **ui.content**: Stores content package (pages, configurations) that need to be deployed.
- **ui.frontend**: Contains frontend-related assets (JavaScript, CSS, and React code) for the AEM application.

8. Why Are We Using Run Mode?

Run modes in AEM define different configurations based on the environment (e.g., development, staging, production).

Configurations can be defined under:

```
/apps/my-project/config.author  
/apps/my-project/config.publish
```

-
- AEM selects configurations based on the environment's run mode.

To check the current run mode:

```
http://localhost:4502/system/console/status-
```

9. What is the Publish Environment?

- The **publish environment** in AEM is responsible for serving content to end users.
- It contains **approved content** and does not allow direct modifications.
- Content is pushed from the **author instance** to the **publish instance** using **replication**.

10. Why Are We Using Dispatcher?

The **AEM Dispatcher** is used for caching and security purposes.

Roles of Dispatcher:

1. **Caching:** Stores static content to reduce load on AEM.
2. **Load Balancing:** Distributes traffic across multiple instances.
3. **Security:** Blocks unauthorized requests before they reach AEM.

Dispatcher is configured using **dispatcher.any** and **rewrite rules**.

11. From Where Can We Access CRX/DE?

CRX/DE is the AEM content repository where developers can manage nodes and content.

To access CRX/DE, use:

- **Author Instance:** <http://localhost:4502/crx/de/>
- **Publish Instance:** <http://localhost:4503/crx/de/>

Here, developers can browse, edit, and create JCR nodes.

