

DATABASE VERSION: 0.11

Voir aussi database-models.md

core_settings		
V1	id PK	bigint AUTO

core_abstractaudit (Model AbstractAudit)		
POC	id PK	bigint AUTO
POC	created_at	datetime AUTO_NOW_ADD
POC	updated_at	datetime AUTO_NOW
MVP	created_by_id FK	bigint NULLABLE
MVP	updated_by_id FK	bigint NULLABLE

core_image (AbstractAudit)		
V1	id PK	bigint AUTO
V1	image	varchar ImageField
V1	 alt_text	varchar NULLABLE BLANKABLE d=NULL
V1	 legend	varchar NULLABLE BLANKABLE d=NULL

LÉGENDE

Plus de détails : database-models.md

Colonne 1: Fonction complète à partir de la version...

- POC Proof of Concept
- MVP Minimal Viable Product
- V1 Première version complète
- VX Version future (fonctionnalité envisagée mais non planifiée)

Colonne 2: nom du champs

- nom souligné Champs UNIQUE (together ou non)
- *nom en italique* Champs INDEXÉ
- PK/FK Primary / Foreign Key
 - (FK) Foreign Key au niveau ORM seulement

Colonne 3: type du champs et propriétés

- AUTO Auto increment
- NULLABLE
- d= Default Value
- > Champs ne pouvant pas être négatif

LIBRAIRIES TIERCES

Arbre: **django-treebeard** sera utilisé pour gérer les arbres de manière optimisée avec la classe **MP_Node** (*company* -> *Location* et *catalogue* -> *Category*)

Traduction des données de l'utilisateur: **django-parler**.
 Les données dynamiques pouvant être traduites sont marquées par le symbole  devant le nom du champs.

users_user (AbstractUser)		
POC	id PK	bigint
POC	password NATIF	varchar
POC	last_login NATIF	datetime
POC	is_superuser NATIF	tinyint
POC	username NATIF	varchar
POC	first_name NATIF	varchar
POC	last_name NATIF	varchar
POC	email NATIF	varchar
POC	is_staff NATIF	tinyint
POC	is_active NATIF	tinyint
POC	date_joined NATIF	datetime AUTO_NOW_ADD
POC	is_owner	tinyint d=False
POC	update_at	datetime AUTO_NOW_UPDATE
POC	created_by_id FK self	bigint NULLABLE d=NULL
POC	updated_by_id FK self	bigint NULLABLE d=NULL
V1	photo_id FK	bigint NULLABLE d=NULL
V1	preferred_language	varchar
V1	preferred_home_page	varchar

users_userhierarchy (MP_Node)		
POC	id PK	bigint AUTO
POC	user_id FK	bigint

users_userrole		
POC	id PK	bigint AUTO
POC	user_id FK	bigint
POC	role_id FK	bigint
POC	company_id FK	bigint NULLABLE d=NULL
POC	location_id FK	bigint NULLABLE d=NULL
POC	is_active	tinyint d=True

users_userrolelog		
MVP	id PK	bigint AUTO
MVP	uuid	UUIDField
MVP	userrole_id (FK)	bigint
MVP	user_id (FK)	bigint
MVP	role_id (FK)	bigint
MVP	company_id (FK)	bigint NULLABLE
MVP	location_id (FK)	bigint NULLABLE
MVP	changed_at	datetime AUTO_NOW_ADD
MVP	changed_by_id (FK) User	bigint
MVP	action	enum
MVP	snap_infos	JSONField

context ENUM

- SYSTEM
- COMPANY
- MULTICOMPANIES
- LOCATION
- MULTILOCATIONS

sensibility ENUM

- HIGH
- MEDIUM
- LOW

action ENUM

- CREATE
- UPDATE
- DELETE

access_permission		
POC	id PK	int AUTO
POC	<u>codename</u>	varchar
POC	 name	varchar
POC	 help_text	text
POC	context	enum
POC	sensibility	enum
POC	is_active	tinyint d=True
POC	display_order	int

access_role		
POC	id PK	int AUTO
POC	<u>slug</u>	varchar
POC	company_id FK	bigint NULLABLE
POC	 name	varchar
POC	 description	text
POC	is_active	tinyint d=True

access_rolepermissions (Many-to-many)		
POC	id PK	int AUTO
POC	role_id FK	int
POC	permission_id FK	int

access_log		
MVP	id PK	bigint AUTO
MVP	uuid	UUIDField
MVP	target_table	varchar
MVP	target_id	bigint
MVP	role_id (FK)	bigint
MVP	action	ENUM
MVP	changed_at	datetime AUTO_NOW_ADD
MVP	changed_by_id (FK)	bigint
MVP	snap_infos	JSONField

action ENUM

- CREATE
- UPDATE
- DELETE

company_company (AbstractAudit)		
POC	id PK	bigint
POC	<u>official_name</u>	varchar
POC	<u>slug</u>	varchar
POC	 name	varchar
V1	logo_id FK Image	bigint
V1	is_multilingual_on	tinyint d=False
V1	default_location_transit_entrance FK	bigint NULLABLE d=NULL
V1	default_location_transit_intercompany FK	bigint NULLABLE d=NULL
V1	is_archived	tinyint d=False

company_uom (AbstractAudit)		
V1	id PK	bigint AUTO
V1	company_id FK	bigint
V1	type	enum
V1	system	enum
V1	 name	varchar
V1	 code	varchar
V1	is_reference	tinyint
V1	ratio	decimal
V1	is_active	tinyint d=True

type ENUM

- UNIT
- WEIGHT
- LENGTH
- VOLUME
- AREA
- TIME

system ENUM

- IMPERIAL
- METRIC
- NONE

company_location (AbstractAudit, MP_Node)		
POC	id PK	bigint
POC	company_id FK	bigint
POC	<u>slug</u>	varchar
POC	 name	varchar
MVP	location_type_id FK	bigint
MVP	 address_line1	varchar NULLABLE d=NULL
MVP	 address_line2	varchar NULLABLE d=NULL
MVP	 city	varchar NULLABLE d=NULL
MVP	 state_province	varchar NULLABLE d=NULL
MVP	 country	varchar NULLABLE d=NULL
MVP	 postal_code	varchar NULLABLE d=NULL
V1	time_zone	varchar NULLABLE d=NULL
V1	image_id FK	bigint NULLABLE d=NULL

company_locationtype		
MVP	id PK	int
MVP	company_id FK	bigint
MVP	<u>slug</u>	varchar
MVP	 name	varchar
MVP	 description	text
MVP	is_stockable	tinyint d=True

catalogue_productmodel (AbstractAudit)		
POC	id PK	bigint AUTO
POC	company_id FK	bigint
POC	<u>slug</u>	varchar
POC	 name	varchar
MVP	 description	longtext BLANK
V1	is_productvariant_on	tinyint d=False
V1	is_productpackaging_on	tinyint d=False
V1	is_archived	tinyint d=False

catalogue_product (AbstractAudit)		
POC	id PK	bigint AUTO
POC	company_id FK	bigint
POC	<u>slug</u>	varchar
POC	productmodel_id FK	bigint
V1	is_archived	tinyint d=False

catalogue_productpackaging (AbstractAudit)		
MVP	id PK	bigint AUTO
MVP	company_id FK	bigint
MVP	product_id FK	bigint
MVP	<u>sku</u>	varchar
V1	 name	varchar
V1	 code	varchar NULLABLE
V1	base_uom_id FK	bigint
V1	ratio	decimal

catalogue_category (MP_Node)		
MVP	id PK	bigint
MVP	company_id FK	bigint
MVP	<u>slug</u>	varchar
MVP	 name	varchar
V1	image_id FK	bigint NULLABLE d=NULL

catalogue_productcategory (association)		
	id PK	bigint AUTO
MVP	productmodel_id FK	bigint
MVP	category_id FK	bigint
MVP	is_main	tinyint

catalogue_productconfig (AbstractAudit)		
V1	id PK	bigint AUTO
V1	product_id FK	bigint
V1	location_id FK	bigint
V1	productpackaging_id FK	bigint
V1	alert_threshold	decimal >=0

catalogue_attributekey		
V1	id PK	bigint AUTO
V1	company_id FK	bigint
V1	 key	varchar

catalogue_attributevalue		
V1	id PK	bigint AUTO
V1	attributekey_id FK	bigint
V1	 value	varchar

catalogue_productattribute		
V1	id PK	bigint AUTO
V1	product_id FK	bigint
V1	attributevalue_id FK	bigint
V1	is_main	tinyint d=False

catalogue_productmodelimage		
V1	id PK	bigint AUTO
V1	productmodel_id FK	bigint
V1	image_id FK	bigint
V1	is_main	tinyint

catalogue_productimage		
V1	id PK	bigint AUTO
V1	product_id FK	bigint
V1	image_id FK	bigint
V1	is_main	tinyint

inventory_stock		
POC	id PK	bigint AUTO
POC	company_id FK	bigint
POC	product_id FK	bigint
POC	location_id FK	bigint
POC	productpackaging_id FK	bigint
POC	quantity	decimal

inventory_movementreason (AbstractAudi)		
V1	id PK	bigint AUTO
V1	company_id FK	bigint
V1	<u>slug</u>	varchar
V1	 name	varchar
V1	permission_required_id FK	varchar

inventory_movement		
POC	id PK	bigint AUTO
POC	uuid	UUID Field
POC	stock_id (FK)	bigint
POC	company_id (FK)	bigint
POC	product_id (FK)	bigint
POC	location_source_id (FK)	bigint NULLABLE
POC	productpackaging_source_id (FK)	bigint
POC	quantity_total_init	decimal
POC	quantity_total_final	decimal
POC	quantity_total_delta	decimal
POC	quantity_packaging_init	decimal
POC	quantity_packaging_final	decimal
POC	quantity_packaging_delta	decimal
POC	reason_id (FK)	bigint
POC	location_dest_id (FK)	bigint NULLABLE
MVP	snap_infos	JSON Field
POC	created_at	datetime AUTO_ADD_NOW
POC	created_by_id (FK)	bigint
POC	created_by_comment	text NULLABLE d=NULL BLANKABLE

inventory_transit		
V1	id PK	bigint AUTO
V1	<u>transit_id</u>	varchar
V1	company_source_id FK	bigint
V1	location_source_id FK	bigint
V1	product_source_id FK	bigint
V1	productpackaging_source_id FK	bigint
V1	quantity_send	decimal
V1	product_name	varchar
V1	product_sku	varchar
V1	company_dest_id FK	bigint
V1	location_dest_id FK	bigint NULLABLE d=NULL
V1	uom_dest_id FK	bigint NULLABLE d=NULL
V1	quantity_received	decimal NULLABLE d=NULL
V1	is_completed	tinyint d=False
V1	comment_source	text NULLABLE. BLANKABLE
V1	comment_dest	text NULLABLE. BLANKABLE