19/09/2023, 21:54 lab_session 5

Import relevant packages here.

```
In []: import matplotlib.pyplot as plt
   import numpy as np
   import pandas as pd
   import math
```

Load the data and verify it is loaded correctly.

- Print it (head, tail, or specific rows, choose a sensible number of rows).
- Compare it to the source file.

```
In [ ]: data = pd.read csv('cf data.csv')
        print(data.info)
        print(data.head(10))
        # print(data.tail())
        <bound method DataFrame.info of</pre>
                                                    dv
             -0.743240 53.5427 1.242570
              -0.557230 53.6120 1.777920
        1
              -0.454769 53.6541 0.544107
             -0.525396 53.7030 -0.294755
             -0.601285 53.7592 -0.290961
                    . . .
        73903 5.198740 116.1390 -0.795081
        73904 5.104280 115.6270 -0.314263
        73905 5.137640 115.1180 0.232283
        73906
              5.153480 114.5990 0.262078
        73907 5.258680 113.1120 -0.612440
        [73908 rows x 3 columns]>
                dv
                          S
        0 -0.743240 53.5427
                             1.242570
        1 -0.557230 53.6120 1.777920
        2 -0.454769 53.6541 0.544107
        3 -0.525396 53.7030 -0.294755
        4 -0.601285 53.7592 -0.290961
        5 -0.682448 53.8232 -0.283414
        6 -0.768859 53.8957 -0.271604
        7 -0.860452 53.9770 -0.133532
        8 -0.832777 54.0678 0.243356
        9 -0.576125 54.1436 0.406759
```

In the ensuing, you will use numpy.

Let's create a grid for the values to plot. But first create **two arrays named dv and s** using numpy.linspace that hold the grid values at the relevant indices in their respective dimension of the grid.

Create a **grid named a** with zeros using **numpy.zeros** in to which calculated acceleration values can be stored.

Let the grid span:

- Speed difference dv [m/s]
 - From -10 till 10

19/09/2023, 21:54 lab_session 5

With 41 evenly spaced values

- Headway s [m]
 - From 0 till 200
 - With 21 evenly spaced values

```
In []: dv = np.linspace(-10, 10, 41)
s = np.linspace(0, 200, 21)
a = np.zeros((len(dv), len(s)))
```

Create from the imported data 3 separate $\begin{array}{c} \text{numpy} \end{array}$ arrays for each column $\begin{array}{c} \text{dv} \end{array}$, $\begin{array}{c} \text{s} \end{array}$ and $\begin{array}{c} \text{a} \end{array}$. (We do this for speed reasons later.)

- Make sure to name them differently from the arrays that belong to the grid as above.
- You can access the data of each column in a DataFrame using data.xxx where xxx is the column name (not as a string).
- Use the method to_numpy() to convert a column to a numpy array.

```
In []: dv_ar = data.dv.to_numpy()
s_ar = data.s.to_numpy()
a_ar = data.a.to_numpy()
```

Create an algorithm that calculates all the acceleration values and stores them in the grid. The algorithm is described visually in the last part of the lecture. At each grid point, it calculates a weighted mean of all measurements. The weights are given by an exponential function, based on the 'distance' between the grid point, and the measurement values of dv and s. To get you started, how many for -loops do you need?

For this you will need math .

Use an upsilon of 1.5m/s and a sigma of 30m.

Warning: This calculation may take some time. So:

- Print a line for each iteration of the outer-most for -loop that shows you the progress.
- Test you code by running it only on the first 50 measurements of the data.

```
In []: ypsilon = 1.5 # m/s
sigma = 30.0 # m

for i in range(len(dv)):
    for j in range(len(s)):
        sum_weights = 0
        tot_weight = 0

    for k in range(len(dv_ar)):
        dv_diff = (dv[i] - dv_ar[k]) / ypsilon
        s_diff = s[j] - s_ar[k]
        weight = math.exp(-math.sqrt(dv_diff ** 2 + s_diff ** 2) / sigma sum_weights += a_ar[k] * weight
        tot_weight += weight
```

19/09/2023, 21:54 lab_session 5

```
if tot_weight > 0:
    a[i, j] = sum_weights / tot_weight
else:
    a[i, j] = 0
```

The following code will plot the data for you. Does it make sense when considering:

- Negative (slower than leader) and positive (faster than leader) speed differences?
- Small and large headways?

```
In []: X, Y = np.meshgrid(dv, s)

a = a.T

axs = plt.axes()
p = axs.pcolor(X, Y, a, shading='nearest')
axs.set_title('Acceleration [m/s/s]')
axs.set_xlabel('Speed difference [m/s]')
axs.set_ylabel('Headway [m]')
axs.figure.colorbar(p);
axs.figure.set_size_inches(10, 7)
```

