

NORDSTROM RACK – TURNKEY PROTOTYPE

SECTION 033536 – POLISHED CONCRETE FINISHING

- D. Warranty Draft: Concurrent with initial product data submittal, submit draft of manufacturer's warranty for Owner's/Tenant's (Nordstrom's) review of terms. Draft shall include exceptions and inclusions.

1.5 CLOSEOUT SUBMITTALS

- A. Submit in accordance with Section 017700.
- B. Maintenance Instructions: Provide polishing system manufacturer's maintenance instructions to the Owner's/Tenant's (Nordstrom's) maintenance personnel.
- C. Overage products applicable to maintenance.
- D. Warranty: Provide manufacturer's standard warranty.
- E. Extra Stock: Provide 5 gallons of the polishing system manufacturer's recommended compatible cleaning agent to onsite Owner's//Tenant's (Nordstrom's) personnel.

1.6 QUALITY ASSURANCE

- A. Applicator Qualifications:
 - 1. Artisan specializing in ground and polished concrete flooring systems that are comparable in type, scope, and quality as specified by this Section.
 - 2. Able to document minimum five years' experience with minimum five successful commercial quality concrete floor finishing projects comparable to work specified for this project.
 - 3. Certified by the proposed floor system manufacturer as qualified to perform work of this Section, prior to Bid date, and accepted by Architect.
- B. Mock-up:
 - 1. Make mock-ups in accordance with Section 014500.
 - 2. Ensure that mock-up is installed by the same installer personnel who will perform work.
 - 3. Provide the following:
 - a. Mock-Up: Polished slab in size of 10 by 10 feet.
 - 4. Apply mock-up to demonstrate surface finish, and level of workmanship. Include saw cut joint between areas with joint filler as specified.
 - 5. Prior to proceeding, ensure that mock-up meets the requirements of the Architect or Owner/Tenant (Nordstrom).
 - 6. Maintain approved mock-up during construction in an undisturbed condition as a standard for judging the work.
- C. Pre-Installation Conference: In accordance with Section 013119.
 - 1. Administer prior to starting the work of this Section.
 - 2. Require in attendance:
 - a. General Contractor.
 - b. Polishing system installer.
 - c. System manufacturer's representative.
 - d. Other parties affected by the work of this Section.
 - 3. Agenda:
 - a. Review Contract Document requirements.
 - b. Review requirements for assessment of sound substrate and subsequent remediation in the case of sub-standard conditions.
 - c. Review requirements for environmental conditions and storage of materials.
 - d. Review system manufacturer's preparation and application instructions including, but not limited to, the following:
 - 1) Details of each step of grinding, honing, and polishing operations.
 - 2) Application of liquid applied products.
 - 3) Protecting concrete floor surfaces until polishing begins.
 - 4) Sealing and protecting polished concrete floors after polishing is completed.