

NORDSTROM RACK – TURNKEY PROTOTYPE

SECTION 033536 – POLISHED CONCRETE FINISHING

- e. Review conditions or techniques which would prevent the satisfactory application of the polishing system.
- 4. Reports: Record discussions, including decisions and agreements reached, and provide copy of record to the Owner/Tenant (Nordstrom) and each party in attendance.

1.7 DELIVERY, STORAGE, AND HANDLING

- A. In accordance with Section 016000 and the system manufacturer's instructions.
- B. Deliver products packaged in manufacturer's packaged and sealed containers with manufacturer's identifying labels intact.
- C. Avoid direct contact with this product as it may cause mild-to-moderate irritation.

1.8 PROJECT CONDITIONS

- A. Comply with the polishing system manufacturer's written instructions for age of cured concrete, substrate temperature and moisture content, ambient temperature and humidity, ventilation, and other conditions affecting the floor finish.
- B. Close areas to all traffic during and after polished concrete system application for the time period recommended by the system manufacturer.
- C. Do not apply product when air, surface, or material temperatures are expected to fall below 40° F (4° C) within four hours of expected application.
- D. Do not use on highly dense or non-porous surfaces.
- E. Limit and control damage from excessive dust caused by grinding/polishing procedure.
- F. Properly dispose of collected dust from polishing.

PART 2 - PRODUCTS

2.1 POLISHING SYSTEM MANUFACTURERS

- A. Ameripolish, Inc. (Lowell, AR; 800-592-9320) "AmeriPolish" polished concrete system.
- B. Ardex Americas (Aliquippa, PA; 888-512-7339) Ardex Polished Concrete System "APCS".
- C. Laticrete International, Inc. (Bethany, CT; 800-243-4788) "FGS PermaShine" concrete polishing system.
- D. Prosoco, Inc. (Lawrence, KS; 800-255-4255) "Consolideck" high performance concrete system.

2.2 MATERIALS

- A. Hardener/Densifier: Low-VOC silicate by system manufacturer accepted from mock-up.
- B. Finishing Sealer: System manufacturer's recommended topical sealer; low-VOC, non-film forming, stain resistant.
- C. Polishing Overlay Topping (when required for surface repair):
 - 1. Toppings (either of the following):
 - a. CTS Cement Manufacturing Corp. (Garden Grove, CA; 800-929-3030) Rapid Set "TRU" or "TRU PC" self-leveling topping and resurfacer.
 - b. Ardex Engineered Cements (Aliquippa, PA; 888-512-7339) "PC-T" polished concrete topping or K520 Series self-leveling topper.
 - 2. Application: For use when existing concrete surface is not suitable for polishing or when existing surface requires leveling. Maintain minimum thickness required by the overlay manufacturer.
- D. Surface Patching and Repair Material (when required for slab repair):