MongoDB connection & Atlas boundary

Architecture overview. Readable node and connection sheets follow.



MongoDB connection & Atlas boundary

Readable detail sheet 1/2. Node numbers and page references preserve every directed connection.

#01 / Trigger / Implemented

Database operation requested

Server code requests a shared MongoDB connection.

src/server/db.ts:30

Next -> #2 (p2)

#02 / IF / Switch / Implemented

MONGODB_URI supplied?

Absence rejects live operations; no credentials are displayed.

src/server/db.ts:31

Yes / accepted -> #3 (p2); No / rejected -> #7 (p3)

#03 / Database Query / Implemented

Shared native-driver pool

MongoClient.connect, maxPoolSize 10 and serverSelectionTimeoutMS 6000 are actual code settings.

src/server/db.ts:34

Next -> #4 (p2)

#04 / External API / Unverified

Hosted cluster / Atlas boundary

MongoDB hosting, Atlas cluster tier, region, replica placement and network access rules cannot be inferred from the connection code.

src/server/db.ts:33

Next -> #5 (p3)

MongoDB connection & Atlas boundary

Readable detail sheet 2/2. Node numbers and page references preserve every directed connection.

#05 / Database Query / Implemented

Database selection and transaction

MONGODB_DB override or ovia default; writes can share ClientSession.withTransaction.

src/server/db.ts:103

Next -> #6 (p3)

#06 / Response / Implemented

Repository result returned

Stored records or a surfaced database error return to business services.

src/server/db.ts:44

END: no outgoing connection

#07 / Error Handler / Implemented

Request failed

Validation, access, conflict or service errors are returned to the caller. Status and error shape depend on the specific route.

src/server/http.ts:69

Next -> #8 (p3)

#08 / Response / Implemented

Show error / retry

Failure end state. Caller receives the actual error; a retry may be offered by the UI.

src/server/http.ts:69

END: no outgoing connection

MongoDB connection & Atlas boundary

Complete directed connection register / no omitted success, failure or proposed edges

#01 Database operation requested -> #02 MONGODB_URI supplied? | Next

#02 MONGODB_URI supplied? -> #03 Shared native-driver pool | Yes / accepted

#03 Shared native-driver pool -> #04 Hosted cluster / Atlas boundary | Next

#04 Hosted cluster / Atlas boundary -> #05 Database selection and transaction | Next

#05 Database selection and transaction -> #06 Repository result returned | Next

#02 MONGODB_URI supplied? -> #07 Request failed | No / rejected | FAILURE

#07 Request failed -> #08 Show error / retry | Next | FAILURE

Note: Source implementation is documented; deployed configuration and provider connectivity are not verified.

Note: The hosted-cluster node is a trust boundary, not proof of an Atlas deployment. No private network, replica topology or production configuration has been invented.