

[Home](#) > [Siemens](#) >



SIEMENS

[Larger Photo](#)



3RV2011-1AA10

Siemens 3RV2011-1AA10 Manual Motor Starter/Overload Protector that is adjustable from 1-1.6A, mounts on DIN rail and has a Class 10 tripping characteristic and screw termination



3RV2011-1AA10 Datasheet

~~List Price: \$179.00~~

Our Price: \$108.47

Savings: \$70.53

Quantity in Stock:5

Availability : Stock - Can ship today if ordered prior to 4 p.m. EST

Product Code: SIEMENS-3RV2011-1AA10

Qty:

-	1	+
---	---	---

Add To Cart

Add To Wishlist

Description	Detailed Specifications
	The 3RV2011 MSP's are UL approved as Self Protected Combination Motor Controllers which are also called Type E. In this application, all the required functions for a motor branch are provided in one device: disconnect, short circuit protection, motor control and overload protection. A type E terminal adapter is required. These Siemens Motor Protectors are also approved for use as follows: – Manual Motor Controller: Motor starter, motor disconnect, control and overload protection. – Group Installation: Motor starter only, motor disconnect, control and overload protection. – Tap conductor Protection in Group Installation acc. NEC: Motor starter only; motor disconnect, control and overload protection.
	Technical Specifications • ON/OFF rotary handle with lockout and visible trip indication. • Adjustment dial for setting to motor FLA. • Class 10 overload trip characteristics. • Short circuit trip at 12 times the maximum setting of the FLA adjustment dial. • Short circuit current rating: • Ambient compensated up to 140° F (applies to side by side mounting). • Phase loss sensitivity. • Test trip function.