

# Rejection Sampling



# Metropolis-Hastings Algorithm

- ▶ Target distribution on  $\mathbb{X} = \mathbb{R}^d$  of density  $\pi(x)$ .
- ▶ Proposal distribution: for any  $x, x' \in \mathbb{X}$ , we have  $q(x'|x) \geq 0$  and  $\int_{\mathbb{X}} q(x'|x) dx' = 1$ .

## Algorithm

1. Starting with  $X^{(1)}$ , for  $t = 2, 3, \dots$
2. Sample  $X^* \sim q(\cdot | X^{(t-1)})$ .
3. Compute  $\alpha(X^* | X^{(t-1)}) = \min \left( 1, \frac{\pi(X^*)q(X^{(t-1)} | X^*)}{\pi(X^{(t-1)})q(X^* | X^{(t-1)})} \right)$ .
4. Sample  $U \sim \mathcal{U}_{[0,1]}$ . If  $U \leq \alpha(X^* | X^{(t-1)})$ , set  $X^{(t)} = X^*$ , otherwise set  $X^{(t)} = X^{(t-1)}$ .

# Metropolis-Hastings Algorithm

- ▶ The proposal distribution  $q$  can be chosen quite freely, but it should be easy to sample from and to evaluate.
- ▶ The acceptance probability  $\alpha(x'|x)$  ensures that the chain has  $\pi$  as its stationary distribution.
- ▶ If  $q$  is symmetric, i.e.,  $q(x'|x) = q(x|x')$ , then the acceptance probability simplifies to  $\alpha(x'|x) = \min\left(1, \frac{\pi(x')}{\pi(x)}\right)$ . This is also known as Metropolis Random Walk.
- ▶ If  $q$  does not depend on the current state, i.e.,  $q(x'|x) = q(x')$ , then the algorithm reduces to the Independent Metropolis-Hastings algorithm.
- ▶ The choice of  $q$  affects the efficiency of the algorithm. A poorly chosen  $q$  can lead to slow mixing and high autocorrelation in the samples.

# Role of $\alpha(X^*|X^{(t-1)})$

- ▶ The acceptance probability  $\alpha(X^*|X^{(t-1)})$  is crucial for ensuring that the Markov chain has the desired stationary distribution  $\pi$ .
- ▶ It corrects for the discrepancy between the proposal distribution  $q$  and the target distribution  $\pi$ .
- ▶ If the proposed state  $X^*$  has a higher density under  $\pi$  than the current state  $X^{(t-1)}$ , it is always accepted ( $\alpha = 1$ ).
- ▶ If  $X^*$  has a lower density, it may still be accepted with a probability proportional to the ratio of densities, allowing exploration of the state space.
- ▶ This mechanism helps to avoid getting stuck in local modes and promotes better mixing of the chain.

# Role of $\alpha(X^*|X^{(t-1)})$

- ▶ If  $\pi(x^*) > \pi(x)$ , then the proposed state has higher probability than current state which favors acceptance
- ▶ If  $\pi(x^*) < \pi(x)$ , then the proposed state has lower probability than current state which favors rejection
- ▶ Intuition: want to spend time in high-probability regions, so moves towards them should be favored
- ▶ Reverse proposal ratio: how easy is it to propose reverse move compared to forward move?
- ▶ Intuition: if proposal mechanism makes it easy to reach certain states, we need to be more selective accepting such moves. otherwise the chain will be biased towards such easy-to-propos-to regions rather than high probability regions

# Transition Kernel

## Lemma

The kernel of the Metropolis–Hastings algorithm is given by

$$K(x, y) = \alpha(y \mid x)q(y \mid x) + (1 - a(x))\delta_x(y).$$

Proof: We have

$$\begin{aligned} K(x, y) &= \int q(x^* \mid x) \{ \alpha(x^* \mid x) \delta_{x^*}(y) + (1 - \alpha(x^* \mid x)) \delta_x(y) \} dx^* \\ &= q(y \mid x) \alpha(y \mid x) + \left\{ \int q(x^* \mid x) (1 - \alpha(x^* \mid x)) dx^* \right\} \delta_x(y) \\ &= q(y \mid x) \alpha(y \mid x) + \left\{ 1 - \int q(x^* \mid x) \alpha(x^* \mid x) dx^* \right\} \delta_x(y) \\ &= q(y \mid x) \alpha(y \mid x) + \{1 - a(x)\} \delta_x(y). \end{aligned}$$

# Reversibility

## Proposition

The Metropolis–Hastings kernel  $K$  is  $\pi$ -reversible and thus admits  $\pi$  as invariant distribution.

Proof: For any  $x, y \in \mathbb{X}$ , with  $x \neq y$

$$\begin{aligned}\pi(x)K(x, y) &= \pi(x)q(y \mid x)\alpha(y \mid x) \\ &= \pi(x)q(y \mid x) \left( 1 \wedge \frac{\pi(y)q(x \mid y)}{\pi(x)q(y \mid x)} \right) \\ &= (\pi(x)q(y \mid x) \wedge \pi(y)q(x \mid y)) \\ &= \pi(y)q(x \mid y) \left( \frac{\pi(x)q(y \mid x)}{\pi(y)q(x \mid y)} \wedge 1 \right) = \pi(y)K(y, x).\end{aligned}$$

If  $x = y$ , then obviously  $\pi(x)K(x, y) = \pi(y)K(y, x)$ .