

45 Line



A brand of
BASF - We create chemistry

45- Basecoat

Application Waterborne metallic and solid color basecoat / clearcoat finishing

- Key Features**
- Easy application combined with good hiding power
 - Flash-off times can be reduced significantly by using appropriate air blow equipment
 - Mixtures will keep for up to 6 months when stored in plastic containers or cans coated inside

Mixing Ratio Stir immediately after completion of 45 Line tinters, then again after addition of 45-R45.



Mixing Ratio 100 % by volume



Reducer 70 % by volume 45-R45 - Reducer

Spray Viscosity at 20°C DIN 4: 16 - 22 s



Application		 HVLP Spray Gun	
Application Pressure		2 bar	
Nozzle Pressure		0.7 bar	
Nozzle Size		1.4	
Number of Coats		2 (spray to cover), ½ to match the effect	
Flash Off at 20°C		5 min Flash off approx. 5 min after each spray coat	
Film thickness		10 - 15 µm	

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

45 Line

45- Basecoat



A brand of
BASF - We create chemistry

Safety Advice

It cannot be ruled out that this product contains particles $< 0.1 \mu\text{m}$. The products are suitable for professional use only. For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

2004/42/IIB(d)(420)419: The EU limit value for this product (product category: IIB.d) in ready-for-use form is max 420 g/l. The VOC content of this product is 419 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH - Automotive Refinish Coatings Solutions Europe - Glasuritstrasse 1 - 48165 Münster - Germany