

Technical Information

Recommended spray guns (Sata, Iwata, Devilbiss, Walcom)



Sata

Spray gun	Nozzle set-up	Air pressure (bar)	45 Line	35 Line	30 Line	Clears	20-35 20-95	20-24 20-34 20-94
Sata Jet 5000 HVLP	1.4	2.0	x					
Sata Jet 5000 HVLP	1.3	2.0		x	x	x	x	
Sata Jet 5000 RP	1.3	2.0		x	x	x	x	
Sata Jet x5500 HVLP	1.4 O	2.0	x					
Sata Jet x5500 HVLP	1.3 I + O	2.0		x	x	x	x	
Sata Jet x5500 RP	1.3 I + O	2.0		x	x	x	x	
Sata Jet x5500 RP	1.2 I + O	2.0				x		
Sata Jet 100 BF RP	1.6	2.0						x
Sata Jet 100 BF HVLP	1.7-1.8	2.0						x
Sata jetX RP	1.3 I + O	2.0				x	x	
Sata jetX HVLP	1.3 O	2.0	x			x	x	
Sata jetX RP	1.2 I + O	2.0				x		
Sata jet 1500 B HVLP*	1.4	2.0	x					
Sata jet 1500 B RP*	1.3	2.0		x	x	x	x	

*entry level

Iwata

Spray gun	Nozzle set-up	Air pressure (bar)	45 Line	35 Line	30 Line	Clears	20-35 20-95	20-24 20-34 20-94
WS 400	1.5 HD	2.0	x					
WS 400	1.3-1.4 HD	2.0	x	x	x	x	x	
LS 400	1.4 ET	1.8			x	x	x	
W 400 WB 2	1.3	2.0		x	x	x	x	
W 400 WBX	1.3	2.0			x	x	x	
W 400 LV1/2	1.8	2.0						x
WS-primer WET ON WET	1.3-1.4	2.0				x	x	
WS-primer FILLER	1.6-1.8	2.0						x

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH, Automotive Refinish Coatings Solutions, Europe, Glasuritstraße 1, 48165 Münster, Germany 01/2026

Technical Information

Recommended spray guns (Sata, Iwata, Devilbiss, Walcom)



Devilbiss

Spray gun	Nozzle set-up	Air pressure (bar)	45 Line	35 Line	30 Line	Clears	20-35 20-95	20-24 20-34 20-94
Devilbiss GTI HVLP aircap 115	1.3	2.0	x	x	x	x	x	
Devilbiss GTI Transtec aircap 110	1.3	2.0	x	x	x	x	x	
Devilbiss PRI transtec	1.7-1.8	2.0						x
Devilbiss PRI Pro	1.7-1.8	2.0						x
Devilbiss GTI PRO HVLP aircap H1	1.3	2.0	x	x	x	x	x	
Devilbiss GTI Pro transtec aircap T1	1.3	2.0			x	x	x	
Devilbiss GTI PRO transtec aircap T110	1.3	2.0			x	x	x	
Devilbiss GTI PRO Lite 110	1.3-1.4	2.0			x	x	x	
Devilbiss GTI PRO Lite TE 10	1.3-1.4	2.0	x	x	x	x		
Devilbiss GTI PRO Lite HV 30	1.3	1.7	x	x	x	x	x	
Devilbiss PRI PRO Lite	1.6 PR 10	2.0						x
Devilbiss GPI 1	1.7-1.8	2.0						x
Devilbiss DV1 HVLP PLUS DV1-B+	1.3	2.0*	x					
Devilbiss DV1 C C1 Plus	1.2-1.3	2.0*				x		

*at gun handle, 1.5 at digital gauge

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH, Automotive Refinish Coatings Solutions, Europe, Glasuritstraße 1, 48165 Münster, Germany 01/2026

Technical Information

Recommended spray guns (Sata, Iwata, Devilbiss, Walcom)



Walcom

Spray gun	Nozzle set-up	Air pressure (bar)	45 Line	35 Line	30 Line	Clears	20-35 20-95	20-24 20-34 20-94
Walcom Genesi HTE	1.3	2.0	x		x	x	x	
Walcom SLIM HTE	1.3	2.0	x	x	x	x	x	
Walcom SLIM HTE	1.7	2.0						x
Walcom SLIM HVLP	1.7	2.0						x
Walcom Genesi Carbonio 360 HTE base	1.3	2.0	x	x				
Walcom Genesi Carbonio 360 HTE Clear	1.3	2.0			x	x	x	
Walcom Genesi Carbonio 360 HVLP	1.3	2.0	x	x	x	x	x	

Safety instructions:

**The products are suitable for professional use only.
It cannot be ruled out that this product contains particles < 0.1 µm.**

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH, Automotive Refinish Coatings Solutions, Europe, Glasuritstraße 1, 48165 Münster, Germany 01/2026