


baslac® Temperature Chart – VOC



baslac® 40-100 High Speed 2K VOC Clear / 40-440 VOC Clear

more than 2 panels	Hardeners	50-420	50-420	50-430	50-430
up to 2 vertical panels	Hardeners	50-415	50-415	50-420	50-420
up to 1 panel	Hardeners	50-415	50-415	50-420	50-420



baslac® 40-450 VOC Clear

more than 2 panels	Hardeners	50-420	50-420	50-430	50-430
	Reducers	60-20	60-30	60-30	60-30
up to 2 vertical panels	Hardeners	50-415	50-420	50-420	50-420
	Reducers	60-10/20	60-10/20	60-20	60-20
up to 1 panel	Hardeners	50-415	50-415	50-420	50-420
	Reducers	60-10/20	60-10/20	60-20	60-20
Spot repair	Hardeners	50-415			
	Reducers	60-05			



baslac® primer filler

more than 1 panel	Hardeners	50-15	50-15	50-15	50-15
	Reducers	60-10	60-20	60-20	60-20
up to 1 panel	Hardeners	50-05/15	50-05/15	50-15	50-15
	Reducers	60-05/10	60-10	60-10	60-20
Spot repair	Hardeners	50-05			
	Reducers	60-05			



°C



More information on
www.baslac.com

