33. Search in Rotated Sorted Array ★

Question Editorial Solution

My Submissions (/problems/search-in-rotated-sorted-array/submissions/)

Total Accepted: 117163 Total Submissions: 377025 Difficulty: Hard

Suppose a sorted array is rotated at some pivot unknown to you beforehand.

```
(i.e., 0 1 2 4 5 6 7 might become 4 5 6 7 0 1 2).
```

You are given a target value to search. If found in the array return its index, otherwise return -1.

You may assume no duplicate exists in the array.

Subscribe (/subscribe/) to see which companies asked this question

Show Tags

Show Similar Problems

Have you met this question in a real interview? Yes No

Discuss (https://leetcode.com/discuss/questions/oj/search-in-rotated-sorted-array)

Pick One (/problems/random-one-question/)

```
C++ • 2 4
```

```
class Solution {
 2
    public:
         int search(vector<int>& nums, int target) {
 3
             int first = 0, end = nums.size();
 4
 5
             while (first != end) {
 6
 7
                 int mid = first + (end - first) / 2;
 8
                 if (nums[mid] == target) {
 9
                      return mid;
10
                 else if (nums[mid] >= nums[first] && nums[mid] >= nums[end - 1]) { //
11
                      if (target >= nums[first] && target < nums[mid]) {</pre>
12
                          end = mid;
13
14
                      }
15
                     else {
                          first = mid + 1;
16
17
                 }
19
                 else if (nums[mid] <= nums[first] && nums[mid] <= nums[end - 1]) { //
20
                      if (target > nums[mid] && target <= nums[end - 1]) {</pre>
                          first = mid + 1; Send Feedback (mailto:admin@leetcode.com?subject=Feedback)
21
22
                      }
                     else {
23
```

□ Notes

```
24
                          end = mid;
25
                     }
                 }
26
27
                 else { // normal
                     if (target > nums[mid]) { // right
28
29
                         first = mid + 1;
30
                     else { // left
31
                         end = mid;
32
33
                 }
34
35
36
             return -1;
37
        }
38
```

Custom Testcase

Run Code

Submit Solution

Frequently Asked Questions (/faq/) | Terms of Service (/tos/)

Privacy

Copyright © 2016 LeetCode