264. Ugly Number II ★

Question Editorial Solution My Submissions (/problems/ugly-number-ii/submissions/)

Total Accepted: 40280 Total Submissions: 132576 Difficulty: Medium

Write a program to find the n-th ugly number.

Ugly numbers are positive numbers whose prime factors only include 2, 3, 5. For example, 1, 2, 3, 5, 6, 8, 9, 10, 12 is the sequence of the first 10 ugly numbers.

Note that 1 is typically treated as an ugly number.



Credits:

Special thanks to @jianchao.li.fighter (https://leetcode.com/discuss/user/jianchao.li.fighter) for adding this problem and creating all test cases.

Subscribe (/subscribe/) to see which companies asked this question

Show Similar Problems

Have you met this question in a real interview? Yes No

Discuss (https://leetcode.com/discuss/questions/oj/ugly-number-ii)

Pick One (/problems/random-one-question/)

```
class Solution {
 2
    public:
        int nthUglyNumber(int n) {
 3
 4
            static vector<int> uglyArray = {1};
 5
            static int L2index = 0, L3index = 0, L5index = 0;
 6
            if (n <= 0) return 0;
 7
 8
            if (uglyArray.size() >= n) return uglyArray[n - 1];
 9
            while (!(uglyArray.size() == n)) {
10
11
                 initializer_list<int> compareNum = { uglyArray[L2index] * 2, uglyArra
                uglyArray.push back(min(compareNum));
12
                 if (uglyArray[L2index] * 2 == uglyArray.back()) ++L2index;
13
                 if (uglyArnayA Sientle Feedback-(mailtonadanin @leetoode.com natebject=Feedback)
14
                 if (uglyArray[L5index] * 5 == uglyArray.back()) ++L5index;
15
```

```
16 }
17
18 return uglyArray[n - 1];
19 }
20 };

Custom Testcase

Run Code Submit Solution
```

Frequently Asked Questions (/faq/) | Terms of Service (/tos/)

Privacy

Copyright © 2016 LeetCode