

138. Copy List with Random Pointer ★

[Question](#)[Editorial Solution](#)[My Submissions \(/problems/copy-list-with-random-pointer/submissions/\)](/problems/copy-list-with-random-pointer/submissions/)Total Accepted: **76145** Total Submissions: **290190** Difficulty: **Hard**

A linked list is given such that each node contains an additional random pointer which could point to any node in the list or null.

Return a deep copy of the list.

[Subscribe \(/subscribe/\)](/subscribe/) to see which companies asked this question

[Show Tags](#)[Show Similar Problems](#)Have you met this question in a real interview? [Discuss \(https://leetcode.com/discuss/questions/oj/copy-list-with-random-pointer\)](https://leetcode.com/discuss/questions/oj/copy-list-with-random-pointer)[Pick One \(/problems/random-one-question/\)](/problems/random-one-question/)[Notes](#)

C++



```
1  /**
2   * Definition for singly-linked list with a random pointer.
3   * struct RandomListNode {
4   *     int label;
5   *     RandomListNode *next, *random;
6   *     RandomListNode(int x) : label(x), next(NULL), random(NULL) {}
7   * };
8   */
9  class Solution {
10 public:
11     RandomListNode *copyRandomList(RandomListNode *head) {
12         unordered_map<RandomListNode*, RandomListNode*> hash;
13         for (auto it = head; it != NULL; it = it->next) {
14             hash[it] = new RandomListNode(it->label);
15         }
16         for (auto it = head; it != NULL; it = it->next) {
17             hash[it]->next = hash[it->next];
18             hash[it]->random = hash[it->random];
19         }
20         return hash[head];
21     }
22 };
```

[✉ Send Feedback \(mailto:admin@leetcode.com?subject=Feedback\)](mailto:admin@leetcode.com?subject=Feedback)

Submit Solution

[Frequently Asked Questions \(/faq/\)](/faq/) | [Terms of Service \(/tos/\)](/tos/)

[Privacy](#)

Copyright © 2016 LeetCode

 Notes

 [Send Feedback \(mailto:admin@leetcode.com?subject=Feedback\)](mailto:admin@leetcode.com?subject=Feedback)