

31. Next Permutation ★

[Question](#)[Editorial Solution](#)[My Submissions \(/problems/next-permutation/submissions/\)](/problems/next-permutation/submissions/)

Total Accepted: **78121** Total Submissions: **284338** Difficulty: **Medium**

Implement next permutation, which rearranges numbers into the lexicographically next greater permutation of numbers.

If such arrangement is not possible, it must rearrange it as the lowest possible order (ie, sorted in ascending order).

The replacement must be in-place, do not allocate extra memory.

Here are some examples. Inputs are in the left-hand column and its corresponding outputs are in the right-hand column.

1,2,3 → 1,3,2

3,2,1 → 1,2,3

1,1,5 → 1,5,1

[Subscribe \(/subscribe/\)](/subscribe/) to see which companies asked this question

[Show Tags](#)[Show Similar Problems](#)

Have you met this question in a real interview?

[Discuss \(https://leetcode.com/discuss/questions/oj/next-permutation\)](https://leetcode.com/discuss/questions/oj/next-permutation)

[Pick One \(/problems/random-one-question/\)](/problems/random-one-question/)

C++



```
1 class Solution {
2 public:
3     void nextPermutation(vector<int>& nums) {
4         auto first = nums.begin(), last = nums.end();
5         if (first == last) return;
6         auto i = last;
7         if (first == --i) return;
8
9         while (1) {
10             auto i1 = i;
11             if (*--i < *i1) {
12                 auto i2 = last;
13                 while (!(*i < *i2)) i2--;
14                 iter_swap(i, i2);
```

```
15         reverse(i1, last);
16         return;
17     }
18     if (i == first) {
19         reverse(first, last);
20         return;
21     }
22 }
23 }
24 };
```

Custom Testcase ☐

Run Code

Submit Solution

Notes

[Frequently Asked Questions \(/faq/\)](/faq/) | [Terms of Service \(/tos/\)](/tos/)

[Privacy](#)

Copyright © 2016 LeetCode

✉ [Send Feedback \(mailto:admin@leetcode.com?subject=Feedback\)](mailto:admin@leetcode.com?subject=Feedback)