61. Rotate List ★

Question Editorial Solution

My Submissions (/problems/rotate-list/submissions/)

Total Accepted: 81615 Total Submissions: 345602 Difficulty: Medium

Given a list, rotate the list to the right by *k* places, where *k* is non-negative.

For example:

```
Given 1->2->3->4->5->NULL and k = 2, return 4->5->1->2->3->NULL.
```

Subscribe (/subscribe/) to see which companies asked this question

Show Tags

Show Similar Problems

Have you met this question in a real interview? Yes No

Discuss (https://leetcode.com/discuss/questions/oj/rotate-list)

Pick One (/problems/random-one-question/)

```
/**
 1
     * Definition for singly-linked list.
 2
     * struct ListNode {
 3
 4
           int val;
 5
           ListNode *next;
     *
           ListNode(int x) : val(x), next(NULL) {}
 6
 7
     * };
     */
 8
 9
    class Solution {
10
    public:
        ListNode* rotateRight(ListNode* head, int k) {
11
             if (!head) return head;
12
             ListNode* curNode = head, *endNode = NULL;
13
             vector<ListNode*> cache;
14
15
             while (curNode) {
16
                 cache.push_back(curNode);
                 curNode = curNode->next;
17
             }
18
             k %= cache.size();
19
             if (k == 0) {
20
21
                 return head;
22
            else {
23
                 cache.back()->next = cache.front();
24
25
                 cache [cache . Sehot Fleedback/(naxiito-allHih@leetcode.com?subject=Feedback)
26
                 return cache[cache.size() - k];
```

□ Notes

	27 28	٦.	}	}	
_		_			

Custom Testcase

Run Code

Submit Solution

Frequently Asked Questions (/faq/) | Terms of Service (/tos/)

Privacy

Copyright © 2016 LeetCode