



Information Retrieval

IR Evaluation

Danilo Montesi
Stefano Giovanni Rizzo



Measuring Relevance

- Methods pioneered by Cyril Cleverdon in the *Cranfield Experiments* in the 1960s
- Three elements:
 1. A benchmark **document collection**
 2. A benchmark suite of **queries**
 3. A **human assessment** of either Relevant or Nonrelevant for each query and each document



Cyril Cleverdon



Assessments

- Note: **user need** is translated into a **query**
- Relevance is assessed relative to the **user need**, *not* the **query**
- E.g., Information need: *My swimming pool bottom is becoming black and needs to be cleaned.*
- Query: ***pool cleaner***
- Assess whether the doc addresses the underlying need, not whether it has these words



Relevance judgments

- Binary (relevant vs. non-relevant) in the simplest case, or more precisely (0, 1, 2, 3 ...) in others
- If, for each query, we consider all the set of documents to be judged, the relevance assessment can be huge and expensive
- The depth-**k** pooling solution:
 - Take in consideration the top-**k** (e.g. 100) documents of **N** (e.g. 100) different information retrieval systems
 - Humans must judge a “pool” of no more than **k x N** documents (e.g. 10'000), which is far less than the entire document collection (could be millions of documents).



Qualified Test Collections

<i>Collection</i>	<i>NDocs</i>	<i>NQrys</i>	<i>Size (MB)</i>	<i>Term/Doc</i>	<i>Q-D RelAss</i>
ADI	82	35			
AIT	2109	14	2	400	>10,000
CACM	3204	64	2	24.5	
CISI	1460	112	2	46.5	
Cranfield	1400	225	2	53.1	
LISA	5872	35	3		
Medline	1033	30	1		
NPL	11,429	93	3		
OSHMED	34,8566	106	400	250	16,140
Reuters	21,578	672	28	131	
TREC	740,000	200	2000	89-3543	» 100,000

Typical
TREC



TREC Collections

Text REtrieval Conference (TREC)

...to encourage research in information retrieval
from large text collections.

- The U.S. *National Institute of Standards and Technology* (NIST) has run a large IR test bed evaluation series since 1992. Within this framework, there have been **many tracks** over a range of **different test collections**.
- TREC GOV2 is now the largest Web collection easily available for research purposes, including 25 million pages.



Mechanical Turk

- Present query-document pairs to low-cost labor on online crowd-sourcing platforms
 - Hope that this is cheaper than hiring qualified assessors
- Lots of literature on using crowd-sourcing for such tasks
- Main takeaway – you get some signal, but the variance in the resulting judgments is very high




Effectiveness measures


- To assess the *effectiveness* of an IR system (the quality of its search results), there are two parameters about the system's returned results for a query:
 - **Precision:** What fraction of the **returned** documents are relevant to the information need?
 - **Recall:** What fraction of the **relevant** documents in the collection were returned by the system?


Collection of documents

Each dot • is a document of the collection





Relevant documents

Given a query, the set in green  is the set of all the documents **really relevant** to the query.



Returned documents


Given the same query, the set in yellow  is the set of all the documents **returned by the system** we want to **evaluate**.






Relevant retrieved documents

$$\text{Relevant Retrieved Documents} = \text{Relevant Documents} \cap \text{Retrieved Documents}$$




Relevant retrieved documents

$$\text{Relevant Retrieved Documents} = \text{Relevant Documents} \cap \text{Retrieved Documents}$$




Precision

$$\text{Precision} = \frac{\text{Relevant Retrieved Documents}}{\text{Retrieved Documents}}$$



Recall


$$\text{Recall} = \frac{\text{Relevant Retrieved Documents}}{\text{Relevant Documents}}$$






Precision @ K


- Set a rank threshold K
- Compute % relevant in top K
- Ignores documents ranked lower than K
- Ex:
 - Precision@1 is 1 rel. /1 ret.
 - Precision@2 is 1 rel. /2 ret.
 - Precision@3 is 2 rel. /3 ret.
- In similar fashion we have Recall@K




#1 is relevant



#2 is not relevant



#3 is relevant








#4 is not relevant



#5 is relevant



Recall @ K

- Set a rank threshold K
 - Compute % relevant in top K
 - Ignores documents ranked lower than K
 - Ex:
 - Recall@1 is 1 rel. /3 rel. tot
 - Recall@2 is 1 rel. /3 rel. tot
 - Recall@3 is 2 rel. /3 rel. tot
- | | |
|---|--------------------|
|  | #1 is relevant |
|  | #2 is not relevant |
|  | #3 is relevant |
|  | #4 is not relevant |
|  | #5 is relevant |



Average Precision (AP)

- Average Precision is an aggregated measure for ranked results.
- It is computed as follows:
 - Instead of setting an arbitrary K we stop only when **all the relevant documents** are retrieved.
 - This coincides with the first K for which $\text{Recall}@K$ is equal to 1.
 - We compute the Precisions $@K$ **only for those K where relevant result is retrieved**.
 - The **average** of this Precision measures is the **Average Precision**.



Example: Average Precision (AP)



= the relevant documents

Ranking #1



Recall@k	0.17	0.17	0.33	0.5	0.67	0.83	0.83	0.83	0.83	1.0
Precision@k	1.0	0.5	0.67	0.75	0.8	0.83	0.71	0.63	0.56	0.6

We stop
when
Recal@k=1

Ranking #2



Recall@k	0.0	0.17	0.17	0.17	0.33	0.5	0.67	0.67	0.83	1.0
Precision@k	0.0	0.5	0.33	0.25	0.4	0.5	0.57	0.5	0.56	0.6

We stop
when
Recal@k=1

Ranking #1: $(1.0 + 0.67 + 0.75 + 0.8 + 0.83 + 0.6)/6 = 0.78$

Ranking #2: $(0.5 + 0.4 + 0.5 + 0.57 + 0.56 + 0.6)/6 = 0.52$

Recall@10 and Precision@10 is equal for the two rankings.

However, AP is able to capture that Ranking #1 is better, as it ranks more relevant documents in higher positions.




Mean Average Precision











- When evaluating a system we usually measure the effectiveness over **more than one query**.
 - Test collections usually span from 50 to 500 queries.
- After computing the Average Precision of each query in the test collection, the **Mean Average Precision (MAP)** is the average of the Average Precision over all the queries.




Mean Average Precision (MAP)











 = relevant documents for query 1

Ranking #1

										
Recall	0.2	0.2	0.4	0.4	0.4	0.6	0.6	0.6	0.8	1.0
Precision	1.0	0.5	0.67	0.5	0.4	0.5	0.43	0.38	0.44	0.5

 = relevant documents for query 2

Ranking #2

										
Recall	0.0	0.33	0.33	0.33	0.67	0.67	1.0	1.0	1.0	1.0
Precision	0.0	0.5	0.33	0.25	0.4	0.33	0.43	0.38	0.33	0.3

average precision query 1 = $(1.0 + 0.67 + 0.5 + 0.44 + 0.5)/5 = 0.62$

average precision query 2 = $(0.5 + 0.4 + 0.43)/3 = 0.44$

mean average precision = $(0.62 + 0.44)/2 = 0.53$



MAP - Observations

- If a relevant document never gets retrieved, we assume the precision corresponding to that relevant doc to be zero.
- MAP is macro-averaging: each query counts equally
- Now perhaps most commonly used measure in research papers
- MAP assumes user is interested in finding many relevant documents for each query
- MAP requires many relevance judgments in text collection



Beyond binary relevance

- We assumed a **binary notion of relevance**:
 - either a document is relevant to the query or
 - it is non relevant to the query.
- Some documents can be **less relevant** than others, but still relevant (non binary notion)
 - Specific measure with non-binary assessments: **DCG** (Discounted Cumulative Gain) or **NDCG** (Normalized Discounted Cumulative Gain).
- Binary relevance is still more common and provide a good estimation for IR evaluation



References

[Christopher D. Manning, Prabhakar Raghavan and Hinrich Schütze](#)
[Introduction to Information Retrieval](#)
[Cambridge University Press.](#)
[2008](#)

The book is also online for free:

- [HTML edition \(2009.04.07\)](#)
- [PDF of the book for online viewing \(with nice hyperlink features, 2009.04.01\)](#)
- [PDF of the book for printing \(2009.04.01\)](#)

