

6. Trees, Heaps, and Binary Search Trees (BSTs)

- Trees: tree terminology, tree ADT, operations and efficiency
- Binary trees: properties, expression trees
- Heaps: heap applications, heap operations and efficiency, heap as priority queue, heap sort
- BSTs: operations and efficiency

Trees, Heap, and BST


1

Trees



What is a Tree

- ◆ In computer science, a tree is an abstract model of a hierarchical structure
- ◆ A tree consists of nodes and edges with a parent-child relation
- ◆ Applications:
 - Organization charts
 - File systems
 - Decision processes




Trees, Heap, and BST

3

Tree Terminology

- ◆ **Root**: node without parent (A)
- ◆ **Internal node**: node with at least one child (A, B, C, F)
- ◆ **External node** (a.k.a. **leaf**): node without children (E, I, J, K, G, H, D)
- ◆ **Path** to a node: a sequence of nodes and edges from the root to the node
- ◆ **Ancestors** of a node: parent, grandparent, grand-grandparent, etc.
- ◆ **Depth** of a node: number of edges on the path to the node
- ◆ **Height** of a tree: the number of edges on the longest path
- ◆ **Descendant** of a node: child, grandchild, grand-grandchild, etc.



Trees, Heap, and BST

4

Tree ADT

- ◆ **Generic functions**:
 - `int size()`
 - `boolean isEmpty()`
- ◆ **Access functions**:
 - `node root(tree)`
 - `node parent(p)`
 - `node_list children(p)`
 - `node left_child(p)`
 - `node right_child(p)`

- ◆ **Query functions**:
 - `boolean isInternal(p)`
 - `boolean isExternal(p)`
 - `boolean isRoot(p)`
 - `int height(tree)`
- ◆ **Additional update functions** may be defined by data structures implementing the Tree ADT

Trees, Heap, and BST

5


Preorder Traversal

- ◆ A **traversal** visits the nodes of a tree in a systematic manner
- ◆ In a **preorder** traversal, a node is visited before its descendants
- ◆ Application: print a structured document

```

function preorder(v)
  visit(v);
  for (each w of children(v)){
    preorder(w);
  }

```




Trees, Heap, and BST

6

Postorder Traversal

- In a **postorder** traversal, a node is visited after all its descendants
- Application: compute space used by files in a directory and its subdirectories

```
function postOrder(v)
for (each w of children(v)){
    postOrder(w);
}
visit(v);
```



Trees, Heap, and BST


7

Binary Tree

- A binary tree is a tree in which each internal node has at most two children
- We call the children of an internal node left child and right child
- Alternative recursive definition: a binary tree is either
 - a tree consisting of a single node, or
 - a tree whose root has one or two children, each of which is a binary tree

- Applications:

- arithmetic expressions
- decision processes
- searching




Trees, Heap, and BST

8

Arithmetic Expression Tree

- Binary tree associated with an arithmetic expression
 - internal nodes: operators
 - external nodes: operands
- Example: arithmetic expression tree for the expression $(2 \times (a - 1) + (3 \times b))$




Trees, Heap, and BST

9

Decision Tree

- Binary tree associated with a decision process
 - internal nodes: questions with yes/no answer
 - external nodes: decisions
- Example: dining decision



Trees, Heap, and BST

10


Properties of Binary Trees

- Notation

n number of nodes
 e number of external nodes
 i number of internal nodes
 h height

- Properties:

- $e = i + 1$
- $n = 2e - 1$
- $h \leq i$
- $h \leq (n - 1)/2$
- $e \leq 2^h$
- $h \geq \log_2 e$
- $h \geq \log_2 (n + 1) - 1$




Trees, Heap, and BST

11

Inorder Traversal

- In an inorder traversal a node is visited after its left subtree and before its right subtree
- Application: draw a binary tree
 - $x(v)$ = inorder rank of v
 - $y(v)$ = depth of v

```
function inOrder(v)
if (isInternal (v)){
    inOrder (leftChild (v));
    visit(v);
    if (isInternal (v)){
        inOrder (rightChild (v));
    }
}
```




Trees, Heap, and BST

12

Print Arithmetic Expressions

- Specialization of an inorder traversal
 - print "(" before traversing left subtree
 - print operand or operator when visiting node
 - print ")" after traversing right subtree



```
function printExpr(v)
    if (isInternal (v)){
        printf("%c", '(');
        inOrder (leftChild (v));
    }
    print(v); // depends on v's data
    if (isInternal (v)){
        inOrder (rightChild (v));
        printf("%c", ')');
    }
}
```


((2 × (a − 1)) + (3 × b))

Trees, Heap, and BST

13

Evaluate Arithmetic Expressions

- Specialization of a postorder traversal
 - recursive method returning the value of a subtree
 - when visiting an internal node, combine the values of the subtrees



```
function evalExpr(v)
    if (isExternal (v)){
        return v.value ();
    }
    else{
        x = evalExpr(leftChild (v));
        y = evalExpr(rightChild (v));
        ⧫ ← operator stored at v;
        return x ⧫ y;
    }
}
```

Trees, Heap, and BST

14

Priority Queue ADT

- A priority queue stores a collection of items
- An item is a pair (key, element)
- Main methods of the Priority Queue ADT
 - insertItem(k, o)** inserts an item with key k and element o
 - removeMin()** removes the item with smallest key and returns its element
- Additional methods
 - minKey()** returns, but does not remove, the smallest key of an item
 - minElement()** returns, but does not remove, the element of an item with smallest key
 - size()**, **isEmpty()**
- Applications:
 - Standby flyers
 - Auctions

Trees, Heap, and BST

15

Example: Priority Queue

| Operator | Output | Priority Queue |
|------------------|--------|-------------------------|
| insertItem(5, A) | — | (5,A) |
| insertItem(9, C) | — | (5,A),(9,C) |
| insertItem(3, B) | — | (3,B),(5,A),(9,C) |
| insertItem(7, D) | — | (3,B),(5,A),(7,D),(9,C) |
| minElement() | B | (3,B),(5,A),(7,D),(9,C) |
| minKey() | 3 | (3,B),(5,A),(7,D),(9,C) |
| removeMin() | B | (5,A),(7,D),(9,C) |
| size() | 3 | (5,A),(7,D),(9,C) |
| removeMin() | A | (7,D),(9,C) |
| removeMin() | D | (9,C) |
| removeMin() | C | |
| removeMin() | error | |
| isEmpty() | true | |

Trees, Heap, and BST

16

Total Order Relation

- Keys in a priority queue can be arbitrary objects on which an order is defined
- Two distinct items in a priority queue can have the same key
- Mathematical concept of total order relation ≤
 - Reflexive property: $x \leq x$
 - Antisymmetric property: $x \leq y \wedge y \leq x \Rightarrow x = y$
 - Transitive property: $x \leq y \wedge y \leq z \Rightarrow x \leq z$

Trees, Heap, and BST


17

What is a heap

- A heap is a binary tree storing keys at its internal nodes and satisfying the following properties:

- The last node of a heap is the rightmost internal node of depth $h - 1$

- Heap-Order:** for every internal node v other than the root, $key(v) \geq key(parent(v))$
- Complete Binary Tree:** let h be the height of the heap
 - for $i = 0, \dots, h - 2$, there are 2^i nodes of depth i
 - at depth $h - 1$, the internal nodes are to the left of the external nodes



Trees, Heap, and BST


18

Height of a Heap

◆ **Theorem:** A heap storing n keys has height $O(\log n)$

Proof: (we apply the complete binary tree property)


- Let h be the height of a heap storing n keys
- Since there are 2^i keys at depth $i = 0, \dots, h-2$ and at least one key at depth $h-1$, we have $n \geq 1 + 2 + 4 + \dots + 2^{h-2} + 1$
- Thus, $n \geq 2^{h-1}$, i.e., $h \leq \log n + 1$



19

Heaps and Priority Queues

- ◆ We can use a heap to implement a priority queue
- ◆ We store a (key, element) item at each internal node
- ◆ We keep track of the position of the last node
- ◆ For simplicity, we show only the keys in the pictures




20

Insertion into a Heap

◆ The insertion algorithm consists of three steps

- Find the insertion position z (always the new last node)
- Store k at z and expand z into an internal node
- Restore the heap-order property (discussed next)



Trees, Heap, and BST

21


```
void insert(Heap *H, ItemType ItemToInsert) {
    NodeType *N;          /* Pointer to the new node to be inserted to H */
    NodeType *P;          /* Let P be the pointer to the new node */
    N = (create a new node with ItemToInsert);
    if (*H is not empty) {
        /* Find the position to hold the new node */
        P = (the pointer to the new node);
        (P's value) = N;
        /* Re-heapify the values in the remaining nodes of H starting at the root, R */
        (Re-heapify the heap H starting at node R);
    }
    else {
        (Root in H) = N;
    }
    return;
}
```

Trees, Heap, and BST

22

Upheap

- ◆ After the insertion of a new key k , the heap-order property may be violated
- ◆ Algorithm upheap restores the heap-order property by swapping k along an upward path from the insertion node
- ◆ Upheap terminates when the key k reaches the root or a node whose parent has a key smaller than or equal to k
- ◆ Since a heap has height $O(\log n)$, upheap runs in $O(\log n)$ time




Trees, Heap, and BST

23

Removal from a Heap

◆ The removal algorithm consists of three steps

- Replace the root key with the key of the last node w
- Delete w
- Restore the heap-order property (discussed next)



Trees, Heap, and BST

24

```

ItemType remove(Heap *H) {
    NodeType L;           /* let L be the last node of H in level order */
    NodeType R;           /* R is used refer to the root node of H */
    ItemType ItemToRemove; /* temporarily stores item to remove */
    if (H is not empty) {
        /* Remove the highest priority item which is stored in H's root node, R */
        ItemToRemove = (the value stored in the root node, R, of H);
        /* Move L's value into the root of H, and delete L */
        (R's value) = (the value in last node L);
        (delete node L);
        /* Reheapify the values in the remaining nodes of H starting at the root, R */
        if (H is not empty) {
            (Reheapify the heap H starting at node R);
        }
    }
    return (ItemToRemove);
}


```

Trees, Heap, and BST

25

Downheap

- After replacing the root key with the key k of the last node, the heap-order property may be violated
- Algorithm downheap restores the heap-order property by swapping key k along a downward path from the root
- Downheap terminates when key k reaches a leaf or a node whose children have keys greater than or equal to k
- Since a heap has height $O(\log n)$, downheap runs in $O(\log n)$ time




Trees, Heap, and BST

26

Merging Two Heaps

- We are given two heaps and a key k
- We create a new heap with the root node storing k and with the two heaps as subtrees
- We perform downheap to restore the heap-order property




Trees, Heap, and BST

27

Bottom Up Heap Construction

- We can construct a heap storing n keys by using a bottom-up construction with $\log n$ phases
- In phase i , pairs of heaps with $2^i - 1$ keys are merged into heaps with $2^{i+1} - 1$ keys



Trees, Heap, and BST

28

Bottom Up Algorithm:

```


function BottomUpHeap(S, n):
    Input: An array S storing  $n = 2^h - 1$  keys
    Output: A heap T storing the keys in S
    if (n == 0) then return NULL;
    k = S[0];
    S1 = S[1 .. (n-1)/2]; /* split S into two sub-arrays */
    S2 = S[(n-1)/2+1 .. n];
    T1 = BottomUpHeap(S1, (n-1)/2);
    T2 = BottomUpHeap(S2, (n-1)/2);
    T = treeNode(k, T1, T2);
    DownHeap(T);
    return T;

```

Trees, Heap, and BST

29

Example



Trees, Heap, and BST

30

Trees, Heap, and BST

31

Trees, Heap, and BST

31

Diagram illustrating the deletion of node 9 from a B+ tree. The tree structure shows internal nodes (yellow circles) and leaf nodes (blue squares). The root node is 9. Its left child is 15, and its right child is 8. Node 15 has children 16 and 25. Node 8 has children 6 and 20. Node 6 has children 11 and 9. Node 20 has children 23 and 27. The diagram shows the process of merging node 9 with its parent node 4, resulting in a new root node 4. The new root node 4 has children 15 and 6. Node 15 has children 16 and 25. Node 6 has children 11 and 9. Node 20 has children 23 and 27. The leaf nodes are: [16, 25], [5, 12], [11, 9], [23, 27] under node 15; [16, 25], [5, 12], [11, 9], [23, 27] under node 4; [16, 25], [5, 12], [11, 9], [23, 27] under node 6.

32

Trees, Heap, and BST

32


Trees, Heap, and BST

33

Trees, Heap, and BST

33

Constructing a heap from list 7, 5, 8, 9, 4, 6



Trees, Heap, and BST

34

- ◆ Two steps:
 1. Construct a complete binary tree with the list from the root down and from left to right.
 2. Apply downheap to every parent node starting with the last one and backwards to the root.
- ◆ The complexity is $O(n \log n)$.

Trees, Heap, and BST



35

- ◆ Heapsort is based on heap. It is a two-stage algorithm.
- ◆ The first stage is heap construction. A heap is constructed from the items to be sorted. This stage is $O(n)$
- ◆ The second stage is minimum removals. Each time the minimum at the heap root is removed and placed in the result, then the downheap algorithm is used to restore the heap-order property. This process continues until all the items have been placed in the result. This stage is $O(n \log n)$.

Trees, Heap, and BST

36



Heapsort Example



Trees, Heap, and BST

37

Heapsort Example (cont.)




Trees, Heap, and BST

38

Array-based Implementation

- ◆ We can represent a heap with n keys by means $n + 1$ array cells.
- ◆ Cell 0 is not used.
- ◆ Links are not explicitly stored.
- ◆ Leaves are not represented.
- ◆ Operation **insert** corresponds to inserting at cell $n + 2$.
- ◆ Operation **remove** corresponds to removing at cell 1.




Trees, Heap, and BST

39

Array-based Implementation

- ◆ parent nodes are in the first $\lfloor n/2 \rfloor$ array cells.
- ◆ Non-parent nodes are in the last $\lfloor n/2 \rfloor$ cells.
- ◆ The children of the node at cell i ($1 \leq i \leq \lfloor n/2 \rfloor$) are at cells $2i$ and $2i + 1$.
- ◆ The parent of the node at cell i ($2 \leq i \leq n$) is in cell $\lfloor i/2 \rfloor$.



Trees, Heap, and BST

40

Array-Based Heapsort Example

Sort the list 1, 9, 7, 4, 3, 8 in ascending order by heapsort

Stage 1 (heap construction)

```

1 9 7 4 3 8
1 9 8 4 3 7
1 9 8 4 3 7
9 1 8 4 3 7
9 4 8 1 3 7
1 2 3 4 5 6
    
```

We construct a heap in which the key of a node is greater than or equal to the keys of its children.

Stage 2 (root/max removal)

```


9 4 8 1 3 7
7 4 8 1 3 9
8 4 7 1 3 9
3 4 7 1 8 9
1 4 3 7 8 9
4 1 3 7 8 9
3 1 4 7 8 9
3 1 4 7 8 9
1 3 4 7 8 9
1 2 3 4 5 6
    
```

Trees, Heap, and BST

41

Binary Search Tree

- ◆ A binary search tree is a binary tree storing keys (or key-element pairs) at its internal nodes and satisfying the following property:
 - Let v be a tree node, and L , R be subtrees such that L is the left subtree of v and R is the right subtree of v . We have $keys(L) \leq key(v) \leq keys(R)$
- ◆ External nodes do not store items (NULL's)
- ◆ An inorder traversal of a binary search trees visits the keys in increasing order




Trees, Heap, and BST

42

Search

- ◆ To search for a key k , we trace a downward path starting at the root
- ◆ The next node visited depends on the outcome of the comparison of k with the key of the current node
- ◆ If we reach a leaf, the key is not found and we return NO_SUCH_KEY
- ◆ Example: `findElement(4, root)`

```
function findElement(k, v)
    if (isExternal(v)) {
        return NO_SUCH_KEY;
    }
    if (k < key(v)) {
        return findElement(k, leftChild(v));
    }
    else if (k == key(v)) {
        return element(v);
    }
    else { // k > key(v)
        return findElement(k, rightChild(v));
    }
```




Trees, Heap, and BST

43

Insertion

- ◆ To perform operation `insertItem(k, o)`, we search for key k
- ◆ Assume k is not already in the tree, and let w be the leaf reached by the search
- ◆ We insert k at node w and expand w into an internal node
- ◆ Example: insert 5




Trees, Heap, and BST

44

Deletion

- ◆ To perform operation `removeElement(k)`, we search for key k
- ◆ Assume key k is in the tree, and let v be the node storing k
- ◆ If node v has a leaf child w (a NULL subtree), we remove v and w from the tree with operation `removeAboveExternal(w)`
- ◆ Example: remove 4




Trees, Heap, and BST

45

Deletion (cont.)

- ◆ We consider the case where the key k to be removed is stored at a node v whose children are both internal
 - we find the internal node w that follows v in an inorder traversal
 - we copy `key(w)` into node v
 - we remove node w and its left child z (which must be a leaf) by means of operation `removeAboveExternal(z)`
- ◆ Example: remove 3




Trees, Heap, and BST

46

Performance

- ◆ Consider a dictionary with n items implemented by means of a binary search tree of height h
 - the space used is $O(n)$
 - methods `findElement`, `insertItem` and `removeElement` take $O(h)$ time
- ◆ The height h is $O(n)$ in the worst case and $O(\log n)$ in the best case



Trees, Heap, and BST


47

Trees - Implementation

◆ Data structure

```
typedef struct node {
    void *item;
    struct node *left;
    struct node *right;
} node;
```

```
typedef struct {
    node* root;
    ...
} tree;
```



Trees, Heap, and BST

48

Trees - Implementation

```
extern int keyCmp( void *a, void *b );
/* Returns -1, 0, 1 for a < b, a == b, a > b */

void *find( node* np, void *key ) {
    if ( np == NULL ) return NULL;
    switch( keyCmp( key, np->item ) ) {
        case -1 : return find( np->left, key );
        case 0 : return np->item;
        case +1 : return find( np->right, key );
    }
}

void *findInTree( tree t, void *key ) {
    return find( t.root, key );
}
```

Less,
search left

Greater,
search right


Trees, Heap, and BST

49

Trees - Implementation

◆ Example:

■ key = 22;
if (findInTree(t.root, &key))




Trees, Heap, and BST

50

Trees - Addition

◆ Add 21 to the tree



- We need at most $h+1$ comparisons
- Create a new node (constant time)
- So addition to a tree takes time proportional to $\log n$

Trees, Heap, and BST

51

Trees - Addition - implementation

```
void insert( node **t, node *new ) {
    node base = *t;
    if ( base == NULL ) {
        *t = new; return;
    }
    else {
        if ( keyLess( new->item, base->item ) )
            insert( &(base->left), new );
        else
            insert( &(base->right), new );
    }
}

void addToTree( tree t, void *item ) {
    node* new;
    new = (node*) malloc( sizeof( struct t_node ) );
    new->item = item;
    new->left = new->right = NULL;
    insert( &(t.root), new );
}
```

Trees, Heap, and BST

52