

Graphs - Shortest Paths

- ◆ In a graph in which edges have costs ...
- ◆ Find the shortest path from a **source** to a **destination**.
- ◆ Common algorithm for **single-source shortest paths** is due to Edsger **Dijkstra**
 - While finding the shortest path from a source to one destination,
 - *we can find the shortest paths to all destinations as well!*
- ◆ Applications: transportation planning ...

graphs

1


Dijkstra's Algorithm - Data Structures

- ◆ For a graph,
 $G = (V, E)$
- ◆ Dijkstra's algorithm keeps *two* sets of vertices:
 - S Vertices whose shortest paths already been determined
 - V-S Remainder
- ◆ Also
 - d Best estimates of shortest path to each vertex
 - π Predecessors for each vertex

graphs

2

The Shortest Path:
from vertex 1 to vertex 5



graphs

3

Predecessor Sub-graph

- ◆ Array of vertex indices, $\pi[j]$, $j = 1 \dots |V|$
 - $\pi[j]$ contains the predecessor for node j
 - $\pi[j]$'s predecessor is in $\pi[\pi[j]]$, and so on
 - The **edges** in the predecessor sub-graph are $(\pi[j], j)$

graphs

4

Dijkstra's Algorithm - Operation

- ◆ Initialize d and π
 - For each vertex, j , in V
 - $d_j = \infty$ ← Initial estimates are all ∞
 - $\pi_j = \text{nil}$ ← No connections
 - Source distance, $d_s = 0$
- ◆ Set S to empty
- ◆ While $V-S$ is not empty
 - Sort $V-S$ based on d
 - Add u , the closest vertex in $V-S$, to S ← Add s first!
 - Relax all the vertices still in $V-S$ connected to u

graphs

5

Dijkstra's Algorithm - Operation

- ◆ The Relaxation process


```

relax( Node u, Node v, double w[ ][ ] )
{
    if (d[v] > d[u] + w[u][v]) {
        d[v] = d[u] + w[u][v];
        pi[v] = u;
    }
}
          
```

 - Relax the node v attached to node u
 - Edge cost matrix
 - If the current best estimate to v is greater than the path through u ..
 - Update the estimate to v
 - Make v 's predecessor point to u

graphs

6

Dijkstra's Algorithm - Full

◆ The Shortest Paths algorithm

Given a graph, g , and a source, s

```
shortest_paths( Graph g, Node s ){
    initialise_single_source( g, s );
    S = { 0 }; /* Make S empty */
    Q = Vertices(g); /* Put the vertices in a PQ */
    while (! Empty(Q)){
        u = removeMin( Q );
        AddNode( S, u ); /* Add u to S */
        for each vertex v in Adjacent( u )
            relax( u, v, w )
    }
}
```

graphs

7

Dijkstra's Algorithm - Initialise

◆ The Shortest Paths algorithm

Given a graph, g ,
and a source, s

Initialize d, π, S ,
vertex Q

```
shortest_paths( Graph g, Node s ){
    initialise_single_source( g, s );
    S = { 0 }; /* Make S empty */
    Q = Vertices(g) /* Put the vertices in a PQ */
    while (! Empty(Q)){
        u = removeMin( Q );
        AddNode( S, u ); /* Add u to S */
        for each vertex v in Adjacent( u )
            relax( u, v, w );
    }
}
```

graphs

8

Dijkstra's Algorithm - Loop

◆ The Shortest Paths algorithm

Given a graph, g ,
and a source, s

```
shortest_paths( Graph g, Node s ){
    initialise_single_source( g, s );
    S = { 0 }; /* Make S empty */
    Q = Vertices(g); /* Put the vertices in a PQ */
    while (! Empty(Q)){
        u = removeMin( Q );
        AddNode( S, u ); /* Add u to S */
        for each vertex v in Adjacent( u )
            relax( u, v, w );
    }
}
```

While there are
still nodes in Q

Greedy!

graphs

9

Dijkstra's Algorithm - Relax neighbours

◆ The Shortest Paths algorithm

Given a graph, g ,
and a source, s

Update the
estimate of the
shortest paths to
all nodes
attached to u

```
shortest_paths( Graph g, Node s ){
    initialise_single_source( g, s );
    S = { 0 }; /* Make S empty */
    Q = Vertices(g); /* Put the vertices in a PQ */
    while (! Empty(Q)){
        u = removeMin( Q );
        AddNode( S, u ); /* Add u to S */
        for each vertex v in Adjacent( u )
            relax( u, v, w );
    }
}
```


Greedy!

graphs

10

Dijkstra's Algorithm - Operation

◆ Initial Graph




graphs

11

Dijkstra's Algorithm - Operation

◆ Initial Graph




graphs

12

Dijkstra's Algorithm - Operation


Initial Graph



graphs

13


Dijkstra's Algorithm - Operation



graphs

14


Dijkstra's Algorithm - Operation



graphs

15


Dijkstra's Algorithm - Operation



graphs

16


Dijkstra's Algorithm - Operation



graphs

17


Dijkstra's Algorithm - Operation



graphs

18


Dijkstra's Algorithm - Operation



graphs

19


Dijkstra's Algorithm - Operation



graphs

20

Dijkstra's Algorithm - Operation



graphs

21

Dijkstra's Algorithm - Time Complexity

◆ Dijkstra's Algorithm

- A key step is sorting the remaining vertices after each vertex joins S . This can be done by creating a heap as a priority queue.
 - Complexity is
 - ◆ $O(|E|)$ ($\sum_{v \in V} (deg(v) + \log |V|)$)
 - ◆ or $O(n^2)$ ($n(n + \log n) = n^2 + n \log n$)
- for a dense graph with $n = |V|$ and $|E| \approx |V|^2$

graphs

22

Graphs: Minimum Spanning Trees

- ◆ A spanning tree of an undirected connected graph is a tree that contains all the vertices of the graph.
- ◆ If the graph has weights with the edges, a minimum spanning tree of the graph is a spanning tree of the smallest weight.
- ◆ The weight of a tree is the sum of the weights on all the edges in the tree.
- ◆ Applications: cable network design, etc.

graphs

23


Prim's Algorithm

- ◆ The initial subtree contains a single vertex.
- ◆ In each iteration, the algorithm expands the subtree by adding the nearest vertex that is not in the tree.
- ◆ After adding a vertex to the subtree, the algorithm re-calculates the distances of the remaining vertices to the subtree.
- ◆ The algorithm terminates when all the vertices are contained in the subtree.

graphs

24


Example



graphs

25


Example



graphs

26


Example



graphs

27


Example



graphs

28


Example



graphs

29


Example



graphs

30


Example



graphs

31


Example



graphs

32

Example



graphs

33

Prim's Algorithm - Time Complexity

- ◆ Prim's Algorithm
 - Prim's algorithm has the same time complexity.
 - Complexity is
 - ◆ $O(|E|)$ or
 - ◆ $O(n^2)$
- for a dense graph with $n = |V|$ and $|E| \approx |V|^2$

graphs

34

Graphs - Topological Ordering

- ◆ Topological ordering is an operation on directed acyclic graphs (DAGs).
- ◆ A topological ordering for the vertices in graph G is a sequential list L of the vertices, such that if there is a directed edge from vertex A to vertex B in G , then A comes before B in L .
- ◆ Applications: scheduling of tasks from the given dependencies among tasks ...

graphs

35


Topological Ordering

- ◆ An algorithm for topological ordering is *source removal*.
- ◆ In each step of the algorithm, a *source* is identified. A source is a vertex with no incoming edges. The source is removed from the graph along with all its outgoing edges. The vertex is then added at the end of the list.
- ◆ The process continues till all vertices are removed from the graph.

graphs

36


Example



graphs

37


Example



graphs

38

Example



graphs

39


Example



graphs

40

Example



graphs

41


Example



graphs

42

Example



graphs

43

Source Removal - Time Complexity

◆ Source removal

- After removing a vertex (and its outgoing edges), the algorithm examines the remaining vertices for a source.

■ Complexity is

- ◆ $O(|E|)$ or
- ◆ $O(n^2)$

for a dense graph with $n = |V|$ and $|E| \approx |V|^2$

graphs

44