

From ERS-111 Behavior Diagrams to Distributed Embodiment: SOFTSIM and GA144 as an Executable Framework

Dr. Christopher A. Tucker

Abstract

This paper proposes a follow-on implementation framework derived from prior analysis of Sony **ERS-111 R-CODE** behavior diagrams. The earlier corpus study showed that many sample routines are organized around a compact embodied state vocabulary centered on initialization, sensing, iterative action, synchronization, and recovery. The present paper asks how such behavioral organization may be carried toward executable distributed control. Its central claim is that behavior diagrams can function not only as descriptive artifacts, but also as executable organizational models when they are mapped onto communicating node ensembles, initialized through the documented GreenArrays workflow, and exercised functionally in **SOFTSIM**. In this framing, **SOFTSIM** serves as a functional execution and inspection environment, while **GA144** provides a candidate distributed asynchronous hardware target for studying fast reactive loops, slower supervisory intervention, and low-energy embodied control organization.

Introduction

This paper is a follow-on to the **ERS-111** behavior-diagram study rather than a replacement for it. The earlier paper was closed around the corpus itself: it aggregated the generated **R-CODE** diagrams, identified their recurring state vocabulary, and argued that apparently different routines are often built from a compact embodied grammar. That result remains the starting point here, but not the final objective.

The present question is implementation-oriented. If a robot behavior corpus can be described as a recurring state vocabulary, can that same vocabulary support a path toward executable distributed control? More specifically, can behavior diagrams be treated as organizational models for implementation on a communicating many-node substrate rather than only as retrospective diagrams of legacy code?

This question matters because current robotics research increasingly distinguishes between faster embodied control and slower supervisory or reasoning layers. In contemporary work, low-latency action generation and higher-level semantic or deliberative guidance are often separated functionally even when they remain tightly coupled in deployment (*Zhu et al., 2024; Bjorck et al., 2025; Song et al., 2025*). The present work does not claim priority over that general idea. Instead, it explores a different contribution: how a compact behavioral vocabulary may be instantiated, inspected, and eventually realized on a distributed asynchronous substrate.

The paper makes four main contributions. First, it restates the **ERS-111** corpus result in the narrower form needed for implementation work: the diagrams expose a compact embodied state vocabulary rather than a collection of unrelated scripts. Second, it shows that the GreenArrays documentation provides a continuous toolchain from per-node implementation through declarative initialization to functional simulation. Third, it argues that behavior diagrams can be treated as executable organizational models for distributed control rather than only as analytic artifacts.

Fourth, it defines a conservative experiment program in which **SOFTSIM** is used for functional execution and inspection while **GA144** remains the hardware target for later realization rather than a source of premature timing claims.

Background from ERS-111

The prior **ERS-111** study matters here because it supplies the abstraction that this paper seeks to operationalize. At corpus scale, the generated **R-CODE** diagrams repeatedly returned to a small set of state-types such as **Sense / Decide**, **Action Loop**, **Boot / Safe Pose**, **Synchronize**, **Sense Fall State**, and **Recover**. The significance of that finding was not merely that one title appeared more frequently than another. The stronger result was that many distinct routines were organized through repeated recombination of a compact reactive and embodied control vocabulary.

That result provides a useful bridge for implementation work. If behavior can be described at the level of recurring compartments such as initialization, sensing, bounded action, synchronization, and recovery, then those compartments can in principle be mapped onto concrete execution units. The present paper therefore uses the **ERS-111** corpus not as its primary object of analysis, but as the source of a compact behavioral grammar that may be carried forward into implementation experiments.

GreenArrays Toolchain

The GreenArrays documentation supplies the implementation path required for this next step. **DB001** describes the **F18A** node as a highly constrained asynchronous processing element with local memory, direct port execution, and communication semantics centered on suspension and handoff across neighboring nodes. This matters because it means that distributed behavior is not added as an afterthought. Communication is part of the machine model itself.

DB013 Chapter 4 shows how code is assembled per node and stored through the object-bin workflow. That chapter is important because it demonstrates that the programmer is not targeting a single flattened image alone, but a persistent collection of node-local artifacts. **DB013 Chapter 6** then shows how those artifacts can be gathered into a Boot Descriptor Language workflow that defines how a multi-node configuration is initialized and streamed into execution.

DB013 Chapter 7 completes the path by documenting **SOFTSIM** as a high-level software simulator for up to two **GA144** chips. Its role is not to reproduce physical timing faithfully, but to provide functional execution, operator inspection, stepping, and breakpoint control for distributed node programs. That distinction is critical. The present paper therefore uses **SOFTSIM** as a functional and observational environment, not as a timing-accurate proof of hardware behavior.

Taken together, these chapters define a continuous workflow:

```
node implementation -> object bins -> BDL initialization -> SOFTSIM execution ->
GA144 realization
```

That continuity is one of the main reasons the GreenArrays environment is relevant to the present paper. It offers a concrete bridge from behavioral organization to executable distributed embodiment.

Behavior Diagrams as Executable Models

The central interpretive claim of this paper is that behavior diagrams can be promoted from descriptive visualizations into executable organizational models. A state diagram already distinguishes stable behavioral compartments, entry conditions, transition conditions, and return paths. These distinctions are analytically useful on their own, but they are also structurally close to what distributed implementation requires.

On a node-based asynchronous substrate, one can treat each state as a small executable routine with bounded responsibilities. Some states may remain local to a single node. Others may be split across communicating nodes when sensing, local action, and supervisory intervention should be kept distinct. In this view, the transition structure functions as an implementation guide: it suggests where behavior must remain local, where communication must occur, and where synchronization or recovery paths need to be observable.

This is not yet a claim that every behavior diagram should be mapped one-to-one onto hardware nodes. It is a more modest claim. The diagrams provide a tractable intermediate representation that can guide distributed implementation decisions while preserving behavioral clarity. They help identify what is stable in the organization of a behavior even when the sensing words, actuation words, or supervisory policies later change.

Fast and Slow Cadence

Recent robotics literature gives added relevance to this approach by showing that explicit fast/slow or dual-system decompositions are now common enough to support comparison. In **GR00T N1**, **Hume**, and **Language-Conditioned Robotic Manipulation with Fast and Slow Thinking**, faster reactive or action-generation layers are paired with slower supervisory, semantic, or reasoning-capable layers (Zhu et al., 2024; Bjorck et al., 2025; Song et al., 2025).

The present work does not claim that the GreenArrays environment already matches the scale or capability of those systems. Its value is different. It offers a small, inspectable, distributed implementation framework in which a similar cadence can be studied concretely. In the working interpretation used here, fast reactive behavior corresponds to local low-latency node execution, while slower supervisory behavior corresponds to a less frequent layer that modulates or redirects local loops.

Within that framing, **GA144** is valuable not because it replaces contemporary large-scale robot foundation models, but because it offers a contrasting substrate for embodied control experiments. As a distributed asynchronous many-node device, it supports organizing behavior as multiple small communicating reactive processes rather than as one monolithic controller. This is especially relevant for the present work because it provides a plausible low-energy hardware target for the reactive layer while **SOFTSIM** provides the functional environment needed to inspect node state, communication, and supervisory handoff before stronger hardware claims are made.

Experiment Program

The experiment program proposed here is deliberately conservative. Its purpose is not to demonstrate superiority over current embodied AI systems, nor to make timing claims that **SOFTSIM** cannot support. Its purpose is to establish a credible sequence of executable evidence.

The first paper-facing target in that sequence should be the existing **Move** diagram from the **ERS-111** study. **Move** is compact, reactive, and already organized around a loop of repeated action,

fall sensing, recovery, and return to execution. That makes it the best first candidate for a direct diagram-to-program mapping using the documented 1737-style minimal load path in SOFTSIM. The immediate implementation goal is not yet a full locomotion controller, but a minimal structural mutation of the 1737 baseline whose repeated region, alternate region, and return-to-loop behavior correspond to the main organizational features of Move. A second small target should then be a reduced recovery-oriented control slice centered on Boot / Safe Pose, Sense Fall State, Recover, and Action Loop, rather than a more specialized family such as Football.

- establish that the local SOFTSIM installation is a usable functional execution environment
- preserve a smallest confirmed baseline such as the documented 1737 example
- demonstrate a minimal one-node mutation that proves custom executable behavior is possible
- demonstrate a minimal two-node reactive/supervisory handoff
- make node-local state and communication markers observable during execution
- carry at least one stable organization toward later realization on GA144

This sequence matters because it distinguishes functional evidence from hardware-performance evidence. If the sequence succeeds in SOFTSIM, it supports claims about executable organization, inspection, and distributed behavioral decomposition. If a later hardware realization succeeds on GA144, it supports the stronger claim that at least one such organization survives translation onto the physical substrate. It still would not by itself prove large-scale robot-level capability, but it would validate the implementation pathway.

Claim Boundaries

Because this work sits between historical analysis and future hardware implementation, its claim boundaries must remain explicit.

What can be claimed safely. The prior ERS-111 corpus study identified a compact embodied state vocabulary. The GreenArrays documentation defines a continuous path from per-node implementation through declarative initialization to functional simulation. Live local execution confirms that SOFTSIM can load, step, and inspect distributed node programs. These points support the claim that behavior diagrams can function as executable organizational models in a distributed asynchronous implementation workflow.

What should not yet be claimed. The present evidence does not show timing fidelity in SOFTSIM, does not demonstrate superiority to contemporary foundation-model robot architectures, and does not prove robot-level performance on real embodied tasks. It also does not show that every behavior diagram admits a simple one-to-one mapping onto node hardware.

These boundaries do not weaken the contribution. Rather, they define it more clearly. The paper’s value lies in identifying and operationalizing a tractable bridge between behavioral abstraction and executable distributed embodiment.

Conclusion

The original ERS-111 behavior-diagram paper established that the Sony R-CODE corpus is organized around a compact embodied state vocabulary. The present follow-on paper asks what that result

can be used for. Its answer is that such a vocabulary can serve as an intermediate representation between historical behavior diagrams and distributed executable control.

The GreenArrays environment is especially useful for this purpose because it provides a continuous path from node-local implementation, through declarative multi-node initialization, to functional execution and inspection in `SOFTSIM`, and ultimately to realization on `GA144`. In that sense, the contribution is not the invention of fast/slow embodied control as an abstract concept. It is the proposal of an executable framework for studying how such control may be organized, inspected, and carried toward hardware on a distributed asynchronous substrate.

References

- Arkin, Ronald C. *Behavior-Based Robotics*. MIT Press, 1998.
- Bjorck, Johan, Eric Jang, Dibya Ghosh, et al. “GR00T N1: An Open Foundation Model for Generalist Humanoid Robots.” arXiv, 2025. <https://arxiv.org/abs/2503.14734>
- Brooks, Rodney A. “Intelligence without Representation.” *Artificial Intelligence* 47, no. 1-3 (1991): 139-159.
- Song, Jiankai, Yilun Du, Kalyan S. Perumalla, et al. “Hume: Toward a Universal and Fine-Grained Human-Centric Understanding Model for Embodied AI.” arXiv, 2025. <https://arxiv.org/abs/2505.21432>
- Xu, Zhiyuan, Kun Wu, Junjie Wen, Jinming Li, Ning Liu, Zhengping Che, and Jian Tang. “A Survey on Robotics with Foundation Models: toward Embodied AI.” arXiv, 2024. <https://arxiv.org/abs/2402.02385>
- Zhu, Xianghao, Yizhou Wang, Junheng Hao, et al. “Language-Conditioned Robotic Manipulation with Fast and Slow Thinking.” arXiv, 2024. <https://arxiv.org/abs/2401.04181>