

From Behavioral State Vocabularies to Distributed Embodiment: SOFTSIM and GA144 as an Executable Framework

Christopher A. Tucker

Abstract

This paper is the implementation-oriented third step in a sequence of related studies. A prior historical paper argued that an older line of machine-intelligence thought remains architecturally useful when read in terms of sensing, state, control, action, and adaptation. A second paper showed that Sony’s ERS-111 R-CODE sample corpus can be read through a compact behavioral state vocabulary rather than as a set of unrelated scripts. The present paper asks what follows if that vocabulary is treated not only as an analytic description, but as a candidate implementation grammar. Its main claim is that the GreenArrays toolchain, especially `arrayForth`, boot-descriptor loading, SOFTSIM, and physical GA144 deployment, provides a continuous path from behavioral decomposition to executable distributed embodiment. On this reading, behavior diagrams are neither loose metaphors nor final programs. They are intermediate control descriptions that can be mapped onto communicating F18A nodes, initialized reproducibly, exercised functionally in simulation, and then carried toward hardware realization. The paper positions this workflow as a concrete framework for studying fast-reactive and slow-supervisory embodied control without collapsing both layers into one monolithic controller.

1 Introduction

This paper is written as the third in a sequence. The first paper argued that a historically underused architecture of machine intelligence can be recovered by reading symbolic logic, circuitry, control, and embodied behavior together rather than apart. The second paper moved from historical reconstruction to preserved robotic software and argued that Sony’s ERS-111 R-CODE sample set is organized by a compact behavioral state vocabulary centered on initialization, sensing, action, synchronization, and recovery [1]. The present paper takes the next step. It asks how such a vocabulary can be made executable on a distributed substrate instead of remaining a descriptive layer over legacy code.

That question matters because much current robotics work still separates high-level cognition from low-level embodied viability too sharply. Systems may be rich in perception, planning, or language conditioning while remaining comparatively weak in persistent local organization: postural maintenance, contact response, local recovery, and bounded reactive loops that keep a physical agent workable in the world while larger tasks are being pursued. One common way of talking about that split is through fast/slow or *System 1* / *System 2* language, where rapid background response and slower supervisory interpretation are treated as distinct but cooperating cadences [2, 3].

The aim of this paper is not to claim that GreenArrays hardware solves contemporary robotics in general. It is narrower and more practical. The claim is that the F18A / `arrayForth` / SOFTSIM

/ **GA144** stack offers a usable experimental path for implementing distributed embodied control in explicit small processes. That makes it a good setting in which to test whether behavioral decompositions derived from robot code can be turned into node-local loops, inter-node handoffs, and slower supervisory interventions without being absorbed into a single centralized controller.

2 Research Question and Thesis

The guiding question is how a behavioral state vocabulary should function after analysis. Is it only a retrospective interpretive device for reading robot scripts, or can it serve as an intermediate implementation layer that connects behavior design to executable distributed systems?

The thesis of this paper is that the GreenArrays toolchain supports the stronger reading. In this environment, a behavior description can be mapped onto concrete communicating **F18A** nodes, assembled into persistent per-node images, initialized declaratively through boot-descriptor mechanisms, executed functionally in **SOFTSIM**, and then carried to physical **GA144** hardware [4, 5]. The result is not yet a finished robotic architecture. It is an executable framework for studying how fast reactive loops, local state, and slower supervisory control might be separated, coordinated, inspected, and eventually embodied in hardware.

3 From Behavioral Vocabulary to Implementation Grammar

The earlier **R-CODE** study argued that apparently different Sony sample routines reuse a small recurrent vocabulary of control forms: startup regularization, sensing, conditional branching, iterative action, synchronization, and recovery [1]. That finding has two possible interpretations. The weaker one is taxonomic: the vocabulary merely groups legacy scripts into comparable families. The stronger one is constructive: the vocabulary identifies a set of behavior blocks that can be re-instantiated on another substrate.

This paper adopts the stronger interpretation. In that reading, a behavior diagram is not yet machine code, but it is more than a sketch. It specifies roles that an implementation must realize: persistent loops, transition conditions, local memory, recovery paths, and coordination points. Such a description is therefore well suited to a substrate whose basic unit is not a single giant process but a collection of communicating node-local programs.

That is where the GreenArrays environment becomes relevant. The **F18A** architecture is already distributed in form. It consists of many small communicating nodes with explicit port semantics, node-local memory, and fine-grained execution [4]. The programming model described by **arrayForth** then reinforces that decomposition by treating code as persistent per-node object images rather than as one flat binary [5]. What the earlier paper recovered at the level of behavioral analysis thus meets a substrate that is already organized for decomposition.

4 The GreenArrays Execution Path

The practical value of the GreenArrays stack lies in the continuity of its workflow. The manuals and local notes together support a five-stage path: behavioral model, node allocation, per-node assembly, declarative initialization, and executable realization.

The first stage is the behavior description itself. Here the relevant object is a compact control representation: a loop, a sensing condition, a supervisory trigger, a recovery branch, or a state-maintaining routine. The second stage assigns these roles to concrete nodes and communication paths. This is the point at which a state machine or behavior ladder becomes a distributed organization rather than a conceptual diagram.

The third stage is per-node implementation. **arrayForth** Chapter 4 describes an incremental environment in which each node has a persistent object bin containing RAM image, ROM image, and labels [5]. That matters because it makes implementation structurally congruent with the distributed behavior idea. One does not begin from a monolithic application image and then discover decomposition afterward. The decomposition is present in the object model from the start.

The fourth stage is declarative initialization. Chapter 6’s boot-descriptor machinery provides a way to specify how many nodes are touched, how memory and registers are initialized, and how a node ensemble is brought into execution-ready form [5]. This is not just a loading convenience. It is part of the argument of the paper. If a behavior architecture is to be studied seriously, it must be instantiated reproducibly. The boot-descriptor layer supplies that reproducible instantiation path.

The fifth stage is executable realization. **SOFTSIM** provides a functional environment in which the resulting node program can be loaded, stepped, and inspected, while **GA144** provides the physical distributed substrate on which the same style of program can be manifested. The important constraint is that the simulator should be treated as a functional witness, not as a timing-faithful proxy for the hardware. It can validate organization and value-level behavior, while real-chip testing remains necessary for timing, contention, and physical I/O questions.

5 Fast and Slow Cadence

One reason this implementation path is worth isolating is that it offers a concrete place to study fast and slow control decomposition. Public robotics literature now contains multiple explicit versions of this pattern, in which a faster reactive layer cooperates with a slower interpretive or value-guided layer [3]. The GreenArrays stack is relevant not because it replicates those systems wholesale, but because it offers a different implementation emphasis: distributed low-latency node processes instead of one heavy central controller.

In the present framing, fast control corresponds to local reactive loops: posture maintenance, contact response, bounded actuator logic, sensing, and recovery. Slow control corresponds to supervisory choice, mode transition, task redirection, or larger behavioral revision. This is conceptually close to familiar behavior-based and layered-control traditions [6, 7], but the present paper adds

an implementation claim. It argues that the split can be explored on a distributed asynchronous substrate whose programming and loading machinery already respects node locality.

This has methodological value. It lets a researcher ask not only whether a behavior architecture is intelligible on paper, but whether its parts can be given separate executable homes, separate initialization conditions, and separate inspection points. That makes the architecture more testable. One can begin with a minimal one-node reactive loop, then expand to a two-node handoff, then move toward richer supervisory decomposition while keeping the relationship among behavior, implementation, and loading visible.

6 A Minimal Research Program

The current local notes suggest a practical research program that starts small and stays traceable. The first step is not a large multi-node robotic brain. It is a minimal structural mutation of a known-good `SOFTSIM` load pattern. That means preserving a confirmed small example, introducing a controlled one-node variant, verifying that it still loads and steps correctly, and only then extending the pattern toward a two-node cadence experiment.

This sequence is methodologically important because it separates three kinds of error that would otherwise be conflated: syntax or assembly error, load-and-initialization error, and inter-node coordination error. Once these are disentangled, the implementation path becomes suitable for more serious behavior experiments. A reactive loop can be isolated, a supervisory trigger can be added, and the resulting handoff can be inspected first in `SOFTSIM` and later on hardware.

The broader value proposition is architectural rather than benchmark-driven. `GA144` is interesting here because it offers a plausible low-energy, many-node substrate for persistent small embodied loops. The point is not that current notes prove superior robot performance or timing efficiency. The point is that the substrate fits the decomposition under study: background reactive processes that remain active continuously rather than as occasional subroutines.

7 Contribution of the Third Paper

Within the three-paper sequence, the present paper occupies a distinct role. The first paper recovered an architectural lineage for embodied machine intelligence. The second showed that a preserved robot-code corpus can be read through a stable behavioral state vocabulary. The third paper turns that vocabulary toward execution. Its contribution is to identify a concrete toolchain in which behavior blocks, node decomposition, initialization, and functional execution can be studied together rather than in isolation.

That contribution should be stated carefully. The paper does not yet present a completed distributed robot controller, nor does it claim timing validation, energy benchmarking, or parity with contemporary foundation-model robot systems. Its claim is narrower and still useful: behavior diagrams can serve as an intermediate representation for executable distributed embodiment, and

the GreenArrays stack provides a disciplined environment in which that claim can be explored incrementally.

8 Conclusion

The main result of this paper is a framework claim. A behavioral state vocabulary need not remain a retrospective analytic lens over preserved robot code. It can function as an implementation grammar when paired with a substrate that already supports node-local programming, explicit communication, reproducible initialization, and functional execution.

Within that framing, the GreenArrays environment supplies a continuous path from behavior description to distributed realization: node-level implementation in `arrayForth`, declarative ensemble setup through boot descriptors, functional execution in `SOFTSIM`, and eventual physical manifestation on `GA144`. This does not complete the larger research program, but it makes the next step concrete. Instead of discussing fast and slow embodied control only at the level of architecture, we can now study how such a decomposition behaves when given explicit executable form on a distributed substrate.

References

- [1] Christopher A. Tucker. A behavioral state vocabulary in Sony ERS-111 R-CODE, 2026. arXiv:2607.12115.
- [2] Daniel Kahneman. *Thinking, Fast and Slow*. Farrar, Straus and Giroux, 2011.
- [3] Y. Wang et al. Hume: Introducing system-2 thinking in visual-language-action model, 2025. URL <https://arxiv.org/abs/2505.21432>.
- [4] GreenArrays, Inc. *F18A Technology Reference*, 2011. Document DB001.
- [5] GreenArrays, Inc. *arrayForth User’s Manual*, 2011. Document DB013.
- [6] Ronald C. Arkin. *Behavior-Based Robotics*. MIT Press, 1998.
- [7] Rodney A. Brooks. Intelligence without representation. *Artificial Intelligence*, 47(1–3):139–159, 1991.