8-Bit Buffers with Schmitt Trigger Inputs

SN54/74LS310 SN54/74S310
SN54/74LS340 SN54/74S340
SN54/74LS341 SN54/74S341
SN54/74LS344 SN54/74S344

Features

- **Schmitt-trigger inputs guarantee high noise margin**
- **Three-state outputs drive bus lines**
- **Typical input and output capacitance ≤10 pf**
- **Low-current PNP inputs reduce loading**
- **20-pin SKINNYDIP® saves space**
- **8-bit data path matches byte boundaries**
- **Ideal for microprocessor interface**
- **Complementary-enable '310 and '341 types combine multiplexer and driver functions**
- **Pin-compatible with SN54/74S210/240/1/4 and SN54/74LS210/240/1/4; can be direct replacement in systems with noise problems**

Description

In addition to the standard Schottky and low-power Schottky 8-bit buffers, Monolithic Memories provides full hysteresis with a "true" Schmitt-trigger circuit. The improved performance characteristics are designed (1) for the low-power Schottky buffers, to be consistent with the SN54/74LS14 hex Schmitt-trigger inverter, and to guarantee a full 400 mV noise immunity; (2) for the Schottky buffers, to have low propagation delays and to guarantee a full 500 mV noise immunity. The Schmitt-trigger operation makes these LS/S buffers ideal for bus receivers in a noisy environment.

These 8-bit buffers provide high-speed and high-current interface capability for bus-organized digital systems. The three-state drivers will source a termination to ground (up to 133Ω) or sink a pull-up to V_{CC} as in the popular 220Ω/330Ω computer peripheral termination. The PNP inputs provide improved fan-in with 0.2 mA I_{IL} for the low-power Schottky buffers and 0.25 mA I_{IL} for the Schottky buffers.

The '340 and '344 provide inverting and non-inverting outputs respectively, with assertive-low enables. The '310 and '341 also provide inverting and non-inverting outputs respectively, but with complementary (both assertive-low and assertive-high) enables, to allow transceiver or multiplexer operation.

All of the 8-bit devices are packaged in the popular 20-pin SKINNYDIP®.

Ordering Information

PART NUMBER	PKG*	TEMP	ENABLE	POLARITY	POWER
SN54LS310	J,F	mil	High-Low	Invert	LS
SN74LS310	N,J	com			
SN54LS340	J,F	mil	Low		
SN74LS340	N,J	com			
SN54LS341	J,F	mil	High-Low	Non-Invert	
SN74LS341	N,J	com			
SN54LS344	J,F	mil	Low		
SN74LS344	N,J	com			
SN54S310	J,F	mil	High-Low	Invert	S
SN74S310	N,J	com			
SN54S340	J,F	mil	Low		
SN74S340	N,J	com			
SN54S341	J,F	mil	High-Low	Non-Invert	
SN74S341	N,J	com			
SN54S344	J,F	mil	Low		
SN74S344	N,J	com			

Logic Symbols

'310 8-Bit Buffer



'340 8-Bit Buffer

'341 8-Bit Buffer



'344 8-Bit Buffer



*For other package types, please contact your local sales representative.

2175 Mission College Blvd. Santa Clara, CA 95054-1592 Tel: (408) 970-9700 TWX: 910-338-2374
TWX: 910-338-2376
Monolithic Memories MMI

IEEE Symbols









12

Absolute Maximum Ratings

Supply voltage V_{CC} ..... 7 V
Input voltage ..... 7 V
Off-state output voltage ..... 5.5 V
Storage temperature ..... -65° to +150°C

Operating Conditions

SYMBOL	PARAMETER	MILITARY MIN	MILITARY TYP	MILITARY MAX	COMMERCIAL MIN	COMMERCIAL TYP	COMMERCIAL MAX	UNIT
V_{CC}	Supply voltage	4.5	5	5.5	4.75	5	5.25	V
T_A	Operating free-air temperature	-55		125	0		75	°C

Electrical Characteristics Over Operating Conditions

SYMBOL	PARAMETER		TEST CONDITIONS		MILITARY MIN	MILITARY TYP	MILITARY MAX	COMMERCIAL MIN	COMMERCIAL TYP	COMMERCIAL MAX	UNIT
V_{T+}	Positive threshold voltage		Any A*		1.5	1.7	2.0	1.5	1.7	2.0	V
V_{T-}	Negative threshold voltage		Any A*		0.6	0.9	1.1	0.6	0.9	1.1	V
V_{IC}	Input clamp voltage		V_{CC} = MIN	I_I = -18 mA			-1.5			-1.5	V
ΔV_T	Hysteresis (V_{T+}-V_{T-})		Any A*		0.4	0.8		0.4	0.8		V
ΔV_{DB}	Dead band voltage		Any A*		0.4			0.4			V
V_{IL}	Input low voltage		Any E*				0.8			0.8	V
V_{IH}	Input high voltage		Any E*		2.0			2.0			V
I_{IL}	Low-level input current		V_{CC} = MAX	V_I = 0.4 V			-0.2			-0.2	mA
I_{IH}	High-level input current		V_{CC} = MAX	V_I = 2.7 V			20				μA
I_I	Maximum input current		V_{CC} = MAX	V_I = 7 V			0.1			0.1	mA
V_{OL}	Low-level output voltage		V_{CC} = MIN, V_{T+} = 2 V, V_{T-} = 0.6 V	I_{OL} = 12 mA			0.4			0.4	V
				I_{OL} = 24 mA						0.5	
V_{OH}	High-level output voltage		V_{CC} = MIN, V_{T+} = 2 V, V_{T-} = 0.6 V	I_{OH} = -3 mA	2.4	3.4		2.4	3.4		V
				I_{OH} = -12 mA	2						
				I_{OH} = -15 mA				2			
I_{OZL}	Off-state output current		V_{CC} = MAX, V_{T+} = 2 V, V_{T-} = 0.6 V	V_O = 0.4 V			-20			-20	μA
I_{OZH}				V_O = 2.7 V			20			20	μA
I_{OS}	Output short-circuit current**		V_{CC} = MAX		-40		-225	-40		-225	mA
I_{CC}	Supply Current	Outputs High	V_{CC} = MAX, Outputs open	'LS310,'LS340		17	27		17	27	mA
				'LS341, 'LS344		18	35		18	35	
		Outputs Low		'LS310, 'LS340		26	44		26	44	
				'LS341, 'LS344		32	46		32	46	
		Outputs Disabled		'LS310, 'LS340		29	50		29	50	
				'LS341, 'LS344		34	54		34	54	

** Not more than one output should be shorted at a time and duration of the short-circuit should not exceed one second.
* "A" indicates data input, "E" indicates enable input.

Switching Characteristics V_{CC} = 5 V, T_A = 25°C

SYMBOL	PARAMETER	TEST CONDITIONS (See Test Load/Waveforms)	'LS310, 'LS340 MIN	TYP	MAX	'LS341, 'LS344 MIN	TYP	MAX	UNIT
t_{PLH}	Data to Output delay	C_L = 45 pF R_L = 667 Ω		19	25		19	25	ns
t_{PHL}				19	25		19	25	ns
t_{PZL}	Output Enable delay			32	40		25	40	ns
t_{PZH}				23	35		24	35	ns
t_{PLZ}	Output Disable delay	C_L = 5 pF R_L = 667 Ω		18	30		21	30	ns
t_{PHZ}				15	25		18	25	ns

Absolute Maximum Ratings

Supply voltage V_{CC} ..... 7.0 V
Input voltage ..... 5.5 V
Off-state output voltage ..... 5.5 V
Storage temperature ..... −65° to +150°C

Operating Conditions

SYMBOL	PARAMETER	MILITARY MIN	MILITARY TYP	MILITARY MAX	COMMERCIAL MIN	COMMERCIAL TYP	COMMERCIAL MAX	UNIT
V_{CC}	Supply voltage	4.5	5	5.5	4.75	5	5.25	V
T_A	Operating free-air temperature	−55		125	0		75	°C

Electrical Characteristics Over Operating Conditions

SYMBOL	PARAMETER		TEST CONDITIONS		MILITARY MIN	MILITARY TYP	MILITARY MAX	COMMERCIAL MIN	COMMERCIAL TYP	COMMERCIAL MAX	UNIT
V_{T+}	Positive threshold voltage		Any A*		1.5	1.8	2.05	1.6	1.8	2.0	V
V_{T-}	Negative threshold voltage		Any A*		0.8	1.1	1.35	0.8	1.1	1.3	V
V_{IC}	Input clamp voltage		V_{CC} = MIN	I_I = −18 mA			−1.2			−1.2	V
ΔV_T	Hysteresis (V_{T+}−V_{T-})		Any A*		0.5	0.7		0.5	0.7		V
ΔV_{DB}	Dead band voltage		Any A*		0.15			0.3			V
V_{IL}	Input low voltage		Any E*				0.8			0.8	V
V_{IH}	Input high voltage		Any E*		2.0			2.0			V
I_{IL}	Low-level input current		V_{CC} = MAX	V_I = 0.5 V			−0.25			−0.25	mA
I_{IH}	High-level input current		V_{CC} = MAX	V_I = 2.7 V			50			50	μA
I_I	Maximum input current		V_{CC} = MAX	V_I = 5.5 V			1			1	mA
V_{OL}	Low-level output voltage		V_{CC} = MIN, V_{T+} = 2 V, V_{T-} = 0.8 V	I_{OL} = 48 mA			0.55				V
				I_{OL} = 64 mA						0.55	
V_{OH}	High-level output voltage		V_{CC} = MIN, V_{T+} = 2 V, V_{T-} = 0.8 V	I_{OH} = −1 mA				2.7			V
				I_{OH} = −3 mA	2.4	3.4		2.4	3.4		
				I_{OH} = −12 mA	2						
				I_{OH} = −15 mA				2			
I_{OZL}	Off-state output current		V_{CC} = MAX, V_{IH} = 2.0 V, V_{IL} = 0.8 V	V_O = 0.5 V			−50			−50	μA
I_{OZH}				V_O = 2.7 V			50			50	μA
I_{OS}	Output short-circuit current**		V_{CC} = MAX		−50		−225	−50		−225	mA
I_{CC}	Supply Current	Outputs High	V_{CC} = MAX, Outputs open	'S310,'S340		50	80		50	80	mA
				'S341, 'S344		80	130		80	130	
		Outputs Low		'S310, 'S340		110	155		100	155	
				'S341, 'S344		130	180		130	185	
		Outputs Disabled		'S310, 'S340		135	180		135	180	
				'S341, 'S344		155	180		150	200	

** Not more than one output should be shorted at a time and duration of the short-circuit should not exceed one second.
* "A" indicates data input, "E" indicates enable input.

Switching Characteristics V_{CC} = 5 V, T_A = 25°C

SYMBOL	PARAMETER	TEST CONDITIONS (See Test Load/Waveforms)	'S310, 'S340 MIN	'S310, 'S340 TYP	'S310, 'S340 MAX	'S341, 'S344 MIN	'S341, 'S344 TYP	'S341, 'S344 MAX	UNIT
t_{PLH}	Data to Output delay	C_L = 50 pF R_L = 90Ω		11	15		16	22	ns
t_{PHL}				16	22		10	15	ns
t_{PZL}	Output Enable delay			8	15		10	15	ns
t_{PZH}				6	12		7	12	ns
t_{PLZ}	Output Disable delay	C_L = 5 pF R_L = 90Ω		10	15		10	15	ns
t_{PHZ}				7	12		7	12	ns

Function Tables

'310

$\overline{E_1}$	E_2	1Y OUTPUTS	2Y OUTPUTS
H	H	Z	Enabled (Inverting)
H	L	Z	Z
L	H	Enabled (Inverting)	Enabled (Inverting)
L	L	Enabled (Inverting)	Z

'340

$\overline{E_1}$	$\overline{E_2}$	1Y OUTPUTS	2Y OUTPUTS
H	H	Z	Z
H	L	Z	Enabled (Inverting)
L	H	Enabled (Inverting)	Z
L	L	Enabled (Inverting)	Enabled (Inverting)

'341

$\overline{E_1}$	E_2	1Y OUTPUTS	2Y OUTPUTS
H	H	Z	Enabled
H	L	Z	Z
L	H	Enabled	Enabled
L	L	Enabled	Z

'344

$\overline{E_1}$	$\overline{E_2}$	1Y OUTPUTS	2Y OUTPUTS
H	H	Z	Z
H	L	Z	Enabled
L	H	Enabled	Z
L	L	Enabled	Enabled

Z ≡ High impedance (output off).

INPUT VS OUTPUT VOLTAGE TRANSFER CHARACTERISTIC



THRESHOLD VOLTAGE VS OPERATING TEMPERATURE



* Dead Band: The hysteresis is guaranteed at any operating temperature and voltage.