

WIRING TABLE



C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
39	AWG 30	39
40	AWG 30	40

HARTING P/N	REVISION	Cable length (L)
3315 243 010 0308	00	100 ± 3
3315 243 020 0308	00	200 ± 3
3315 243 050 0308	00	500 ± 5

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATE CODE
HARTING P/N

		All Dimensions in mm Original Size DIN A3		Scale 2:1	Free size tol. \\		Ref. \\			
							Sub. \\			
		All rights reserved		Created by ZHENGL		Inspected by		Standardisation		
		Department HCS - CN						Date 2018-02-05		
								State In Work		
HARTING Customised Solutions		D-32339 Espelkamp		Title Har-Flex 40Pole,Dul-end,With SR,L=XXMM					Doc-Key / ECM-Nr. 100765155/UGD/000/A	
				Type TB		Number 33 15 243 XXX0308				
						Page 1/1				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

[33152430500308](#) [33152430100308](#) [33152430200308](#)