
DUAL-IN-LINE SOCI

SERIES 110, 122, 123 • INTEGRAL DECOUPLING CAPACITOR • OPEN FRAME



- Low profile DIP sockets w/ integral decoupling capacitor: .1μ F 20%-50V multi-layer ceramic epoxy encapsulated. Temp. range: -25° C to +85° C
- Hi-Rel, 4-finger BeCu #30 contact is rated at 3 amps. See page 253 for details
- Series 110, 122 and 123 use MM #1001, #0088 or #0089 pins. See pages 165 & 198 for details
- Insulators are high temperature thermoplastic, suitable for all soldering operations
- For Electrical, Mechanical and Environmental Data, see page 264 for details



| Total number of pins | B 000 000 1 | | | Quantity per tube | ORDERING INFORMATION | | | | | | | |
|--|---|---|---|--|--|---|-----|--|---|--|--|--|
| | A | B | С | or De | Solder Tail | | | L = .370 (2 Level Wrapost) | | st) | L = .510 (3 Level Wrapost) | |
| 14 16 18 20 22 24 28 24 28 32 40 | 0.7 0.8 0.9 1.0 1.1 1.2 1.4 1.6 2.0 | 0.3 0.3 0.3 0.3 0.3 0.3 0.6 0.6 0.6 | 0.4 0.4 0.4 0.4 0.4 0.7 0.7 0.7 0.7 | 28 25 22 20 18 16 14 16 14 12 10 | 110-XX-3 110-XX-3 110-XX-3 110-XX-3 110-XX-6 110-XX-6 110-XX-6 110-XX-6 | 114-41-801000 116-41-801000 118-41-801000 120-41-801000 122-41-801000 124-41-801000 124-41-801000 124-41-801000 124-41-801000 124-41-801000 124-41-801000 124-41-801000 126-41-801000 127-41-801000 128-41-801000 | | 122- 122- 122- 122- 122- 122- 122- 122- | XX-314-41-801 XX-316-41-801 XX-318-41-801 XX-320-41-801 XX-324-41-801 XX-328-41-801 XX-624-41-801 XX-632-41-801 XX-640-41-801 | 1000 1000 1000 1000 1000 1000 | 123-XX-314-4 123-XX-316-4 123-XX-318-4 123-XX-320-4 123-XX-322-4 123-XX-328-4 123-XX-624-4 123-XX-632-4 123-XX-640-4 | 1-801000 1-801000 1-801000 1-801000 1-801000 1-801000 1-801000 1-801000 1-801000 |
| SPECIFY PLATING CODE XX = | | | | | 13 🔷 | | | 93 | | | 43 ◆ | |
| Sleev | ve (Pin) | | | • | 10 μ" Au | | 200 | μ" Sn/Pb | | | 200 μ″ Sn | |
| Cont | act (Cli _l | 0) | | | 30 μ" Au | | 30 | 30 μ" Au | | | 30 μ" Au | |



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mill-Max:

123-43-624-41-801000 110-93-316-41-801000 110-93-318-41-801000 110-93-314-41-801000 110-93-320-41-801000 110-93-324-41-801000 110-90-316-00-000000 110-90-628-00-000000 123-93-628-41-801000 123-93-624-41-801000 123-93-640-41-801000 123-93-314-41-801000 123-93-316-41-801000 123-93-318-41-801000 123-93-320-41-801000 123-93-324-41-801000 110-13-628-41-801000 110-13-624-41-801000 110-13-314-41-001100 110-13-640-41-801000 110-93-632-41-801000 110-93-624-41-801000 110-93-628-41-801000 110-93-640-41-801000 110-13-314-41-801000 110-13-316-41-801000 110-13-318-41-801000 110-13-320-41-801000 110-13-324-41-801000 110-13-322-41-801000 110-13-328-41-801000 110-13-422-41-801000 110-13-632-41-801000 110-93-322-41-801000 110-93-328-41-801000 110-93-422-41-801000 122-13-314-41-801000 122-13-316-41-801000 122-13-318-41-801000 122-13-320-41-801000 122-13-322-41-801000 122-13-324-41-801000 122-13-328-41-801000 122-13-422-41-801000 122-13-624-41-801000 122-13-628-41-801000 122-13-632-41-801000 122-13-640-41-801000 123-13-314-41-801000 123-13-316-41-801000 123-13-318-41-801000 123-13-320-41-801000 123-13-322-41-801000 123-13-324-41-801000 123-13-328-41-801000 123-13-422-41-801000 123-13-624-41-801000 123-13-628-41-801000 123-13-632-41-801000 123-13-640-41-801000 123-93-322-41-801000 123-93-328-41-801000 123-93-422-41-801000 123-93-632-41-801000 110-43-318-41-801000 123-43-314-41-801000 123-43-640-41-801000 123-43-316-41-801000 123-43-320-41-801000 123-43-628-41-801000 110-43-624-41-801000 110-43-324-41-801000 110-43-628-41-801000 110-43-320-41-801000 110-43-640-41-801000 110-43-314-41-801000 110-43-316-41-801000 123-43-318-41-801000 110-43-322-41-801000 110-43-328-41-801000 110-43-422-41-801000 110-43-632-41-801000 123-43-322-41-801000 123-43-324-41-801000 123-43-328-41-801000 123-43-632-41-801000 110-13-652-61-001000 110-41-422-41-605000 110-13-628-61-001000 110-91-952-61-001000 110-43-632-61-605000 110-33-320-41-530000 110-93-964-61-001000 110-41-624-61-001000 110-93-422-61-001000 110-41-952-61-001000 110-13-322-61-801000 110-43-648-61-001000 110-11-308-41-001000 110-44-964-61-001000