


DDR3:~1GByte



Options:

=====

1. Use 2(DDR3 256Mx16 Memory chips)x4Gb = 1GByte, i.e. 2xH5TQ4G63MFR-PBC(or K4B4G1646Q-HYK0) -> Default
2. Use 2(DDR3 512Mx16 Memory chips)x8Gb = 2GBytes, i.e. 2xH5TC8G63AMR-PBA(or K4B8G1646Q-MYK0)

Note:

=====

We have used a number of fully compatible, but different DDR3 memories due to supply unavailability. In such cases the memory part name in the schematic might remain outdated. It is recommended to always refer to the exact memory name printed on the component itself.


DDR3 Memory		
<c> 2015		
OLIMEX LTD, Bulgaria		
Sheet: /		
File: A64-OLinuXino_Rev_B.sch		
Title: A64-OLinuXino		
Size: A3	Date: 2015-10-15	Rev: Rev_A
KiCad E.D.A. kicad 4.1.0-alpha+201605180746+681344ubuntu15.10.1-pdoddy		

NAND Flash

eMMC


Option!

eMMC is default, because in this case, SPI0 is not multiplexed with eMMC as is with the NAND Flash!
SPI0 is available on the UEXT connector!




Audio

CPVEE and VEE to be made as Kelvin connection.



T-Card



<c> 2015

OLIMEX LTD, Bulgaria

Sheet: /NAND Flash , eMMC, T-Card and Audio/
File: NAND Flash , eMMC, T-Card and Audio.sch



Title: A64-OLinuxino

Size: A3	Date: 2015-10-15
----------	------------------


Size: A5	Date: 2015-10-15	Rev: Rev. 2
KiCad E.D.A. kicad 4.1.0-alpha+201605180746+681344ubuntu15.10.1	product	

	7	8
--	---	---



HDMI






WiFi & BT




USB




Gigabit Ethernet or LCD




Power Supply




UEXT



Extension



Crystal, RTC & Control



MiPi-DSI

