OLinuXino EEPROM content layout

Olimex Ltd

September 21, 2017

Contents

1	Intro	oduction	2
2	Memory layout		
	2.1	Header	3
	2.2	ID	3
	2.3	Revision	3
	2.4	Serial	4
	2.5	Configuration	4
3	Codes		
4	Revision		

1 Introduction

2 Memory layout





Figure 1: Memory layout schematic

2.1 Header

Header is 4 bytes long. It marks the beginning of configuration page. It is hard-coded and always should be the same.



2.2 ID

ID field is 4 bytes long. Value is stored as unsigned int.

2.3 Revision


This section is 2 bytes long. It stores board revision number in ASCII code: C, J1, etc.

Where:

- **Major** General revision of the board, when there are big changes. For example: A, B, C, etc.
- **Minor** When PCB is the same, but some values differ resistors, capacitors, etc. If not used should be *00h*.


2.4 Serial

Serial number is hold as hexadecimal unsigned long int. It's sequential number.



2.5 Configuration

This section is 4 bytes long. Here is stored board configuration - *NAND*, *eMMC*, etc.



Where:

- **Storage** Describes if there is external storage chip.
- **Size** Capacity of the device. Usable only if "Storage" is different from 0xFF.
- RAM RAM capacity.
- **Grade** Board grade.

3 Codes

Code	Description
0x00	Default value. No external storage.
0x45	eMMC chip.
0x4E	NAND chip.
0x53	SPI flash.

Table 1: Storage configuration codes

Code Description Size is 1B. 00 Size is 2B. 01 Size is 1KB. 10

Size is 1MB. 20

Size is 1GB. 30

. . .

Table 2: Size configuration codes

Code Description RAM is 1B. 00 01 RAM is 2B. 10 RAM is 1KB. RAM is 1MB. 20 RAM is 1GB. 30 . . .

Table 3: RAM configuration codes

Code Description

0x00Commercial grade. 0x01 Industrial grade.

Table 4: Grade configuration codes

Revision 4

- Rev.A 2 May 2017 Initial release
- Rev.B 1 Sep 2017 Reworked layout