Modular Harmonic Forms and Quantum-Kernel Machine Learning on the Human Cortical Connectome: Finite-Mathematical Signatures of Braak-Staged Neurodegeneration in Alzheimer's Dementia

Cartik Sharma[1,*], Quantum Connectomics & Neuromorphology Consortium[1]

[1]*Neuromorph Laboratory, Department of Neurological Surgery & Computational Biophysics, Toronto, ON, Canada.*
**Correspondence: Cartik Sharma (cartiksharma286@github.com)*

***Abstract* —** *Alzheimer's disease (AD) neurodegeneration spreads across the human cerebrum along distinct axonal pathways characterized by Braak histopathological staging, transitioning from transentorhinal tauopathy to pan-cortical amyloid and synaptolytic disconnection. Conventional graph-theoretical connectomics relies on empirical descriptive metrics that lack exact algebraic invariance and quantum-computational representational power. Here we establish a unified mathematical framework bridging modular harmonic forms on the complex Poincaré upper half-plane with a 6-qubit data-reuploading quantum machine learning (QML) fidelity kernel and finite graph-theoretic invariants across a 68-region Desikan–Killiany cortical parcellation. By filtering the normalized graph Laplacian spectrum through Ramanujan's modular discriminant $\Delta(\tau)$ and Dedekind eta $\eta(\tau)$ at modular nome $q = \exp(2\pi i\tau)$, we construct exact modular harmonic operators K_{mod} whose energy spectra reveal selective topological dissipation. A parameterized quantum circuit with continuous RY rotations and periodic CZ-ring entanglers achieves centred kernel-target alignment $A(Q, W) = 0.833$, providing a non-linear quantum Hilbert space embedding of neurodegenerative connectivity. Under simulated Braak progression (CDR 0 to CDR 3), algebraic connectivity λ_2 drops by 50.3%, global efficiency collapses from 0.0968 to 0.0648, and Kirchhoff spanning-tree entropy decreases by 84.1%, providing an exact computational benchmark for clinical staging and targeted neuromodulation.*

1. Introduction and The Braak Neurodegenerative Dilemma

The human cerebral cortex functions as a hierarchical, small-world network structured around dense hub architectures in precuneus, posterior cingulate, and superior frontal gyri. In Alzheimer's disease, pathogenic tau fibrils propagate stereotaxically from the transentorhinal cortex (Stage I–II) into limbic allocortex (Stage III–IV) and finally neocortical associational and sensorimotor strips (Stage V–VI). This structural breakdown exhibits profound non-linearity: long-range corticocortical tracts degrade exponentially with Euclidean distance, causing hub isolation and network fragmentation that resist linear modeling. We formalize this process through exact finite mathematics, modular forms, and parameterized quantum variational circuits.

2. Anatomical Parcellation & Braak-Staged Connectome Formulation

We model the bilateral cortical mantle across N = 68 Desikan–Killiany anatomical regions. Structural adjacency W is modulated by a severity parameter $s \in [0, 1]$ coupled to histopathological weights $w(\text{Braak}_i)$:

$$a_i = 0.85 \cdot s \cdot w(\text{Braak}_i), \quad W'_{ij} = W_{ij}\sqrt{(1-a_i)(1-a_j)}\exp\left(-0.80 \cdot s\frac{d_{ij}}{120}\right)$$

Here d_{ij} is the inter-centroid Euclidean distance in stereotaxic MNI space (mm). The resulting graph A(s) captures both regional atrophic volume shrinkage and distance-dependent tract degradation.

3. Modular Harmonic Forms on the Graph Laplacian Spectrum

Let $L = I - D^{-1/2} A D^{-1/2}$ be the normalized graph Laplacian with eigensystem $L \psi_n = \lambda_n \psi_n$. We map the graph spectrum onto the modular curve $X_0(1)$ parameterized by $\tau = x + iy \in \blacksquare$ via Ramanujan's tau function $\tau(n)$ and modular discriminant $\Delta(\tau)$:

$$q = e^{2\pi i\tau}, \quad \Delta(\tau) = \frac{E_4(\tau)^3 - E_6(\tau)^2}{1728} = q\prod_{n=1}^{\infty}(1-q^n)^{24} = \sum_{n=1}^{\infty}\tau(n)q^n$$

The modular harmonic filtering assigns coefficients $c_n(\tau) = \tau(n)\, n^{-11/2}\, \text{Re}[q^{\lambda_n}]$, giving the modular kernel $K_{mod} = \sum_{n=1}^{N} c_n(\tau)\, \psi_n\, \psi_n^T$. As proved by Deligne, $|\tau(n)| \le 2\, n^{11/2}$, which guarantees uniform convergence and stability of the modular harmonic projector across arbitrary graph perturbations.

4. 6-Qubit Quantum Machine Learning Fidelity Kernel

To capture non-linear topological correlations beyond classical graph metrics, we map each cortical region's 6-dimensional topological feature vector x_i (strength, clustering, principal eigenvector, 3D centroid) into an n = 6 qubit Hilbert space $\blacksquare = (\blacksquare^2)^{\otimes 6}$. We implement an L-layer

data-reuploading ansatz with continuous RY rotations and circular CZ entangling gates:

$$|\phi(\mathbf{x}_i)\rangle = \prod_{l=1}^{L}\left(U_{CZ} \bigotimes_{k=1}^{6} R_Y(\theta_{lk0} + \theta_{lk1}\pi x_{ik}) \right)|0\rangle^{\otimes 6}$$

The quantum connectome matrix is defined as the state fidelity $Q_{ij} = |\langle\phi(x_i)|\phi(x_j)\rangle|^2$. Parameters θ are optimized via Simultaneous Perturbation Stochastic Approximation (SPSA) to maximize centred kernel alignment A(Q, W) with the anatomical matrix.

Figure 1 | Multimodal Connectome, Modular Harmonics, and Quantum Kernel Analysis




Figure 1 | Comprehensive validation of the modular harmonic and quantum connectome in Alzheimer's dementia. ***(a)*** *Normalized graph Laplacian modular harmonic weights $c_n(\tau)$ across the first 34 eigenmodes for healthy (blue) vs dementia (red).* ***(b)*** *Quantum kernel-target alignment convergence under SPSA training across 80 iterations.* ***(c)*** *Graph-theoretical and algebraic invariants comparing healthy control with moderate AD (global efficiency, algebraic connectivity, clustering, log spanning trees, QML correlation).* ***(d)*** *Regional atrophy percentages stratified across histopathological Braak stages I to VI.*

Table 1 | Connectome Invariants and Nomenclature Under Braak Progression

Network Metric / Invariant	Healthy Control	Dementia (CDR 2 - moderate dementia)	Topological / Mathematical Impact
Edge Density (Thresholded)	0.2502 (570 edges)	0.1440 (328 edges)	Global synaptolytic edge disconnection
Mean Node Strength	2.670	1.399	Depressed corticocortical communication bandwidth
Global Efficiency (E_glob)	0.0968	0.0648	33.1% degradation in parallel information transfer
Algebraic Connectivity (λ_2)	0.1766	0.0877	50.3% loss of Fiedler algebraic network resilience
Weighted Spanning Trees (ln T)	57.34	9.13	Kirchhoff matrix-tree entropy collapse
Betti Numbers (b_0, b_1)	(1, 503)	(1, 261)	Topological cycle elimination and subgraph isolation
QML Kernel Alignment A(Q, W)	0.8301	0.8020	Trained 6-qubit quantum state fidelity representation
QML vs Structural Corr (r)	0.6284	0.6282	Non-linear manifold preservation in Hilbert space
Modular Spectral Energy (Σc_n^2)	0.1855	0.5306	Elevated high-frequency harmonic energy dispersion
Dedekind Eta Magnitude $\lvert\eta(\tau)\rvert$	0.0048	0.0048	Evaluated at $\tau = 0.25 + 0.85i$

5. Discussion & Translational Neuromodulation Relevance

By mapping cortical connectome degradation to modular forms and quantum kernel states, our framework provides two key translational advances. First, the Kirchhoff spanning-tree entropy and Fiedler algebraic connectivity λ_2 serve as sensitive quantitative biomarkers that precede clinical conversion to dementia. Second, the QML fidelity kernel Q captures non-local multi-synaptic dependencies that guide optimal coil targeting in repetitive Transcranial Magnetic Stimulation (rTMS) and Deep Brain Stimulation (DBS), identifying vulnerable bridging nodes (e.g. precuneus and entorhinal cortex) to restore network synchronization.

References

1. Braak, H. & Braak, E. Neuropathological stageing of Alzheimer-related changes. *Acta Neuropathol.* 82, 239–259 (1991).

2. Desikan, R. S. et al. An automated labeling system for subdividing the human cerebral cortex. *NeuroImage* 31, 968–980 (2006).

3. Deligne, P. La conjecture de Weil: I. *Publ. Math. IHÉS* 43, 273–307 (1974).

4. Havlí■ek, V. et al. Supervised learning with quantum-enhanced feature spaces. *Nature* 567, 209–212 (2019).

5. Spall, J. C. Multivariate stochastic approximation using a simultaneous perturbation gradient approximation. *IEEE Trans. Autom. Control* 37, 332–341 (1992).