

NOTES (UNLESS OTHERWISE SPECIFIED):

GENERAL

- 1) PCB IS 12-LAYER, .062" THICK.
- 2) CONSTRUCTION IS SOLDER-MASK-OVER-BARE-COPPER (SMOBC).
- 3) ACCEPTABILITY SHALL BE BASED ON IPC-A-600, CLASS 2.
- 4) THE FOLLOWING GERBER RS274X PHOTO TOOL FILES SHALL BE USED TO DEFINE ALL CIRCUIT FEATURES:
*GTL -- TOP LAYER GERBER DATA
*GP1 -- INTERNAL PLANE LAYER 1 GERBER DATA
*G1 -- MID LAYER 1 GERBER DATA
*GP2 -- INTERNAL PLANE LAYER 2 GERBER DATA
*GP3 -- INTERNAL PLANE LAYER 3 GERBER DATA
*GP4 -- INTERNAL PLANE LAYER 4 GERBER DATA
*GP5 -- INTERNAL PLANE LAYER 5 GERBER DATA
*GP6 -- INTERNAL PLANE LAYER 6 GERBER DATA
*GP7 -- INTERNAL PLANE LAYER 7 GERBER DATA
*GP8 -- INTERNAL PLANE LAYER 8 GERBER DATA
*GP9 -- INTERNAL PLANE LAYER 9 GERBER DATA
*GBL -- BOTTOM LAYER GERBER DATA
*GTO -- TOP OVERLAY GERBER DATA
*GBO -- BOTTOM OVERLAY GERBER DATA
*GTP -- TOP-SIDE SOLDER PASTE MASK
*GBP -- BOTTOM-SIDE SOLDER PASTE MASK
*GTS -- TOP SOLDER MASK GERBER DATA
*GBS -- BOTTOM SOLDER MASK GERBER DATA
- 5) THE PHOTO TOOL SHALL NOT BE COMPENSATED WITHOUT PRIOR ENGINEERING APPROVAL.
PCB DESIGNER: RICH LOBELL PH (805) 880-1621 FAX (805) 961-1792.

FABRICATION TOLERANCES

- 6) END PRODUCT CONDUCTOR WIDTHS AND PAD DIAMETERS SHALL NOT VARY MORE THAN 0.002" FROM THE 1:1 DIMENSIONS OF THE MASTER ARTWORK.
- 7) THE CONDUCTIVE PATTERN SHALL BE POSITIONED SO THAT THE LOCATION OF ANY PAD OR LAND SHALL BE WITHIN 0.005" DIAMETER TO THE TRUE POSITION OF THE HOLE IT CIRCUMSCRIBES.
- 8.1) DRILL TOLERANCES +/- 0.003"
- 8.2) ALL DRILL HOLE SIZES AND TOLERANCES APPLY AFTER PLATING.
- 9) THE MINIMUM ANNULAR RING SHALL BE 0.005".
- 10) BOW AND TWIST SHALL NOT EXCEED 0.010" PER INCH.
- 11) FOR PCB ROUTING DIMENSIONS: .XXX = +/- .005" .XX = +/- .020"

MATERIAL

- 12) BASE MATERIAL IS FR4 EPOXY FIBERGLASS
- 13) SEE STACK-UP LEGEND FOR COPPER CLADDING CALL OUTS

PLATING

- 14) ALL HOLES AND CONDUCTIVE SURFACES SHALL BE PLATED WITH A MINIMUM OF 0.001" COPPER.
- 15) AFTER SOLDERMASK, ALL EXPOSED HOLES AND CONDUCTIVE SURFACES SHALL BE COATED WITH A GOLD IMMERSION PLATING TO PRESERVE SOLDERABILITY.

COATINGS


- 16) THE SOLDERMASK SHALL BE BLACK LIQUID PHOTO-IMAGEABLE PER IPC-SM-840, TYPE-B, CLASS 2.
- 17) THE SOLDERMASK REGISTRATION ALLOWANCE IS 0.003". THERE SHALL BE NO SOLDERMASK ON ANY SOLDER PAD OR LAND.

MARKING

- 18) THE LEGEND SHALL BE SCREEN-PRINTED USING PERMANENT YELLOW EPOXY INK.
- 19) THE SCREEN PRINTING REGISTRATION ALLOWANCE IS 0.007". THERE SHALL BE NO INK ON ANY SOLDER PAD OR LAND.
- 20) THE VENDOR CODE AND UL FLAMMABILITY RATING MAY BE ETCHED IN THE FOIL OR MARKED IN PERMANENT EPOXY INK (VENDOR'S OPTION).

ELECTRICAL TESTING

- 21) ALL BOARDS SHALL BE ELECTRICALLY TESTED TO THE SUPPLIED IPC-D-356A NET LIST FOR CONTINUITY, OPENS AND SHORTS.



Layer Stack Up Detail for: 175-00014.Revi, PCB, Sinistro Backplane,PcbDoc		
Layer Name	Copper cladding	
Top Layer (*,GTL)	1/2 oz.	(1 oz. Finished)
AGND (*,GP1)	1/2 oz	
Mid-Layer 1 (*,G1)	1/2 oz	
GND (*,GP2)	1/2 oz	
+12V (*,GP3)	1/2 oz	
-12V (*,GP4)	1/2 oz	
+5ANA (*,GP5)	1/2 oz	
-5ANA (*,GP6)	1/2 oz	
+2B (*,GP7)	1/2 oz	
UCC (*,GP8)	1/2 oz	
+24V (*,GP9)	1/2 oz	
Bottom Layer (*,GBL)	1/2 oz.	(1 oz. Finished)

PRIMARY PCB SPECIFICATIONS	
(REFER TO COMPLETE SPEC LISTING AT LEFT FOR FURTHER DETAILS)	
NUMBER OF LAYERS	12
FINISHED THICKNESS	.062"
BASE MATERIAL	FR4
PLATING TYPE	GOLD IMMERSION
SOLDER MASK COLOR	BLACK

Las Cumbres Observatory		Las Cumbres Observatory, Inc.	
Gñ'nd Tùkàngu Nùm'èk		6740 Cortona Dr.	
		Goleta, CA 93117	
		www.lcogt.net	
DATE	6/11/2010	DESIGNED	Rich Lobell
DRAWN		BAW	Rich Lobell
SIZE		SCALE	1 : 1
PARTS		PROCESS	
REV	175-00014, Sinistro Backplane		
REV	C	REV	- GPT
REV	1	REV	1 OF 20

NOTICE
THIS DRAWING EMBODIES A PROPRIETARY DESIGN OWNED BY LAS CUMBRES OBSERVATORY. IT IS SUBMITTED FOR A SPECIFIC PURPOSE UNDER A CONFIDENTIAL RELATIONSHIP, AND EXCEPT FOR PURPOSES EXPRESSLY GRANTED IN WRITING, ALL RIGHTS ARE RESERVED BY LAS CUMBRES OBSERVATORY.