

FABRICATION NOTES

GENERAL

- 1) Manufactuered in accordance with IPC-6012B Class 1
- 2) Number of layers: 2
- 3) Finished thickness: 0.062
- 4) Base material: FR4
- 5) Plating: Gold immersion
- 6) Solder mask color: Any

EXCEPTIONS

- 7) Silkscreen on top only
- 8) Minimum dielectric thickness is 0.031 in
- 9) All drill hole sizes and tolerances apply after plating
- 10) All holes plated
- 11) All exposed holes and surfaces gold immersion plated to preserve solderability

ROUTING TOLERANCES


- 12) X.XX = +/- 0.02 in
- 13) X.XXX = +/- 0.005 in

LAYER STACK

- *.GTL - 1 Oz. Cu (finished) TOP LAYER GERBER DATA
- *.GBL - 1 Oz. Cu (finished) BOTTOM LAYER GERBER DATA
- *.GTS - TOP LAYER SOLDERMASK
- *.GBS - BOTTOM LAYER SOLDERMASK
- *.GTO - TOP LAYER (ONLY) SILKSCREEN
- *.GDI - DRILL DRAWING
- *.GMI - BOARD OUTLINE
- *.GM2 - BOARD DRAWING AND NOTES

Layer	Name	Material	Thickness	Constant	Board Layer Stack
1	Top Silkscreen				
2	Top Soldermask	Solder Resist	0.40mil	3.5	
3	Top Layer	Copper	1.40mil		
4	Dielectric 1	FR-4	58.40mil	4.2	
5	Bottom Layer	Copper	1.40mil		
6	Bottom Soldermask	Solder Resist	0.40mil	3.5	

Symbol	Hit Count	Finished Hole Size	Plated	Hole Type
▽	4	70.87mil (1.800mm)	PTH	Round
○	31	17.72mil (0.450mm)	PTH	Round
□	31	55.12mil (1.400mm)	PTH	Round
☆	41	35.00mil (0.889mm)	PTH	Round
	107 Total			



NOTICE:
This drawing embodies a proprietary design owned by Las Cumbres Observatory Global Telescope Network, Inc. It is submitted for a specific purpose under a confidential relationship, and except for purposes expressly granted in writing, all rights are reserved by Las Cumbres Observatory.

Las Cumbres Observatory Global Telescope Network		LCOGT 6740 Cortona Dr., Ste. 102 Goleta, CA 93117 www.lcogt.net	
DATE 2015-12-22	DESIGNED Joe Tufts	DRAWN Joe Tufts	SCALE 1 : 1
CHECKED/DATE		APPROVED/DATE	
TITLE 175-00065-A Sinistro Camera Controller Extension			
SIZE B	DOC NO. - GPT		REV A
		SHEET 1 OF 1	