

# MeasurementSet definition version 3.0

eds.

March, 2018

## Contents

<b>1</b>	<b>Summary</b>	<b>2</b>
<b>2</b>	<b>Introduction</b>	<b>3</b>
<b>3</b>	<b>Summary of changes</b>	<b>4</b>
3.1	MAIN table . . . . .	4
3.2	ARRAY table . . . . .	4
3.3	FIELD table . . . . .	5
3.3.1	Direction information . . . . .	5
3.4	FLAG_CMD . . . . .	5
3.5	OBSERVATION table . . . . .	5
3.6	SOURCE table . . . . .	5
3.7	SPECTRAL_WINDOW table . . . . .	5
<b>4</b>	<b>New sub-tables</b>	<b>5</b>
4.0.1	BEAM subtable . . . . .	6
4.0.2	EPHEMERIDES . . . . .	6
4.1	INTERFEROMETER_MODEL . . . . .	6
4.1.1	Multi element station based antenna (PHASED_ARRAY subtable) . . . . .	6
4.1.2	SCAN subtable . . . . .	6
4.1.3	Associated tables (CAL_TABLES) . . . . .	6
<b>5</b>	<b>MS v3.0 layout</b>	<b>6</b>
5.1	MAIN table: Data, coordinates and flags . . . . .	8

5.2	MAIN table: continued	9
5.3	ANTENNA: Antenna characteristics	11
5.4	BEAM: Beam information	13
5.5	CORRELATOR_TYPE: Doppler tracking information	14
5.6	DOPPLER: Doppler tracking information	15
5.7	EPHEMERIS: Ephemerides information	16
5.8	FEED: Feed characteristics	17
5.9	FIELD: Field positions for each source	19
5.10	FLAG_CMD: Flag commands	20
5.11	FREQ_OFFSET: Frequency offset information	21
5.12	HISTORY: History information	22
5.13	INTERFEROMETER_MODEL: VLBI Interferometer information	23
5.14	OBSERVATION: Observation information	24
5.15	PHASED_ARRAY: phased array stations information	25
5.16	POINTING: Antenna pointing information	26
5.17	POLARIZATION: Polarization setup information	28
5.18	PROCESSOR: Processor information	29
5.19	SCAN: Scan information	30
5.20	SOURCE: Source information	31
5.21	SPECTRAL_WINDOW: Spectral window description	33
5.22	STATE: State information	35
5.23	SYSCAL: System calibration	36
5.24	WEATHER: weather station information	38
<b>6</b>	<b>References</b>	<b>39</b>

## 1 Summary

This note describes a revised MeasurementSet definition which extends that previously given in casa/casacore Note 229(Kemball and Wieringa 2000). The new definition is designed to support features that were felt missing from v2.0 or tedious to deal with, provide support for VLBI processing and non dish arrays.

## 2 Introduction

The MeasurementSet (MS) defines the format in which visibility and single-dish data are stored for packages using casa/casacore code.

- **Explicit keys** One of the major complaints of ms v2.0 is the use of row ids in subtables as implicit keys. In v3.0 we are moving to explicit keys; e.g ANTENNA subtable will have a column ANTENNA\_ID so that when making a subset MS re-indexing is not needed in the main table.
- **Single-dish processing:** FLOAT\_DATA is going to be replaced by DATA unifying it with interferometer. It is left to the column implementation to store floats efficiently rather than have multiple columns defined for data types
- **Synthesis calibration:** The need for calibrations table as part the MeasurementSet has been felt by several telescopes and those using v2.0 (e.g ALMA and EVLA) have been using non standard tables to carry calibration type information.
- **Data,weight, flag versioning** Non standard columns (e.g CORRECTED\_DATA) or kludges have been used by casa (for e.g) to deal with having version of data, flag or weight. These 3 columns are having the same shapes in every row of an msv3.0. Whenever changes are made example flagging or calibration and a new version is needed. A new triplet of columns will be made. It is left to software implementation to do the smart thing (not making unnecessary copies). E.g if flagging only is done and need to be saved in a new version of FLAG column, the new version of DATA an WEIGHT are going to be just virtual columns pointing back to the previous version.
- **Data Description** The concept of data description is being deprecated it saved a column of integers but users found it confusing. SPECTRAL\_WINDOW\_ID and POLARIZATION\_ID are explicit columns in the main table
- **VLBI data reduction:** From v2.0 added an optional subtable INTERFEROMETER\_MODEL
- **Phased Array interferometers:** A new optional subtable, PHASED\_ARRAY, which will be defining which antennas form a phased array station.

Some features:

- **Incremental change:** The changes proposed here are designed to be as incremental as possible and taking into account what usage at different telescopes and software packages has found lacking.
- **Compatibility:** Some of the changes proposed here are not backwards compatible
- **Calibration information:** Many of the direct and peripheral information stored at data collection can be stored as calibration terms (Jones or Mueller matrices). Therefore MS v3.0 will carry in its definition optional calibration table which may carry monitoring information that can be used to modify the data, weights and flags
- **Storage:** A future document will provide results and suggestion for data storage structures for some commonly used access patterns and storage system in use.
- **Multi measurement sets:** In a different document we will describe the format of having an MS which consists of valid sub MSs without physical concatenation

### 3 Summary of changes

This section contains a description of the changes proposed for each table in the MS definition. A full definition of the v3.0 MS format is given in Section 5.

All the subtables not mentioned here will have an explicit ID column; in v3.0 implicit row number being an ID is no longer valid. For example ANTENNA subtable will have a ANTENNA\_ID column added as a key.

#### 3.1 MAIN table

- **removal of FLAG\_CATEGORY**

This column has not been used effectively. With the versioning of FLAG below it is redundant.

- **Removal of SIGMA WEIGHT** being always considered to be  $\frac{1}{\sigma^2}$  this a redundant column.

- **Removal of FLAG\_ROW** Unnecessary and confusing column when used in conjunction with WEIGHT

- **Redefinition of WEIGHT to be WEIGHT\_SPECTRUM** With most of contemporary inteferometers being spectral machines with possibility of distinctive weights per channel, usage of MSv2.0 WEIGHT is low w.r.t WEIGHT\_SPECTRUM. In this version WEIGHT column will have the same shape as the data.

- **Versioning of (DATA, WEIGHT, FLAG) triplet** These three columns will have the same shapes. There may be many versions them in an MS. But the active version will be refered to as DATA, WEIGHT and FLAG. The versions need not be copies. For e.g if only DATA is corrected and a new version is made. The active DATA will refer to DATA1 column while the active WEIGHT, FLAG (thus WEIGHT1 and FLAG1) will refer to the to WEIGHT0 and FLAG0 respectively. We leave it to the software to implement these in the most optimal fashion without making duplicate copies. This removes the need for non-standard column like CORRECTED\_DATA or FLAG\_VERSION etc.

- **Merging of DATA and FLOAT\_DATA** It is unnecessary to have explicit DATA and FLOAT\_DATA. The software implementation can do the optimal storage in the presence of float data only and serve it as complex.

- **Replacement of DATA\_DESC\_ID** This unique ID has caused more confusion than the extra column of integers is worth. In this version we are reverting to having explicit POLARIZATION\_ID and SPECTRAL\_WINDOW\_ID which refers to keys in the POLARIZATION and SPECTRAL\_WINDOW subtables directly. DATA\_DESC\_ID column is removed.

#### 3.2 ARRAY table

- **ARRAY\_ID** An explicit ID column is newly defined.

- **ARRAY\_CENTER** A new column which will give the full Measures position of where the array center is assumed for each ARRAY\_ID

### 3.3 FIELD table

Changes applicable to the FIELD table are discussed in this section.

An explicit FIELD\_ID

#### 3.3.1 Direction information

The PHASE\_DIR information is to be derived from the ephemeris subtable if the EPHEMERIS\_ID is not -1.

A new column optional DURATION column is added; when present in combination with TIME (time origin) it defines the time range for when the information for direction for a given FIELD\_ID. In this fashion step function phasecentering that happens in some correlators

### 3.4 FLAG\_CMD

FLAG\_CMD table is made an optional subtable.

### 3.5 OBSERVATION table

Apart from the explicit OBSERVATION\_ID column version 3.0 adds the **ARRAY\_CENTER**: A new column which will give the full Measures position of where the array center is assumed for each ARRAY\_ID

### 3.6 SOURCE table

The SOURCE table already had a SOURCE\_ID column. In this version it is proposed to generalize the SOURCE\_MODEL. Apart from a TableRecord it can take a URL which will point to catalogue style source list or even images representing the model associated with a SOURCE\_ID and SPECTRAL\_WINDOW\_ID.

### 3.7 SPECTRAL\_WINDOW table

Apart from the explicit SPECTRAL\_WINDOW\_ID column; an optional column LO\_FREQUENCY which (can be vector of frequencies) gives the Local Oscillator frequencies in the chain of frequency conversion.

## 4 New sub-tables

New sub-tables added to MS v3.0 are included in this Section.

#### **4.0.1 BEAM subtable**

This table proposed in v2.0 but we explicitly define it here. It is referenced from the FEED table or from the newly proposed PHASED\_ARRAY table here.

#### **4.0.2 EPHEMERIDES**

This optional table is explicitly defined and is referred to from the FIELD table via the EPHEMERIS\_ID column.

### **4.1 INTERFEROMETER\_MODEL**

This optional subtable contains information necessary for VLBI arrays

#### **4.1.1 Multi element station based antenna (PHASED\_ARRAY subtable)**

Information about elements that makes a station antenna, combination scheme etc

#### **4.1.2 SCAN subtable**

This will carry the information about the scan intent and information necessary to tie back information from the online system

#### **4.1.3 Associated tables (CAL\_TABLES)**

A lot of data processing or online correction information are carried as non standard subtables. The formal existence of calibration tables associated with a given MS will satisfy the needs of many of the non-standard subtables.

## **5 MS v3.0 layout**

There is a MAIN table containing a number of data columns and keys into various subtables. There is at most one of each subtable. The subtables are stored as keywords of the MS, and all defined sub-tables are tabulated below. Optional sub-tables are shown in *italics*.

Subtables		
Table	Contents	Keys
ANTENNA	Antenna characteristics	ANTENNA_ID
BEAM	Beam information	BEAM_ID
( <i>DOPPLER</i> )	Doppler tracking	DOPPLER_ID,
		SOURCE_ID
( <i>EPHEMERIDES</i> )	Ephemeris information for near field objects	EPHEMERIS_ID, TIME
FEED	Feed characteristics	FEED_ID, ANTENNA_ID,
		TIME, SPECTRAL_WINDOW_ID
FIELD	Field position	FIELD_ID
( <i>FLAG_CMD</i> )	Flag commands	TIME
( <i>FREQ_OFFSET</i> )	Frequency offset information	FEED_ID, ANTENNA_ID,
		FEED_ID, TIME, SPECTRAL_WINDOW_ID
HISTORY	History information	OBSERVATION_ID, TIME
( <i>INTERFEROMETER_MODEL</i> )	Information for VLBI observations	ANTENNA_ID, FIELD_ID, SPECTRAL_WINDOW_ID, TIME
OBSERVATION	Observer, Schedule, etc	OBSERVATION_ID
PHASED_ARRAY	phased array stations information	PHASED_ARRAY_ID, ANTENNA_ID
POINTING	Pointing information	ANTENNA_ID, TIME
POLARIZATION	Polarization setup	POLARIZATION_ID
PROCESSOR	Processor information	PROCESSOR_ID
SCAN	scan information	SCAN_NUMBER
( <i>SOURCE</i> )	Source information	SOURCE_ID, SPECTRAL_WINDOW_ID, TIME
SPECTRAL_WINDOW	Spectral window setups	SPECTRAL_WINDOW_ID
STATE	State information	STATE_ID
( <i>SYSCAL</i> )	System calibration characteristics	FEED_ID, ANTENNA_ID,
		TIME, SPECTRAL_WINDOW_ID
( <i>WEATHER</i> )	Weather info for each antenna	ANTENNA_ID, TIME

Note that all optional columns are indicated in italics and in parentheses.

## 5.1 MAIN table: Data, coordinates and flags

MAIN table: Data, coordinates and flags				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Keywords</i>				
MS_VERSION	Float			MS format version
<i>Key</i>				
TIME	Double	s	EPOCH	Integration midpoint
(TIME_EXTRA_PREC)	Double	s		extraTIME precision
(ANTENNA1)	Int			First antenna
(ANTENNA2)	Int			Second antenna
(ANTENNA3)	Int			Third antenna
(PHASED_ARRAY1)	Int			First combined antenna
(PHASED_ARRAY2)	Int			Second combined antenna
(PHASED_ARRAY3)	Int			Third combined antenna
FEED1	Int			Feed on ANTENNA1
FEED2	Int			Feed on ANTENNA2
(FEED3)	Int			Feed on ANTENNA3
SPECTRAL_WINDOW_ID	Int			Spectral window id.
POLARIZATION_ID	Int			polarization id.
PROCESSOR_ID	Int			Processor id.
(PHASE_ID)	Int			Phase id.
FIELD_ID	Int			Field id.
<i>Non-key attributes</i>				
INTERVAL	Double	s	EPOCH	Sampling interval
EXPOSURE	Double	s		The effective integration time
TIME_CENTROID	Double	s		Time centroid
(PULSAR_BIN)	Int			Pulsar bin number
(PULSAR_GATE_ID)	Int			Pulsar gate id.
SCAN_NUMBER	Int			Scan number
ARRAY_ID	Int			Subarray number
OBSERVATION_ID	Int			Observation id.
STATE_ID	Int			State id.
(BASELINE_REF)	Bool			Reference antenna
UVW	Double(3)	m	UVW	UVW coordinates
(UVW2)	Double(3)	m	UVW	UVW (baseline 2)



## 5.2 MAIN table: continued

MAIN table: continued				
Name	Format	Units	Measure	Comments
<i>Data</i>				
(DATA)	Complex( $N_c, N_f$ )			Complex visibility matrix (synthesis arrays)
(VIDEO_POINT)	Complex( $N_c$ )			Video point
(LAG_DATA)	Complex( $N_c, N_l$ )			Correlation function
WEIGHT	Float( $N_c, N_f^*$ )			Weight for each channel
<i>Flag information</i>				
FLAG	Bool( $N_c, N_f^*$ )			Cumulative data flags

### Notes:

Note that  $N_l$ = number of lags,  $N_c$ = number of correlators,  $N_f$ = number of frequency channels, and  $N_{cat}$ = number of flag categories.

**MS\_VERSION** The MeasurementSet format revision number, expressed as *major\_revision.minor\_revision*. This version is 2.0.

**SORT\_ORDER** Sort order as either "ASCENDING" or "DESCENDING".

**TIME** Mid-point (not centroid) of data interval.

**TIME\_EXTRA\_PREC** Extra time precision.

**ANTENNA $n$**  Antenna number ( $\geq 0$ ), and a direct key index into the ANTENNA sub-table. For  $n > 2$ , triple-product data are implied. Either one ANTENNA $n$  or PHASED\_ARRAY $n$  should exist in a valid MS

**FEED $n$**  Feed number ( $\geq 0$ ). For  $n > 2$ , triple-product data are implied. For PHASED\_ARRAY $n$  feed id for each antenna in phased\_array is given in the PHASED\_ARRAY subtable.

**SPECTRAL\_WINDOW\_ID** Spectral window identifier ( $\geq 0$ ), and a direct key index into the SPECTRAL\_WINDOW sub-table.

**POLARIZATION\_ID** Polarization identifier ( $\geq 0$ ), and a direct key index into the POLARIZATION sub-table.

**PROCESSOR\_ID** Processor identifier ( $\geq 0$ ), and a direct key index into the PROCESSOR sub-table.

**PHASE\_ID** Switching phase identifier ( $\geq 0$ )

**FIELD\_ID** Field identifier ( $\geq 0$ ) a direct key index into the FIELD sub-table.

**INTERVAL** Data sampling interval. This is the nominal data interval and does not include the effects of bad data or partial integration.

**EXPOSURE** Effective data interval, including bad data and partial averaging.

**PULSAR\_BIN** Pulsar bin number for the data record. Pulsar data may be measured for a limited number of pulse phase bins. The pulse phase bins are described in the PULSAR sub-table and indexed by this bin number.

**PULSAR\_GATE\_ID** Pulsar gate identifier ( $\geq 0$ ), and a direct index into the PULSAR\_GATE sub-table *rownr*.

**SCAN\_NUMBER** Arbitrary scan number to identify data taken in the same logical scan. Not required to be unique; ( $\geq 0$ ) a direct key index into the SCAN sub-table.

**ARRAY\_ID** Subarray identifier ( $\geq 0$ ), which identifies data in separate subarrays, as defined in Section 3.3.

**OBSERVATION\_ID** Observation identifier ( $\geq 0$ ), which identifies data from separate observations, as defined in Section 3.3.

**STATE\_ID** State identifier ( $\geq 0$ ), as defined in Section 3.1.5.

**BASELINE\_REF** Flag to indicate the original correlator reference antenna for baseline-based correlators (True for ANTENNA1; False for ANTENNA2).

**UVW** *uvw* coordinates for the baseline from ANTENNE2 to ANTENNA1, i.e. the baseline is equal to the difference POSITION2 - POSITION1. The UVW given are for the TIME\_CENTROID, and correspond in general to the reference type for the PHASE\_DIR of the relevant field. I.e. J2000 if the phase reference direction is given in J2000 coordinates. However, any known reference is valid. Note that the choice of baseline direction and UVW definition (*W* towards source direction; *V* in plane through source and system's pole; *U* in direction of increasing longitude coordinate) also determines the sign of the phase of the recorded data.

**UVW2** *uvw* coordinates for the baseline from ANTENNE3 to ANTENNA1 (triple-product data only), i.e. the baseline is equal to the difference POSITION3 - POSITION1. The UVW given are for the TIME\_CENTROID, and correspond in general to the reference type for the PHASE\_DIR of the relevant field. I.e. J2000 if the phase reference direction is given in J2000 coordinates. However, any known reference is valid. Note that the choice of baseline direction and UVW definition (*W* towards source direction; *V* in plane through source and system's pole; *U* in direction of increasing longitude coordinate) also determines the sign of the phase of the recorded data.

**DATA, LAG\_DATA** At least one of these columns should be present in a given MeasurementSet. In special cases one or more could be present (e.g., single dish data used in synthesis imaging or a mix of auto and crosscorrelations on a multi-feed single dish). If only correlation functions are stored in the MS, then  $N_f^*$  is the maximum number of lags ( $N_l$ ) specified in the LAG table for this LAG.ID. If both correlation functions and frequency spectra are stored in the same MS, then  $N_f^*$  is the number of frequency channels, and the weight information refers to the frequency spectra only. The units for these columns (eg. 'Jy') specify whether the data are in flux density units or correlation coefficients.

**VIDEO\_POINT** The video point for the spectrum, to allow the full reverse transform.

**WEIGHT** The weight for each channel, with the same shape as DATA, as assigned by the correlator or processor.

**FLAG** An array of Boolean values with the same shape as DATA (see the DATA item above) representing the cumulative flags applying to this data matrix. Data are flagged bad if the FLAG array element is True.

### 5.3 ANTENNA: Antenna characteristics

ANTENNA: Antenna characteristics				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<b>Keys</b>				
ANTENNA_ID	Int			unique antenna id
<i>Data</i>				
NAME	String			Antenna name
STATION	String			Station name
TYPE	String			Antenna type
MOUNT	String			Mount type:alt-az, equatorial, X-Y, nasmyth, coude, orbiting, bizarre
POSITION	Double(3)	m	POSITION	Antenna X,Y,Z phase reference positions
OFFSET	Double(3)	m	POSITION	Axes offset of mount to FEED REFERENCE point
DISH_DIAMETER	Double	m		Diameter of dish
(ORBIT_ID)	Int			Orbit id.
(MEAN_ORBIT)	Double(6)			Mean Keplerian elements
(PHASED_ARRAY_ID)	Int			Phased array id.
Flag information				
FLAG_ROW	Bool			Row flag

**Notes:** This sub-table contains the global antenna properties for each antenna in the MS. It is indexed directly from MAIN via ANTENNA $n$ .

**ANTENNA\_ID** ID of the antenna.

**NAME** Antenna name (e.g. "NRAO.140")

**STATION** Station name (e.g. "GREENBANK")

**TYPE** Antenna type. Reserved keywords include: ("GROUND-BASED" - conventional antennas; "SPACE-BASED" - orbiting antennas; "TRACKING-STN" - tracking stations).

**MOUNT** Mount type of the antenna. Reserved keywords include: ("EQUATORIAL" - equatorial mount; "ALT-AZ" - azimuth-elevation mount; "X-Y" - x-y mount; "SPACE-HALCA" - specific orientation model.)

**POSITION** In a right-handed frame, X towards the intersection of the equator and the Greenwich meridian, Z towards the pole. The exact frame should be specified in the MEASURE\_REFERENCE keyword (ITRF or WGS84). The reference point is the point on the az or ha axis closest to the el or dec axis.

**OFFSET** Axes offset of mount to feed reference point.

**DISH\_DIAMETER** Nominal diameter of dish, as opposed to the effective diameter.

**ORBIT\_ID** Orbit identifier. Index used in ORBIT sub-table if ANTENNA\_TYPE is "SPACE-BASED".

**MEAN\_ORBIT** Mean Keplerian orbital elements, using the standard convention (Flatters 1998):

- **0:** Semi-major axis of orbit ( $a$ ) in  $m$ .
- **1:** Ellipticity of orbit ( $e$ ).
- **2:** Inclination of orbit to the celestial equator ( $i$ ) in  $deg$ .

- **3:** Right ascension of the ascending node ( $\Omega$ ) in *deg*.
- **4:** Argument of perigee ( $\omega$ ) in *deg*.
- **5:** Mean anomaly ( $M$ ) in *deg*.

**PHASED\_ARRAY\_ID** Phased array identifier. Points to a PHASED\_ARRAY sub-table which points back to multiple entries in the ANTENNA sub-table and contains information on how they are combined.

**FLAG\_ROW** Boolean flag to indicate the validity of this entry. Set to True for an invalid row. This does not imply any flagging of the data in MAIN, but is necessary as the ANTENNA index in MAIN points directly into the ANTENNA sub-table. Thus FLAG\_ROW can be used to delete an antenna entry without re-ordering the ANTENNA indices throughout the MS.

## 5.4 BEAM: Beam information

BEAM: Beam information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
BEAM_ID	Int			Beam id.
<i>Data</i>				
TYPE	String			definition type from a fixed set of strings. E.g POLYNOMIAL,AIRY, NUMERIC, IMAGE Depending on TYPE would be polynomial coefficients or numeric values rescaled at 1GHz sign of rotation w.r.t parallactic angle for types that cannot be expressed as coefficients e.g IMAGE
COEFFICIENTS	Double(NUM.COEFFICIENTS)			
BEAM_ROTATION	Int			
(ALTERNATE_URL)	String url			

**Notes:** This sub-table contains Beam information. Referred to from the FEED and PHASED\_ARRAY subtables.

**BEAM\_ID** Beam identifier

**TYPE** The way the beam information is expressed. Fixed set of strings possible (POLYNOMIAL, AIRY, NUMERIC, IMAGE, GAUSSIAN, INVERSEPOLYNOMIAL, COSPOLYNOMIAL, ZERNIKE)

**COEFFICIENTS** The coefficients for the expressed type. All the beams are defined at 1GHz; exceptio for IMAGE: it can have the spectral coordinates expressed in the image

**BEAM\_ROTATION** sign of beam rotation angle with respect to parallactic angle.

**ALTERNATE\_URL** Information on how to access beams that are expressed as images (from some telescope archive for e.g).

## 5.5 CORRELATOR\_TYPE: Doppler tracking information

CORRELATOR_TYPE: Doppler tracking information				
Name	Format	Units	Measure	Comments

**Notes:** This optional sub-table contains correlator information referred to from the PROCESSOR subtable.

## 5.6 DOPPLER: Doppler tracking information

DOPPLER: Doppler tracking information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
DOPPLER_ID	Int			Doppler tracking id.
SOURCE_ID	Int			Source id.
<i>Data</i>				
TRANSITION_INDEX	Int			Transition index. Indexes into transitions list in SOURCE
VELDEF	Double	m/s	Doppler	Velocity definition of Doppler shift.

**Notes:** This sub-table contains frame information for different Doppler tracking modes. It is indexed from the SPECTRAL\_WINDOW\_ID sub-table (with SOURCE\_ID as a secondary index) and thus allows the specification of a source-dependent Doppler tracking reference for each SPECTRAL\_WINDOW. This model allows multiple possible transitions per source per spectral window, but only one reference at any given time.

**DOPPLER\_ID** Doppler identifier, as used in the SPECTRAL\_WINDOW sub-table.

**SOURCE\_ID** Source identifier (as used in the SOURCE sub-table).

**TRANSITION\_INDEX** This index selects the appropriate line from the list of transitions stored for each SOURCE\_ID in the SOURCE table.

**VELDEF** Velocity definition of the Doppler shift, e.g., RADIO or OPTICAL velocity in m/s.

## 5.7 EPHEMERIS: Ephemerides information

EPHEMERIS: Ephemerides information				
Name	Format	Units	Measure	Comments
<i>Keywords</i>				
OBSLOC	String			observer's location for ephemerides
<b>Columns</b>				
<i>Key</i>				
EPHEMERIS_ID	Int			ephemeris id.
<i>Data</i>				
TIME	Double	s	EPOCH	Time of direction measurement
DIRECTION	Double(2)	rad	DIRECTION	Direction of object from obsloc position.
DISTANCE	Double	km		Distance from observer at time
RADIAL_VELOCITY	Double	m/s		Radial velocity of source
(SHAPE)	Double(3)	rad		Apparent elliptical shape in angular units (Major, minor, pos. angle)
(ALTERNATE_URL)	String			Location of Ephemerides table for this ephemeris_id

**Notes:** This sub-table contains ephemeris information as referred to from FIELD table.

Either multiple rows of information for a given EPHEMERIS\_ID is given in this table with time or a URL is provided to get an ephemeris table of known format (e.g the one used by Measures in casacore)

**EPHEMERIS\_ID** identifier referenced in FIELD table

**TIME** Epoch of observation of object

**DIRECTION** Measures direction of object at given time and seen from OBSLOC position.

**RADIAL\_VELOCITY** Velocity of object

**SHAPE** Apparent Elliptical shape of object

**ALTERNATE\_URL** Location of a ephemeris table in documented format.



## 5.8 FEED: Feed characteristics

FEED: Feed characteristics				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
ANTENNA_ID	Int			Antenna id
FEED_ID	Int			Feed id
SPECTRAL_WINDOW_ID	Int			Spectral window id.
TIME	Double	s	EPOCH	Interval midpoint
INTERVAL	Double	s		Time interval
<i>Data description</i>				
NUM_RECEPTORS	Int			# receptors on this feed
<i>Data</i>				
BEAM_ID	Int			Beam model
BEAM_OFFSET	Double(2, NUM_RECEPTORS)	rad	DIRECTION	Beam position offset (on sky but in antenna reference frame).
(FOCUS_LENGTH)	Double	m		Focus length
(PHASED_FEED_ID)	Int			Phased feed
POLARIZATION_TYPE	String (NUM_RECEPTORS)			Type of polarization to which a given RECEPTOR responds.
POL_RESPONSE	Complex (NUM_RECEPTORS, NUM_RECEPTORS)			Feed polzn. response
POSITION	Double(3)	m	POSITION	Position of feed relative to feed reference position for this antenna
RECEPTOR_ANGLE	Double (NUM_RECEPTORS)	rad		The reference angle for polarization.

**Notes:** A feed is a collecting element on an antenna, such as a single horn, that shares joint physical properties and makes sense to calibrate as a single entity. It is an abstraction of a generic antenna feed and is considered to have one or more RECEPTORS that respond to different polarization states. A FEED may have a time-variable beam and polarization response. Feeds are numbered from 0 on each separate antenna for each SPECTRAL\_WINDOW\_ID. Consequently, FEED\_ID should be non-zero only in the case of feed arrays, i.e. multiple, simultaneous beams on the sky at the same frequency and polarization.

**ANTENNA\_ID** Antenna number, as indexed from ANTENNA $n$  in MAIN.

**FEED\_ID** Feed identifier, as indexed from FEED $n$  in MAIN.

**SPECTRAL\_WINDOW\_ID** Spectral window identifier. A value of -1 indicates the row is valid for all spectral windows.

**TIME** Mid-point of time interval for which the feed parameters in this row are valid. The same Measure reference used for the TIME column in MAIN must be used.

**INTERVAL** Time interval.

**NUM\_RECEPTORS** Number of receptors on this feed. See POLARIZATION\_TYPE for further information.

**BEAM\_ID** Beam identifier. Points to an optional BEAM sub-table defining the primary beam and polarization response for this FEED. A value of -1 indicates that no associated beam response is defined.

**BEAM\_OFFSET** Beam position offset, as defined on the sky but in the antenna reference frame.

**FOCUS\_LENGTH** Focus length. As defined along the optical axis of the antenna.

**PHASED\_FEED\_ID** Phased feed identifier. Points to a PHASED\_FEED sub-table which in turn points back to multiple entries in the FEED table, and specifies the manner in which they are combined.

**POLARIZATION\_TYPE** Polarization type to which each receptor responds (e.g. "R", "L", "X" or "Y"). This is the receptor polarization type as recorded in the final correlated data (e.g. "RR"); i.e. as measured after all polarization combiners.

**POL\_RESPONSE** Polarization response at the center of the beam for this feed. Expressed in a linearly polarized basis ( $\vec{e}_x, \vec{e}_y$ ) using the IEEE convention.

**POSITION** Offset of feed relative to the feed reference position for this antenna (see ANTENNA sub-table).

**RECEPTOR\_ANGLE** Polarization reference angle. Converts into parallactic angle in the sky domain.

## 5.9 FIELD: Field positions for each source

FIELD: Field positions for each source				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
FIELD_ID	Int			Field id.
<i>Data</i>				
NAME	String			Name of field
CODE	String			Special characteristics of field
TIME	Double	s	EPOCH	Time origin for the directions and rates
NUM_POLY	Int			Series order
DELAY_DIR	Double(2, NUM_POLY+1)	rad	DIRECTION	Direction of delay center.
PHASE_DIR	Double(2, NUM_POLY+1)	rad	DIRECTION	Phase center.
REFERENCE_DIR	Double(2, NUM_POLY+1)	rad	DIRECTION	Reference center
SOURCE_ID	Int			Index in Source table
(EPHEMERIS_ID)	Int			Ephemeris id.
<i>Flags</i>				
FLAG_ROW	Bool			Row flag

**Notes:** The FIELD table defines a field position on the sky. For interferometers, this is the correlated field position. For single dishes, this is the nominal pointing direction.

**FIELD\_ID** Field id.

**NAME** Field name; user specified.

**CODE** Field code indicating special characteristics of the field; user specified.

**TIME** Time reference for the directions and rates. Required to use the same TIME Measure reference as in MAIN.

**NUM\_POLY** Series order for the \*\_DIR columns.

**DELAY\_DIR** Direction of delay center; can be expressed as a polynomial in time. Final result converted to the defined Direction Measure type.

**PHASE\_DIR** Direction of phase center; can be expressed as a polynomial in time. Final result converted to the defined Direction Measure type.

**REFERENCE\_DIR** Reference center; can be expressed as a polynomial in time. Final result converted to the defined Direction Measure type. Used in single-dish to record the associated reference direction if position-switching has already been applied. For interferometric data, this is the original correlated field center, and may equal DELAY\_DIR or PHASE\_DIR.

**SOURCE\_ID** Points to an entry in the optional SOURCE subtable, a value of  $-1$  indicates there is no corresponding source defined.

**EPHEMERIS\_ID** Points to an entry in the EPHEMERIS sub-table, which defines the ephemeris used to compute the field position. Useful for moving, near-field objects, where the ephemeris may be revised over time.

**FLAG\_ROW** True if data in this row are invalid, else False. Does not imply flagging in MAIN.

## 5.10 FLAG\_CMD: Flag commands

FLAG_CMD: Flag commands				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
TIME	Double	s	EPOCH	Mid-point of interval
INTERVAL	Double	s		Time interval
<i>Data</i>				
TYPE	String			FLAG or UNFLAG
REASON	String			Flag reason
LEVEL	Int			Flag level
SEVERITY	Int			Severity code
APPLIED	Bool			True if applied in MAIN
COMMAND	String			Flag command

**Notes:** The FLAG\_CMD sub-table defines global flagging commands which apply to the data in MAIN, as described in Section 3.1.8.

**TIME** Mid-point of the time interval to which this flagging command applies. Required to use the same TIME Measure reference as used in MAIN.

**INTERVAL** Time interval.

**TYPE** Type of flag command, representing either a flagging ("FLAG") or un-flagging ("UNFLAG") operation.

**REASON** Flag reason; user specified.

**LEVEL** Flag level ( $\geq 0$ ); reflects different revisions of flags which have the same REASON.

**SEVERITY** Severity code for the flag, on a scale of 0-10 in order of increasing severity; user specified.

**APPLIED** True if this flag has been applied to MAIN, and update in FLAG\_CATEGORY and FLAG. False if this flag has not been applied to MAIN.

**COMMAND** Global flag command, expressed in the standard syntax for data selection, as adopted within the project as a whole.

## 5.11 **FREQ\_OFFSET**: Frequency offset information

<b>FREQ_OFFSET: Frequency offset information</b>				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
ANTENNA1	Int			Antenna 1.
ANTENNA2	Int			Antenna 2.
FEED_ID	Int			Feed id.
SPECTRAL_WINDOW_ID	Int			Spectral window id.
TIME	Double	s	EPOCH	Interval midpoint
INTERVAL	Double	s		Time interval
<i>Data</i>				
OFFSET	Double	Hz		Frequency offset

**Notes:** The table contains frequency offset information, to be added directly to the defined frequency labeling in the SPECTRAL\_WINDOW sub-table as a Measure offset. This allows bands with small, time-variable, ad hoc frequency offsets to be labeled as the same SPECTRAL\_WINDOW\_ID, and calibrated together if required.

**ANTENNA $n$**  Antenna identifier, as indexed from ANTENNA $n$  in MAIN.

**FEED\_ID** Antenna identifier, as indexed from FEED $n$  in MAIN.

**SPECTRAL\_WINDOW\_ID** Spectral window identifier.

**TIME** Mid-point of the time interval for which this offset is valid. Required to use the same TIME Measure reference as used in MAIN.

**INTERVAL** Time interval.

**OFFSET** Frequency offset to be added to the frequency axis for this spectral window, as defined in the SPECTRAL\_WINDOW sub-table. Required to have the same Frequency Measure reference as CHAN\_FREQ in that table.

## 5.12 HISTORY: History information

HISTORY: History information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
TIME	Double	s	EPOCH	Time-stamp for message
OBSERVATION_ID	Int			Points to OBSERVATION table
<i>Data</i>				
MESSAGE	String			Log message
PRIORITY	String			Message priority
ORIGIN	String			Code origin
OBJECT_ID	String			Originating ObjectID
APPLICATION	String			Application name
CLI.COMMAND	String(*)			CLI command sequence
APP_PARAMS	String(*)			Application paramters

**Notes:** This sub-table contains associated history information for the MS.

**TIME** Time-stamp for the history record. Required to have the same TIME Measure reference as used in MAIN.

**OBSERVATION\_ID** Observation identifier (see the OBSERVATION table)

**MESSAGE** Log message.

**PRIORITY** Message priority, with allowed types: ("DEBUGGING", "WARN", "NORMAL", or "SEVERE").

**ORIGIN** Source code origin from which message originated.

**OBJECT\_ID** Originating ObjectID, if available, else blank.

**APPLICATION** Application name.

**CLI.COMMAND** CLI command sequence invoking the application.

**APP\_PARAMS** Application parameter values, in the adopted project-wide format.

### 5.13 INTERFEROMETER\_MODEL: VLBI Interferometer information

INTERFEROMETER_MODEL: VLBI Interferometer information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
TIME	Double	s	EPOCH	Time-stamp for message
ANTENNA_ID	Int			Antenna id.
FIELD_ID	Int			field id.
SPECTRAL_WINDOW_ID	Int			Spectral window id.
<i>Data</i>				
PHASE_DELAY	Double( $N_r$ , num_poly)	s		Phase delay polynomial for each receptor
GROUP_DELAY	Double( $N_r$ , num_poly)	s		Group delay polynomial for each receptor
PHASE_RATE	Double( $N_r$ , num_poly)			Rate of change of phase delay
GROUP_RATE	Double( $N_r$ , num_poly)			Rate of change of group delay
DISP_DELAY	Double( $N_r$ , num_poly)	s		Dispersive delay
DISP_DELAY_RATE	Double( $N_r$ , num_poly)			Dispersive delay rate
CLOCK_ERROR	Double( $N_r$ , num_poly)			Clock error as delay polynomial
CLOCK_ERROR_RATE	Double( $N_r$ , num_poly)			Rate of clock error modelled as a delay rate polynomial

**Notes:** This sub-table contains information associated for VLBI

**TIME** Time-stamp as origin for all time based polynomials model.

**FIELD\_ID** Field id, FIELD subtable

**ANTENNA\_ID** antenna id, antenna subtable

**SPECTRAL\_WINDOW\_ID** Spectral window id.

**PHASE\_DELAY** phase delay modelled as a time polynomial for each receptor.

**PHASE\_RATE** rate of change for phase delay .

**GROUP\_DELAY** Group delay.

**GROUP\_RATE** Group delay rate.

**DISP\_DELAY** Dispersive delay

**DISP\_DELAY\_RATE** Dispersive delay rate

**CLOCK\_ERROR**

**CLOCK\_ERROR\_RATE**

## 5.14 OBSERVATION: Observation information

OBSERVATION: Observation information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
OBSERVATION_ID	Int			Observation id.
<i>Data</i>				
TELESCOPE_NAME	String	m	POSITION	Telescope name
ARRAY_CENTER	Double(3)			Reference position for array
TIME_RANGE	Double(2)	s	EPOCH	Start, end times
OBSERVER	String			Name of observer(s)
LOG	String(*)			Observing log
SCHEDULE_TYPE	String			Schedule type
SCHEDULE	String(*)			Project schedule
PROJECT	String			Project identification string.
RELEASE_DATE	Double	s	EPOCH	Target release date
<i>Flags</i>				
FLAG_ROW	Bool			Row flag.

**Notes:** This table contains information specifying the observing instrument or epoch. See the discussion in Section 3.3 for details. It is indexed directly from MAIN via OBSERVATION\_ID.

**OBSERVATION\_ID** Observation id. key

**TELESCOPE\_NAME** Telescope name (e.g. "WSRT" or "VLBA").

**ARRAY\_CENTER** Reference position used by the correlator for e.g.

**TIME\_RANGE** The start and end times of the overall observing period spanned by the actual recorded data in MAIN. Required to use the same TIME Measure reference as in MAIN.

**OBSERVER** The name(s) of the observer(s).

**LOG** The observing log, as supplied by the telescope or instrument.

**SCHEDULE\_TYPE** The schedule type, with current reserved types ("VLBA-CRD", "VEX", "WSRT", "ATNF").

**SCHEDULE** Unmodified schedule file, of the type specified, and as used by the instrument.

**PROJECT** Project code (e.g. "BD46")

**RELEASE\_DATE** Project release date. This is the date on which the data may become public.

**FLAG\_ROW** Row flag. True if data in this row is invalid, but does not imply any flagging in MAIN.



## 5.15 PHASED\_ARRAY: phased array stations information

PHASED_ARRAY: phased array stations information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
PHASED_ARRAY_ID	Int			phased array id.
<i>Data</i>				
ANTENNA	Int( $N_{ant}$ )			List of antenna ids
FEED_ID	Int( $N_{ant}$ )			List of Feed id used on each antenna
DIRECTION	Double	rad	DIRECTION	Direction on sky where phased array has ccen-tered beam
( <i>BEAM_ID</i> )	Int			Beam id.
ELEMENT_FLAG	Bool( $N_{ant}$ )			Flag of elements in array

**Notes:** The table contains information about phased array information. It refers to antenna ids in ANTENNA table, FEED\_ID for feed used in forming this phased array.

**ANTENNA** list Antenna identifier, as indexed from ANTENNA table, that is used to form this array

**FEED\_ID** list of feed for each antenna used in array

**DIRECTION** Direction of beam phased on the sky.

**BEAM\_ID** Beam id as defined in BEAM table.

**ELEMENT\_FLAG** flag for invalid antennas in array not used.

## 5.16 POINTING: Antenna pointing information

POINTING: Antenna pointing information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
ANTENNA_ID	Int			Antenna id.
TIME	Double	s	EPOCH	Interval midpoint
INTERVAL	Double	s		Time interval
<i>Data</i>				
NAME	String			Pointing position desc.
NUM_POLY	Int			Series order
TIME_ORIGIN	Double	s	EPOCH	Origin for the polynomial
DIRECTION	Double(2, NUM_POLY+1)	rad	DIRECTION	Antenna pointing direction
TARGET	Double(2, NUM_POLY+1)	rad	DIRECTION	Target direction
(POINTING_OFFSET)	Double(2, NUM_POLY+1)	rad	DIRECTION	A priori pointing correction
(SOURCE_OFFSET)	Double(2, NUM_POLY+1)	rad	DIRECTION	Offset from source
(ENCODER)	Double(2)	rad	DIRECTION	Encoder values
(POINTING_MODEL_ID)	Int			Pointing model id.
TRACKING	Bool			True if on-position
(ON_SOURCE)	Bool			True if on-source
(OVER_THE_TOP)	Bool			True if over the top

**Notes:** This table contains information concerning the primary pointing direction of each antenna as a function of time. Note that the pointing offsets for individual feeds on a given antenna are specified in the FEED sub-table with respect to this pointing direction.

**ANTENNA\_ID** Antenna identifier, as specified by ANTENNA<sub>n</sub> in MAIN.

**TIME** Mid-point of the time interval for which the information in this row is valid. Required to use the same TIME Measure reference as in MAIN.

**INTERVAL** Time interval.

**NAME** Pointing direction name; user specified.

**NUM\_POLY** Series order for the polynomial expressions in DIRECTION and POINTING\_OFFSET.

**TIME\_ORIGIN** Time origin for the polynomial expansions.

**DIRECTION** Antenna pointing direction, optionally expressed as polynomial coefficients. The final result is interpreted as a Direction Measure using the specified Measure reference.

**TARGET** Target pointing direction, optionally expressed as polynomial coefficients. The final result is interpreted as a Direction Measure using the specified Measure reference. This is the true expected position of the source, including all coordinate corrections such as precession, nutation etc.

**POINTING\_OFFSET** The a priori pointing corrections applied by the telescope in pointing to the DIRECTION position, optionally expressed as polynomial coefficients. The final result is interpreted as a Direction Measure using the specified Measure reference.

**SOURCE\_OFFSET** The commanded offset from the source position, if offset pointing is being used.

**ENCODER** The current encoder values on the primary axes of the mount type for the antenna, expressed as a Direction Measure.

**TRACKING** True if tracking the nominal pointing position.

**ON-SOURCE** True if the nominal pointing direction coincides with the source, i.e. offset-pointing is not being used.

**OVER-THE-TOP** True if the antenna was driven to this position "over the top" (az-el mount).

## 5.17 POLARIZATION: Polarization setup information

POLARIZATION: Polarization setup information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Data description columns</i>				
NUM_CORR	Int			# correlations
<i>Data</i>				
CORR_TYPE	Int(NUM_CORR)			Polarization of correlation
CORR_PRODUCT	Int(2, NUM_CORR)			Receptor cross-products
<i>Flags</i>				
FLAG_ROW	Bool			Row flag

**Notes:** This table defines the polarization labeling of the DATA array in MAIN, and is directly indexed from the DATA\_DESCRIPTION table via POLARIZATION\_ID.

**NUM\_CORR** The number of correlation polarization products. For example, for (RR) this value would be 1, for (RR, LL) it would be 2, and for (XX,YY,XY,YX) it would be 4, etc.

**CORR\_TYPE** An integer for each correlation product indicating the Stokes type as defined in the Stokes class enumeration.

**CORR\_PRODUCT** Pair of integers for each correlation product, specifying the receptors from which the signal originated. The receptor polarization is defined in the POLARIZATION\_TYPE column in the FEED table. An example would be (0,0), (0,1), (1,0), (1,1) to specify all correlations between two receptors.

**FLAG\_ROW** Row flag. True is the data in this row are not valid, but does not imply the flagging of any DATA in MAIN.

## 5.18 PROCESSOR: Processor information

PROCESSOR: Processor information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Data</i>				
TYPE	String			Processor type
SUB_TYPE	String			Processor sub-type
TYPE_ID	Int			Processor type id.
MODE_ID	Int			Processor mode id.
(PASS_ID)	Int			Processor pass number
<i>Flags</i>				
FLAG_ROW	Bool			Row flag

**Notes:** This table holds summary information for the back-end processing device used to generate the basic data in the MAIN table. Such devices include correlators, radiometers, spectrometers, pulsar-timers, amongst others. See Section 4.0.4 for further details.

**TYPE** Processor type; reserved keywords include ("CORRELATOR" - interferometric correlator; "SPECTROMETER" - single-dish correlator; "RADIOMETER" - generic detector/integrator; "PULSAR-TIMER" - pulsar timing device).

**SUB\_TYPE** Processor sub-type, e.g. "GBT" or "JIVE".

**TYPE\_ID** Index used in a specialized sub-table named as *subtype.type*, which contains time-independent processor information applicable to the current data record (e.g. a JIVE-CORRELATOR sub-table). Time-dependent information for each device family is contained in other tables, dependent on the device type.

**MODE\_ID** Index used in a specialized sub-table named as *subtype.type.mode*, containing information on the processor mode applicable to the current data record. (e.g. a GBT-SPECTROMETER.MODE sub-table).

**PASS\_ID** Pass identifier; this is used to distinguish data records produced by multiple passes through the same device, where this is possible (e.g. VLBI correlators). Used as an index into the associated table containing pass information.

**FLAG\_ROW** Row flag. True if data in the row is not valid, but does not imply flagging in MAIN.

## 5.19 SCAN: Scan information

SCAN: Scan information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
SCAN_NUMBER	Int			Scan number id; referred from the Main table
<i>Data</i>				
SCAN_INTENT	String			Fixed set of string defining the intent of the scan
(EXECBLOCK_ID)	Int			Execution block id
(TIME)	Double	s	EPOCH	start time of scan
(INTERVAL)	Double	s		time from beginning from which scan is valid

**Notes:** This sub-table contains associated scan information for the MS.

**SCAN\_NUMBER** Scan number as referred from main table

**SCAN\_INTENT** Intent for the scan (an scan number may have multiple intents). Fixed set of string for a telescope e.g CAL\_POINTING or TARGET

**EXECBLOCK\_ID** A number that is unique to the observation execution block. Used to get more info from the online system of some telescopes.

**TIME** Time of start for that scan

**TIME\_INTERVAL** interval for which this scan is observed from TIME

## 5.20 SOURCE: Source information

SOURCE: Source information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
SOURCE_ID	Int			Source id
TIME	Double	s	EPOCH	Midpoint of time for which this set of parameters is accurate
INTERVAL	Double	s		Interval
SPECTRAL_WINDOW_ID	Int			Spectral Window id
<i>Data description</i>				
NUM_LINES	Int			Number of spectral lines
<i>Data</i>				
NAME	String			Name of source as given during observations
CALIBRATION_GROUP	Int			# grouping for calibration purpose
CODE	String			Special characteristics of source, e.g. Bandpass calibrator
DIRECTION	Double(2)	rad	DIRECTION	Direction (e.g. RA, DEC)
(POSITION)	Double(3)	m	POSITION	Position (e.g. for solar system objects)
PROPER_MOTION	Double(2)	rad/s		Proper motion
(TRANSITION)	String(NUM_LINES)			Transition name
(REST_FREQUENCY)	Double(NUM_LINES)	Hz	FREQUENCY	Line rest frequency
(SYSVEL)	Double(NUM_LINES)	m/s	RADIAL VELOCITY	Systemic velocity at reference
(SOURCE_MODEL)	TableRecord or String			Default csm
(PULSAR_ID)	Int			Pulsar id.

**Notes:** This table contains time-variable source information, optionally associated with a given FIELD\_ID.

**SOURCE\_ID** Source identifier ( $\geq 0$ ), as specified in the FIELD sub-table.

**TIME** Mid-point of the time interval for which the data in this row is valid. Required to use the same TIME Measure reference as in MAIN.

**INTERVAL** Time interval.

**SPECTRAL\_WINDOW\_ID** Spectral window identifier. A -1 indicates that the row is valid for all spectral windows.

**NUM\_LINES** Number of spectral line transitions associated with this source and spectral window id. combination.

**NAME** Source name; user specified.

**CALIBRATION\_GROUP** Calibration group number to which this source belongs; user specified.

**CODE** Source code, used to describe any special characteristics of the source, such as the nature of a calibrator. Reserved keyword, including ("BANDPASS CAL").

**DIRECTION** Source direction at this TIME.

**POSITION** Source position  $(x, y, z)$  at this TIME (for near-field objects).

**PROPER\_MOTION** Source proper motion at this TIME.

**TRANSITION** Transition names applicable for this spectral window (e.g. "v=1, J=1-0, SiO").

**REST\_FREQUENCY** Rest frequencies for the transitions.

**SYSVEL** Systemic velocity for each transition.

**SOURCE\_MODEL** Reference to an assigned component source model table or a URL to access source model

**PULSAR\_ID** An index used in the PULSAR sub-table to define further pulsar-specific properties if the source is a pulsar.



## 5.21 SPECTRAL\_WINDOW: Spectral window description

SPECTRAL_WINDOW: Spectral window description				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
SPECTRAL_WINDOW_ID	Int			Spectral window id
<i>Data description columns</i>				
NUM_CHAN	Int			# spectral channels
<i>Data</i>				
NAME	String			Spectral window name
REF_FREQUENCY	Double	Hz	FREQUENCY	The reference frequency.
CHAN_FREQ	Double(NUM_CHAN)	Hz	FREQUENCY	Center frequencies for each channel in the data matrix.
CHAN_WIDTH	Double(NUM_CHAN)	Hz		Channel width for each channel in the data matrix.
MEAS_FREQ_REF	Int			FREQUENCY Measure ref.
EFFECTIVE_BW	Double(NUM_CHAN)	Hz		The effective noise bandwidth of each spectral channel
RESOLUTION	Double(NUM_CHAN)	Hz		The effective spectral resolution of each channel
TOTAL_BANDWIDTH	Double	Hz		total bandwidth for this window
NET_SIDE BAND	Int			Net sideband
(BBC_NO)	Int			Baseband converter no.
(BBC_SIDE BAND)	Int			BBC sideband
IF_CONV_CHAIN	Int			The IF conversion chain
(RECEIVER_ID)	Int			Receiver id.
(LO_FREQUENCY)	Double			LO frequency
FREQ_GROUP	Int			Frequency group
FREQ_GROUP_NAME	String			Freq. group name
(DOPPLER_ID)	Int			Doppler id.
(ASSOC_SPW_ID)	Int(*)			Associated spw.id.
(ASSOC_NATURE)	String(*)			Nature of association
<i>Flags</i>				
FLAG_ROW	Bool			

**Notes:** This table describes properties for each defined spectral window. A spectral window is both a frequency label for the associated DATA array in MAIN, but also represents a generic frequency conversion chain that shares joint physical properties and makes sense to calibrate as a single entity.

**SPECTRAL\_WINDOW\_ID** spectral window id key.

**NUM\_CHAN** Number of spectral channels.

**NAME** Spectral window name; user specified.

**REF\_FREQUENCY** The reference frequency. A frequency representative of this spectral window, usually the sky

frequency corresponding to the DC edge of the baseband. Used by the calibration system if a fixed scaling frequency is required or in algorithms to identify the observing band.

**CHAN\_FREQ** Center frequencies for each channel in the data matrix. These can be frequency-dependent, to accommodate instruments such as acousto-optical spectrometers. Note that the channel frequencies may be in ascending or descending frequency order.

**CHAN\_WIDTH** Nominal channel width of each spectral channel. Although these can be derived from CHAN\_FREQ by differencing, it is more efficient to keep a separate reference to this information.

**MEAS\_FREQ\_REF** Frequency Measure reference for CHAN\_FREQ. This allows a row-based reference for this column in order to optimize the choice of Measure reference when Doppler tracking is used. Modified only by the MS access code.

**EFFECTIVE\_BW** The effective noise bandwidth of each spectral channel.

**RESOLUTION** The effective spectral resolution of each channel.

**TOTAL\_BANDWIDTH** The total bandwidth for this spectral window.

**NET\_SIDE BAND** The net sideband for this spectral window.

**BBC\_NO** The baseband converter number, if applicable.

**BBC\_SIDE BAND** The baseband converter sideband, is applicable.

**IF\_CONV\_CHAIN** Identification of the electronic signal path for the case of multiple (simultaneous) IFs. (e.g. VLA: AC=0, BD=1, ATCA: Freq1=0, Freq2=1)

**RECEIVER\_ID** Index used to identify the receiver associated with the spectral window. Further state information is planned to be stored in a RECEIVER sub-table.

**LO\_FREQUENCY** LO frequency used for this spectral window

**FREQ\_GROUP** The frequency group to which the spectral window belongs. This is used to associate spectral windows for joint calibration purposes.

**FREQ\_GROUP\_NAME** The frequency group name; user specified.

**DOPPLER\_ID** The Doppler identifier defining frame information for this spectral window.

**ASSOC\_SPW\_ID** Associated spectral windows, which are related in some fashion (e.g. "channel-zero").

**ASSOC\_NATURE** Nature of the association for ASSOC\_SPW\_ID; reserved keywords are ("CHANNEL-ZERO" - channel zero; "EQUAL-FREQUENCY" - same frequency labels; "SUBSET" - narrow-band subset).

**FLAG\_ROW** True if the row does not contain valid data.

## 5.22 STATE: State information

STATE: State information				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
STATE_ID	Int			State id key
<i>Data</i>				
SIG	Bool			Signal
REF	Bool			Reference
CAL	Double	K		Noise calibration
LOAD	Double	K		Load temperature
SUB_SCAN	Int			Sub-scan number
OBS_MODE	String			Observing mode
<i>Flags</i>				
FLAG_ROW	Bool			Row flag

**Notes:** This table defines the state parameters for a particular data record as they refer to external loads, calibration sources or references, and also characterizes the observing mode of the data record, as an aid to defining the scheduling heuristics. It is indexed directly via STATE\_ID in MAIN.

**SIG** True if the source signal is being observed.

**REF** True for a reference phase.

**CAL** Noise calibration temperature (zero if not added).

**LOAD** Load temperature (zero if no load).

**SUB\_SCAN** Sub-scan number ( $\geq 0$ ), relative to the SCAN\_NUMBER in MAIN. Used to identify observing sequences.

**OBS\_MODE** Observing mode; defined by a set of reserved keywords characterizing the current observing mode (e.g. "OFF-SPECTRUM"). Used to define the schedule strategy.

**FLAG\_ROW** True if the row does not contain valid data. Does not imply flagging in MAIN.

### 5.23 SYSCAL: System calibration

SYSCAL: System calibration				
Name	Format	Units	Measure	Comments
<b>Columns</b>				
<i>Key</i>				
ANTENNA_ID	Int			Antenna id
FEED_ID	Int			Feed id
SPECTRAL_WINDOW_ID	Int			Spectral window id
TIME	Double	s	EPOCH	Midpoint of time for which this set of parameters is accurate
INTERVAL	Double	s		Interval
<i>Data</i>				
(PHASE_DIFF)	Float	rad		Phase difference between receptor 0 and receptor 1
(TCAL)	Float ( $N_r$ )	K		Calibration temp
(TRX)	Float ( $N_r$ )	K		Receiver temperature
(TSKY)	Float ( $N_r$ )	K		Sky temperature
(TSYS)	Float ( $N_r$ )	K		System temp
(TANT)	Float ( $N_r$ )	K		Antenna temperature
(TANT_TSYS)	Float ( $N_r$ )			$\frac{T_{ant}}{T_{sys}}$
(TCAL_SPECTRUM)	Float ( $N_r, N_f$ )	K		Calibration temp
(TRX_SPECTRUM)	Float ( $N_r, N_f$ )	K		Receiver temperature
(TSKY_SPECTRUM)	Float ( $N_r, N_f$ )	K		Sky temperature spectrum
(TSYS_SPECTRUM)	Float ( $N_r, N_f$ )	K		System temp
(TANT_SPECTRUM)	Float ( $N_r, N_f$ )	K		Antenna temperature spectrum
(TANT_TSYS_SPECTRUM)	Float ( $N_r, N_f$ )			$\frac{T_{ant}}{T_{sys}}$ spectrum
<i>Flags</i>				
(PHASE_DIFF_FLAG)	Bool			Flag for PHASE_DIFF
(TCAL_FLAG)	Bool			Flag for TCAL
(TRX_FLAG)	Bool			Flag for TRX
(TSKY_FLAG)	Bool			Flag for TSKY
(TSYS_FLAG)	Bool			Flag for TSYS
(TANT_FLAG)	Bool			Flag for TANT
(TANT_TSYS_FLAG)	Bool			Flag for $\frac{T_{ant}}{T_{sys}}$

**Notes:** This table contains time-variable calibration measurements for each antenna, as indexed on feed and spectral window. Note that  $N_r$ = number of receptors, and  $N_f$ = number of frequency channels.

**ANTENNA\_ID** Antenna identifier, as indexed by ANTENNA $n$  in MAIN.

**FEED\_ID** Feed identifier, as indexed by FEED $n$  in MAIN.

**SPECTRAL\_WINDOW\_ID** Spectral window identifier.

**TIME** Mid-point of the time interval for which the data in this row are valid. Required to use the same TIME Measure reference as that in MAIN.

**INTERVAL** Time interval.

**PHASE\_DIFF** Phase difference between receptor 0 and receptor 1.

**TCAL** Calibration temperature.

**TRX** Receiver temperature.

**TSKY** Sky temperature.

**TSYS** System temperature.

**TANT** Antenna temperature.

**TANT\_TSYS** Antenna temperature over system temperature.

**TCAL\_SPECTRUM** Calibration temperature spectrum.

**TRX\_SPECTRUM** Receiver temperature spectrum.

**TSKY\_SPECTRUM** Sky temperature spectrum.

**TSYS\_SPECTRUM** System temperature spectrum.

**TANT\_SPECTRUM** Antenna temperature spectrum.

**TANT\_TSYS\_SPECTRUM** Antenna temperature over system temperature spectrum.

**PHASE\_DIFF\_FLAG** True if PHASE\_DIFF flagged.

**TCAL\_FLAG** True if TCAL flagged.

**TRX\_FLAG** True if TRX flagged.

**TSKY\_FLAG** True if TSKY flagged.

**TSYS\_FLAG** True if TSYS flagged.

**TANT\_FLAG** True if TANT flagged.

**TANT\_TSYS\_FLAG** True if TANT\_TSYS flagged.

## 5.24 WEATHER: weather station information

WEATHER: weather station information				
Name	Format	Units	Measure	Comments
Columns				
Key				
ANTENNA_ID	Int		EPOCH	Antenna number
TIME	Double	s		Mid-point of interval
INTERVAL	Double	s		Interval over which data is relevant
Data				
(H2O)	Float	$m^{-2}$		Average column density of water
(IONOS_ELECTRON)	Float	$m^{-2}$		Average column density of electrons
(PRESSURE)	Float	hPa		Ambient atmospheric pressure
(REL_HUMIDITY)	Float			Ambient relative humidity
(TEMPERATURE)	Float	K		Ambient air temperature for an antenna
(DEW_POINT)	Float	K		Dew point
(WIND_DIRECTION)	Float	rad		Average wind direction
(WIND_SPEED)	Float	m/s		Average wind speed
Flags				
(H2O_FLAG)	Bool			Flag for H2O
(IONOS_ELECTRON_FLAG)	Bool			Flag for IONOS.ELECTRON
(PRESSURE_FLAG)	Bool			Flag for PRESSURE
(REL_HUMIDITY_FLAG)	Bool			Flag for REL.HUMIDITY
(TEMPERATURE_FLAG)	Bool			Flag for TEMPERA-TURE
(DEW_POINT_FLAG)	Bool			Flag for DEW_POINT
(WIND_DIRECTION_FLAG)	Bool			Flag for WIND.DIRECTION
(WIND_SPEED_FLAG)	Bool			Flag for WIND.SPEED

**Notes:** This table contains mean external atmosphere and weather information.

**ANTENNA\_ID** Antenna identifier, as indexed by ANTENNA $n$  from MAIN.

**TIME** Mid-point of the time interval over which the data in the row are valid. Required to use the same TIME Measure reference as in MAIN.

**INTERVAL** Time interval.

**H2O** Average column density of water.

**IONOS.ELECTRON** Average column density of electrons.

**PRESSURE** Ambient atmospheric pressure.

**REL\_HUMIDITY** Ambient relative humidity.

**TEMPERATURE** Ambient air temperature.  
**DEW\_POINT** Dew point temperature.  
**WIND\_DIRECTION** Average wind direction.  
**WIND\_SPEED** Average wind speed.  
**H2O\_FLAG** Flag for H2O.  
**IONOS\_ELECTRON\_FLAG** Flag for IONOS\_ELECTRON.  
**PRESSURE\_FLAG** Flag for PRESSURE.  
**REL\_HUMIDITY\_FLAG** Flag for REL\_HUMIDITY.  
**TEMPERATURE\_FLAG** Flag for TEMPERATURE.  
**DEW\_POINT\_FLAG** Flag for DEW\_POINT.  
**WIND\_DIRECTION\_FLAG** Flag for DEW\_POINT.  
**WIND\_SPEED\_FLAG** Flag for DEW\_POINT.

## 6 References

Kemball, A.J., Wieringa, M.H., 2000, casacore Note 229.