

tolerance

March 29, 2025

This file is part of CasADi.

CasADi -- A symbolic framework for dynamic optimization.
Copyright (C) 2010–2023 Joel Andersson, Joris Gillis, Moritz Diehl,
KU Leuven. All rights reserved.
Copyright (C) 2011–2014 Greg Horn

CasADi is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 3 of the License, or (at your option) any later version.

CasADi is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with CasADi; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

1 Integrator tolerances

```
[1]: from casadi import *  
    from numpy import *  
    from pylab import *  
  
[2]: x= SX.sym('x')  
    dx= SX.sym('dx')  
    states = vertcat(x,dx)  
  
[3]: dae={'x':states, 'ode':vertcat(dx,-x)}  
  
[4]: tend = 2*pi*3  
    ts = linspace(0,tend,1000)  
  
[5]: tolerances = [-10,-5,-4,-3,-2,-1]
```

```
[6]: figure()
```

```
[6]: <Figure size 640x480 with 0 Axes>
```

```
<Figure size 640x480 with 0 Axes>
```

```
[7]: for tol in tolerances:
      opts = {'reltol':10.0**tol, 'abstol':10.0**tol, 'grid':ts, 'output_t0':True}
      F = integrator('F', 'cvodes', dae, opts)
      res = F(x0=[1,0])
      plot(ts,array(res['xf'])[0,:].T,label='tol = 1e%d' % tol)
      legend( loc='upper left')
      xlabel('Time [s]')
      ylabel('State x [-]')
      show()
```

CasADi - 2025-03-29 19:15:15 WARNING("The options 't0', 'tf', 'grid' and 'output_t0' have been deprecated.


The same functionality is provided by providing additional input arguments to the 'integrator' function, in particular:

- * Call integrator(..., t0, tf, options) for a single output time, or
- * Call integrator(..., t0, grid, options) for multiple grid points.

The legacy 'output_t0' option can be emulated by including or excluding 't0' in 'grid'.

Backwards compatibility is provided in this release only.")

[.../casadi/core/integrator.cpp:692]



```
[8]: tolerances = logspace(-15,1,500)
     endresult=[]
```

```
[9]: for tol in tolerances:
     opts = {}
     opts['reltol'] = tol
     opts['abstol'] = tol
     opts['tf'] = tend
     F = integrator('F', 'cvodes', dae, opts)
     res = F(x0=[1,0])
     endresult.append(res['xf'][0])
```

```
[10]: endresult = vcat(endresult)
```

```
[11]: figure()
     loglog(tolerances,(array(endresult)-1),'b',label='Positive error')
     loglog(tolerances,-(array(endresult)-1),'r',label='Negative error')
     xlabel('Integrator relative tolerance')
     ylabel('Error at the end of integration time')
     legend(loc='upper left')
     show()
```

