veccat

October 26, 2026

This file is part of CasADi.

CasADi -- A symbolic framework for dynamic optimization.
Copyright (C) 2010-2023 Joel Andersson, Joris Gillis, Moritz Diehl,
                        KU Leuven. All rights reserved.
Copyright (C) 2011-2014 Greg Horn

CasADi is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 3 of the License, or (at your option) any later version.

CasADi is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with CasADi; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

1 veccat

[1]:
```
import casadi as ca
from numpy import *
```

[2]:
```
A = ca.MX.sym("A",2)           # Here a matrix
B = ca.MX.sym("B",2,1)         # There a matrix
C = ca.MX.sym("C")             # And an other little matrix
D = ca.MX.sym("D",ca.Sparsity.lower(4))  # Triangular matrix
```

[3]:
```
L = ca.veccat(A,B,C,D)
print(L)
```

```
vertcat(A, B, C, vec(D))
```