KinsolSolver

October 26, 2026


```
This file is part of CasADi.

CasADi -- A symbolic framework for dynamic optimization.
Copyright (C) 2010-2023 Joel Andersson, Joris Gillis, Moritz Diehl,
                        KU Leuven. All rights reserved.
Copyright (C) 2011-2014 Greg Horn

CasADi is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 3 of the License, or (at your option) any later version.

CasADi is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with CasADi; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA
```


1 KinsolSolver

[1]:
```
import casadi as ca
from numpy import *
from pylab import *
```

We will investigate the working of rootfinder with the help of the parametrically exited Duffing equation.

$\ddot{u} + \dot{u} - \epsilon(2\mu\dot{u} + \alpha u^3 + 2ku\cos(\Omega t))$ with $\Omega = 2 + \epsilon\sigma$. \

The first order solution is $u(t) = a\cos(\frac{1}{2}\Omega t - \frac{1}{2}\gamma)$ with the modulation equations: \ $\frac{da}{d\epsilon t} = -\left[\mu a + \frac{1}{2}ka\sin\gamma\right]$ \ $a\frac{d\gamma}{d\epsilon t} = -\left[-\sigma a + \frac{3}{4}\alpha a^3 + ka\cos\gamma\right]$ \

We seek the stationair solution to these modulation equations.

Parameters

[2]:
```
eps   = ca.SX.sym("eps")
mu    = ca.SX.sym("mu")
alpha = ca.SX.sym("alpha")
k     = ca.SX.sym("k")
sigma = ca.SX.sym("sigma")
params = [eps,mu,alpha,k,sigma]
```

Variables

[3]:
```
a     = ca.SX.sym("a")
gamma = ca.SX.sym("gamma")
```

Equations

[4]:
```
res0 = mu*a+1.0/2*k*a*sin(gamma)
res1 = -sigma * a + 3.0/4*alpha*a**3+k*a*cos(gamma)
```

```
/casadi_python/casadi/casadi.py:913: FutureWarning:
casadi: a numpy function was called on a casadi value (issue #2959).
This used legacy casadi 3.7.2 behaviour, where the result type follows
the input:
  - a numeric input (DM)       -> a plain numpy array
  - a symbolic input (SX / MX) -> a casadi value, or an error if the
                                  function has no casadi equivalent

For a shape-correct, type-preserving result, opt in to the
casadi-aware numpy support:

    try:
        ca.GlobalOptions.setNumpyMode(1)
    except AttributeError:
        pass

Or use setNumpyMode(-1) to keep legacy behaviour silently.
Shown once; run python with -W always to see every occurrence.

  _w.warn(_NUMPY_LEGACY_NOTICE, FutureWarning)
```

Numerical values

[5]:
```
sigma_ = 0.1
alpha_ = 0.1
k_     = 0.2
params_ = [0.1,0.1,alpha_,k_,sigma_]
```

We create a Function instance

[6]:
```
f=ca.Function("f", [ca.vertcat(a,gamma),ca.vertcat(*params)],[ca.
↪vertcat(res0,res1)])
```

```
opts = {}
opts["strategy"] = "linesearch"
opts["abstol"] = 1e-14
```

Require $a > 0$ and $\gamma < 0$

[7]:
```
opts["constraints"] = [2,-2]
s=ca.rootfinder("s", "kinsol", f, opts)
```

Initialize $[a,\gamma]$ with a guess and solve

[8]:
```
x_ = s([1,-1], params_)
print("Solution = ", x_)
```

```
Solution =  [1.1547, -1.5708]
```

Compare with the analytic solution:

[9]:
```
x = [sqrt(4.0/3*sigma_/alpha_),-0.5*pi]
print("Reference solution = ", x)
```

```
Reference solution =  [1.1547005383792515, -1.5707963267948966]
```

We show that the residual is indeed (close to) zero

[10]:
```
residual = f(x_, params_)
print("residual = ", residual)
```

```
residual =  [4.16334e-15, 8.34363e-15]
```

[11]:
```
for i in range(1):
  assert(abs(x_[i]-x[i])<1e-6)
```

Solver statistics

[12]:
```
print(s.stats())
```

```
{'n_call_jac_g_x': 0, 'return_status': 'KIN_SUCCESS', 'success': True,
't_proc_jac_g_x': 0.0, 't_wall_jac_g_x': 0.0, 'unified_return_status':
'SOLVER_RET_UNKNOWN'}
```