

assertion

August 22, 2026

This file is part of CasADi.

CasADi -- A symbolic framework for dynamic optimization.
Copyright (C) 2010-2023 Joel Andersson, Joris Gillis, Moritz Diehl,
KU Leuven. All rights reserved.
Copyright (C) 2011-2014 Greg Horn

CasADi is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 3 of the License, or (at your option) any later version.

CasADi is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with CasADi; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

```
[1]: import casadi as ca
```

CasADi provides a mechanism to add assertions in an MX expression graph. This can be useful to debug your code, e.g. debugging why the end-result of a computation yields NaN.

Consider this example:

```
[2]: x = ca.MX.sym("x")  
     y = ca.sin(x)  
     z = ca.sqrt(y)
```

```
[3]: f = ca.Function("f", [x], [z])
```

```
[4]: z0 = f(5)
```

```
[5]: print(z0)
```

-nan

For some mysterious reason we get NaN here

Next, we add an assertion:

```
[6]: y = y.attachAssert(y>0, "bummer") # Add assertion here
     z = ca.sqrt(y)
```

```
[7]: f = ca.Function("f", [x],[z])
```

```
[8]: try:
     z0 = f(5)
     except Exception as e:
         print("An exception was raised here:")
         print(e)
```

An exception was raised here:

Error in Function::call for 'f' [MXFunction] at

.../casadi/core/function.cpp:514:

.../casadi/core/assertion.cpp:71: Assertion error: bummer

You can combine this with Callback to do powerful assertions

```
[9]: class Dummy(ca.Callback):
     def __init__(self, name, opts={}):
         ca.Callback.__init__(self)
         self.construct(name, opts)
     def get_n_in(self): return 1
     def get_n_out(self): return 1
     def eval(self, arg):
         import numpy
         x = arg[0]
         m = max(numpy.real(numpy.linalg.eig(ca.blockcat([[x,-1],[-1,2]]))[0]))
         print("m=",m)
         return [int(m>2)]
```

```
[10]: foo = Dummy("foo")
```

```
[11]: y = ca.sin(x)
```

```
[12]: y = y.attachAssert(foo(y), "you are in trouble") # Add assertion here
     z = ca.sqrt(y)
```

```
[13]: f = ca.Function("f", [x],[z])
```

```
[14]: z0 = f(5)
```

m= 2.3062613059254473

/casadi_python/casadi/casadi.py:913: FutureWarning:

casadi: a numpy function was called on a casadi value (issue #2959).

This used legacy casadi 3.7.2 behaviour, where the result type follows the input:

- a numeric input (DM) -> a plain numpy array
- a symbolic input (SX / MX) -> a casadi value, or an error if the function has no casadi equivalent

For a shape-correct, type-preserving result, opt in to the casadi-aware numpy support:

```
try:
    ca.GlobalOptions.setNumpyMode(1)
except AttributeError:
    pass
```

Or use `setNumpyMode(-1)` to keep legacy behaviour silently.
Shown once; run python with `-W always` to see every occurrence.

```
_w.warn(_NUMPY_LEGACY_NOTICE, FutureWarning)
```