



Overview

CasWAF is an open-source Web Application Firewall (WAF) software developed by Go and React.

CasWAF features

1. Front-end and back-end separate architecture, developed by Golang, CasWAF provides web-based managing UI and supports multiple languages(Chinese, English).
2. Databases. CasWAF supports mainstream databases: MySQL, PostgreSQL, SQL Server, etc.
3. Casdoor SSO. CasWAF uses [Casdoor](#) as the Identity Provider (IdP) for OAuth login.
4. Reverse proxy. CasWAF supports reverse proxy, which can be used as a reverse proxy server to protect the backend server.
5. OAuth proxy. CasWAF supports OAuth login, which can be integrated with the existing OAuth system such as [Casdoor](#).

How it works

CasWAF has both reverse proxy and OAuth proxy functionalities. If you haven't configured OAuth for your website, it will function solely as a reverse proxy server.

Reverse proxy

CasWAF appears externally as a reverse proxy server, providing an additional layer of security for your web servers and applications.

It sits between the users and web servers, acting as an intermediary, receiving requests from users, and forwarding them to the target web servers.

OAuth proxy

CasWAF OAuth proxy acts as an Identity Provider (IdP) and collaborates with your application to perform authentication and authorization through the OAuth protocol.

When a user attempts to access a resource that requires authentication, CasWAF will redirect the user to the real Identity Provider (IdP).

Subsequently, the OAuth proxy will guide the user to the configured Identity Provider (e.g., Google, Facebook, or an internal authentication service within the company) for authentication.

In CasWAF, we use [Casdoor](#) as the Identity Provider (IdP). More information of Casdoor SSO can be found [here](#).

Online Demo

Here is an online demo:

- Deployed site: <https://waf.casbin.com/>

Global admin login:

- Username: `admin`
- Password: `123`

Architecture

Caswaf contains 2 parts:

Name	Description	Language	Source code
Frontend	Web frontend UI for CasWAF	Javascript + React	https://github.com/casbin/caswaf/tree/master/web
Backend	RESTful API backend for CAsWAF	Golang + Beego + MySQL	https://github.com/casbin/caswaf

[The Basics](#)[Core Concepts](#)

Core Concepts

As CasWAF's administrator, you should get familiar with at least 2 core concepts:

[Site](#), [Cert](#).

Site

In CasWAF, [Site](#) is representing the real applications or websites you wish to protect. Each Site is associated with specific domain names or IP addresses, and you can configure multiple Sites according to different needs to ensure comprehensive security protection for all your applications.

The Site class definition is shown as follows:

```
type Site struct {
    Owner      string `xorm:"varchar(100) notnull pk"
    json:"owner"`
    Name       string `xorm:"varchar(100) notnull pk" json:"name"`
    CreatedTime string `xorm:"varchar(100)" json:"createdTime"`
    DisplayName string `xorm:"varchar(100)" json:"displayName"`

    Domain     string `xorm:"varchar(100)" json:"domain"`
    Host       string `xorm:"varchar(100)" json:"host"`
    SslMode    string `xorm:"varchar(100)" json:"sslMode"`
    SslCert    string `xorm:"varchar(100)" json:"sslCert"`
    PublicIp   string `xorm:"varchar(100)" json:"publicIp"`
    Node       string `xorm:"varchar(100)" json:"node"`
    IsSelf     bool   `json:"isSelf"`

    CasdoorApplication string `xorm:"varchar(100)"`
}
```

Cert

In CasWAF, `Cert` is representing the certificates used for HTTPS authentication. By configuring `Cert`, CasWAF can establish secure encrypted connections between itself and the clients, ensuring the confidentiality and integrity of data and preventing information leakage and tampering attacks.

The `Cert` class definition is shown as follows:

```
type Cert struct {
    Owner      string `xorm:"varchar(100) notnull pk"
    json:"owner"`
    Name       string `xorm:"varchar(100) notnull pk" json:"name"`
    CreatedTime string `xorm:"varchar(100)" json:"createdTime"`
    DisplayName string `xorm:"varchar(100)" json:"displayName"`

    Type       string `xorm:"varchar(100)" json:"type"`
    CryptoAlgorithm string `xorm:"varchar(100)"
    json:"cryptoAlgorithm"`
    ExpireTime  string `xorm:"varchar(100)" json:"expireTime"`

    Certificate string `xorm:"mediumtext" json:"certificate"`
    PrivateKey  string `xorm:"mediumtext" json:"privateKey"`
}
```

Installation

CasWAF uses Casdoor to manage members. So you need to create an organization and an application for CasWAF in a Casdoor instance.

Requirements

OS

All major operating systems including Windows, Linux and macOS are supported.

Environments

- [Go 1.17+](#)
- [Node.js LTS \(16 or 14\)](#)
- [Yarn 1.x](#)

ⓘ 信息

We strongly suggest you use [Yarn 1.x](#) to run & build CasWAF frontend, using NPM might cause UI styling issues, see more details at: [casdoor#294](#)

⚠ 警告

For Chinese users, in order to download the Go dependency packages successfully, you need to use a Go proxy by Configuring the GOPROXY environment variable. We strongly recommend: <https://goproxy.cn/>

Download

The source code of CasWAF is hosted at GitHub: <https://github.com/casbin/caswaf>. Both the Go backend code and React frontend code are inside the single repository.

Name	Description	Language	Source code
Frontend	Web frontend UI for CasWAF	Javascript + React	https://github.com/casbin/caswaf/tree/master/web
Backend	RESTful API backend for CAsWAF	Golang + Beego + MySQL	https://github.com/casbin/caswaf

CasWAF supports Go Modules. To download the code, you can just simply clone the code both via `go get` and `git`:

```
go get github.com/casbin/casdoor
go get github.com/casbin/caswaf
```

or

```
git clone https://github.com/casbin/casdoor
git clone https://github.com/casbin/caswaf
```

Necessary configuration

Set up database

CasWAF will store its users, nodes and topics information in a MySQL database named: `caswaf`. CasWAF will create it if not existed. The DB connection string can be specified at: <https://github.com/casbin/caswaf/blob/master/conf/app.conf>

```
dataSourceName = root:123@tcp(localhost:3306)/
```

CasWAF uses XORM to connect to DB, so all DBs supported by XORM can also be used.

Configure Casdoor

After creating an organization and an application for CasWAF in a Casdoor, you need to update `clientId`, `clientSecret`, `casdoorOrganization` and `casdoorApplication` in `app.conf`.

More details about Casdoor configuration can be found at: [casdoor-ssso](#)

Run CasWAF

- Build backend of CasWAF
 - `go build github.com/casbin/caswaf`
- Build frontend of CasWAF
 - `yarn start`
- Now you can visit CasWAF configuration website at:
 - `http://localhost:16001/`

Optional configuration

Set up your WAF to enable some third-party login platform

CasWAF uses Casdoor to manage members. If you want to log in with oauth, you should see [casdoor oauth configuration](#).

OSS, Mail, and SMS services

CasWAF uses Casdoor to upload files to cloud storage, send Emails and send SMSs. See Casdoor for more details.



The Basics



Casdoor SSO

Casdoor SSO

Introduction


Casdoor is a UI-first centralized authentication / Single-Sign-On (SSO) platform based on OAuth 2.0 / OIDC. It provides OAuth 2.0 / OIDC based signup and login, as well as third-party login including GitHub, Google, QQ, WeChat, etc. CasWAF uses Casdoor as an SSO provider to manage users and permissions.

Login to CasWAF

CasWAF supports logging in with Casdoor. You need to register CasWAF as a Casdoor application first.

About how to register CasWAF as a Casdoor application, please refer to [Casdoor documentation](#).

After registering CasWAF as a Casdoor application, you can log in to CasWAF with Casdoor.



After logging in, you can manage the site and certificate according to the instructions provided in the [Sites documentation](#) and [Cert documentation](#).

Home Sites Certs ...									admin Admin ▾
Sites Add									
Name ▾	Display name ▾	Domain ▾	Host ▾	Public IP ▾	Node ▾	SSL mode ▾	SSL cert ▾	Casdoor app ▾	Action
site_y9wchu	New Site - y9wchu	door.casdoor.com	http://localhost:8000	8.131.81.162		HTTP			Edit Delete
< 1 >									

! TODO

add content



Sites

Sites



Site List

Learn how to configure your site in CasWAF.



Sites



Site List

Site List

`Site` is representing the real applications or websites you wish to protect.

This section will provide a detailed explanation of the properties and usage of `Site`.

Site properties


- `Name`: The name of the site.
- `DisplayName`: The display name of the site.
- `Domain`: The domain of the site.
 - e.g. `blog.example.com`
- `Host`: The host of the site.
 - e.g. `localhost:8080`
- `Public IP (Optional)`: The public IP of the site (if available).
- `Node (Optional)`: The name of the host on which the site is deployed.
- `SSL mode`: The SSL mode of the site. It can be `HTTP` or `HTTPS` and `HTTP` or `HTTPS Only`.
 - `HTTP`: The site is not using SSL. Users can access the site **only** via HTTP.
 - `HTTPS and HTTP`: The site is using SSL and HTTP. Users can access the site via **both** HTTP and HTTPS.
 - `HTTPS only`: The site is using SSL only. Users can access the site **only** via HTTPS. If users access the site via HTTP, they will be redirected to HTTPS.
- `SSL cert`: The SSL certificate of the site. User can select the SSL certificate

from the dropdown list.

- About how to add SSL certificate, please refer to [SSL Certificates](#).
- **Casdoor app**: If your site needs OAuth login, you can select the Casdoor app from the dropdown list.
 - CasWAF uses Casdoor as the OAuth server. So you need to register your site as a Casdoor app first.
 - About how to add Casdoor app, please refer to [Casdoor SSO](#).

Usage

Manage sites




[Home](#)

[Sites](#)

[Certs](#)

[...](#)




Admin

▼


Sites

Add

Name	Display name	Domain	Host	Public IP	Node	SSL mode	SSL cert	Casdoor app	Action
<div><div></div><div>No Data</div></div>									

In the Sites page, you will see all sites you have created. You can create, edit, delete and view the site details. But now we don't have any sites.

Add a site


casbin

[Home](#)[Sites](#)[Certs](#)[...](#)

Site added successfully

Admin

SitesAdd

Name	Display name	Domain	Host	Public IP	Node	SSL mode	SSL cert	Casdoor app	Action
site_y9wchu	New Site - y9wchu	door.casdoor.com	http://localhost:8000			HTTP			<div>EditDelete</div>

<

1

>

Just click the **Add** button, you will create a site. The created Site will have some default information that you can modify.

Edit site

After you create a site, you can click the **edit** button to edit the site.



The screenshot shows a web interface for editing a site. At the top, there is a header bar with the text "Edit Site" and a purple "Save" button. Below this, the form contains several input fields and dropdown menus, each with a label on the left and a value in the input area. The fields are: "Name" (site_y9wchu), "Display name" (New Site - y9wchu), "Domain" (door.casdoor.com), "Host" (http://localhost:8000), "Public IP" (8.131.81.162), "Node" (empty), "SSL mode" (HTTP), "SSL cert" (empty), and "Casdoor app" (empty). Each of the last four fields has a small downward arrow on the right side, indicating they are dropdown menus. At the bottom left of the form, there is a purple "Save" button.

Each field's meaning is as described above, and you can freely modify them according to the actual situation of your website.

After you have completed the modifications, you only need to click the **Save** button to save your settings.



Certs

Certs



Cert List

Learn how to add your server's certificates in CasWAF.

Cert List


If your website supports HTTPS access, you need to configure an SSL certificate in CasWAF to enable it to establish a secure connection with your server as a reverse proxy.

This section will provide a detailed explanation of the properties and usage of `Cert`.

Cert properties

- `Name`: The name of the certificate.
- `Display name`: The display name of the certificate.
- `Type`: The type of the certificate. This field is usually set to `SSL` since SSL is the most commonly used option.
- `Crypto algorithm`: The crypto algorithm of the certificate. It can be set to `RSA` or `ECC` which is depend on algorithm your certificate used.
- `Expire time`: The expire time of the certificate. This field will be automatically filled in when you set certificate and private key.
- `Certificate`: The certificate content.
 - The certificate is a public key that has been authenticated by a Certificate Authority (CA).
- `Private key`: The private key content.
 - The private key is a secret key that is used to encrypt and decrypt data.

Manage Certificates




The screenshot shows the 'casbin' application interface. The top navigation bar includes 'Home', 'Sites', 'Certs', and an 'Admin' dropdown. The 'Certs' page is active, displaying a table with columns: Name, Create time, Display name, Type, Crypto algorithm, Expire time, Certificate, Private key, and Action. The table is currently empty, with a 'No Data' message and a folder icon in the center.

Name	Create time	Display name	Type	Crypto algorithm	Expire time	Certificate	Private key	Action
No Data								

In the Certs page, you will see all certs you have created. You can create, edit, delete and view the cert details. But now we don't have any certs.

Add a cert



The screenshot shows the 'casbin' application interface after a new certificate has been added. A green notification bubble at the top center says 'Cert added successfully'. The table now contains one row with the following data: Name: cert_gnb6pe, Create time: 2023-08-06 21:03:47, Display name: New Cert - gnb6pe, Type: SSL, Crypto algorithm: RSA, Expire time: (empty), Certificate: (empty), Private key: (empty), and Action: Edit, Delete. The 'Add' button is highlighted in the top left of the table.

Name	Create time	Display name	Type	Crypto algorithm	Expire time	Certificate	Private key	Action
cert_gnb6pe	2023-08-06 21:03:47	New Cert - gnb6pe	SSL	RSA				Edit Delete

Just click the **Add** button, you will create a cert. The created cert will have some default information that you can modify.

Edit cert

After you create a site, you can click the **edit** button to edit the site.

The screenshot shows a web form titled "Edit Cert" with a "Save" button. The form contains the following fields and controls:

- Name:** A text input field containing "cert_gnb6pe".
- Display name:** A text input field containing "New Cert - gnb6pe".
- Type:** A dropdown menu with "SSL" selected.
- Crypto algorithm:** A dropdown menu with "RSA" selected.
- Expire time:** A date and time picker field.
- Certificate:** A section with a "Copy certificate" button and a "Download certificate" button. Below these buttons is a large, empty rectangular box for the certificate content.
- Private key:** A section with a "Copy private key" button and a "Download private key" button. Below these buttons is a large, empty rectangular box for the private key content.

Each field's meaning is as described above, and you can freely modify them according to the actual situation of your website.

After you have completed the modifications, you only need to click the **Save** button to save your settings.