

CAWT: COM Automation With Tcl

1	INTRODUCTION.....	2
1.1	Architecture overview.....	2
1.2	Dependencies.....	3
1.3	Installation and Usage.....	4
2	PACKAGES IN DETAIL.....	5
2.1	CawtCore: Basic automation functionality	5
2.2	CawtEarth: Automation for Google Earth	5
2.3	CawtExcel: Automation for Microsoft Excel	5
2.3.1	Module excelCsv.....	6
2.3.2	Module excelTablelist.....	7
2.3.3	Module excelMatlabFile.....	7
2.3.4	Module excelWord.....	7
2.3.5	Module excelImgRaw	8
2.3.6	Module excelMediaWiki	8
2.3.7	Module excelWikit	8
2.4	CawtExplorer: Automation for Internet Explorer	9
2.5	CawtMatlab: Automation for MathWorks Matlab.....	9
2.6	CawtOcr: Automation for Microsoft Document Imaging.....	9
2.7	CawtOutlook: Automation for Microsoft Outlook.....	9
2.8	CawtPpt: Automation for Microsoft PowerPoint.....	10
2.9	CawtWord: Automation for Microsoft Word	10
3	MISCELLANEOUS CAWT INFORMATION.....	11
3.1	License information.....	11
3.2	Known bugs	11
4	TEST PROGRAMS	12
4.1	Test overview.....	12
4.2	Test execution	13
5	INSIDE CAWT	15
6	RELEASE HISTORY	16

1 Introduction

CAWT is a high-level Tcl interface for scripting Microsoft Windows® applications having a COM interface. It uses **Twapi** for automation via the COM interface.

Currently packages for Microsoft Excel, Word, PowerPoint, Outlook and Internet Explorer, MathWorks Matlab and Google Earth are available.

CAWT sources are available at <https://sourceforge.net/projects/cawt/>.

The CAWT homepage is at <http://www.poSoft.de/html/extCawt.html>

The CAWT user distribution contains the Tcl sources, documentation (this document and a reference manual), several test programs showing the use of the CAWT functionality and the needed external libraries Twapi, TkImag, Base64 and Tablelist (see chapter 1.2 for details). The CAWT developer distribution additionally contains scripts for generating the documentation, the distribution packages and the CAWT Starkit. It also includes the external packages Ruff! and textutil (see chapter 1.2 for details). The developer distribution is intended for programmers who want to extend the CAWT package.

1.1 Architecture overview

The **CAWT** package currently consists of the following sub-packages:

CawtCore	Basic automation functionality.
CawtEarth	Automation functionality for Google Earth.
CawtExcel	Automation functionality for Microsoft Excel.
CawtExplorer	Automation functionality for Microsoft Internet Explorer.
CawtMatlab	Automation functionality for MathWorks Matlab.
CawtOcr	Automation functionality for Microsoft Document Imaging.
CawtOutlook	Automation functionality for Microsoft Outlook.
CawtPpt	Automation functionality for Microsoft PowerPoint.
CawtWord	Automation functionality for Microsoft Word.

Each sub-package is implemented as a separate Tcl package and can be loaded explicitly with the Tcl package command, ex. `package require cawtexcel`. All available CAWT sub-packages can be loaded with a single command: `package require cawt`.

Note: Package names are all lower case.

The next figure shows the architecture of the CAWT package.




Figure 1: Overview of CAWT packages

1.2 Dependencies

The following table shows a list of the external Tcl packages used in the CAWT infrastructure.

Lib	Version	Comment	URL
Libraries needed for the CAWT package			
Twapi	>= 4.0	Mandatory: Included in CAWT user distribution.	http://twapi.magicsplat.com/
Tkimg	>= 1.4.1	Optional: Included in CAWT user distribution.	http://sourceforge.net/projects/tkimg/ http://www.poSoft.de/html/extTkimg.html
Base64		Optional: Included in CAWT user distribution.	http://sourceforge.net/projects/tcllib/
Tablelist	>= 4	Optional: Included in CAWT user distribution.	http://www.nemethi.de
Libraries needed for generating the CAWT documentation			
Ruff!	0.4	Included in CAWT developer distribution.	http://woof.magicsplat.com/ruff_home
Tcllib		Ruff! needs the textutil module from Tcllib. (textutil included in CAWT developer distribution)	http://sourceforge.net/projects/tcllib/

Note:

Twapi: It is recommended to use the official Twapi version 4.0.61.

Tkimg: Needed only for some functionalities (see the CawtExcel package for further details).

Base64: Needed for photo image to clipboard functionality.

Tablelist: Needed only for the excelTablelist module.

1.3 Installation and Usage

Installation of **CAWT** is simple and fast.

If you just want to play with the test programs to get an impression on how CAWT works, unzip the user distribution file in a folder of your choice. Then open a shell window, go to folder *TestPrograms* of the CAWT distribution and execute a test program with a line as follows:

```
> tclsh Excel-01_Basic.tcl
```

See also chapter 4 for scripts to run all or groups of test programs in batch mode.

If you want to use CAWT as a package for your own applications, the *Cawt* folder should be copied into the library section of your Tcl installation (ex. *C:\Tcl\lib*). If write access to this Tcl directory is not permitted, you can copy the *Cawt* directory somewhere else, eg. *C:\myCawt*. To have Tcl look for packages in this location, you must set the `TCLLIBPATH` environment variable with the above specified directory name as value. Note, that on Windows the path must be written with slashes (not backslashes):

```
> set TCLLIBPATH = C:/myCawt.
```

If suitable versions of **Twapi**, **Tkimg**, **Base64** or **Tablelist** are already available on your machine, you may remove the appropriate folders from the *Externals* subfolder. Otherwise you should move these packages into the same folder, where you have copied *Cawt* to.

2 Packages in Detail

This chapter explains the different packages of CAWT.

For a detailed description of the available procedures in the different sub-packages see the CAWT reference manual available at the CAWT homepage or in the distribution.

2.1 CawtCore: Basic automation functionality

The procedures of package **CawtCore** are implemented in namespace `Cawt`.

They provide functionality for the following domains:

Domain	Examples
Package information	<code>HavePkg</code> , <code>GetPkgVersion</code>
Conversion functionality	<code>CentiMetersToPoints</code> , <code>RgbToColor</code> , <code>TclBool</code>
COM access via Twapi	<code>GetOrCreateApp</code> , <code>IsValidId</code> , <code>Destroy</code>
Common Office functionality	<code>GetApplicationName</code>
Testing utilities	<code>CheckString</code> , <code>CheckNumber</code> , <code>CheckMatrix</code>
Image utilities	<code>ClipboardToImg</code> , <code>ImgToClipboard</code>

2.2 CawtEarth: Automation for Google Earth

The procedures of package **CawtEarth** are implemented in namespace `Earth`.

The name of the controlled application is `GoogleEarth.ApplicationGE`.

They provide functionality for the following domains:

Domain	Examples
Application handling	<code>Open</code> , <code>Quit</code>
Camera positioning	<code>SetCamera</code>

See the test programs `Earth-*.tcl` for examples on how to use the procedures of this package.

2.3 CawtExcel: Automation for Microsoft Excel

The procedures of package **CawtExcel** are implemented in namespace `Excel`.

The name of the controlled application is `Excel.Application`.

They provide functionality for the following domains:

Domain	Examples
Application handling	<code>Open</code> , <code>Quit</code> , <code>GetVersion</code>
Workbook handling	<code>OpenWorkbook</code> , <code>AddWorkbook</code> , <code>SaveAs</code> , <code>Close</code>
Worksheet handling	<code>AddWorksheet</code> , <code>DeleteWorksheet</code> , <code>CopyWorksheet</code>
Chart handling	<code>ChartObjToClipboard</code> , <code>CreateChart</code> , <code>AddLineChart</code>
Insert values	<code>SetCellValue</code> , <code>SetRowValues</code> , <code>SetMatrixValues</code>
Retrieve values	<code>GetCellValue</code> , <code>GetRowValues</code> , <code>GetMatrixValues</code>
Formatting functionality	<code>SetColumnWidth</code> , <code>SetHyperlink</code> , <code>SetRangeTextColor</code>
Clipboard functionality	<code>ClipboardToMatrix</code> , <code>ClipboardToWorksheet</code>
External file handling	<code>Csv</code> , <code>Raw Images</code> , <code>MediaWiki</code> , <code>Wikit</code> , <code>Matlab files</code>

External table tools handling	Tablelist, Word tables
-------------------------------	------------------------

The commands are grouped and implemented in the following modules:

Implementation file	Description
excelConst.tcl	All Excel enumeration types.
excelBasic.tcl	Basic Excel commands.
excelUtil.tcl	Higher-level utility commands.
excelChart.tcl	Higher-level commands for chart creation.
excelCsv.tcl	Commands for reading/writing CSV files.
excelTablelist.tcl	Exchange Excel data with Tablelist.
excelMatlabFile.tcl	Exchange Excel data with Matlab MAT-Files. Level 4 files only.
excelWord.tcl	Exchange Excel data with Word tables.
excelImgRaw.tcl	Exchange Excel data with Tk photo images. 1-channel floating-point RAW files only.
excelMediaWiki.tcl	Exchange Excel data with MediaWiki tables.
excelWikit.tcl	Exchange Excel data with Wikit tables.

See the following URL's for details on table file formats:

Matlab: http://www.mathworks.com/help/pdf_doc/matlab/matfile_format.pdf

Raw images: <http://docs.activestate.com/activetcl/8.5/img/doc/img-raw.html>

MediaWiki: <https://meta.wikimedia.org/wiki/Help:Table>

Wikit: <http://wiki.tcl.tk/14>

See the test programs *Excel-*.tcl* for examples on how to use the procedures of this package.

The next chapters explain the Excel modules dealing with data exchange.

2.3.1 Module excelCsv




Figure 2: Module excelCsv

2.3.2 Module excelTablelist




Figure 3: Module excelTablelist

2.3.3 Module excelMatlabFile




Figure 4: Module excelMatlabFile

2.3.4 Module excelWord




Figure 5: Module excelWord

2.3.5 Module excellmgRaw




Figure 6: Module excellmgRaw

2.3.6 Module excelMediaWiki




Figure 7: Module excelMediaWiki

2.3.7 Module excelWikiti




Figure 8: Module excelWikiti

2.4 CawtExplorer: Automation for Internet Explorer

The procedures of package **CawtExplorer** are implemented in namespace `Explorer`.
The name of the controlled application is `InternetExplorer.Application`.

They provide functionality for the following domains:

Domain	Examples
Application handling	Open, Quit
URL navigation	Navigate, GoBack, GoHome

See the test programs `Explorer-*.tcl` for examples on how to use the procedures of this package.

Note: If running on Windows Vista or 7, you have to lower the security settings like follows:

```
Internet Options -> Security -> Trusted Sites      : Low
Internet Options -> Security -> Internet          : Medium + unchecked Enable Protected Mode
Internet Options -> Security -> Restricted Sites  : unchecked Enable Protected Mode
```

2.5 CawtMatlab: Automation for MathWorks Matlab

The procedures of package **CawtMatlab** are implemented in namespace `Matlab`.
The name of the controlled application is `Matlab.Application`.

They provide functionality for the following domains:

Domain	Examples
Application handling	Open, Quit
Command execution	ExecCmd

See the test programs `Matlab-*.tcl` for examples on how to use the procedures of this package.

2.6 CawtOcr: Automation for Microsoft Document Imaging

The procedures of package **CawtOcr** are implemented in namespace `Ocr`.
The name of the controlled application is `MODI.Document`.

They provide functionality for the following domains:

Domain	Examples
Application handling	Open, Close
Character recognition	Scan, GetFullText, GetWord, GetWordStatistics

See the test programs `Ocr-*.tcl` for examples on how to use the procedures of this package.

2.7 CawtOutlook: Automation for Microsoft Outlook

The procedures of package **CawtOutlook** are implemented in namespace `Outlook`.
The name of the controlled application is `Outlook.Application`.

They provide functionality for the following domains:

Domain	Examples
Application handling	Open, Quit, GetVersion
Mail handling	CreateMail, SendMail

See the test programs *Outlook-*.tcl* for examples on how to use the procedures of this package.

2.8 CawtPpt: Automation for Microsoft PowerPoint

The procedures of package **CawtPpt** are implemented in namespace `Ppt`.
The name of the controlled application is `PowerPoint.Application`.

They provide functionality for the following domains:

Domain	Examples
Application handling	Open, Quit, GetVersion
Presentation handling	OpenPres, AddPres, SaveAs, Close
Slide handling	AddSlide, CopySlide, ShowSlide, ExportSlide
SlideShow handling	UseSlideShow, SlideShowFirst, SlideShowNext
Custom layout handling	GetNumCustomLayouts, GetCustomLayoutName

See the test programs *Ppt-*.tcl* for examples on how to use the procedures of this package.

2.9 CawtWord: Automation for Microsoft Word

The procedures of package **CawtWord** are implemented in namespace `Word`.
The name of the controlled application is `Word.Application`.

They provide functionality for the following domains:

Domain	Examples
Application handling	Open, Quit, GetVersion
Document handling	OpenDocument, AddDocument, SaveAs, Close
Table handling	AddTable, GetNumRows, SetCellValue, GetCellValue
Text handling	AddParagraph, AppendText, AddText
Range handling	GetStartRange, GetRangeStartIndex, ExtendRange
Search/Replace functionality	FindString, ReplaceString, ReplaceByProc
Formatting functionality	SetRangeFontBold, SetRangeBackgroundColor

See the test programs *Word-*.tcl* for examples on how to use the procedures of this package.

3 Miscellaneous CAWT information

This chapter contains miscellaneous information about **CAWT**.

3.1 License information

The CAWT package is copyrighted by Paul Obermeier and distributed under the BSD license. CAWT relies on several other Tcl packages. See the table in chapter 1.2 for links to these packages to get their license information.

3.2 Known bugs

There is an issue in CawtExcel with the differing floating-point separators used in languages like German, where the comma is the character used as the “decimal point”.

4 Test programs

4.1 Test overview

The following test and demonstration programs are currently available:

Test Program	Description
Earth-01_Basic.tcl	Test basic functionality of the CawtEarth package.
Earth-02_MunichTour.tcl	Load position information into an Excel sheet, read back that information and create a Tk GUI with buttons corresponding to these positions. Clicking onto one of these buttons triggers Google Earth to fly to that position.
Excel-01_Basic.tcl	Test basic functionality of the CawtExcel package.
Excel-02_Misc.tcl	Test miscellaneous CawtExcel procedures like setting colors, fonts and column width, inserting formulas and images, searching and page setup.
Excel-03_Add.tcl	Test CawtExcel procedures for adding and deleting workbooks and worksheets.
Excel-04_Insert.tcl	Test CawtExcel procedures for inserting data as rows, columns or matrices.
Excel-05_Ranges.tcl	Test CawtExcel procedures for retrieving the number of (used) rows and columns.
Excel-06_Chart.tcl	Test CawtExcel procedures for creating charts and exporting charts as Tk photo images.
Excel-07_Csv.tcl	Test CawtExcel procedures related to CSV files.
Excel-08_Tablelist.tcl	Test CawtExcel procedures to exchange data between Excel and Tablelist.
Excel-09_WordTable.tcl	Test CawtExcel procedures to exchange data between Excel and Word tables.
Excel-10_Matrix.tcl	Test CawtExcel procedures to read data into a matrix and write matrix data into Matlab or RAW image files.
Excel-11_RawImage.tcl	Test CawtExcel procedures to exchange data between Excel and RAW photo images.
Excel-12_MatlabFile.tcl	Test CawtExcel procedures to exchange data between Excel and Matlab files.
Excel-13_MediaWiki.tcl	Test CawtExcel procedures to exchange data between Excel and MediaWiki tables.
Excel-14_Wikit.tcl	Test CawtExcel procedures to exchange data between Excel and Wikit tables.
Excel-15_Clipboard.tcl	Test CawtExcel procedures to exchange data between Excel and the Windows clipboard.
Excel-16_SetGet.tcl	Test CawtExcel procedures for setting and getting cell values.
Excel-17_Diff.tcl	Test CawtExcel procedure for diff'ing Excel files.
Excel-18_SparseMatrix.tcl	Test CawtExcel procedures for handling sparse matrices.
Excel-19_MarkLink.tcl	Test CawtExcel procedures related to marking and linking cells.
Excel-20_ImgUtil.tcl	Test CawtExcel procedures for dealing with images.
Explorer-01_Basic.tcl	Test basic functionality of the CawtExplorer package.
Explorer-02_Misc.tcl	Test miscellaneous CawtExplorer functions like navigating to an URL and using fullscreen mode.
Matlab-01_Basic.tcl	Test basic functionality of the CawtMatlab package.

Matlab-02_MFile.tcl	Test CawtMatlab procedures for executing Matlab commands.
Ocr-01_Basic.tcl	Test basic functionality of the CawtOcr package.
Ocr-02_Misc.tcl	Test miscellaneous CawtOcr procedures.
Outlook-01_Basic.tcl	Test basic functionality of the CawtOutlook package.
Outlook-02_Mail.tcl	Test mail functionality of the CawtOutlook package.
Ppt-01_Basic.tcl	Test basic functionality of the CawtPpt package.
Ppt-02_Misc.tcl	Test miscellaneous CawtPpt procedures like adding slides, inserting images and saving slides as image files.
Ppt-03_Add.tcl	Test CawtPpt procedures for adding and copying slides.
Ppt-04_Present.tcl	Test CawtPpt procedures for presenting a slide show.
Ppt-05_Export.tcl	Test CawtPpt procedures for exporting a PowerPoint presentation as HTML slide show.
Ppt-06_CustomLayout.tcl	Test CawtPpt procedures for using PowerPoint custom layouts.
Word-01_Basic.tcl	Test basic functionality of the CawtWord package.
Word-02_Table.tcl	Test CawtWord procedures related to Word table management.
Word-03_Text.tcl	Test CawtWord procedures for handling text.
Word-04_Find.tcl	Test CawtWord procedures related to search and replace functionality.
Word-05_Report.tcl	Test CawtWord procedures needed for generating a test report. It is assumed that the test data is read from an external data sink (ex. file), there are images to be inserted that are in a format Word does not know about, and a summary should be printed at the first page.

Table 1: Test Programs

The CAWT sub-packages have been tested successfully with the above mentioned programs on the following operating systems and COM application versions:

Package	Operating system	Application version
CawtEarth	Windows XP, Windows 7, Windows 8	6.2, 7.1.2
CawtExcel	Windows XP, Windows 7, Windows 8	2003, 2007, 2010, 2013
CawtExplorer	Windows XP, Windows 7, Windows 8 (*)	IE 8, IE 9, IE 11
CawtMatlab	Windows XP	R2007b
CawtOcr	Windows XP, Windows 7, Windows 8	2003, 2007, 2010, 2013
CawtOutlook	Windows 7, Windows 8	2010, 2013
CawtPpt	Windows XP, Windows 7, Windows 8	2003, 2007, 2010, 2013
CawtWord	Windows XP, Windows 7, Windows 8	2003, 2007, 2010, 2013

(*) See chapter 2.4 for known issues with Internet Explorer on Windows 7 and 8.

4.2 Test execution

To execute a single test program, execute it with the Tcl shell:

```
> tclsh Excel-02_Misc.tcl
```

To execute all test programs of a sub-package, use the utility script `RunTest.tcl`:

```
> tclsh RunTest.tcl Excel
```

To execute all test programs of CAWT, use the batch program `RunTests.bat`:

```
> RunTests.bat
```

Each test program accepts an optional string parameter. If this parameter is set to `auto`, the test program closes and quits the controlled application. If this parameter is not set, the controlled application stays open, so the results can be viewed directly in the application window.

The `RunTest.tcl` utility script, calls all test programs available for a sub-package by specifying the corresponding namespace name. The test programs are called with the above mentioned `auto` parameter. Additionally the script can be supplied with optional parameters to switch off either the tests or to switch off the code coverage checks.

If called without any parameters, the script issues a help message onto standard output.

```
Usage: RunTest.tcl [Options] Namespace [Namespace]
```

Run the test programs and code coverage checks for specified namespace(s).

Namespaces usable: Excel Ppt Word Outlook Ocr Earth Matlab Explorer.

Use "all" as namespace name to run tests and checks for all namespaces.

Options:

- help : Display this usage message and exit.
- verbose: Show the detailed results of the tests. (Default: No)
- notests: Do not run the tests. (Default: Run tests)
- nocover: Do not run the coverage checks. (Default: Run coverage)

5 Inside CAWT

The information in this chapter is for programmers, who want to extend and improve CAWT.

Download the developer distribution from the CAWT homepage. This distribution contains in addition to the user distribution the documentation source files (a Word and a PowerPoint file), the **Ruff!** and **textutil** packages for generating the reference documentation out of the Tcl sources, as well as some additional utility scripts.

Create or update Office enumeration values

The files containing the enumeration values of the Office applications Excel (*excelConst.tcl*), PowerPoint (*pptConst.tcl*), Word (*wordConst.tcl*) and Outlook (*outlookConst.tcl*) are automatically generated with script *createConstFile.tcl*.

The enumeration values of the current CAWT distribution are based on Microsoft Office 2013. If you have a newer Office version and want to update the enumeration files, execute the batch program *createConstFiles.bat*, which is located at the root directory of CAWT. Before calling the batch program, you should edit it to fit the locations of your Office programs. Note also, that the enumeration files are created in the CAWT root directory, so you have to copy them into the appropriate sub-folders by hand (but check and compare the differences to the existing files first).

Create or update CAWT documentation

The CAWT documentation comes in 2 parts, the user manual and a reference manual.

The reference manual is created with the help of the **Ruff!** package from inline documentation. So, if adding new procedures to the CAWT files, be sure to also update the inline documentation.

The sources of the user manual are a Word template document and a PowerPoint presentation located in folder *Documents/UserManual*.

The final documentation is created by Tcl script *genCawtDoc.tcl*, which creates the reference manual by calling Ruff!, and the user manual by exporting the slides of the presentation and inserting them into the Word template document. The final documents are then written into folder *Documents/Final*.

If specifying the strings *ref* or *user* as command line parameter for script *genCawtDoc.tcl*, only the reference manual resp. the user manual is generated.

Create a CAWT distribution

To create a distribution (both user and developer) call Tcl script *makeDist.tcl*.

Note, that you should have updated the documentation before creating a distribution.

The location of the distribution output files and the program to create ZIP files are listed at the top of file *makeDist.tcl*, and must be adapted to your local situation.

6 Release history

The following table gives an overview of the release history of **CAWT** and it's predecessors **TcomOffice** and **TcomExcel**.

Version	Date	Release notes
TcomExcel		
0.1	2008-09-11	Initial release. Support for Excel 2000 and 2003.
0.2	2009-09-19	Extended functionality. Added support for Excel 2007.
0.3	2010-10-29	Bug fixes and extended test programs.
0.3.1	2011-01-13	Extended functionality. Added support for Excel 2010.
0.3.2	2011-04-05	Extended functionality.
TcomOffice		
0.4.0	2011-07-17	New module TcomWord for Word automation.
0.4.1	2011-08-28	Extended functionality.
CAWT		
1.0.0	2012-12-23	Replaced Tcom with Twapi for COM access. Added support for PowerPoint, Internet Explorer, Google Earth and Matlab. Added user and reference manual. Unification of procedure names. Supports Microsoft Office versions 2003, 2007, 2010.
1.0.1	2013-04-28	Extended Excel chart generation. Updated Twapi version to 4.0a16. Added support to generate a CAWT starkit.
1.0.2	2013-07-28	Updated Twapi version to 4.0b22. Updated Img version to 1.4.1. Added new module CawtOcr. New procedures in CawtCore: <ul style="list-style-type: none"> Clipboard2Img, Img2Clipboard New procedures in CawtExcel: <ul style="list-style-type: none"> SetRangeBorder
1.0.3	2013-08-30	New procedures in CawtExcel: <ul style="list-style-type: none"> ExcelFileToMediaWikiFile, ExcelFileToWikiFile ExcelFileToRawImageFile, RawImageFileToExcelFile ExcelFileToMatlabFile, MatlabFileToExcelFile GetTablelistValues, SetTablelistValues
1.0.4	2013-11-23	Improved test suite. Added support for Office 2013. Added support for 64-bit Office. Updated Img extension to version 1.4.2 (32-bit and 64-bit). Update Tablelist to version 5.10. New procedures in CawtWord: <ul style="list-style-type: none"> SaveAsPdf UpdateFields CropImage. New procedures in CawtExcel: <ul style="list-style-type: none"> CopyWorksheetBefore, CopyWorksheetAfter GetWorksheetIndexByName IsWorksheetProtected, IsWorksheetVisible SetWorksheetTabColor UnhideWorksheet

		<ul style="list-style-type: none"> • DiffExcelFiles
1.0.5	2014-01-26	<p>New procedures in CawtExcel:</p> <ul style="list-style-type: none"> • SetCommentDisplayMode, SetRangeComment • SetRangeMergeCells, GetRangeCharacters • SetRangeFontSubscript, SetRangeFontSuperscript
1.0.6	2014-04-21	<p>Improved and extended test suite. Updated Twapi version to 4.0b53 to fix a bug with sparse matrices as well as core dumps with Word 2013. Improved and corrected handling of sparse matrices in Excel. Bug fix in excelCsv module. Possible incompatibility in GetRowValues and GetColumnValues: Changed startRow resp. startCol to default value 0 instead of 1. New procedures in CawtExcel:</p> <ul style="list-style-type: none"> • GetWorksheetAsMatrix • GetMaxRows, GetMaxColumns • GetFirstUsedRow, GetLastUsedRow • GetFirstUsedColumn, GetLastUsedColumn
1.0.7	2014-06-14	<p>Updated Twapi version to official 4.0.61. CawtExcel:</p> <ul style="list-style-type: none"> • Added support for reading and writing CSV files with multi-line cells. <p>CawtPpt:</p> <ul style="list-style-type: none"> • Extended CopySlide to copy slides between presentations. • Extended AddPres with optional parameter for template file. • Extended AddSlide to supply a custom layout object as type parameter. <p>Extended test suite for changed and new procedures. New procedures in CawtCore:</p> <ul style="list-style-type: none"> • ColorToRgb <p>New procedures in CawtExcel:</p> <ul style="list-style-type: none"> • UseImgTransparency, WorksheetToImg, ImgToWorksheet • SetRowHeight, SetRowsHeight • GetRangeFillColor • SetHyperlinkToFile, SetHyperlinkToCell, SetLinkToCell • SetRangeTooltip <p>New procedures in CawtPpt:</p> <ul style="list-style-type: none"> • MoveSlide, • GetTemplateExtString • GetNumCustomLayouts • GetCustomLayoutName, GetCustomLayoutId
1.1.0	2014-08-30	<p>Compatibility issue:</p> <ul style="list-style-type: none"> • Incompatible changes in module CawtWord. • Unified signatures of AddText, AppendText and AddParagraph, AppendParagraph. • Changed handling of text ranges. <p>New module CawtOutlook to control Microsoft Outlook applications:</p> <ul style="list-style-type: none"> • Currently only functionality for creating and sending mails is implemented. <p>Extended test suite for changed and new procedures. New procedures in CawtExcel:</p> <ul style="list-style-type: none"> • FreezePanels, ScreenUpdate <p>New procedures in CawtWord:</p> <ul style="list-style-type: none"> • SelectRange, GetRangeInformation, CreateRange • SetRangeFontName, SetRangeStyle, SetRangeFontSize • InsertText, AddText, GetNumCharacters

		<ul style="list-style-type: none">• AddPageBreak, ToggleSpellCheck
--	--	--