

(1) REQ'D

Part # 12213

Features

- 100 percent cast-iron cylinders and frame
- Belt-driven for quiet operation — 80 dBA
- Heavy-duty ergonomic handle for operator comfort
- Semi-pneumatic tires for easy portability
- Easily accessible side drain valve
- 20-gallon ASME, National Board-coded receiver tank includes discharge-mounted check valve, pressure gauge, drain valve, service valve, and relief valve
- Automatic Start / Stop pressure switch control with manual on / off lever
- Manual thermal overload motor protection — no starter required
- Enclosed belt guard shields flywheel, belt, and motor sheave for extra protection
- Splash lubrication
- All units are prewired and thoroughly tested before shipment
- Meets OSHA standards
- Compliant with UL / CSA / ASME standards



Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialized equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service.

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein.

Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

air.irco.com

*****Risk of Electrical Shock*****

It is advised never to use the compressor outdoors in the rain or on a wet surface.

CAN BE ANCHORED TO THE FLOOR

Specifications

Model #	P1.5IU-A9
Horsepower – hp (kW)	2 (1.5)
Tank size – gal (L)	20 (75.7)
Capacity @ 90 psi / 135 psi (cfm)	5.2 / 4.6
Maximum pressure – psi (bar)	135 (9.3)
Height – in (cm)	43 (109.2)
Width – in (cm)	23 (58.4)
Depth – in (cm)	22 (55.9)
Net weight – lb (kg)	200 (90.7)
Voltage	115 / 1 / 60
Total package amps	15

IR Ingersoll Rand
Industrial Technologies

© 2008 Ingersoll-Rand Company IRITS-1108-126