

DOMINION™ BUTTERFLY VALVES NYLON COATED BODY AND DISC

BODY

- Cast aluminum, semi-lug body with flange lug drilling to meet most ANSI 125/150 specifications.
- RILSAN® Nylon 11 coated.
- 2" minimum neck length clearance.

STEM AND DISC

- Through-stem direct drive design requiring no disc screws or pins to connect stem to disc with no possible leak paths in disc stem connections.
- Stem mechanically retained in body neck with corrosion-resistant 304 stainless steel retainer ring.
- Spherically machined, hand-polished disc edge and hub for minimum torque and maximum sealing capability.
- No part of the stem shall be exposed to line media.

SEAT

- Tongue-and-groove seat design with primary hub flat seal and a molded o-ring suitable for weld-neck and slip-on flanges.
- Seat totally encapsulates the body with no flange gaskets required.
- Seat should be interchangeable with all other valve styles of manufacturer.

STEM SEAL AND BUSHING

- Equipped with fixed stem seal and non-corrosive nylon-6 bushings.

PRESSURE RATINGS

- All valves must be factory tested for bubble-tight shutoff to 110% of it's pressure rating.
- All valves must be rated bi-directionally to the full pressure rating specified.

MATERIAL SPECIFICATIONS

- **BODY:** RILSAN® - Nylon 11 coated cast aluminum – ASTM B179S12C/DIN 1706AC44100 (2"-12" SIZES)
RILSAN® - Nylon 11 coated ductile iron – ASTM A395M:88/DIN ENJS 1020 EN1563 (14"-16" SIZES)
- **DISC:** RILSAN® - Nylon 11 coated ductile iron – ASTM A395M:88/DIN ENJS1020EN1563
- **STEM:** 420 SS – AISI grade 420
- **SEAT:** EPDM