

3 phases

VLT* AQUA Drive			T2 200-240 V				T4 380-480 V				T6 525-600 V				T7 525-690 V		
FC 200	kW		IP 20	IP 21	IP 55	IP 66	IP 20	IP 21	IP 55	IP 66	IP 20	IP 21	IP 55	IP 66	IP 20	IP 21	IP 55
	HO	NO															
PK2S	0.25																
PK37	0.37																
PK5S	0.55																
PK7S	0.75		A2	A2	A4/A5	A4/A5	A2	A2	A4/A5	A4/A5	A3	A3	A5	A5	A3		
P1K1	1.1																
P1K5	1.5																
P2K2	2.2																
P3K0	3.0		A3	A3	A5	A5											
P3K7	3.7																
P4K0	4.0						A2	A2	A4/A5	A4/A5							
P5K5	3.7	5.5					A3	A3	A5	A5	A3	A3	A5	A5	A3		
P7K5	5.5	7.5	B3	B1	B1	B1											
P11K	7.5	11															
P15K	11	15	B4	B2	B2	B2	B3	B1	B1	B1	B3	B1	B1	B1			
P18K	15	18.5															
P22K	18.5	22	C3	C1	C1	C1											
P30K	22	30					B4	B2	B2	B2	B4	B2	B2	B2	B4	B2	B2
P37K	30	37															
P45K	37	45	C4	C2	C2	C2											
P55K	45	55					C3	C1	C1	C1	C3	C1	C1	C1	C3	C2	C2
P75K	55	75															
P90K	75	90					C4	C2	C2	C2	C4	C2	C2	C2			

1 phase

VLT* AQUA Drive			S2 200-240 V				S4 380-480 V		
FC 200	kW		IP 20	IP 21	IP 55	IP 66	IP 21	IP 55	IP 66
P1K1	1.1		A3		A5	A5			
P1K5	1.5								
P2K2	2.2								
P3K0	3.0			B1	B1	B1			
P3K7	3.7								
P5K5	5.5								
P7K5	7.5			B2	B2	B2	B1	B1	B1
P11K	11						B2	B2	B2
P15K	15			C1	C1	C1			
P18K	18.5						C1	C1	C1
P22K	22			C2	C2	C2			
P37K	37						C2	C2	C2

- IP20/Chassis
- IP21/Type 1
- IP21 with upgrade kit
– available in North America only
- IP55/Type 12
- IP66/NEMA 4X

(-) 1000-xxxx VFD xxx/xxxV _ph -HP REQ'D

Frame Sizing Chart

NEMA 12/IP55 NEMA 4X/IP66 Enclosure Size	Height		Width		Depth		200-240V = HP	380-480V = HP	575V = HP
	In	mm	In	mm	In	mm			
A5	16.6	420	9.6	242	7.9	200	0.5-5	0.5-5, 7.5 & 10	1-5, 7.5 & 10
B1	18.9	480	9.6	242	10.3	260	7.5, 10 & 15	15, 20 & 25	15, 20 & 25
B2	25.6	650	9.6	242	10.3	260	20	30 & 40	30 & 40
C1	26.8	680	12.2	308	12.3	310	25, 30 & 40	50, 60 & 75	50, 60 & 75
C2	30.4	770	14.6	370	13.2	335	50 & 60	100 & 125	100 & 125