

VACUUM TRANSFER SYSTEM (VTS)

Item: Vacuum Transfer Unit

Type: Utility

Tank Size: 5 gal.

Tank (Gal.): 5

Peak HP: 5.0

Amps AC: 8.5

Voltage: 120

Hz: 60

Sealed Pressure (PSI): 56

CFM @ 2.5-In Orifice: 112

Tank Orifice (In.): 2.5

Tank Type: Poly

Hose Dimensions: 1 7/8" x 20 ft.

Depth (In.): 7.5

Width (In.): 12.0

Height (In.): 18.0

Filter: Cartridge Filter and Foam Sleeve

Replacement Filter: 551171103

Power Cord Length (Ft.): 20 ft

Agency Compliance: cULus

VTS Remote Receptacle: One UL approved VWM510 receptacle 120V is included along with a Carlon weatherproof "T" box and an in-use Intermatic WP1010MC lockable receptacle cover. The Vacuum Transfer Unit's mounting bracket is factory connected to the Defender® and pre-drilled to accept the remote receptacle assembly, which the VT unit plugs into. Onsite field installations include homerun power feed to the receptacle and connection from the receptacle to the Defender's RMF panel. Remote receptacle configuration can be referenced on the FP-1 schematic page. The assembly's component specifications can be referenced in the subsequent submittal pages.

NOTE: Your Defender® Filter and most of its accessories are acceptable for unprotected installations exposed to the elements. The vacuum transfer system and the compressor require supplementary covers to protect these units from the elements if installed in an unenclosed environment. Neptune Benson recommends a minimum enclosure of an open shelter with a roof to provide protection from direct exposure to rain and snow