docs/references/automation/catzc-base-reports.md

`Catzc.Base.Reports`

Owns the one output shape every quality gate shares: a report written under the output root, the issues printed, and a single verdict — a throw listing every issue, or a result object under `-PassThru` (see test-automation, the quality-gate rule). A gate collects its issues and hands them here last, so no gate writes its own report or invents its own message. It deliberately does **not** decide what a gate checks — that stays with each gate's module.

Responsibilities

Responsibility	Area	Name
responsibility:1	report	Quality-gate reporting
responsibility:2	settings	Report settings

responsibility:1 — Quality-gate reporting

Ending a quality gate the same way every time: a stamped run folder with a markdown report naming the gate, its facts, and every issue; a file beside the stamped folders naming the latest run; each issue and the count printed, then the report path; and one verdict — a throw that lists every issue (fail fast, aggregated), or the result object when the caller asks for it.

responsibility:2 — Report settings

Where reports land and how their files are named, from `configs/reports.yml`. Every setting has a sensible default — the report folder `test-<subject>` under the output root, the report `<subject>.md`, `latest.txt`, and a `yyyyMMdd-HHmmss` stamp — so the file overrides only what differs, and a typed config validates it on load.

What the module does

A quality gate is a check of one property of the whole repository. What differs between quality gates is the check; what must not differ is how a gate reports, because people and CI read every gate's output the same way. This module is that shared ending. It sits low in the module graph — above the config reader, the output-root anchor, and the console writers — so a gate in any module can use it without a new dependency cycle.

Division

Each function belongs to one responsibility.

Responsibility	Function
responsibility:1 — Quality-gate reporting	`Write-QualityGateReport`
responsibility:2 — Report settings	`reports.yml`