1 Label-free graph representation

Input graph
$G = (V, E, X)$

Node features
X

Adjacency
A

	v_1	v_2	⋯	v_n
v_1	0	1	⋯	0
v_2	1	0	⋯	1
⋯	⋮	⋮	⋱	⋮
v_n	0	1	⋯	0

Two augmented views

edge dropping + feature masking

independent augmentation

Shared GRACE encoder
g_ψ

labels are not used

Embedding H^1

Embedding H^2

Frozen normalized representation $\tilde{H}$

2 Label-agnostic granular-ball partition

Geometry-only construction in frozen embedding space $\tilde{H}$

Initialization
$B_0 = V$

Recursive bi-partition

Further recursive splitting

Embedding space $\tilde{H}$ covered by granular balls $B = \{B_j\}_{j=1}^{B}$

selected ball B_j

Label-agnostic recursive 2-means; projected ball covers are shown for visualization

3 Leave-one-out ball-level label consensus

(a) Select a granular ball B_j

Remove node v from its own vote before computing local consensus

(b) Leave-one-out consensus

$p_{j,-v}$ (exclude v)

$$q_{j,-v} = (1 - \beta)p_{j,-v} + \beta e_m$$

If the majority ties: $q_{j,-v} = p_{j,-v}$
(tie-safe; no arbitrary one-hot class)

(c) Construct a soft target t_v

noisy one-hot

local consensus

$$t_v = (1 - \alpha_{j,-v})e_{\tilde{y}_v} + \alpha_{j,-v}q_{j,-v}$$

$\alpha_{j,-v}$ measures vote concentration
$\beta = 0.5$ in the fixed configuration

Output: one node-specific, leave-one-out soft target for each noisy training node

4 X-only MLP training and inference

Training with graph-derived targets

node feature x_v

2-layer MLP f_θ

precomputed t_v

Soft cross-entropy
prediction vs. t_v

Inference after training (transductive)

node feature x_{test}

trained MLP

class probabilities
no graph access

Class 1 · Class 2 · Class 3 · Class 4 · Class 5 · training vote · non-voting node · data flow · contrastive alignment · excluded self-vote

X-only inference: no A, no $\tilde{H}$, no neighbors