

R1. Model fitting

2021 Skagit S/F Chinook Spawner Recruit Model fitting

Contents

Requirements	1
User inputs	9
Loading the fish data	10
Specifying models in JAGS	11
Ricker with with gaussian process errors	11
Fitting the models and generating the one year ahead forecasts	14

This is version 0.24.08.27.

Requirements

All analyses require the R software (v3.4.3) for data retrieval, data processing, and summarizing model results, and the JAGS software (v4.2.0) for Markov chain Monte Carlo (MCMC) simulation. Please note that some of the R code below may not work with older versions of JAGS due to some changes in the ways that arrays are handled.

We also need a few packages that are not included with the base installation of R, so we begin by installing them (if necessary) and then loading them.

```
if(!require("here")) {  
  install.packages("here")  
  library("here")  
}  
if(!require("readr")) {  
  install.packages("readr")  
  library("readr")  
}  
if(!require("rjags")) {  
  install.packages("rjags")  
}
```

```

library("rjags")
}
if(!require("loo")) {
  install.packages("loo")
  library("loo")
}
if(!require("ggplot2")) {
  install.packages("ggplot2")
  library("ggplot2")
}
if(!require("coda")) {
  install.packages("coda")
  library("coda")
}
if(!require("shinystan")) {
  install.packages("shinystan")
  library("shinystan")
}
if(!require("R2jags")) {
  install.packages("R2jags")
  library("R2jags")
}
if(!require("dclone")) {
  install.packages("dclone")
  library("dclone")
}
if(!require("snow")) {
  install.packages("snow")
  library("snow")
}
if(!require("rstan")) {
  install.packages("rstan")
  library("rstan")
}
if(!require("RColorBrewer")) {
  install.packages("RColorBrewer")
  library("RColorBrewer")
}
if(!require("gtools")) {
  install.packages("gtools")
  library("gtools")
}

management_unit <- "summer_fall"

## set directory locations
datadir <- here(paste(management_unit, "/", "data", sep = ""))
jagsdir <- here(paste(management_unit, "/", "jags", sep = ""))
analdir <- here(paste(management_unit, "/", "analysis", sep = ""))
savedir <- here(paste(management_unit, "/", "analysis/cache", sep = ""))

```

We also need a couple of helper functions.

```

## better round
Re2prec <- function(x, map = "round", prec = 1) {
  ## 'map' can be "round", "floor", or "ceiling"
  ## 'prec' is nearest value (eg, 0.1 means to nearest tenth; 1 gives normal behavior)
  if(prec<=0) { stop("\nprec\n cannot be less than or equal to 0") }
  do.call(map,list(x/prec))*prec
}

## wrapper function to fit JAGS models & rearrange output
fit_jags <- function(model, data, params, inits, ctrl, dir = jagsdir) {
  jm <- jags.model(file.path(jagsdir, model),
    data,
    inits,
    ctrl$chains,
    ctrl$burn,
    quiet = TRUE)
  return(coda.samples(jm, params, ctrl$length, ctrl$thin))
}

#alternative wrapper to fit model in parallel; one chain per core
fit_jags2<-function(model,data,params,inits,ctrl,dir=jagsdir){
  cl <- makeCluster(3, type = "SOCK")
  inits2 <- jags.fit(data=data,
    params=params,
    model=file.path(jagsdir, model),
    inits=inits,
    n.chains=ctrl$chains,
    n.adapt = 0,
    n.update = 0,
    n.iter = 0)$state(internal = TRUE)
  jm <- jags.parfit(cl=cl,
    data = data,
    params = params,
    model = file.path(jagsdir, model),
    inits = inits2,
    n.adapt = ctrl$burn*0.5,
    n.update = ctrl$burn*0.5,
    n.iter = ctrl$length-ctrl$burn,
    thin = ctrl$thin,
    n.chains = ctrl$chains
  )
  stopCluster(cl)
  return(jm)
}

#generate summary stats file from MCMC object
sum_stats<-function(mcmcclist){
  ESS<-apply(as.matrix(mcmcclist),2,ess_bulk)
  Rhat<-apply(as.matrix(mcmcclist),2,Rhat)
  summary_stats<-summary(mcmcclist)
  summary_stats<-data.frame(summary_stats$statistics,summary_stats$quantiles,ESS,Rhat)
}

```

```

# functions for approximate LFO
# many functions modified from:
# https://github.com/paul-buerkner/LFO-CV-paper/blob/master/case-study-LFO-CV.Rmd

#load complete model fits & model refits with subset data
loadmodfits<-function(modelnames){
  mod_fits<-list(NULL)
  for(i in 1:length(modelnames)){
    mod_fits[[i]] <- readRDS(file.path(savedir,paste0(modelnames[i],"_y",n_forecasts+1,"_",run,".rds")))
    #mod_fits[[i]] <- readRDS(file.path(savedir,paste0("fit_",modelnames[i],".rds")))
  }
  return(mod_fits)
}

#refits
loadrefits<-function(refitname,N,L){
  numrefits<-N-L+1
  re_fits<-list()
  for(i in 1:numrefits){
    re_fits[[i]] <- readRDS(file.path(savedir,paste0(refitname,"_y",i,"_",run,".rds")))
  }
  return(re_fits)
}

# more stable than log(sum(exp(x)))
log_sum_exp <- function(x) {
  max_x <- max(x)
  max_x + log(sum(exp(x - max_x)))
}

# more stable than log(mean(exp(x)))
log_mean_exp <- function(x) {
  log_sum_exp(x) - log(length(x))
}

# compute log of raw importance ratios
# sums over observations *not* over posterior samples
sum_log_ratios <- function(ll, ids = NULL) {
  if (!is.null(ids)) ll <- ll[, ids, drop = FALSE]
  - rowSums(ll)
}

# for printing comparisons later
rbind_print <- function(...) {
  round(rbind(...), digits = 2)
}

#function to extract log likelihood from fitted model
extract_log_lik<-function(m,esc_only,N,mod_fits){
  #extract pontwise log likelihoods
  tmp_lp <- as.matrix(mod_fits[[m]])
  ## extract pointwise likelihoods
  tmp_lp <- tmp_lp[,grepl("lp-", colnames(tmp_lp))]
  ## if numerical underflows, convert -Inf to 5% less than min(likelihood)

```

```

if(any(is.infinite(tmp_lp))) {
  tmp_lp[is.infinite(tmp_lp)] <- NA
  tmp_min <- min(tmp_lp, na.rm = TRUE)
  tmp_lp[is.na(tmp_lp)] <- tmp_min * 1.05
}
if(esc_only == "Yes"){
  tmp_lp<-tmp_lp[,grepl("esc", colnames(tmp_lp))]
}
#get yrs assoc
names_loglik<-data.frame(strsplit(colnames(tmp_lp), "\\[|\\]"))
yrnames<-as.numeric(names_loglik[2,])

loglik <- matrix(NA, ncol=N, nrow=dim(tmp_lp)[1])
for(i in 1:N){
  if(!is.null(ncol(tmp_lp[,yrnames==i]))){
    loglik[,i] = apply(tmp_lp[,yrnames==i], 1, sum)
  }else(loglik[,i] = tmp_lp[,yrnames==i])
}
return(loglik)
}

#function for printing out a read text file
processFile = function(filepath) {
  con = file(filepath, "r")
  while ( TRUE ) {
    line = readLines(con, n = 1)
    if ( length(line) == 0 ) {
      break
    }
    cat(paste0(noquote(line)), "\n")
  }
  close(con)
}

#####
#function to fit or load modelfits
#####
fit_load_mods<-function(models){

  models <- models

  ## empty list for fits
  mod_fits <- vector("list", n_mods*(n_forecasts+1))
  ## counter to index fitted jags models (33 in total: 3 models x 11 1 year ahead forecasts including u
  ## return year)
  t <- 1
  for(n in 1:n_mods){
    ## counter to index data to feed model for year specific forecasts
    ## first forecast will be for 10 years prior to the most recent return year;
    ## last forecast will be current forecast for the upcoming return year
    c <- 0
    model <- models[n]

```

```

for(i in 1:(n_forecasts+1)){
  if(file.exists(file.path(savedir,paste(model,"_", "y",i,"_",run,".rds",sep = "")))) {
    mod_fits[[t]] <- readRDS(file.path(savedir,paste(model,"_", "y",i,"_",run,".rds",sep = "")))
    #summary_stats<-NULL
    #summary_stats<-sum_stats(mcmclist= mod_fits[[t]])
    #write.csv(summary_stats,file.path(savedir, paste(model,"_", "y",i,"_summary_stats","_",run,".csv",sep = "")))
    c <- c + 1
    t <- t + 1
  } else { ## else, fit & save
    ## cnt & time stamp
    cat("Count =", t, "; Time =", round(((proc.time()-timer_start)/60)["elapsed"], 1), "\n",
        file="cnt_time.txt", append=TRUE)

    #range of years. Last year in range
    dat_yrs <- seq(yr_first,(yr_last - n_forecasts + c),1)

    ## number of years of data
    n_yrs <- length(dat_yrs)

    ## get first & last years
    yr_frst_forecast <- min(dat_yrs)
    yr_last_forecast <- max(dat_yrs)

    ## get escapement data
    dat_esc_forecast <- dat_esc[which(dat_esc$year %in% dat_yrs),]

    ## log of escapement
    ln_dat_esc <- c(log(dat_esc_forecast$escapement),rep(NA,n_fore))

    ## get age data
    dat_age_forecast <- dat_age[which(dat_age$year %in% dat_yrs),]
    ## drop year col & first age_min+age_skip rows
    dat_age_forecast <- dat_age_forecast[-(1:(age_min+age_skip)),-1]

    ## add row(s) of NA's for forecast years
    if(n_fore > 0) {
      dat_age_forecast <- rbind(dat_age_forecast,
                                matrix(0, n_fore, A,
                                         dimnames = list(n_yrs+seq(n_fore),colnames(dat_age_forecast)
                                         )
                                )
      )
    }
    ## total num of age obs by cal yr
    dat_age_forecast[,"sum"] <- apply(dat_age_forecast, 1, sum)
    ## row indices for any years with no obs age comp
    idx_NA_yrs <- which(dat_age_forecast$sum<A, TRUE)
    ## replace 0's in yrs w/o any obs with NA's
    dat_age_forecast[idx_NA_yrs,(1:A)] <- NA
    ## change total in yrs w/o any obs from 0 to A to help dmulti()
    dat_age_forecast[idx_NA_yrs,"sum"] <- A
    ## convert class
    dat_age_forecast <- as.matrix(dat_age_forecast)
  }
}

```

```

## get harvest data
dat_harv_forecast <- dat_harv[which(dat_harv$year %in% dat_yrs),]
## drop year col & first age_max rows
dat_harv_forecast <- c(dat_harv_forecast$catch,rep(NA,n_fore))

## get covariate data
#dat_cvrs_forecast <- dat_cvrs[which(dat_cvrs$year <= yr_last + n_fore - age_min),1:4]
## drop year col
#dat_cvrs_forecast <- dat_cvrs_forecast[,-1]
## transform the covariates to z-scores
#scl_cvrs_forecast <- scale(dat_cvrs_forecast)
## total number of covariates
#n_cov <- dim(dat_cvrs_forecast)[2]

## ----jags_setup-----
## 1. Data to pass to JAGS
dat_jags <- list(dat_age = dat_age_forecast,
                ln_dat_esc = ln_dat_esc,
                dat_harv = dat_harv_forecast,
                A = A,
                age_min = age_min,
                age_max = age_max,
                age_skip = age_skip,
                n_yrs = n_yrs,
                n_fore = n_fore)

## 2. Model params/states for JAGS to return
## These are specific to the process model,
## so we define them in 'par_jags' below.

init_vals <- function() {
  list(alpha = 5,
        #beta_inv = exp(mean(ln_dat_esc, na.rm = TRUE)),
        beta=1/exp(mean(ln_dat_esc, na.rm=TRUE)),
        pi_tau = 10,
        pi_eta = rep(1,A),
        pi_vec = matrix(c(0.020,0.219,0.581,0.179),
                        n_yrs-age_min+n_fore, A,
                        byrow = TRUE),
        Rec_mu = log(1000),
        Rec_sig = 0.1,
        tot_ln_Rec = rep(log(1000), n_yrs - age_min + n_fore))
}

par_jags <- c("alpha","E_Rkr_a","mu_Rkr_a",
             "beta",
             "Sp","Rec","tot_ln_Rec","ln_RS","tot_Run",
             "pi_eta","pi_tau","pi_vec",
             "sigma_r","sigma_s","res_ln_Rec",
             "lp_age","lp_esc","Run")

# init_vals <- function() {

```

```

#   list(alpha = 5,
#         beta_inv = exp(mean(ln_dat_esc, na.rm = TRUE)),
#         pi_tau = 10,
#         pi_eta = rep(1,A),
#         pi_vec = matrix(c(0.020,0.219,0.581,0.179),
#                           n_yrs-age_min+n_fore, A,
#                           byrow = TRUE),
#         Rec_mu = log(1000),
#         Rec_sig = 0.1,
#         tot_ln_Rec = rep(log(1000), n_yrs - age_min + n_fore),
#         phi_prior = 0.5,
#         innov_1 = 0)
# }
#
#
# if(model == "IPM_BH_AR"){
#   ## params/states to return
#   par_jags<- c("alpha","E_BH_a","mu_BH_a",
#               "beta",
#               "Sp","Rec","tot_ln_Rec","ln_RS",
#               "pi_eta","pi_tau","pi_vec",
#               "sigma_r","sigma_s","w","res_ln_Rec",
#               "lp_age","lp_esc","phi","Run"
#               )
#
# }else{
#   ## params/states to return
#   par_jags <- c("alpha","E_Rkr_a","mu_Rkr_a",
#               "beta",
#               "Sp","Rec","tot_ln_Rec","ln_RS","tot_Run",
#               "pi_eta","pi_tau","pi_vec",
#               "sigma_r","sigma_s","res_ln_Rec","w","theta_res","phi",
#               "lp_age","lp_esc","Run"
#               )
#
#
# }#endif
#

## set of multi-covariate models
#cset <- colnames(scl_cvrs_forecast)
#dat_jags$n_cov <- length(cset)
#dat_jags$mod_cvrs <- scl_cvrs_forecast[1:(n_yrs-age_min+1), cset]

## fit model & save it
# mod_fits[[t]] <- fit_jags(paste(model,".txt",sep = ""), dat_jags, par_jags,
#                           init_vals_cov, mcmc_ctrl)
mod_fits[[t]]<-fit_jags2(model=paste(model,".txt",sep = ""),
                        data=dat_jags,
                        params=par_jags,
                        inits=init_vals,

```



```

        ctrl=mcmc_ctrl
      )
      saveRDS(mod_fits[[t]], file.path(savedir,paste(model,"_", "y",i,"_",run,".rds",sep = "")))
      summary_stats<-NULL
      summary_stats<-sum_stats(mcmclist= mod_fits[[t]])
      write.csv(summary_stats,file.path(savedir, paste(model,"_", "y",i,"_summary_stats","_",run,".csv",sep = "")))
      c <- c + 1
      t <- t + 1
    }## end if

    }##next forecast year(i)
  }## next model(n)
  return(mod_fits)
}

```

User inputs

We begin by supplying values for the following parameters, which we need for model fitting and evaluation.

```

## first & last years of fish data
yr_first <- 1992
yr_last <- 2018

## min & max ad ult age classes
age_min <- 2
age_max <- 5

## years (if any) of age-comp to skip; see below
age_skip <- 0

## number of years ahead for run forecasts from the most recent year of data
n_fore <- 0

## number of recent year forecasts
n_forecasts <- 0

## first year of 1 step ahead forecast
#yr_begin <- 2011

## last year of 1 step ahead forecast
#yr_end <- 2020

## upper threshold for Gelman & Rubin's potential scale reduction factor (Rhat).
Rhat_thresh <- 1.1

## run sfck = summer/fall; spck = spring
run <- "sfck"

```

Next we specify the names of three necessary data files containing the following information:

1. observed total number of adult spawners (escapement) by year;
2. observed age composition of adult spawners by year;
3. observed total harvest by year;

```
## 1. file with escapement data
## [n_yrs x 2] matrix of obs counts; 1st col is calendar yr
fn_esc <- paste("skagit","_",run,"_", "esc_new.csv",sep = "")
## 2. file with age comp data
## [n_yrs x (1+A)]; 1st col is calendar yr
fn_age <- paste("skagit","_",run,"_", "age.csv",sep = "")

## 3. file with harvest data
## [n_yrs x 2] matrix of obs catch; 1st col is calendar yr
fn_harv <- paste("skagit","_",run,"_", "catch.csv",sep = "")
```

Loading the fish data

Here we load in the first three data files and do some simple calculations and manipulations. First the spawner data:

```
## escapement
dat_esc <- read_csv(file.path(datadir, fn_esc))
## years of data
dat_yrs <- dat_esc$year

## number of years of data
n_yrs <- length(dat_yrs)

## log of escapement
ln_dat_esc <- c(log(dat_esc$escapement),rep(NA,n_fore))
```

Next the age composition data:

```
## age comp data
dat_age <- read_csv(file.path(datadir, fn_age))
## num of age classes
A <- age_max - age_min + 1

# ## drop year col & first age_min+age_skip rows
# dat_age <- dat_age[-(1:(age_min+age_skip)),-1]
#
# ## add row(s) of NA's for forecast years
# if(n_fore > 0) {
#   dat_age <- rbind(dat_age,
#                     matrix(0, n_fore, A,
#                             dimnames = list(n_yrs+seq(n_fore),
#                                                  colnames(dat_age))))
# }
# ## total num of age obs by cal yr
# dat_age[, "sum"] <- apply(dat_age, 1, sum)
# ## row indices for any years with no obs age comp
# idx_NA_yrs <- which(dat_age$sum < A, TRUE)
```

```

## replace 0's in yrs w/o any obs with NA's
dat_age[idx_NA_yrs,(1:A)] <- NA
## change total in yrs w/o any obs from 0 to A to help dmulti()
dat_age[idx_NA_yrs,"sum"] <- A
## convert class
dat_age <- as.matrix(dat_age)

```

And then the harvest data:

```

## harvest
dat_harv <- read_csv(file.path(datadir, fn_harv))
## drop year col & first age_max rows
dat_harv <- c(dat_harv$catch,rep(NA,n_fore))

```

Specifying models in JAGS

Now we can specify the model in JAGS. For this effort, we are only evaluating a Ricker model with gaussian process errors.

Ricker with with gaussian process errors

```

processFile(file.path(jagsdir, "IPM_RK.txt"))

## model {
##
##   ##-----
##   ## PRIORS
##   ##-----
##   ## alpha = exp(a) = intrinsic productivity
##   alpha ~ dunif(0.1,10);
##   mu_Rkr_a <- log(alpha);
##   E_Rkr_a <- mu_Rkr_a + sigma_r/2;
##
##
##   ## strength of dens depend
##   #beta_inv ~ dnorm(0, 1e-9) T(0,);
##   #beta <- 1/beta_inv;
##   beta ~ dunif(0,0.1);
##
##
##   ## process variance for recruits model
##   sd_r ~ dunif(0.001,20);
##   tau_r <- pow(sd_r,-2);
##   sigma_r <- pow(sd_r,2);
##
##
##   ## obs variance for spawners
##   sd_s ~ dunif(0.001,20);
##   tau_s <- pow(sd_s,-2);
##   sigma_s <- pow(sd_s,2);

```

```

##
##  ## unprojectable early recruits;
##  ## hyper mean across all popns
##  Rec_mu ~ dnorm(0,0.001);
##  ## hyper SD across all popns
##  Rec_sig ~ dunif(0,100);
##  ## precision across all popns
##  Rec_tau <- pow(Rec_sig,-2);
##  ## multipliers for unobservable total runs
##  ttl_run_mu ~ dunif(1,5);
##  ttl_run_tau ~ dunif(1,20);
##
##  ## maturity schedule
##  ## unif vec for Dirch prior
##  for(i in 1:A) { theta[i] <- 1 }
##  ## hyper-mean for maturity
##  pi_eta ~ ddirch(theta);
##  ## hyper-prec for maturity
##  pi_tau ~ dunif(0.001,1e3);
##  for(t in 1:(n_yrs-age_min)) { pi_vec[t,1:A] ~ ddirch(pi_eta*pi_tau) }
##
##  ##-----
##  ## LIKELIHOOD
##  ##-----
##  ## 1st brood yr requires different innovation
##  ## predicted recruits in BY t
##  E_ln_Rec[1] <- ln_Sp[1] - beta*Sp[1] + mu_Rkr_a;
##  tot_ln_Rec[1] ~ dnorm(E_ln_Rec[1],tau_r);
##  res_ln_Rec[1] <- tot_ln_Rec[1] - E_ln_Rec[1];
##  ## median of total recruits
##  tot_Rec[1] <- exp(tot_ln_Rec[1]);
##
##  ## R/S
##  ln_RS[1] <- tot_ln_Rec[1] - ln_Sp[1];
##
##  ## brood-yr recruits by age
##  for(a in 1:A) {
##    Rec[1,a] <- max(1,tot_Rec[1] * pi_vec[1,a]);
##  }
##
##  ## brood years 2:(n_yrs-age_min)
##  for(t in 2:(n_yrs-age_min)) {
##    ## predicted recruits in BY t
##    E_ln_Rec[t] <- ln_Sp[t] - beta*Sp[t] + mu_Rkr_a;
##    tot_ln_Rec[t] ~ dnorm(E_ln_Rec[t],tau_r);
##    res_ln_Rec[t] <- tot_ln_Rec[t] - E_ln_Rec[t];
##    ## median of total recruits
##    tot_Rec[t] <- exp(tot_ln_Rec[t]);
##    ## R/S
##    ln_RS[t] <- tot_ln_Rec[t] - ln_Sp[t];
##    ## brood-yr recruits by age
##    for(a in 1:A) {
##      Rec[t,a] <- max(1,tot_Rec[t] * pi_vec[t,a]);
##    }
##  }

```

```

## } ## end t loop over year
##
## ## get total cal yr returns for first age_min yrs
## for(i in 1:(age_min+age_skip)) {
##   ln_tot_Run[i] ~ dnorm(ttl_run_mu*Rec_mu,Rec_tau/ttl_run_tau);
##   tot_Run[i] <- exp(ln_tot_Run[i]);
## }
##
## ## get predicted calendar year returns by age
## ## matrix Run has dim [(n_yrs-age_min) x A]
## ## step 1: incomplete early broods
## ## first cal yr of this grp is first brood yr + age_min + age_skip
## for(i in 1:(age_max-age_min-age_skip)) {
##   ## projected recruits
##   for(a in 1:(i+age_skip)) {
##     Run[i,a] <- Rec[(age_skip+i)-a+1,a];
##   }
##   ## imputed recruits
##   for(a in (i+1+age_skip):A) {
##     lnRec[i,a] ~ dnorm(Rec_mu,Rec_tau);
##     Run[i,a] <- exp(lnRec[i,a]);
##   }
##   ## total run size
##   tot_Run[i+age_min+age_skip] <- sum(Run[i,1:A]);
##   # predicted age-prop vec for multinom
##   for(a in 1:A) {
##     age_v[i,a] <- Run[i,a] / tot_Run[i+age_min];
##   }
##   ## multinomial for age comp
##   dat_age[i,1:A] ~ dmulti(age_v[i,1:A],dat_age[i,A+1]);
##   lp_age[i] <- logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]);
## }
##
## ## step 2: info from complete broods
## ## first cal yr of this grp is first brood yr + age_max
## for(i in (A-age_skip):(n_yrs-age_min-age_skip)) {
##   for(a in 1:A) {
##     Run[i,a] <- Rec[(age_skip+i)-a+1,a];
##   }
##   ## total run size
##   tot_Run[i+age_min+age_skip] <- sum(Run[i,1:A]);
##   ## predicted age-prop vec for multinom
##   for(a in 1:A) {
##     age_v[i,a] <- Run[i,a] / tot_Run[i+age_min];
##   }
##   ## multinomial for age comp
##   dat_age[i,1:A] ~ dmulti(age_v[i,1:A],dat_age[i,A+1]);
##   lp_age[i] <- logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]);
## }
##
## ## get predicted calendar year spawners
## ## first cal yr is first brood yr
## for(t in 1:(n_yrs)) {
##   ## obs model for spawners

```

```
##   Sp[t] <- max(1,tot_Run[t] * (1 - dat_harv[t]));
##   ln_Sp[t] <- log(Sp[t]);
##   ln_dat_esc[t] ~ dnorm(ln_Sp[t], tau_s);
##   lp_esc[t] <- logdensity.norm(ln_dat_esc[t],ln_Sp[t], tau_s);
## }
##
## } ## end model description
```

Fitting the models and generating the one year ahead forecasts

For the most recent 10 years (2011 - 2020), fit the model to data through year t-1 and generate a forecast for year t.

Before fitting the model in JAGS, we need to specify the MCMC control parameters.

```
## 1. MCMC control params
mcmc_ctrl <- list(
  chains = 4,
  length = 5e5, #200000,
  burn = 2e5, #100000,
  thin = 400 #100
)
## total number of MCMC samples after burnin
mcmc_samp <- mcmc_ctrl$length*mcmc_ctrl$chains/mcmc_ctrl$thin

## fit or load models
models=c("IPM_RK")
n_mods<-length(models)
mod_fits <- fit_load_mods(models=models)
```

```
## Compiling model graph
##   Resolving undeclared variables
##   Allocating nodes
## Graph information:
##   Observed stochastic nodes: 52
##   Unobserved stochastic nodes: 68
##   Total graph size: 993
##
## Initializing model
##
##
## Parallel computation in progress
```